

DAFTAR PUSTAKA

- [1] “• Car production: Number of cars produced worldwide 2018 | Statista.” <https://www.statista.com/statistics/262747/worldwide-automobile-production-since-2000/> (accessed Jun. 26, 2022).
- [2] “The state of the climate in 2021 - BBC Future.” <https://www.bbc.com/future/article/20210108-where-we-are-on-climate-change-in-five-charts> (accessed Jun. 24, 2022).
- [3] “Dafar Negara Penyumbang Terbesar Emisi Karbon di Dunia, Indonesia?” <https://fin.co.id/read/5274/Dafar-Negara-Penyumbang-Terbesar-Emisi-Karbon-di-Dunia-Indonesia> (accessed Jun. 26, 2022).
- [4] “Memahami ‘Kesenjangan Emisi’ dalam 5 Grafik | WRI Indonesia.” <https://wri-indonesia.org/id/blog/memahami-‘kesenjangan-emisi’-dalam-5-grafik> (accessed Jun. 26, 2022).
- [5] “Direktorat Jenderal EBTKE - Kementerian ESDM.” <https://ebtke.esdm.go.id/post/2020/08/24/2613/turunkan.emisi.314.juta.ton.co2.tahun.2030.indonesia.perlu.investasi.rp.3.500.triliun> (accessed Jun. 26, 2022).
- [6] M. A. Hannan, M. M. Hoque, A. Hussain, Y. Yusof, and P. J. Ker, “State-of-the-Art and Energy Management System of Lithium-Ion Batteries in Electric Vehicle Applications: Issues and Recommendations,” *IEEE Access*, vol. 6, pp. 19362–19378, 2018, doi: 10.1109/ACCESS.2018.2817655.
- [7] S. Manzetti and F. Mariasiu, “Electric vehicle battery technologies: From present state to future systems,” *Renew. Sustain. Energy Rev.*, vol. 51, pp. 1004–1012, 2015, doi: 10.1016/j.rser.2015.07.010.
- [8] T. F. Yi, J. Mei, and Y. R. Zhu, “Key strategies for enhancing the cycling stability and rate capacity of LiNi_{0.5}Mn_{1.5}O₄ as high-voltage cathode materials for high power lithium-ion batteries,” *J. Power Sources*, vol. 316, pp. 85–105, 2016, doi: 10.1016/j.jpowsour.2016.03.070.
- [9] D. Yang, Y. Wang, R. Pan, R. Chen, and Z. Chen, “A Neural Network Based State-of-Health Estimation of Lithium-ion Battery in Electric Vehicles,” *Energy Procedia*, vol. 105, pp. 2059–2064, 2017, doi: 10.1016/j.egypro.2017.03.583.
- [10] Q. Fang, X. Wei, T. Lu, H. Dai, and J. Zhu, “A state of health estimation method for

- lithium-ion batteries based on voltage relaxation model,” *Energies*, vol. 12, no. 7, pp. 1–5, 2019, doi: 10.3390/en12071349.
- [11] C. Kun, M. Zhiwei, L. Yuehua, J. Zhinong, and Z. Jinjie, “Lithium-ion battery state of charge estimation based on dynamic neural network and Kalman filter,” *2018 IEEE Int. Conf. Progn. Heal. Manag. ICPHM 2018*, 2018, doi: 10.1109/ICPHM.2018.8448734.
 - [12] A. Sedighfar and M. R. Moniri, “Battery state of charge and state of health estimation for VRLA batteries using Kalman filter and neural networks,” *2018 5th Int. Conf. Electr. Electron. Eng. ICEEE 2018*, pp. 41–46, 2018, doi: 10.1109/ICEEE2.2018.8391298.
 - [13] M. Shahriari and M. Farrokhi, “Online state-of-health estimation of VRLA batteries using state of charge,” *IEEE Trans. Ind. Electron.*, vol. 60, no. 1, pp. 191–202, 2013, doi: 10.1109/TIE.2012.2186771.
 - [14] W. Gao, Y. Zheng, M. Ouyang, J. Li, X. Lai, and X. Hu, “Micro-short-circuit diagnosis for series-connected lithium-ion battery packs using mean-difference model,” *IEEE Trans. Ind. Electron.*, vol. 66, no. 3, pp. 2132–2142, 2019, doi: 10.1109/TIE.2018.2838109.
 - [15] R. Xiong, R. Yang, Z. Chen, W. Shen, and F. Sun, “Online Fault Diagnosis of External Short Circuit for Lithium-Ion Battery Pack,” *IEEE Trans. Ind. Electron.*, vol. 67, no. 2, pp. 1081–1091, 2020, doi: 10.1109/TIE.2019.2899565.
 - [16] A. Sidhu, A. Izadian, and S. Anwar, “Adaptive nonlinear model-based fault diagnosis of li-ion batteries,” *IEEE Trans. Ind. Electron.*, vol. 62, no. 2, pp. 1002–1011, 2015, doi: 10.1109/TIE.2014.2336599.
 - [17] R. Xiong, Q. Yu, W. Shen, C. Lin, and F. Sun, “A Sensor Fault Diagnosis Method for a Lithium-Ion Battery Pack in Electric Vehicles,” *IEEE Trans. Power Electron.*, vol. 34, no. 10, pp. 9709–9718, 2019, doi: 10.1109/TPEL.2019.2893622.
 - [18] S. Dey, H. E. Perez, and S. J. Moura, “Model-Based Battery Thermal Fault Diagnostics: Algorithms, Analysis, and Experiments,” *IEEE Trans. Control Syst. Technol.*, vol. 27, no. 2, pp. 576–587, 2019, doi: 10.1109/TCST.2017.2776218.
 - [19] Y. C. H. Yuwono, B. R. Dewangga, A. I. Cahyadi, and S. Herdjunto, “Fault Detection on the Battery SOC-OCV by Using Observer,” *Proc. - 2018 4th Int. Conf. Sci. Technol. ICST 2018*, pp. 2018–2021, 2018, doi: 10.1109/ICSTC.2018.8528607.
 - [20] N. Kresna Wahvu Hutama, B. R. Dewangga, A. I. Cahyadi, and E. Firmansyah, “Designed Observer of Dual-Polar Battery Model for Fault Detection of Voltage

- Sensor,” in *2021 13th International Conference on Information Technology and Electrical Engineering (ICITEE)*, Oct. 2021, pp. 220–225, doi: 10.1109/ICITEE53064.2021.9611949.
- [21] H. He, R. Xiong, and J. Fan, “Evaluation of lithium-ion battery equivalent circuit models for state of charge estimation by an experimental approach,” *Energies*, vol. 4, no. 4, pp. 582–598, 2011, doi: 10.3390/en4040582.
- [22] R. Xiong, Q. Yu, and W. Shen, “Review on sensors fault diagnosis and fault-tolerant techniques for lithium ion batteries in electric vehicles,” *Proc. 13th IEEE Conf. Ind. Electron. Appl. ICIEA 2018*, pp. 406–410, 2018, doi: 10.1109/ICIEA.2018.8397751.
- [23] X. Hu, K. Zhang, K. Liu, X. Lin, S. Dey, and S. Onori, “Advanced Fault Diagnosis for Lithium-Ion Battery Systems: A Review of Fault Mechanisms, Fault Features, and Diagnosis Procedures,” *IEEE Ind. Electron. Mag.*, vol. 14, no. 3, pp. 65–91, 2020, doi: 10.1109/MIE.2020.2964814.
- [24] D. G. Luenberger, “An Introduction to Observers,” *IEEE Trans. Automat. Contr.*, vol. 16, no. 6, pp. 596–602, 1971, doi: 10.1109/TAC.1971.1099826.
- [25] B. M. T. Lawder *et al.*, “System (BESS) and Battery Management System (BMS) for Grid-Scale Applications,” vol. 102, no. 6, 2014.
- [26] X. Hu, S. Li, and H. Peng, “A comparative study of equivalent circuit models for Li-ion batteries,” *J. Power Sources*, vol. 198, pp. 359–367, 2012, doi: 10.1016/j.jpowsour.2011.10.013.
- [27] P. A. Topan, M. N. Ramadan, G. Fathoni, A. I. Cahyadi, and O. Wahyunggoro, “State of Charge (SOC) and State of Health (SOH) estimation on lithium polymer battery via Kalman filter,” *Proc. - 2016 2nd Int. Conf. Sci. Technol. ICST 2016*, no. 2, pp. 93–96, 2017, doi: 10.1109/ICSTC.2016.7877354.
- [28] M. N. Ramadan, S. T. Dr. Eng. Adha Imam Cahyadi, and M. T. Ir. Oyas Wahyunggoro, “Estimasi State of Charge (Soc) Dan State of Health (Soh) Dengan Algoritme Kalman Filter Pada Baterai Lithium Polymer,” p. 370667, 2016, [Online]. Available: http://etd.repository.ugm.ac.id/index.php?mod=penelitian_detail&sub=PenelitianDetail&act=view&typ=html&buku_id=98188&obyek_id=4%0Ahttp://etd.repository.ugm.ac.id/downloadfile/98188/potongan/S2-2016-370667-introduction.pdf.
- [29] Susanna, B. R. Dewangga, O. Wahyunggoro, and A. I. Cahyadi, “Comparison of simple battery model and thevenin battery model for SOC estimation based on OCV method,”

- 2019 *Int. Conf. Inf. Commun. Technol. ICOIACT 2019*, pp. 738–743, 2019, doi: 10.1109/ICOIACT46704.2019.8938495.
- [30] Y. Kang *et al.*, “A comparative study of fault diagnostic methods for lithium-ion batteries based on a standardized fault feature comparison method,” *J. Clean. Prod.*, vol. 278, p. 123424, 2021, doi: 10.1016/j.jclepro.2020.123424.
- [31] IEEE Power and Energy Society, *IEEE Guide for the Characterization and Evaluation of Lithium-Based Batteries in Stationary Applications*. 2018.
- [32] V. M. Dileepan, K. T. Madhavan, and J. Jayakumar, “Performance analysis of lithium polymer battery and super capacitor,” *2017 Int. Conf. Energy, Commun. Data Anal. Soft Comput. ICECDS 2017*, pp. 2029–2033, 2018, doi: 10.1109/ICECDS.2017.8389805.
- [33] M. A. Hannan, M. S. H. Lipu, A. Hussain, and A. Mohamed, “A review of lithium-ion battery state of charge estimation and management system in electric vehicle applications: Challenges and recommendations,” *Renew. Sustain. Energy Rev.*, vol. 78, no. May, pp. 834–854, 2017, doi: 10.1016/j.rser.2017.05.001.
- [34] F. Wen, R. Zhu, J. Zhang, S. Gong, B. Duan, and C. Zhang, “High-Precision Parameter Identification of Lithium-ion Battery Based on Voltage Signal Reconstruction,” *3rd Conf. Veh. Control Intell. CVCI 2019*, pp. 1–5, 2019, doi: 10.1109/CVCI47823.2019.8951541.
- [35] S. Herdjunto, “Estimation of Open Circuit Voltage and electrical parameters of a battery based on signal processed by Recursive Least Square method using two separate forgetting factors,” *Proc. - 2016 6th Int. Annu. Eng. Semin. Ina. 2016*, pp. 67–71, 2017, doi: 10.1109/INAES.2016.7821909.
- [36] S. Herdjunto, A. Susanto, and O. Wahyunggoro, “Robust residual generation for actuator fault isolation: A case study: Magnetic-tape-drive MIMO system,” *Proc. - 2013 Int. Conf. Inf. Technol. Electr. Eng. "Intelligent Green Technol. Sustain. Dev. ICITEE 2013*, pp. 470–475, 2013, doi: 10.1109/ICITEED.2013.6676288.
- [37] S. Hong, Y. Zhou, J. Shang, C. Xiao, and J. Sun, “Opportunities and challenges of deep learning methods for electrocardiogram data: A systematic review,” *Comput. Biol. Med.*, vol. 122, no. June, p. 103801, 2020, doi: 10.1016/j.combiomed.2020.103801.