

DAFTAR PUSTAKA

- Arai, H., dan Tokimatsu, K., 1998, Evaluation of local site effects based on microtremor H/V spectra, *Proceeding of the Second International Symposium on the Effects of Surface Geology on Seismic Motion*, Yokohama, Japan, pp. 673–680.
- Bard, P.-Y., 1999, Microtremor measurements: A tool for site effect estimation?, *The Effects of Surface Geology on Seismic Motion*, pp. 1251-1279.
- Bolt, B.A., 1976, *Nuclear explosions and earthquakes*. The parted veil.
- Bonnefoy-Claudet, S., Cornou, C., Bard, P.-Y. dan Cotton, F., 2004, Nature of noise wavefield, *SESAME report*, 13 Agustus.
- Bonnefoy-Claudet, S., Cotton, F., dan Bard, P., 2006, The nature of noise wavefield and its applications for site effects studies, a literature review, *Earth Science Reviews*, 79.
- Chouet, B., De Luca, G., Milana, G., Dawson, P., Martini, M., dan Scarpa, R., 1998. Shallow velocity of Stromboli volcano, Italy, derived from small-aperture array measurements of Strombolian tremor. *Bulletin of the Seismological Society of America*, 88, pp. 653–666.
- Cornou, C., 2002. Traitement d'antenne et imagerie sismique dans l'agglomération grenobloise (Alpes Françaises): implications pour les effets de site, *Ph.D. Thesis*, University Joseph Fourier, Grenoble, France. (In French with English abstract).
- Everett, M.E., 2013, *Near-surface applied geophysics*, Cambridge University Press.
- Feng, S., Sugiyama, T., dan Yamanaka, H., 2005, Effectiveness of multimode surface wave inversion in shallow engineering site investigations. *Exploration Geophysics*, 36, pp. 26–33.

- Gorbatikov, A.V., Stepanova, M. Yu., dan Korablev, G. E., 2008, Microseismic Field Affected by Local Geological Heterogeneities and Microseismic Sounding of the Medium, *Izvestiya, Physics of the Solid Earth*, 44, 7, pp. 577–592.
- Horike, M., 1985, Inversion of phase velocity of long-period microtremors to the S-wave-velocity structure down to the basement in urbanized areas, *Journal of Physics of the Earth*, 33, pp. 59–96.
- Horike, M., Zhaoli, B., dan Kawase, H., 2001, Comparison of Site Response Characteristics Inferred from Microtremors and Earthquake Shear Waves, *Bulletin of Seismological Society of America*, pp. 1526-1536.
- Kalinina, A. V., Ammosov, S. M., Volkov, V. A., Volkov, N. V., Hok, J., Brimich, L., dan Sujana, M., 2009, Microseismic identification of geological and tectonic structures in the Komjatice Depression (Western Carpathians), *Geologica Carpathica*, 2009, 60, 4, pp. 331—338.
- Kamura, K., 1997, On Microtremors Observed in Tokyo Bay Area, *Japanese document, in Japanese with English abstract*, pp. 47-53.
- Kanai, K., 1983, *Earthquake Engineering and Structural Dynamics*, University of Tokyo Press.
- Kanai, K., dan Tanaka, T., 1954, Measurement Of The Microtremors, *Bulletin of the Earthquake Research Institute*, Tokyo University, 32, pp. 199-209.
- Köhler, A., Ohrnberger, M., Scherbaum, F., Wathelet, M. dan Cornou, C., 2007, Assessing the reliability of the modified three-component spatial autocorrelation technique, *Geophysical Journal International*, 168(2), pp.779-796.
- Konno, K., dan Ohmachi, T., 1998, Ground-Motion Characteristics Estimated from Spectral Ratio between Horizontal and Vertical Components of Microtremor, *Bulletin of Seismological Society of America*, 88, pp. 228-241.
- Kudo, K., 1995. Practical estimates of site response, state-of-art report, *Proceedings of the fifth International Conference on Seismic Zonation*, Nice, France.

- Lachet, C., dan Bard, P.-Y., 1994, Numerical and theoretical investigations on the possibilities and limitations of Nakamura's technique, *Journal of Physics of the Earth*, 42, 4, pp. 377–397.
- LDS, 2004, Understanding FFT Windows, *Application Note ANO14*.
- Li, T.M.C., Ferguson, J.F., Herrin, E., dan Durham, H.B., 1984. Highfrequency seismic noise at Lajitas, Texas. *Bulletin of the Seismological Society of America*, 74, pp. 2015–2033.
- Love, A.E.H., 1911, *Some Problems of Geodynamics*, The University Press.
- Malischewky, P.G., dan Scherbaum, F., 2004, Love's formula and H/V ratio (ellipticity) of Rayleigh waves. *Wave Motion*, 40, pp. 57–67.
- Marjiyono, 2016, Potensi Penguatan Gelombang Gempa Bumi oleh Sedimen Permukaan Kota Mataram, Nusa Tenggara Barat, *Jurnal Lingkungan dan Bencana Geologi*, 7, 3, Pusat Survei Geologi, pp. 135-144.
- Nakamura, Y., 1989, A Method for Dynamic Characteristics Estimation of Surface using Microtremor on the Ground Surface, *Quarterly Report of Railway Technical Research Institute*, Tokyo, Japan.
- Nakamura, Y., 2000, Clear Identification of Fundamental Idea of Nakamura's Technique and its Applications, *The 12 World Conference on Earthquake Engineering*, Auckland, New Zealand.
- Nakamura, Y., 2008, On The H/V Spectrum, *The 14th World Conference on Earhquake Engineering*, October 12-17 2008, Beijing, China.
- Nogoshi, M. dan Igarashi, T., 1970, On the propagation characteristics of microtremors, *Journal of the Seismological Society of Japan*, 23, pp. 264-280(in Japanese with English abstract).
- Okada, H., 2003, The microtremor survey method, *Geophysical Monograph Series*, Society of Exploration Geophysicists 12.
- Rahardjo, W., Sukandarrumdi, dan Rosidi, H.M.D., 1995, *Peta Geologi Lembar Yogyakarta, Jawa*, Pusat Penelitian dan Pengembangan Geologi, Bandung.

- Rayleigh, L., 1885, On waves propagated along the plane surface of an elastic solid, *Proceedings of the London Mathematical Society*, 1, pp. 4-11.
- Seo, K., Haile, M., Kurita, K., Yamazaki, K., dan Nakamaru, A., 1996, Study of site effects in Kobe area using microtremors, *10th World Conference of Earthquake Engineering*, Acapulco.
- Seo, K., 1997, Cooperative observation of microtremors in Kobe-Hanshin district, *Japanese document, in Japanese with English abstract*, pp. 38-46.
- Seo, K., 1998, A joint microtremor measurement in the Fukui basin to discuss the effects of surface geology on seismic motion during the 1948 Fukui, Japan, earthquake, *Proceedings of the 11th European Conference on Earthquake Engineering*, Paris, September 6-11, Bisch, Labbe and Pecker Editors, Bulkema.
- SESAME, 2004, *Guidelines for the Implementation of the H/V Spectral Ratio Technique on Ambient Vibrations Measurements Processing and Interpretation*, European Commission-Research General Directorate.
- Stephenson, W.R., 2003, Factors bounding prograde Rayleigh-wave particle motion in a soft-soil layer, *Pacific Conference on Earthquake Engineering*.
- Suzuki, T., Adachi, Y., Tanaka, M., 1995, Application of microtremor measurements to the estimation of earthquake ground motions in Kushiro City during the Kushiro-Oki earthquake of 15 January 1993, *Earthquake Engineering Structural Dynamics*, 24, pp. 595-613.
- Tokimatsu, K., 1997, Geotechnical site characterization using surface waves, *Proceedings of the First International Conference on Earthquake Geotechnical Engineering*, 3, pp. 1333-1368.
- van Bemmelen, 1949, *The geology of Indonesia*, Vol. 1 A, Government Printing Office, The Hague.
- Wathelet, M., 2005, Array recordings of ambient vibrations: surface wave inversion, *Ph.D. thesis*, Faculté des Sciences Appliquées, Liege University, Belgium.