

- [1] Hendrayana, “Simulation of hybrid systems for solar, wind and generator energy generation to optimize the utilization of renewable energy,” ISSN 2549-3698, vol. 1, no. 1, pp. 26–43, 2017.
- [2] S. H. Febriansya, Hermawan, “Optimasi kapasitas pembangkit tersebar untuk mengurangi rugi daya aktif menggunakan particle swarm optimization dan pengaruhnya terhadap indeks kestabilan tegangan,” ISSN 2302-9927, vol. 2, pp. 1–8, 2013.
- [3] P. Shintre and A. M. Mulla, “Study of micro grid topology and design of voltage source inverter and charge controller,” ISSN 2395 -0056, vol. 03, 2016.
- [4] Safrizal, “Penentuan lokasi optimal small renewable energy pada bus kritis menggunakan metode bus participation factor (BPF),” in Prosiding SNATIF, 2015, pp. 73–80.
- [5] C. Marinescu and I. Șerban, “Analysis of frequency stability in a residential autonomous microgrid based on a wind turbine and a microhydro power plant,” 2009 IEEE Power Electron. Mach. Wind Appl. PEMWA 2009, 2009, doi: 10.1109/PEMWA.2009.5208400.
- [6] I. G. K. A. I Ketut Suryana; Kadek Amerta Yasa, “Determination of the location and capacity of the distributed plant to reduce active power losses in the distribution sistem using adaptive particle swarm optimization,” ISBN 978-602-8692-34-2, no. 1, pp. 39–43, 2018.
- [7] M. Jesuli, R. Gianto and I. Arsyad, “Pengaruh Pembangkit Tersebar Terhadap Rugi-Rugi Daya Sistem Distribusi Tenaga Listrik” Journal Untan, 2021.
- [8] D. Santoso, “Penentuan Lokasi dan Kapasitas Wind-Based DG pada Sistem Distribusi 20 kV Menggunakan Flower Pollination Algorithm” JTERA, vol. 5, pp.127, 2020.
- [9] A Supardi, A. Budiman, N. Khairudin, “ Pengaruh Kecepatan Putar Dan Beban Terhadap Keluaran Generator Induksi 1 Fase Kecepatan Rendah” Emitor ; Jurnal Teknik Elektro, vol.

- [10] H.Azis, P.Pawenary, M.Sitorus “Simulasi Pemodelan Sistem Eksitasi Statis pada Generator Sinkron terhadap Perubahan Beban” *Journal Energi & Kelistrikan*, vol.11, pp.46-54, 2019.
- [7] A. B. M. Indra Sasmita and I. M. A. Nrratha, “Determination of distributed generation (DG) locations based on the sensitivity factor of losses and optimal capacity using the Artificial Bee Colony (ABC) method,” *Dielektr.* ISSN 2086-9487, vol. 3, no. 2, pp. 184–193, 2016.
- [10] M. T. Dr. Ir. Rizal Munadi M.M., “Studi pemodelan integrase pembangkit skala mikro terdistribusi pada daerah isolated di Aceh,” ISSN 2088-9984, no. November, 2012.
- [11] S. Yunus, “Analisa Pengaruh Integrasi Pembangkit Tersebar Dalam Sistem Komposit,” *J. Nas. Tek. Elektro*, vol. 3, no. 1, pp. 95–105, 2014.
- [12] M. Avin and A. L. Furqon, “Analisis operasi dinamis model generator sinkron dan induksi pada testbed microgrid,” *Univ. Gadjah Mada*, 2018.
- [13] F. Danang Wijaya, E.Firmansyah, Sarjiya, M. Isnaeni B.S, “ Grid Connected-Induction Generator Start-Up Sequence Observation Using Laboratory Simulator” 2015 IEEE Innovative Smart Grid Technologies - Asia (ISGT ASIA), 2015.
- [14] A. B. M. Nrratha, I Made Ari, “Analysis of the effect of scattered generating units on the dynamic stability of the power sistem,” P-ISSN: 1693-2951; E-ISSN: 2503-2372, vol. 8, no. 1, pp. 1–6, 2012.
- [15] F. Delfino, G. Ferro, M. Robba, and M. Rossi, “An architecture for the optimal control of tertiary and secondary levels in small-size islanded microgrids,” *Int. J. Electr. Power Energy Syst.*, vol. 103, no. April, pp. 75–88, 2018, doi: 10.1016/j.ijepes.2018.05.026.
- [16] O. Badran, S. Mekhilef, H. Mokhlis, and W. Dahalan, “Optimal reconfiguration of distribution sistem connected with distributed generations: A review of different



UNIVERSITAS
GADJAH MADA

**DINAMIKA KERJA GENERATOR SINKRON DAN GENERATOR INDUKSI PADA SISTEM TESTBED
MICROGRID DENGAN VARIASI
PANJANG SALURAN DAN PEMBEBANAN**

methodologies,” *Renew. Sustain. Energy Rev.*, vol. 73, no. January, pp. 854–867, 2017, doi:
UNIVERSITAS GADJAH MADA, 2022 | Diunduh dari <http://etd.repository.ugm.ac.id/>

10.1016/j.rser.2017.02.010.