

## DAFTAR PUSTAKA

- Abdel-Magid, B., Ziaee, S., Gass, K., & Schneider, M. (2005). The combined effects of load, moisture and temperature on the properties of E-glass/epoxy composites. *Composite Structures*, 71(3–4), 320–326.  
<https://doi.org/10.1016/j.compstruct.2005.09.022>
- Afendi, M., Banks, W. M., & Kirkwood, D. (2005). Bubble free resin for infusion process. *Composites Part A: Applied Science and Manufacturing*, 36(6), 739–746. <https://doi.org/10.1016/j.compositesa.2004.10.030>
- Akil, H. M., Cheng, L. W., Mohd Ishak, Z. A., Abu Bakar, A., & Abd Rahman, M. A. (2009). Water absorption study on pultruded jute fibre reinforced unsaturated polyester composites. *Composites Science and Technology*, 69(11:12), 1942:1948. <https://doi.org/10.1016/j.compscitech.2009.04.014>
- Alves, F. C., Monticeli, F. M., Neves, R. M., Voorwald, H. J. C., Cioffi, M. O. H., & Ornaghi, H. L. (2021). Influence of void content and morphology on the creep behavior on glass/epoxy composites. *Composites Communications*, 25(March). <https://doi.org/10.1016/j.coco.2021.100712>
- Bhatt, A. T., Gohil, P. P., & Chaudhary, V. (2021). Degassing and Layers Variation Effect on Composite Processing by Vacuum Assisted Resin Transfer Moulding. *Journal of Engineering Research*.  
<https://doi.org/10.36909/jer.9941>
- Bignotti, F., Pandini, S., Baldi, F., & Santis, R. De. (2011). Effect of the Resin/Hardener Ratio on Curing, Structure and Glass Transition Temperature of Nanofilled Epoxies. *Polymers and Polymer Composites*, 32(7), 1034:1048. <https://doi.org/https://doi.org/10.1002/pc.21120>
- Callister Jr, W. D., & Rethwisch, D. G. (2018). *Materials Science and Engineering - An Introduction 10th Edition*.
- D’Almeida, J. R. M., & Monteiro, S. N. (1996). The Effect of the resin/hardener ratio on the compressive behavior of an epoxy system. *Polymer Testing*, 15(4), 329–339. [https://doi.org/10.1016/0142-9418\(95\)00037-2](https://doi.org/10.1016/0142-9418(95)00037-2)

- D'Almeida, J. R. M., & Monteiro, S. N. (1998). The Influence Of The Hardener/Resin Ratio On The Impact Behavior Of An Epoxy System. *Journal of Polymer Engineering*, 4, 235–248.
- Fernandez-Nograro, F., Mondragon, I., Valea, A., & Llano-Ponte, R. (1996). *Epoxy Resins As a Function of Stoichiometry*. 32(2), 257–266.
- Ghani, M. A. A., Salleh, Z., Hyie, K. M., Berhan, M. N., Taib, Y. M. D., & Bakri, M. A. I. (2012). Mechanical properties of kenaf/fiberglass polyester hybrid composite. *Procedia Engineering*, 41, 1654:1659.  
<https://doi.org/10.1016/j.proeng.2012.07.364>
- Grand Rapids. (n.d.). *Differences - Amine, Amide, Cycloaliphatic, Amine Adduct Epoxy*. <https://www.vanguardconcretecoating.com/types-of-epoxy-resins.htm>
- Grave, C., Mcewan, I., & Pethrick, R. A. (1998). Influence of Stoichiometric Ratio on Water Absorption in Epoxy Resins. *Journal of Applied Polymer Science*, 69(12), 2369–2376.  
[https://doi.org/https://doi.org/10.1002/\(SICI\)1097-4628\(19980919\)69:12<2369::AID-APP8>3.0.CO;2-6](https://doi.org/https://doi.org/10.1002/(SICI)1097-4628(19980919)69:12<2369::AID-APP8>3.0.CO;2-6)
- Hoa, S. V. (2009). Principles of the Manufacturing of Composite Materials. In *DEStech Publications* (Vol. 39, Nomor 2). <https://doi.org/10.2307/3000>
- Huang, L. (2021). *Everything You Need to Know About Hardness of Materials*. <https://www.rapiddirect.com/blog/hardness-of-materials/>
- Katnam, K. B., Stevenson, J. P. J., Stanley, W. F., Buggy, M., & Young, T. M. (2011). Tensile strength of two-part epoxy paste adhesives: Influence of mixing technique and micro-void formation. *International Journal of Adhesion and Adhesives*, 31(7), 666–673.  
<https://doi.org/10.1016/j.ijadhadh.2011.06.005>
- King, R. L. (1989). Fibre-reinforced composites materials, manufacturing and design. In *Composites* (Vol. 20, Nomor 2). [https://doi.org/10.1016/0010-4361\(89\)90651-4](https://doi.org/10.1016/0010-4361(89)90651-4)
- Liu, L., Zhang, B. M., Wang, D. F., & Wu, Z. J. (2006). Effects of cure cycles on

void content and mechanical properties of composite laminates. *Composite Structures*, 73(3), 303–309. <https://doi.org/10.1016/j.compstruct.2005.02.001>

Makala, V. (n.d.). *Select Curing Agents for Coating Formulations*.

<https://coatings.specialchem.com/selection-guide/curing-agents-for-coating-formulations>

Maslinda, A. B., Abdul Majid, M. S., Ridzuan, M. J. M., Afendi, M., & Gibson, A. G. (2017). Effect of water absorption on the mechanical properties of hybrid interwoven cellulosic-cellulosic fibre reinforced epoxy composites. *Composite Structures*, 167, 227–237. <https://doi.org/10.1016/j.compstruct.2017.02.023>

Mazumdar, S. K. (2001). *Composites Manufacturing: Materials, Product, and Process Engineering* (First). CRC Press.

Meyer, F., Sanz, G., Eceiza, A., Mondragon, I., & Mijović, J. (1995). The effect of stoichiometry and thermal history during cure on structure and properties of epoxy networks. *Polymer*, 36(7), 1407–1414. [https://doi.org/10.1016/0032-3861\(95\)95918-Q](https://doi.org/10.1016/0032-3861(95)95918-Q)

Minty, R. F., Yang, L., & Thomason, J. L. (2018). The influence of hardener-to-epoxy ratio on the interfacial strength in glass fibre reinforced epoxy composites. *Composites Part A: Applied Science and Manufacturing*, 112, 64–70. <https://doi.org/10.1016/j.compositesa.2018.05.033>

Mora, A., Tayouo, R., Boutevin, B., David, G., Caillol, S., Caillol, S., Gerhardt, I. C., & Emile, A. (2020). A Perspective Approach on the Amine Reactivity and the Hydrogen Bonds Effect on Epoxy-amine Systems. *European Polymer Journal*, 123. <https://doi.org/https://doi.org/10.1016/j.eurpolymj.2019.109460>

Nunemaker, J. D., Voth, M. M., Miller, D. A., Samborsky, D. D., Murdy, P., & Cairns, D. S. (2018). Effects of moisture absorption on damage progression and strength of unidirectional and cross-ply fiberglass-epoxy composites. *Wind Energy Science*, 3(1), 427–438. <https://doi.org/10.5194/wes-3-427-2018>

- Ozeren Ozgul, E., & Ozkul, M. H. (2018). Effects of epoxy, hardener, and diluent types on the workability of epoxy mixtures. *Construction and Building Materials*, 158, 369–377. <https://doi.org/10.1016/j.conbuildmat.2017.10.008>
- Protz, R., Kosmann, N., Gude, M., Hufenbach, W., Schulte, K., & Fiedler, B. (2015). Voids and their effect on the strain rate dependent material properties and fatigue behaviour of non-crimp fabric composites materials. *Composites Part B: Engineering*, 83, 346–351. <https://doi.org/10.1016/j.compositesb.2015.08.018>
- Ran, Z., Liu, X., Jiang, X., Wu, Y., & Liao, H. (2020). Study on curing kinetics of epoxy-amine to reduce temperature caused by the exothermic reaction. *Thermochimica Acta*, 692(August), 178735. <https://doi.org/10.1016/j.tca.2020.178735>
- Romero, M. A. T. (2014). *State of the Art of degasification techniques, in the shaping processes of composite materials prepared by resin infusion* (Nomor February) [Universitat Politècnica de Catalunya]. <https://upcommons.upc.edu/handle/2117/86346>
- Schubnell, M., Caro, C. A. De, & Kunz, R. (2020). Moisture content, water content, loss on drying - Part 1: What exactly is meant and how are these quantities determined? *Thermal Analysis*, 1–8. <https://www.researchgate.net/publication/342420649>
- Sulaiman, S., Yunus, R., Ibrahim, N. A., & Rezafi, F. (2008). Effect of Hardener on Mechanical Properties of Carbon Fibre Reinforced Phenolic Resin Composites. *Journal of Engineering Science and Technology*, 3, 79–86.
- VanLandingham, M. R., Eduljee, R. F., & Gillespie, J. W. (1999). Moisture Diffusion in Epoxy Systems. *Journal of Applied Polymer Science*, 71(5), 787–798. [https://doi.org/10.1002/\(SICI\)1097-4628\(19990131\)71:5<787::AID-APP12>3.0.CO;2-A](https://doi.org/10.1002/(SICI)1097-4628(19990131)71:5<787::AID-APP12>3.0.CO;2-A)
- Vera Zambrano, M., Dutta, B., Mercer, D. G., MacLean, H. L., & Touchie, M. F. (2019). Assessment of moisture content measurement methods of dried food products in small-scale operations in developing countries: A review. *Trends*

*in Food Science and Technology*, 88(December 2018), 484–496.

<https://doi.org/10.1016/j.tifs.2019.04.006>

Wesolowski, P. (2013). *What is Moisture Content Analysis*.

<https://www.scientistlive.com/content/what-moisture-content-analysis>

Yohanes, Sidharta, I., Pramono, A. S., & Varian, K. (2021). The effect of epoxy/hardener composition ratio on the young's modulus of bulk adhesive at high strain rate. *IOP Conference Series: Materials Science and Engineering*, 1034(1), 012162. <https://doi.org/10.1088/1757-899x/1034/1/012162>

Yu, B., Jiang, Z., & Yang, J. (2015). Long-term moisture effects on the interfacial shear strength between surface treated carbon fiber and epoxy matrix. *Composites Part A: Applied Science and Manufacturing*, 78, 311–317. <https://doi.org/10.1016/j.compositesa.2015.08.027>

Zhu, H., Wu, B., Li, D., Zhang, D., & Chen, Y. (2011). Influence of Voids on the Tensile Performance of Carbon/epoxy Fabric Laminates. *Journal of Materials Science and Technology*, 27(1), 69–73. [https://doi.org/10.1016/S1005-0302\(11\)60028-5](https://doi.org/10.1016/S1005-0302(11)60028-5)