

TABLE OF CONTENT

| | |
|--|-------------|
| TITLE PAGE | i |
| SUPERVISOR APPROVAL PAGE | ii |
| EXAMINERS APPROVAL PAGE | iii |
| STATEMENT | iv |
| PREFACE | v |
| TABLE OF CONTENT | vii |
| LIST OF FIGURE | ix |
| LIST OF TABLE | xii |
| LIST OF ATTACHMENT | xiii |
| LIST OF NOTATION AND ABBREVIATION | xiv |
| ABSTRACT | xv |
| CHAPTER I | 1 |
| 1.1 Background | 1 |
| 1.2 Problem Statement | 3 |
| 1.3 Assumption | 3 |
| 1.4 Objectives of Research | 4 |
| 1.5 Benefit of Research | 4 |
| CHAPTER II | 5 |
| 2.1 Environmental Conditions | 6 |
| 2.2 Properties of Powder | 7 |
| 2.3 Design of Hopper | 10 |
| 2.4 Vibration Characteristic | 14 |
| CHAPTER III | 21 |
| 3.1 Composite | 21 |
| 3.1.1 Particle-reinforced | 21 |
| 3.1.2 Fiber-reinforced | 22 |
| 3.1.3 Structural-reinforced | 23 |
| 3.1.4 Nanocomposite | 24 |
| 3.2 Flowability of Powder | 25 |

| | | |
|---------------------|---|-----------|
| 3.3 | Powder Characterization Techniques | 26 |
| 3.4 | Porosity of material | 28 |
| 3.5 | Powder addition on the 3D printed product | 29 |
| 3.5.1 | Contiuous powder addition | 29 |
| 3.5.1 | Intermittent powder addition | 30 |
| CHAPTER IV | | 31 |
| 4.1 | Research Materials | 31 |
| 4.2 | Research Tools | 32 |
| 4.3 | Experimental Flowchart | 35 |
| 4.4 | Experimental Procedure | 37 |
| CHAPTER V | | 43 |
| 5.1 | Result | 43 |
| 5.1.1 | Powder Flowrate Characteristics | 43 |
| 5.1.2 | Printing Process with Continuous Powder Addition Method | 44 |
| 5.1.3 | Printing Process with Intermittent Powder Addition Method | 46 |
| 5.2 | Discussion | 52 |
| 5.2.1 | Powder Flowrate Characteristics | 52 |
| 5.2.2 | Printing process | 53 |
| CHAPTER VI | | 60 |
| 6.1 | Conclusion | 60 |
| 6.2 | Suggestion | 61 |
| BIBLIOGRAPHY | | 62 |
| ATTACHMENT | | 66 |