

BIBLIOGRAPHY

- Albaraki, S., & Antony, S. J. (2014). How does internal angle of hoppers affect granular flow? Experimental studies using digital particle image velocimetry. *Powder Technology*, 268(1), 253–260. <https://doi.org/10.1016/j.powtec.2014.08.027>
- Al-Hashemi, H. M. B., & Al-Amoudi, O. S. B. (2018). A review on the angle of repose of granular materials. In *Powder Technology* (Vol. 330, pp. 397–417). Elsevier B.V. <https://doi.org/10.1016/j.powtec.2018.02.003>
- Beran, T., Mulholland, T., Henning, F., Rudolph, N., & Osswald, T. A. (2018). Nozzle clogging factors during fused filament fabrication of spherical particle filled polymers. *Additive Manufacturing*, 23(August), 206–214. <https://doi.org/10.1016/j.addma.2018.08.009>
- Callister, W. D., & David Rethwisch, J. G. (2014). *MATERIALS SCIENCE and ENGINEERING* (D. Sayre, Ed.; 9th ed.).
- Chianrabutra, S., Mellor, B. G., & Yang, S. (2014). A dry powder material delivery device for multiple material additive manufacturing. *25th Annual International Solid Freeform Fabrication Symposium � An Additive Manufacturing Conference, SFF 2014*, 36–48.
- Clayton, J. (2018). An introduction to powder characterization. In *Handbook of Pharmaceutical Wet Granulation: Theory and Practice in a Quality by Design Paradigm* (pp. 569–613). Elsevier. <https://doi.org/10.1016/B978-0-12-810460-6.00021-X>
- Cleary, P. W., & Sawley, M. L. (2002). DEM modelling of industrial granular flows: 3D case studies and the effect of particle shape on hopper discharge. *Applied Mathematical Modelling*, 26(2), 89–111. [https://doi.org/10.1016/S0307-904X\(01\)00050-6](https://doi.org/10.1016/S0307-904X(01)00050-6)
- Fan, T., Liu, M., Ma, H., Liu, B., Shao, Y., & Zhao, Y. (2021). Investigation of the vibrating feeding system for sphericity separation of coated fuel particles using DEM. *Powder Technology*, 383, 131–142. <https://doi.org/10.1016/j.powtec.2021.01.037>
- Forsyth, A. J., Hutton, S., & Rhodes, M. J. (2002). Effect of cohesive interparticle force on the flow characteristics of granular material. *Powder Technology*, 126(2), 150–154. [https://doi.org/10.1016/S0032-5910\(02\)00046-3](https://doi.org/10.1016/S0032-5910(02)00046-3)
- Fraige, F. Y., Langston, P. A., & Chen, G. Z. (2008). Distinct element modelling of cubic particle packing and flow. *Powder Technology*, 186(3), 224–240. <https://doi.org/10.1016/j.powtec.2007.12.009>
- Gu, D. D., Meiners, W., Wissenbach, K., & Poprawe, R. (2012). Laser additive manufacturing of metallic components: Materials, processes and mechanisms. *International Materials Reviews*, 57(3), 133–164. <https://doi.org/10.1179/1743280411Y.0000000014>
- Hague, R., Campbell, I., & Dickens, P. (2003). Implications on design of rapid manufacturing. *Mechanical Engineering Science*, 217, 25–30.
- Hernandez, S. G., Gonzalez, D. G., Jérusalem, A., & Arias, A. (2020). Design of FDM 3D printed polymers: An experimental-modelling methodology for the

- prediction of mechanical properties. *Materials and Design*, 188. <https://doi.org/10.1016/j.matdes.2019.108414>
- Hussin, N. (2011). *The effects of crosslinking byproducts on the electrical properties of low density polyethylene Damping Improvement of Power System Oscillations by Using Optimal Coordinated Design between PSS and SVC-Based Stabilizer View project The Effect of Crosslinking Byproduct on the electrical properties of LDPE View project*. <https://www.researchgate.net/publication/279640781>
- Jenike, A. W. (1967). Design of Mass-Flow. *Powder Technology*, 4(1), 237–244.
- Jiang, Y., Matsusaka, S., Masuda, H., & Qian, Y. (2009a). Development of measurement system for powder flowability based on vibrating capillary method. *Powder Technology*, 188(3), 242–247. <https://doi.org/10.1016/j.powtec.2008.05.003>
- Keleş, Ö., Blevins, C. W., & Bowman, K. J. (2017). Effect of build orientation on the mechanical reliability of 3D printed ABS. *Rapid Prototyping Journal*, 23(2), 320–328. <https://doi.org/10.1108/RPJ-09-2015-0122>
- Lee, C. Y., & Liu, C. Y. (2019). The influence of forced-air cooling on a 3D printed PLA part manufactured by fused filament fabrication. *Additive Manufacturing*, 25, 196–203. <https://doi.org/10.1016/j.addma.2018.11.012>
- Lu, H., Guo, X., Liu, Y., & Gong, X. (2015). Effect of particle size on flow mode and flow characteristics of pulverized coal. *KONA Powder and Particle Journal*, 32, 143–153. <https://doi.org/10.14356/kona.2015002>
- Lu, X., Yang, S., & Evans, J. R. G. (2006). Studies on ultrasonic microfeeding of fine powders. *Journal of Physics D: Applied Physics*, 39(11), 2444–2453. <https://doi.org/10.1088/0022-3727/39/11/020>
- Mathew, A. P., Oksman, K., & Sain, M. (2006). The effect of morphology and chemical characteristics of cellulose reinforcements on the crystallinity of polylactic acid. *Journal of Applied Polymer Science*, 101(1), 300–310. <https://doi.org/10.1002/app.23346>
- Matsusaka, S., Yamamoto, K., & Masuda, H. (1996). Micro-feeding of a fine powder using a vibrating capillary tube. *Advanced Powder Technology*, 7(2), 141–151. [https://doi.org/10.1016/S0921-8831\(08\)60509-9](https://doi.org/10.1016/S0921-8831(08)60509-9)
- Nakashima, H., Shioji, Y., Kobayashi, T., Aoki, S., Shimizu, H., Miyasaka, J., & Ohdoi, K. (2011). Determining the angle of repose of sand under low-gravity conditions using discrete element method. *Journal of Terramechanics*, 48(1), 17–26. <https://doi.org/10.1016/j.jterra.2010.09.002>
- Ngo, T. D., Kashani, A., Imbalzano, G., Nguyen, K. T. Q., & Hui, D. (2018). Additive manufacturing (3D printing): A review of materials, methods, applications and challenges. *Composites Part B: Engineering*, 143(December 2017), 172–196. <https://doi.org/10.1016/j.compositesb.2018.02.012>
- Ning, F., Cong, W., Qiu, J., Wei, J., & Wang, S. (2015a). Additive manufacturing of carbon fiber reinforced thermoplastic composites using fused deposition modeling. *Composites Part B: Engineering*, 80, 369–378. <https://doi.org/10.1016/j.compositesb.2015.06.013>
- Pandzic, A., Hodzic, D., & Milovanovic, A. (2019). Influence of material colour on mechanical properties of pla material in fdm technology. *Annals of DAAAM and*

- Proceedings of the International DAAAM Symposium*, 30(1), 555–561.
<https://doi.org/10.2507/30th.daaam.proceedings.075>
- Pedersen, B. (2013). *Additive Manufacturing: Multi Material Processing and Part Quality Control*. Technical University of Denmark.
- Pratama, J., Cahyono, S. I., Suyitno, S., Muflikhun, M. A., Salim, U. A., Mahardika, M., & Arifvianto, B. (2021). A review on reinforcement methods for polymeric materials processed using fused filament fabrication (Fff). *Polymers*, 13(22), 1–23. <https://doi.org/10.3390/polym13224022>
- Schulze, D. (2021). Powders and Bulk Solids. In *Powders and Bulk Solids*.
<https://doi.org/10.1007/978-3-030-76720-4>
- Shrivastava, A. (2018). Introduction to Plastics Engineering. In *Introduction to Plastics Engineering* (pp. 1–16). Elsevier. <https://doi.org/10.1016/b978-0-323-39500-7.00001-0>
- Sood, A. K., Ohdar, R. K., & Mahapatra, S. S. (2012). Experimental investigation and empirical modelling of FDM process for compressive strength improvement. *Journal of Advanced Research*, 3(1), 81–90.
<https://doi.org/10.1016/j.jare.2011.05.001>
- Spoerk, M., Arbeiter, F., Cajner, H., Sapkota, J., & Holzer, C. (2017). Parametric optimization of intra- and inter-layer strengths in parts produced by extrusion-based additive manufacturing of poly(lactic acid). *Journal of Applied Polymer Science*, 134(41). <https://doi.org/10.1002/app.45401>
- Sutton, A. T., Kriewall, C. S., Leu, M. C., & Newkirk, J. W. (2017). Powder characterisation techniques and effects of powder characteristics on part properties in powder-bed fusion processes. *Virtual and Physical Prototyping*, 12(1), 3–29. <https://doi.org/10.1080/17452759.2016.1250605>
- Turner, B. N., Strong, R., & Gold, S. A. (2014). A review of melt extrusion additive manufacturing processes: I. Process design and modeling. *Rapid Prototyping Journal*, 20(3), 192–204. <https://doi.org/10.1108/RPJ-01-2013-0012>
- Wei, C., Gu, H., Zhang, X., Chueh, Y. hui, & Li, L. (2020). Hybrid ultrasonic and mini-motor vibration-induced irregularly shaped powder delivery for multiple materials additive manufacturing. *Additive Manufacturing*, 33(November 2019), 101138. <https://doi.org/10.1016/j.addma.2020.101138>
- Wijaya. (2018). *PENGARUH PENAMBAHAN SERBUK NANO MAGNETITE PADA POLIMER PLA DENGAN MENGGUNAKAN 3D PRINTER MELALUI METODE COMPRESSED-AIR-ASSISTED*. Universitas Gadjah Mada.
- Wu, H., Pritchett, D., Wolff, S., Cao, J., Ehmann, K., & Zou, P. (2020). A VIBRATION-ASSISTED POWDER DELIVERY SYSTEM FOR ADDITIVE MANUFACTURING - An experimental investigation -. *Additive Manufacturing*, 34(November 2019), 101170. <https://doi.org/10.1016/j.addma.2020.101170>
- Yang, S., & Evans, J. R. G. (2004). Acoustic control of powder dispensing in open tubes. *Powder Technology*, 139(1), 55–60.
<https://doi.org/10.1016/j.powtec.2003.10.008>
- Yang, S., & Evans, J. R. G. (2007). Metering and dispensing of powder; the quest for new solid freeforming techniques. *Powder Technology*, 178(1), 56–72.
<https://doi.org/10.1016/j.powtec.2007.04.004>

- Zainuddin, I. M., Yasuda, M., Horio, T., & Matsusaka, S. (2012). Experimental study on powder flowability using vibration shear tube method. *Particle and Particle Systems Characterization*, 29(1), 8–15.
<https://doi.org/10.1002/ppsc.201100052>
- Zainuddin, M. I., Yasuda, M., Liu, Y. H., Maruyama, H., & Matsusaka, S. (2012). Development of vibration shear tube method for powder flowability evaluation. *Powder Technology*, 217, 548–553.
<https://doi.org/10.1016/j.powtec.2011.11.013>
- Zhang, X., Wei, C., Chueh, Y. H., & Li, L. (2019). An integrated dual ultrasonic selective powder dispensing platform for three-dimensional printing of multiple material metal/glass objects in selective laser melting. *Journal of Manufacturing Science and Engineering, Transactions of the ASME*, 141(1).
<https://doi.org/10.1115/1.4041427>
- Zhu, K., Tan, R. B. H., Chen, F., Ong, K. H., & Heng, P. W. S. (2007). Influence of particle wall adhesion on particle electrification in mixers. *International Journal of Pharmaceutics*, 328(1 SPEC. ISS.), 22–34.
<https://doi.org/10.1016/j.ijpharm.2006.07.041>