

## DAFTAR PUSTAKA

- [1] M. Santamouris dan K. Vasilakopoulou, "Present and future energy consumption of buildings: Challenges and opportunities towards decarbonisation," *e-Prime - Advances in Electrical Engineering, Electronics and Energy*, vol. 1, hlm. 100002, 2021.
- [2] International Energy Agency, *Perspective from the clean energy transition. The critical role of buildings*. 2019.
- [3] United Nations Environment Programme dan Global Alliance for Buildings and Construction, *2020 Global Status Report for Buildings and Construction: Towards a Zero-emissions, Efficient and Resilient Buildings and Construction Sector - Executive Summary*. 2020.
- [4] N. Al-Tamimi, "Passive Design Strategies for Energy Efficient Buildings in the Arabian Desert," *Frontiers in Built Environment*, vol. 7, no. 805603, hlm. 1–11, 2022.
- [5] B. Nourozi, A. Ploskić, Y. Chen, J. Ning-Wei Chiu, dan Q. Wang, "Heat transfer model for energy-active windows – An evaluation of efficient reuse of waste heat in buildings," *Renewable Energy*, vol. 162, hlm. 2318–2329, Des 2020, doi: 10.1016/j.renene.2020.10.043.
- [6] S. C. Nunes dkk., "Sustainable Dual-Mode Smart Windows for Energy-Efficient Buildings," *ACS Appl. Energy Mater.*, vol. 2, no. 3, hlm. 1951–1960, 2019.
- [7] Y. Li, E. Vasileva, I. Sychugov, S. Popov, dan L. Berglund, "Optically Transparent Wood: Recent Progress, Opportunities, and Challenges," *Advanced Optical Materials*, vol. 6, no. 14, hlm. 1800059, 2018.
- [8] Hermawan, E. Prianto, dan E. Setyowati, "The Difference of Thermal Performance between Houses with Wooden Walls and Exposed Brick Walls in Tropical Coasts," *Procedia Environmental Sciences*, vol. 23, hlm. 168–174, Jan 2015, doi: 10.1016/j.proenv.2015.01.026.
- [9] S. Fink, "Transparent Wood – A New Approach in the Functional Study of Wood Structure," vol. 46, no. 5, hlm. 403–408, Jan 1992, doi: 10.1515/hfsg.1992.46.5.403.
- [10] Y. Li, Q. Fu, S. Yu, M. Yan, dan L. Berglund, "Optically Transparent Wood from a Nanoporous Cellulosic Template: Combining Functional and Structural Performance," *Biomacromolecules*, vol. 17, no. 4, hlm. 1358–1364, Apr 2016, doi: 10.1021/acs.biomac.6b00145.
- [11] R. Mi dkk., "A Clear, Strong, and Thermally Insulated Transparent Wood for Energy Efficient Windows," *Advanced Functional Materials*, vol. 30, no. 1, hlm. 1907511, 2020.
- [12] Y. Li, Q. Fu, R. Rojas, M. Yan, M. Lawoko, dan L. Berglund, "Lignin-Retaining Transparent Wood," *ChemSusChem*, vol. 10, no. 17, hlm. 3445–3451, 2017, doi: 10.1002/cssc.201701089.
- [13] Y. Wu dkk., "Study on the Colorimetry Properties of Transparent Wood Prepared from Six Wood Species," *ACS Omega*, vol. 5, no. 4, hlm. 1782–1788, Feb 2020, doi: 10.1021/acsomega.9b02498.



- [14] J. Wu, Y. Wu, F. Yang, C. Tang, Q. Huang, dan J. Zhang, "Impact of delignification on morphological, optical and mechanical properties of transparent wood," *Composites Part A: Applied Science and Manufacturing*, vol. 117, hlm. 324–331, Feb 2019, doi: 10.1016/j.compositesa.2018.12.004.
- [15] D. Yue, G. Fu, dan Z. Jin, "Transparent Wood Prepared by Polymer Impregnation of Rubber Wood (*Hevea brasiliensis* Muell. Arg)," *BioResources*, vol. 16, no. 2, Art. no. 2, Feb 2021, Diakses: 11 Oktober 2022. [Daring]. Tersedia pada: [https://ojs.cnr.ncsu.edu/index.php/BioRes/article/view/BioRes\\_16\\_2\\_2491\\_Yue\\_Transparent\\_Wood\\_Polymer\\_Impregnation](https://ojs.cnr.ncsu.edu/index.php/BioRes/article/view/BioRes_16_2_2491_Yue_Transparent_Wood_Polymer_Impregnation)
- [16] N. Y. M. Yunus, N. N. Sofian, W. M. N. W. A. Rahman, dan N. H. M. Hassan, "DELIGNIFICATION AND EPOXY IMPREGNATION ON KEDONDONG VENEER," *International Journal of Engineering Advanced Research*, vol. 4, no. 1, Art. no. 1, Mar 2022, Diakses: 26 September 2022. [Daring]. Tersedia pada: <https://myjms.mohe.gov.my/index.php/ijear/article/view/17728>
- [17] C. Jia dkk., "Clear Wood toward High-Performance Building Materials," *ACS Nano*, vol. 13, no. 9, hlm. 9993–10001, Sep 2019, doi: 10.1021/acsnano.9b00089.
- [18] A. N. Subba Rao, G. B. Nagarajappa, S. Nair, A. M. Chathoth, dan K. K. Pandey, "Flexible transparent wood prepared from poplar veneer and polyvinyl alcohol," *Composites Science and Technology*, vol. 182, hlm. 107719, Sep 2019, doi: 10.1016/j.compscitech.2019.107719.
- [19] M. Zhu dkk., "Transparent and haze wood composites for highly efficient broadband light management in solar cells," *Nano Energy*, vol. 26, hlm. 332–339, Agu 2016, doi: 10.1016/j.nanoen.2016.05.020.
- [20] L. Yang, Y. Wu, F. Yang, dan W. Wang, "Study on the preparation process and performance of a conductive, flexible, and transparent wood," *Journal of Materials Research and Technology*, vol. 15, hlm. 5396–5404, Nov 2021, doi: 10.1016/j.jmrt.2021.11.021.
- [21] Y. Wu, J. Zhou, F. Yang, Y. Wang, J. Wang, dan J. Zhang, "A strong multilayered transparent wood with natural wood color and texture," *J Mater Sci*, vol. 56, no. 13, hlm. 8000–8013, Mei 2021, doi: 10.1007/s10853-021-05833-1.
- [22] E. Jungstedt, C. Montanari, S. Östlund, dan L. Berglund, "Mechanical properties of transparent high strength biocomposites from delignified wood veneer," *Composites Part A: Applied Science and Manufacturing*, vol. 133, hlm. 105853, 2020.
- [23] W. Zou, D. Sun, Z. Wang, R. Li, W. Yu, dan P. Zhang, "Eco-friendly transparent poplar-based composites that are stable and flexible at high temperature," *RSC Adv.*, vol. 9, no. 37, hlm. 21566–21571, Jul 2019, doi: 10.1039/C9RA03550H.
- [24] P. Bisht, K. K. Pandey, dan S. G., "Optical properties of transparent wood composites prepared using transverse sections of poplar wood," *Holzforschung*, vol. 76, no. 7, hlm. 658–667, Jul 2022, doi: 10.1515/hf-2021-0242.



- [25] J. Popović *dkk.*, “Light Transmittance of Mahogany Wood Treated with 20% Hydrogen Peroxide Solution,” *BioResources*, vol. 17, no. 4, Art. no. 4, Nov 2022, Diakses: 6 Januari 2023. [Daring]. Tersedia pada: <https://ojs.cnr.ncsu.edu/index.php/BRJ/article/view/22053>
- [26] Q. Xia *dkk.*, “Solar-assisted fabrication of large-scale, patternable transparent wood,” *Science Advances*, vol. 7, no. 5, hlm. eabd7342, Jan 2021, doi: 10.1126/sciadv.abd7342.
- [27] H. S. Yaddanapudi, N. Hickerson, S. Saini, dan A. Tiwari, “Fabrication and characterization of transparent wood for next generation smart building applications,” *Vacuum*, vol. 146, hlm. 649–654, Des 2017, doi: 10.1016/j.vacuum.2017.01.016.
- [28] Z. Yu *dkk.*, “Transparent wood containing CsxWO<sub>3</sub> nanoparticles for heat-shielding window applications,” *J. Mater. Chem. A*, vol. 5, no. 13, hlm. 6019–6024, 2017, doi: 10.1039/C7TA00261K.
- [29] L. J. Gibson, “The hierarchical structure and mechanics of plant materials,” *Journal of The Royal Society Interface*, vol. 9, no. 76, hlm. 2749–2766, Nov 2012, doi: 10.1098/rsif.2012.0341.
- [30] M. H. Ramage *dkk.*, “The wood from the trees: The use of timber in construction,” *Renewable and Sustainable Energy Reviews*, vol. 68, hlm. 333–359, Feb 2017.
- [31] L. Hu, X. Fang, M. Du, F. Luo, dan S. Guo, “Hemicellulose-Based Polymers Processing and Application,” *American Journal of Plant Sciences*, vol. 11, no. 12, Art. no. 12, Des 2020, doi: 10.4236/ajps.2020.1112146.
- [32] E. Sjöström, “Chapter 1 - THE STRUCTURE OF WOOD,” dalam *Wood Chemistry (Second Edition)*, E. Sjöström, Ed. San Diego: Academic Press, 1993, hlm. 1–20. doi: 10.1016/B978-0-08-092589-9.50005-X.
- [33] R. M. Rowell, R. Pettersen, dan M. A. Tshabalala, *Handbook of Wood Chemistry and Wood Composites*. Routledge Handbooks Online, 2012. doi: 10.1201/b12487-5.
- [34] M. A. Frey, “Delignified and Densified Wood - A Versatile Concept for New High-Performance Wood-Based Materials,” ETH Zurich, 2020.
- [35] P. K. Gupta *dkk.*, *An Update on Overview of Cellulose, Its Structure and Applications*. IntechOpen, 2019. doi: 10.5772/intechopen.84727.
- [36] L.-Z. Huang, M.-G. Ma, X.-X. Ji, S.-E. Choi, dan C. Si, “Recent Developments and Applications of Hemicellulose From Wheat Straw: A Review,” *Front Bioeng Biotechnol*, vol. 9, hlm. 690773, Jun 2021, doi: 10.3389/fbioe.2021.690773.
- [37] A. More, T. Elder, dan Z. Jiang, “A review of lignin hydrogen peroxide oxidation chemistry with emphasis on aromatic aldehydes and acids,” *Holzforschung*, vol. 75, no. 9, hlm. 806–823, Sep 2021, doi: 10.1515/hf-2020-0165.
- [38] S. Wang, “Chemical Modification of Nanostructured Wood for Functional Biocomposites,” KTH Royal Institute of Technology, Swedia, 2021. Diakses: 11 Januari 2023. [Daring]. Tersedia pada: <https://www.diva-portal.org/smash/get/diva2:1555818/FULLTEXT01.pdf>



- [39] C. Montanari, "Transparent Wood Biocomposites for Sustainable Development," KTH Royal Institute of Technology, 2022. Diakses: 11 Januari 2023. [Daring]. Tersedia pada: <http://urn.kb.se/resolve?urn=urn:nbn:se:kth:diva-306718>
- [40] D. Barman, A. Md, Md. M. Hossain, S. Paul, dan H. Yun, "Deconstruction of Pine Wood (*Pinus sylvestris*) Recalcitrant Structure Using Alkali Treatment for Enhancing Enzymatic Saccharification Evaluated by Congo Red," *Waste and Biomass Valorization*, vol. 11, Mei 2020, doi: 10.1007/s12649-018-00547-z.
- [41] J. Li, C. Chen, J. Y. Zhu, A. J. Ragauskas, dan L. Hu, "In Situ Wood Delignification toward Sustainable Applications," *Acc. Mater. Res.*, vol. 2, no. 8, hlm. 606–620, Agu 2021, doi: 10.1021/accountsmr.1c00075.
- [42] M. C. Iglesias, D. Gomez-Maldonado, B. K. Via, Z. Jiang, dan M. S. Peresin, "Pulping Processes and Their Effects on Cellulose Fibers and Nanofibrillated Cellulose Properties: A Review," *Forest Products Journal*, vol. 70, no. 1, hlm. 10–21, 2020, doi: 10.13073/FPJ-D-19-00038.
- [43] H. Sixta, Ed., *Handbook of Pulp*. Wiley-VCH, 2006.
- [44] Y. Li, Q. Fu, X. Yang, dan L. Berglund, "Transparent wood for functional and structural applications," *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, vol. 376, no. 2112, hlm. 20170182, Feb 2018, doi: 10.1098/rsta.2017.0182.
- [45] C. Wan, X. Liu, Q. Huang, W. Cheng, J. Su, dan Y. Wu, "A Brief Review of Transparent Wood: Synthetic Strategy, Functionalization and Applications," *Current Organic Synthesis*, vol. 18, no. 7, hlm. 615–623, 2021, Diakses: 18 Januari 2023. [Daring]. Tersedia pada: <https://www.eurekaselect.com/article/116146>
- [46] D. Halliday, R. Resnick, dan J. Walker, *Fundamentals of Physics, 7th Extended Edition*. John Wiley & Sons, 2005.
- [47] A. G. Alkholidi, K. S. Altowij, A. G. Alkholidi, dan K. S. Altowij, *Free Space Optical Communications — Theory and Practices*. IntechOpen, 2014. doi: 10.5772/58884.
- [48] D. Al-Shamkhee, A. B. Al-Aasam, A. H. A. Al-Waeli, G. Y. Abusaibaa, dan H. Moria, "Passive cooling techniques for ventilation: an updated review," *Renew. Energy Environ. Sustain.*, vol. 7, hlm. 23, 2022, doi: 10.1051/rees/2022011.
- [49] M. Santamouris, A. A. Argiriou, dan C. A. Balaras, "Developments on passive cooling in buildings -- Results from recent research," dalam *ASHRAE Transactions*, 1997. Diakses: 18 Januari 2023. [Daring]. Tersedia pada: <https://www.osti.gov/biblio/345297>
- [50] F. C. Campbell, Ed., "Mechanical Behavior," dalam *Elements of Metallurgy and Engineering Alloys*, ASM International, 2008, hlm. 201–220. Diakses: 11 Januari 2023. [Daring]. Tersedia pada: <https://dl.asminternational.org/technical-books/monograph/94/chapter/2104457/Mechanical-Behavior>
- [51] N. Özkaya, D. Leger, D. Goldsheyder, dan M. Nordin, "Stress and Strain," dalam *Fundamentals of Biomechanics: Equilibrium, Motion, and Deformation*,



- N. Özkaya, D. Leger, D. Goldsheyder, dan M. Nordin, Ed. Cham: Springer International Publishing, 2017, hlm. 287–315. doi: 10.1007/978-3-319-44738-4\_13.
- [52] D. W. Green, J. E. Winandy, dan D. E. Kretschmann, “Mechanical properties of wood,” dalam *Wood Handbook: Wood as an Engineering Material*, vol. 113, 1999. Diakses: 15 Januari 2023. [Daring]. Tersedia pada: <https://www.srs.fs.usda.gov/pubs/7149>
- [53] S. Shang, L. Gan, dan C.-W. M. Yuen, “Water-dispersible graphene stabilized by PVA grafted graphene and its poly (vinyl alcohol) nanocomposites,” *Technical Proceedings of the 2014 NSTI Nanotechnology Conference and Expo, NSTI-Nanotech 2014*, vol. 1, hlm. 388–391, Jan 2014.
- [54] I. Brensons, S. Polukoshko, A. Silins, dan N. Mozga, “FDM Prototype Experimental Research of Processing Parameter Optimization to Achieve Higher Tensile Stress,” *Solid State Phenomena*, vol. 220–221, hlm. 767–773, Jan 2015, doi: 10.4028/www.scientific.net/SSP.220-221.767.
- [55] E.-S. Jang dan C.-W. Kang, “Porosity analysis of three types of balsa (Ochroma pyramidale) wood depending on density,” *Journal of Wood Science*, vol. 68, no. 1, hlm. 31, Mei 2022, doi: 10.1186/s10086-022-02037-2.
- [56] G. Newaz, M. Mayeed, dan A. Rasul, “Characterization of balsa wood mechanical properties required for continuum damage mechanics analysis,” *Proceedings of the Institution of Mechanical Engineers, Part L: Journal of Materials: Design and Applications*, vol. 230, no. 1, hlm. 206–218, Feb 2016, doi: 10.1177/1464420714564711.
- [57] X. Yin, Y. Zhang, dan Y. Xu, “Luminescent Transparent Wood from Balsa wood (Ochroma pyramidale) Loaded by Graphite Carbon Nitride for Implication of Photoelectric Devic.” 2022. doi: 10.21203/rs.3.rs-1974379/v1.
- [58] R. Mi dkk., “Scalable aesthetic transparent wood for energy efficient buildings,” *Nat Commun*, vol. 11, no. 1, Art. no. 1, Jul 2020, doi: 10.1038/s41467-020-17513-w.
- [59] Y. Wu, J. Wu, F. Yang, C. Tang, dan Q. Huang, “Effect of H<sub>2</sub>O<sub>2</sub> Bleaching Treatment on the Properties of Finished Transparent Wood,” *Polymers*, vol. 11, no. 5, Art. no. 5, Mei 2019, doi: 10.3390/polym11050776.
- [60] S. Migneault, A. Koubaa, P. Perré, dan B. Riedl, “Effects of wood fiber surface chemistry on strength of wood–plastic composites,” *Applied Surface Science*, vol. 343, hlm. 11–18, Jul 2015, doi: 10.1016/j.apsusc.2015.03.010.
- [61] B. Buchelt dan A. Pfriem, “Influence of wood specimen thickness on its mechanical properties by tensile testing: Solid wood versus veneer,” *Holzforschung*, vol. 65, hlm. 249–252, Mar 2011, doi: 10.1515/hf.2011.032.
- [62] G. Y. Jeong, D. Hindman, D. Finkenbinder, J. Lee, dan Z. Lin, “Effect of loading rate and thickness on the tensile properties of wood strands,” *Forest Products Journal*, vol. 58, hlm. 33–37, Okt 2008.
- [63] M. Pramreiter dkk., “The Influence of Thickness on the Tensile Strength of Finnish Birch Veneers under Varying Load Angles,” *Forests*, vol. 12, no. 1, Art. no. 1, Jan 2021, doi: 10.3390/f12010087.





- [64] X. Wang *dkk.*, “Large-Size Transparent Wood for Energy-Saving Building Applications,” *ChemSusChem*, vol. 11, no. 23, hlm. 4086–4093, 2018, doi: 10.1002/cssc.201801826.

