

## DAFTAR PUSTAKA

- Al Issa, S., & Macian-Juan, R. (2011). A review of CCFL phenomenon. *Annals of Nuclear Energy*, 38(9), 1795–1819.  
<https://doi.org/10.1016/j.anucene.2011.04.021>
- Al Issa, S., & Macian-Juan, R. (2014). Experimental investigation of countercurrent flow limitation (CCFL) in a large-diameter hot-leg geometry: A detailed description of CCFL mechanisms, flow patterns and high-quality HSC imaging of the interfacial structure in a 1/3.9 scale of PWR geometry. *Nuclear Engineering and Design*, 280, 550–563.  
<https://doi.org/10.1016/j.nucengdes.2014.08.021>
- Al Issa, Suleiman. (2021). A new correlation for CCFL at full scale PWR excluding the Hutze effect in UPTF data. *Nuclear Engineering and Design*, 383(July). <https://doi.org/10.1016/j.nucengdes.2021.111402>
- Al Issa, Suleiman, & Macián-Juan, R. (2017). Image-processing of time-averaged interface distributions representing CCFL characteristics in a large scale model of a PWR hot-leg pipe geometry. *Annals of Nuclear Energy*, 103, 282–293. <https://doi.org/10.1016/j.anucene.2017.01.021>
- Ardron, K. H., & Banerjee, S. (1986). Flooding in an elbow between a vertical and a horizontal or near-horizontal pipe. Part II: Theory. *International Journal of Multiphase Flow*, 12(4), 543–558. [https://doi.org/10.1016/0301-9322\(86\)90059-5](https://doi.org/10.1016/0301-9322(86)90059-5)
- Astyanto, A. H., Nugroho, A. N. A., Catrawedarma, I. G. N. B., Indarto, Lucas, D., & Deendarlianto. (2023). Statistical characterization of the interfacial behavior captured by a novel image processing algorithm during the gas / liquid counter-current two-phase flow in a 1 / 3 scaled down of PWR hot leg. *Nuclear Engineering and Design*, 404(2), 112179.  
<https://doi.org/10.1016/j.nucengdes.2023.112179>
- Astyanto, A. H., Pramono, J. A. E., Catrawedarma, I. G. N. B., Deendarlianto, & Indarto. (2022). Statistical characterization of liquid film fluctuations during gas-liquid two-phase counter-current flow in a 1/30 scaled-down test facility of a pressurized water reactor (PWR) hot leg. *Annals of Nuclear Energy*, 172, 109065. <https://doi.org/10.1016/j.anucene.2022.109065>
- Astyanto, A. H., Rahman, Y., Adhikara, A. Y., Indarto, & Deendarlianto. (2021). Time-series differential pressure fluctuations of a flooding regime : A preliminary experimental results investigation on a 1 / 30 down- scaled PWR hot leg geometry. *AIP Conference Proceedings*, 060001(2011).
- Astyanto, A. H., Rahman, Y., Medha, A. Y. A., Deendarlianto, & Indarto. (2021). Pengaruh Rasio I/D terhadap Permulaan Flooding dan Fluktuasi Voltase Sinyal Tekanan Rezim Flooding pada Geometri Kompleks. *Rekayasa Mesin*, 12(August), 447–457.  
<https://doi.org/https://doi.org/10.21776/ub.jrm.2021.012.02.21>
- Badarudin, A., Pinindriya, S. T., Yoanita, Y. V., Hadipranoto, M. S., Hartono, S., Ariawan, R., Indarto, & Deendarlianto. (2018). The effect of horizontal pipe length to the onset of flooding position on the air-water counter current two-

- phase flow in a 1/30 scale of pressurized water reactor (PWR). *AIP Conference Proceedings*, 2001(June 2020).  
<https://doi.org/10.1063/1.5049983>
- Badarudin, Apip, Indarto, Deendarlianto, & Setyawan, A. (2016). Characteristics of the air-water counter current two-phase flow in a 1/30 scale of pressurized water reactor (PWR): Interfacial behavior and CCFL data. *AIP Conference Proceedings*, 1737. <https://doi.org/10.1063/1.4949303>
- Badarudin, Apip, Setyawan, A., Dinaryanto, O., Widyatama, A., Indarto, & Deendarlianto. (2018). Interfacial behavior of the air-water counter-current two-phase flow in a 1/30 scale-down of pressurized water reactor (PWR) hot leg. *Annals of Nuclear Energy*, 116, 376–387.  
<https://doi.org/10.1016/j.anucene.2018.03.007>
- Canière, H., T'joen, C., Willockx, a., De Paepe, M., Christians, M., Van Rooyen, E., Liebenberg, L., & Meyer, J. P. (2007). Horizontal two-phase flow characterization for small diameter tubes with a capacitance sensor. *Measurement Science and Technology*, 18(9), 2898–2906.  
<https://doi.org/10.1088/0957-0233/18/9/020>
- Catrawedarma, I., Deendarlianto, & Indarto. (2021). Hydrodynamic behaviors of air–water two-phase flow during the water lifting in a bubble generator type of airlift pump system. *Heat and Mass Transfer/Waerme- Und Stoffuebertragung*, 0123456789. <https://doi.org/10.1007/s00231-021-03157-z>
- Catrawedarma, I. G. N. B., Deendarlianto, & Indarto. (2021). Statistical Characterization of Flow Structure of Air–water Two-phase Flow in Airlift Pump–Bubble Generator System. *International Journal of Multiphase Flow*, 138, 103596. <https://doi.org/10.1016/j.ijmultiphaseflow.2021.103596>
- Catrawedarma, I. G. N. B., Resnaraditya, F. A., Deendarlianto, & Indarto. (2021). Statistical characterization of the flow Structure of air–water–solid particles three-phase flow in the airlift pump–bubble generator system. *Flow Measurement and Instrumentation*, 82(2018), 102062.
- Cetinbudaklar, A. G., & Jameson, G. J. (1969). The mechanism of flooding in vertical countercurrent two-phase flow. *Chemical Engineering Science*, 24(11), 1669–1680. [https://doi.org/10.1016/0009-2509\(69\)87032-6](https://doi.org/10.1016/0009-2509(69)87032-6)
- Choi, K. Y., & No, H. C. (1995). Experimental studies of flooding in nearly horizontal pipes. *International Journal of Multiphase Flow*, 21(3), 419–436. [https://doi.org/10.1016/0301-9322\(94\)00087-Z](https://doi.org/10.1016/0301-9322(94)00087-Z)
- Clift, R., Pritchard, C. L., & Nedderman, R. M. (1966). The effect of viscosity on the flooding conditions in wetted wall columns. *Chemical Engineering Science*, 21(1), 87–95. [https://doi.org/10.1016/0009-2509\(66\)80009-X](https://doi.org/10.1016/0009-2509(66)80009-X)
- De Kerpel, K., De Schampheleire, S., De Keulenaer, T., & De Paepe, M. (2015). Two-phase flow regime assignment based on wavelet features of a capacitance signal. *International Journal of Heat and Fluid Flow*, 56, 317–323. <https://doi.org/10.1016/j.ijheatfluidflow.2015.09.002>
- Deendarlianto, D., Höhne, T., Lucas, D., Vallée, C., & Zabala, G. A. M. (2011). CFD studies on the phenomena around counter-current flow limitations of gas/liquid two-phase flow in a model of a PWR hot leg. *Nuclear Engineering and Design*, 241(12), 5138–5148.

- <https://doi.org/10.1016/j.nucengdes.2011.08.071>
- Deendarlianto, Höhne, T., Apanasevich, P., Lucas, D., Vallée, C., & Beyer, M. (2012). Application of a new drag coefficient model at CFD-simulations on free surface flows relevant for the nuclear reactor safety analysis. *Annals of Nuclear Energy*, 39(1), 70–82. <https://doi.org/10.1016/j.anucene.2011.09.010>
- Deendarlianto, Höhne, T., Lucas, D., & Vierow, K. (2012). Gas-liquid countercurrent two-phase flow in a PWR hot leg: A comprehensive research review. *Nuclear Engineering and Design*, 243(2), 214–233. <https://doi.org/10.1016/j.nucengdes.2011.11.015>
- Deendarlianto, Ousaka, A., Indarto, Kariyasaki, A., Lucas, D., Vierow, K., Vallee, C., & Hogan, K. (2010). The effects of surface tension on flooding in counter-current two-phase flow in an inclined tube. *Experimental Thermal and Fluid Science*, 34(7), 813–826. <https://doi.org/10.1016/j.expthermflusci.2010.01.010>
- Deendarlianto, Ousaka, A., Kariyasaki, A., & Fukano, T. (2005). Investigation of liquid film behavior at the onset of flooding during adiabatic counter-current air-water two-phase flow in an inclined pipe. *Nuclear Engineering and Design*, 235(21), 2281–2294. <https://doi.org/10.1016/j.nucengdes.2005.03.006>
- Deendarlianto, Ousaka, A., Kariyasaki, A., Fukano, T., & Konishi, M. (2004). The Effects of Surface Tension on the Flow Pattern and Counter-Current Flow Limitation (CCFL) in Gas-Liquid Two-Phase Flow in an Inclined Pipe. *Japanese Journal of Multiphase Flow*, 18(4), 337–350.
- Deendarlianto, Vallée, C., Lucas, D., Beyer, M., Pietruske, H., & Carl, H. (2011). Erratum: Experimental study on the air/water counter-current flow limitation in a model of the hot leg of a pressurized water reactor (Nuclear Engineering and Design). *Nuclear Engineering and Design*, 241(8), 3359–3372. <https://doi.org/10.1016/j.nucengdes.2011.02.028>
- dos Reis, E., & Goldstein, L. J. (2010). Characterization of slug flows in horizontal piping by signal analysis from a capacitive probe. *Flow Measurement and Instrumentation*, 21(3), 347–355. <https://doi.org/10.1016/j.flowmeasinst.2010.04.006>
- Drosos, E. I. P., Paras, S. V., & Karabelas, A. J. (2006). Counter-current gas-liquid flow in a vertical narrow channel-Liquid film characteristics and flooding phenomena. *International Journal of Multiphase Flow*, 32(1), 51–81. <https://doi.org/10.1016/j.ijmultiphaseflow.2005.07.005>
- Elperin, T., & Klochko, M. (2002). Flow regime identification in a two-phase flow using wavelet transform. *Experiments in Fluids*, 32(6), 674–682. <https://doi.org/10.1007/s00348-002-0415-x>
- Gardner, G. C. (1988). Co-current flow of air and water from a reservoir into a short horizontal pipe. *International Journal of Multiphase Flow*, 14(4), 375–388.
- Gargallo, M., Schulenberg, T., Meyer, L., & Laurien, E. (2005). Counter-current flow limitations during hot leg injection in pressurized water reactors. *Nuclear Engineering and Design*, 235(7), 785–804. <https://doi.org/10.1016/j.nucengdes.2004.11.002>

- Ghiaasiaan, S. M., Wu, X., Sadowski, D. L., & Abdel-Khalik, S. I. (1997). Hydrodynamic characteristics of counter-current two-phase flow in vertical and inclined channels: Effects of liquid properties. *International Journal of Multiphase Flow*, 23(6), 1063–1083. [https://doi.org/10.1016/s0301-9322\(97\)00027-x](https://doi.org/10.1016/s0301-9322(97)00027-x)
- Ghosh, S., Pratihar, D. K., Maiti, B., & Das, P. K. (2012). Identification of flow regimes using conductivity probe signals and neural networks for counter-current gas-liquid two-phase flow. *Chemical Engineering Science*, 84, 417–436. <https://doi.org/10.1016/j.ces.2012.08.042>
- Ghosh, S., Pratihar, D. K., Maiti, B., & Das, P. K. (2013). Automatic classification of vertical counter-current two-phase flow by capturing hydrodynamic characteristics through objective descriptions. *International Journal of Multiphase Flow*, 52, 102–120. <https://doi.org/10.1016/j.ijmultiphaseflow.2012.12.007>
- Grassberger, P., & Procaccia, I. (1983). Estimation of the Kolmogorov entropy for a chaotic signal. *Physical Review*, 28(4), 2591–2593.
- Green, S. J., & Hetsroni, G. (1995). PWR Steam Generator. *International Journal of Multiphase Flow*, 21, 1–97.
- Harinaldi. (2021). *Statistik untuk Sains dan Teknik*. Penerbit Erlangga. Jakarta
- Hudaya, A. Z., Widyatama, A., Dinaryanto, O., Juwana, W. E., Indarto, & Deendarlianto. (2019). The liquid wave characteristics during the transportation of air-water stratified co-current two-phase flow in a horizontal pipe. *Experimental Thermal and Fluid Science*, 103(January), 304–317. <https://doi.org/10.1016/j.expthermflusci.2019.01.021>
- Jana, A. K., Das, G., & Das, P. K. (2006). Flow regime identification of two-phase liquid-liquid upflow through vertical pipe. *Chemical Engineering Science*, 61(5), 1500–1515. <https://doi.org/10.1016/j.ces.2005.09.001>
- Jin, N. D., Nie, X. B., Ren, Y. Y., & Liu, X. B. (2003). Characterization of oil/water two-phase flow patterns based on nonlinear time series analysis. *Flow Measurement and Instrumentation*, 14(4–5), 169–175. [https://doi.org/10.1016/S0955-5986\(03\)00022-0](https://doi.org/10.1016/S0955-5986(03)00022-0)
- Johnsson, F., Zijerveld, R. C., Schouten, J. C., Van Den Bleek, C. M., & Leckner, B. (2000). Characterization of fluidization regimes by time-series analysis of pressure fluctuations. *International Journal of Multiphase Flow*, 26(4), 663–715. [https://doi.org/10.1016/S0301-9322\(99\)00028-2](https://doi.org/10.1016/S0301-9322(99)00028-2)
- Johnston, A. J. (1988). Investigation Into Stratified Co and Counter Current Two-Phase Flows. *Society of Petroleum Engineers of AIME, (Paper) SPE*, 393–399.
- Juwana, W. E., Widyatama, A., Dinaryanto, O., Budhijanto, W., Indarto, & Deendarlianto. (2019). Hydrodynamic characteristics of the microbubble dissolution in liquid using orifice type microbubble generator. *Chemical Engineering Research and Design*, 141, 436–448. <https://doi.org/10.1016/j.cherd.2018.11.017>
- Kang, S.-K., Chu, I.-C., No, H. C., & Chun, M.-H. (1999). Air-Water Countercurrent Flow Limitation in a Horizontal Pipe Connected to an Inclined Riser. *Journal of the Korean Nuclear Society*, 31(6), 548–560.

- <https://doi.org/10.1080/01457630600793897>
- Kim, H. T., & No, H. C. (2002). Assessment of RELAP5/MOD3.2.2 $\gamma$  against flooding database in horizontal-to-inclined pipes. *Annals of Nuclear Energy*, 29(7), 835–850. [https://doi.org/10.1016/S0306-4549\(01\)00074-3](https://doi.org/10.1016/S0306-4549(01)00074-3)
- Kinoshita, I., Murase, M., Utanohara, Y., & Minami, N. (2010). Numerical Simulation of Countercurrent Gas- Liquid Flow in a PWR Hot Leg under Reflux Cooling Numerical Simulation of Countercurrent Gas-Liquid Flow. *Journal of Nuclear Science and Technology*, 47(10), 963–972. <https://doi.org/10.1080/18811248.2010.9720975>
- Kinoshita, I., Nriai, T., Tomiyama, A., Lucas, D., & Murase, M. (2011). Effects of Liquid Properties on CCFL in a Scaled-Down Model of a PWR Hot Leg. *Journal of Power and Energy Systems*, 5(3), 316–329. <https://doi.org/10.1299/jpes.5.316>
- Koskie, J. E., Mudawar, I., & Tiederman, W. G. (1989). Parallel-wire probes for measurement of thick liquid films. *International Journal of Multiphase Flow*, 15(4), 521–530. [https://doi.org/10.1016/0301-9322\(89\)90051-7](https://doi.org/10.1016/0301-9322(89)90051-7)
- Kusunoki, T., Murase, M., Fujii, Y., Nozue, T., Hayashi, K., Hosokawa, S., & Tomiyama, A. (2015). Effects of fluid properties on CCFL characteristics at a vertical pipe lower end. *Journal of Nuclear Science and Technology*, 52(6), 887–896. <https://doi.org/10.1080/00223131.2014.990533>
- Lee; Bankoff, S. C. S. C. (1982). Stability of steam-water countercurrent flow in an inclined channel. *Journal of Heat Transfer*, 105, 713–718.
- Lee, K. (2022). *Sample Entropy* (<https://www.matworks.com/matlabcentral/fileexchange/35784-sample-entropy>), *MALTA B Central File Exchange*. Retrieved.
- Lucas, D., Beyer, M., Pietruske, H., & Szalinski, L. (2017). Counter-current flow limitation for air-water and steam-water flows in a PWR hot leg geometry. *Nuclear Engineering and Design*, 323(April), 56–67. <https://doi.org/10.1016/j.nucengdes.2017.07.032>
- Ma, Y., Shao, J., Lyu, J., & Peng, J. (2020). Experimental study on the effect of diameter on gas-liquid CCFL characteristics of horizontal circular pipes. *Nuclear Engineering and Design*, 364(516), 110645. <https://doi.org/10.1016/j.nucengdes.2020.110645>
- Mawarni, D. I., Juwana, W. E., Yuwana, K. A., Budhijanto, W., Deendarlianto, & Indarto. (2022). Hydrodynamic characteristics of the microbubble dissolution in liquid using the swirl flow type of microbubble generator. *Journal of Water Process Engineering*, 48(2), 102846. <https://doi.org/10.1016/j.jwpe.2022.102846>
- Mayinger, F., Weiss, P., & Wolfert, K. (1993). Two-phase flow phenomena in full-scale reactor geometry. *Nuclear Engineering and Design*, 145(1–2), 47–61. [https://doi.org/10.1016/0029-5493\(93\)90058-H](https://doi.org/10.1016/0029-5493(93)90058-H)
- Minami, N., Nishiwaki, D., Nariai, T., Tomiyama, A., & Murase, M. (2010). Countercurrent gas-liquid flow in a pwr hot leg under reflux cooling (i) air-water tests for 1/15-scale model of a pwr hot leg. *Journal of Nuclear Science and Technology*, 47(2), 142–148. <https://doi.org/10.1080/18811248.2010.9711938>



- Morshed, M., Khan, M. S., Rahman, M. A., & Imtiaz, S. (2020). Flow regime, slug frequency and wavelet analysis of air/Newtonian and air/non-Newtonian two-phase flow. *Applied Sciences (Switzerland)*, 10(9).  
<https://doi.org/10.3390/app10093272>
- Mouza, A. A., Paras, S. V., & Karabelas, A. J. (2003). Incipient flooding in inclined tubes of small diameter. *International Journal of Multiphase Flow*, 29(9), 1395–1412. [https://doi.org/10.1016/S0301-9322\(03\)00124-1](https://doi.org/10.1016/S0301-9322(03)00124-1)
- Murase, M., Tomiyama, A., Lucas, D., Kinoshita, I., Utanohara, Y., & Yanagi, C. (2012). Correlation for countercurrent flow limitation in a PWR hot leg. *Journal of Nuclear Science and Technology*, 49(4), 398–407.  
<https://doi.org/10.1080/00223131.2012.669241>
- Navarro, M. A. (2005). Study of countercurrent flow limitation in a horizontal pipe connected to an inclined one. *Nuclear Engineering and Design*, 235(10–12), 1139–1148. <https://doi.org/10.1016/j.nucengdes.2005.02.010>
- Nguyen, V. T., Euh, D. J., & Song, C. H. (2010). An application of the wavelet analysis technique for the objective discrimination of two-phase flow patterns. *International Journal of Multiphase Flow*, 36(9), 755–768.  
<https://doi.org/10.1016/j.ijmultiphaseflow.2010.04.007>
- Ohnuki, A. (1986). Experimental study of counter-current two-phase flow in horizontal tube connected to inclined riser. *Journal of Nuclear Science and Technology*, 23(3), 219–232.  
<https://doi.org/10.1080/18811248.1986.9734975>
- Ohnuki, A., Adachi, H., & Murao, Y. (1988). Scale effects on countercurrent gas-liquid flow in a horizontal tube connected to an inclined riser. *Nuclear Engineering and Design*, 107(3), 283–294. [https://doi.org/10.1016/0029-5493\(88\)90036-2](https://doi.org/10.1016/0029-5493(88)90036-2)
- Ousaka, A., Deendarlianto, Kariyasaki, A., & Fukano, T. (2006). Prediction of flooding gas velocity in gas-liquid counter-current two-phase flow in inclined pipes. *Nuclear Engineering and Design*, 236(12), 1282–1292.  
<https://doi.org/10.1016/j.nucengdes.2005.12.001>
- Petritsch, G., & Mewes, D. (1999). Experimental investigations of the flow patterns in the hot leg of a pressurized water reactor. *Nuclear Engineering and Design*, 188(1), 75–84. [https://doi.org/10.1016/S0029-5493\(99\)00005-9](https://doi.org/10.1016/S0029-5493(99)00005-9)
- Pratama, A. S., Indarto, & Deendarlianto. (2021). Studi CFD mengenai Pengaruh Sifat Fisis Fluida terhadap Karakteristik Counter-Current Flow Limitation pada Pipa Horizontal. *Journal of Mechanical Design and Testing*, 3(2), 118.  
<https://doi.org/10.22146/jmdt.66408>
- Prayitno, S., Santoso, R. a., Deendarlianto, Höhne, T., & Lucas, D. (2012). Counter current flow limitation of gas-liquid two-phase flow in nearly horizontal pipe. *Science and Technology of Nuclear Installations*, 2012. <https://doi.org/10.1155/2012/513809>
- Rodrigues, R. L. P., Cozin, C., Naidek, B. P., Marcelino Neto, M. a., da Silva, M. J., & Morales, R. E. M. (2020). Statistical features of the flow evolution in horizontal liquid-gas slug flow. *Experimental Thermal and Fluid Science*, 119(May). <https://doi.org/10.1016/j.expthermflusci.2020.110203>
- Rouhani, S. Z., & Sohal, M. S. (1983). Two-phase flow patterns: A review of

- research results. *Progress in Nuclear Energy*, 11(3), 219–259.  
[https://doi.org/10.1016/0149-1970\(83\)90012-4](https://doi.org/10.1016/0149-1970(83)90012-4)
- Samal, K., & Ghosh, S. (2021). Kerosene-water counter-current two-phase flow-structures varying flow-orientation in 15 mm diameter duct. *Flow Measurement and Instrumentation*, 81(July), 102016.  
<https://doi.org/10.1016/j.flowmeasinst.2021.102016>
- Setyawan, A., Indarto, & Deendarlianto. (2016). The effect of the fluid properties on the wave velocity and wave frequency of gas-liquid annular two-phase flow in a horizontal pipe. *Experimental Thermal and Fluid Science*, 71, 25–41. <https://doi.org/10.1016/j.expthermflusci.2015.10.008>
- Siddiqui, H., Banerjee, S., & Ardron, K. H. (1986). Flooding in a N Elbow Between a Vertical a N D a Horizontal or Near-Horizontal Pipe. *International Journal of Multiphase Flow*, 12(4), 531–541.
- Suzuki, S., & Ueda, T. (1977). Behaviour of liquid films and flooding in counter-current two-phase flow-Part 1. Flow in circular tubes. *International Journal of Multiphase Flow*, 3(6), 517–532. [https://doi.org/10.1016/0301-9322\(77\)90027-1](https://doi.org/10.1016/0301-9322(77)90027-1)
- Utanohara, Y., Kinoshita, I., Murase, M., Lucas, D., Vallée, C., & Tomiyama, A. (2012). Numerical simulations for steam-water CCFL tests using the 1/3 scale rectangular channel simulating a PWR hot leg. *Nuclear Engineering and Design*, 249, 14–23. <https://doi.org/10.1016/j.nucengdes.2011.05.041>
- Vallée, C., Deendarlianto, Beyer, M., Lucas, D., & Carl, H. (2008). Counter-current flow limitation experiments in a model of the hot leg of a pressurized water reactor. *Jahrestagung Kerntechnik 2008 - Kompetenzworkshop*.  
<https://doi.org/10.1115/1.3043816>
- Vallée, C., Nariai, T., Futatsugi, T., Tomiyama, A., Lucas, D., & Murase, M. (2012). Experimental characterisation of the interfacial structure during counter-current flow limitation in a model of the hot leg of a PWR. *Science and Technology of Nuclear Installations*, 2012.  
<https://doi.org/10.1155/2012/298452>
- Vallée, C., Seidel, T., Lucas, D., Beyer, M., Prasser, H. M., Pietruske, H., Schütz, P., & Carl, H. (2012). Counter-current flow limitation in a model of the hot leg of a PWR - Comparison between air/water and steam/water experiments. *Nuclear Engineering and Design*, 245, 113–124.  
<https://doi.org/10.1016/j.nucengdes.2012.01.001>
- Vallée, C., Seidel, T., Lucas, D., Tomiyama, A., & Murase, M. (2011). Comparison of countercurrent flow limitation experiments performed in two different models of the hot leg of a pressurized water reactor with rectangular cross section. *Journal of Engineering for Gas Turbines and Power*, 133(5), 1–9. <https://doi.org/10.1115/1.4002884>
- Wallis, G.B. (1969). *One-dimensional Two-phase Flow*. McGraw-Hill, Inc. New York
- Wang, H., & Kondo, S. (1990). A study on the stratified horizontal counter-current two-phase flow. *Nuclear Engineering and Design*, 121(1), 45–52.  
[https://doi.org/10.1016/0029-5493\(90\)90006-J](https://doi.org/10.1016/0029-5493(90)90006-J)
- Wang, M. J., & Mayinger, F. (1995). Simulation and analysis of thermal-

- hydraulic phenomena in a PWR hot leg related to SBLOCA. *Nuclear Engineering and Design*, 155(3), 643–652. [https://doi.org/10.1016/0029-5493\(95\)00977-K](https://doi.org/10.1016/0029-5493(95)00977-K)
- Welsh, S. A., & Ghiaasiaan, S. M. (1999). Countercurrent Gas - Pseudoplastic Liquid Two-Phase Flow. *Ind. Eng. Chem*, 38, 1083–1093.
- Wijayanta, S., Deendarlianto, Indarto, Prasetyo, A., & Hudaya, A. Z. (2023). International Journal of Multiphase Flow The effect of the liquid physical properties on the wave frequency and wave velocity of co-current gas-liquid stratified two-phase flow in a horizontal pipe. *International Journal of Multiphase Flow*, 158(2), 104300. <https://doi.org/10.1016/j.ijmultiphaseflow.2022.104300>
- Wijayanta, S., Indarto, Deendarlianto, Catrawedarma, I. G. N. B., & Hudaya, A. Z. (2022). Statistical characterization of the interfacial behavior of the sub-regimes in gas-liquid stratified two-phase flow in a horizontal pipe. *Flow Measurement and Instrumentation*, 83(2), 102107. <https://doi.org/10.1016/j.flowmeasinst.2021.102107>
- Wongwises, S. (1994). Experimental Investigation of Two-Phase Countercurrent Flow Limitation in a Bend between Horizontal and Inclined Pipes. *Experimental Thermal and Fluid Science*, 8, 245–259.
- Wongwises, S. (1996). Two-phase countercurrent flow in a model of a pressurized water reactor hot leg. *Nuclear Engineering and Design*, 166, 121–133. <https://doi.org/10.1016/j.nucengdes.2010.08.016>
- Xie, T., Ghiaasiaan, S. M., & Karrila, S. (2003). Flow Regime Identification in Gas / Liquid / Pulp Fiber Slurry Flows. *Ind. Eng. Chem. Res*, 42, 7017–7024.
- Zapke, A., & Kröger, D. G. (1996). The influence of fluid properties and inlet geometry on flooding in vertical and inclined tubes. *International Journal of Multiphase Flow*, 22(3), 461–472. [https://doi.org/10.1016/0301-9322\(95\)00076-3](https://doi.org/10.1016/0301-9322(95)00076-3)
- Zapke, A., & Kröger, D. G. (2000a). Countercurrent gas-liquid flow in inclined and vertical ducts - I: Flow patterns, pressure drop characteristics and flooding. *International Journal of Multiphase Flow*, 26(9), 1439–1455. [https://doi.org/10.1016/S0301-9322\(99\)00097-X](https://doi.org/10.1016/S0301-9322(99)00097-X)
- Zapke, A., & Kröger, D. G. (2000b). Countercurrent gas-liquid flow in inclined and vertical ducts - II: The validity of the Froude-Ohnesorge number correlation for flooding. *International Journal of Multiphase Flow*, 26(9), 1457–1468. [https://doi.org/10.1016/S0301-9322\(99\)00098-1](https://doi.org/10.1016/S0301-9322(99)00098-1)
- Zhang, W. H., Li, H., & Li, X. (2010). Identification of regime transitions in an inner-loop airlift reactor using local bubble-induced pressure fluctuation signals. *Chemical Engineering Journal*, 162(1), 296–300. <https://doi.org/10.1016/j.cej.2010.04.038>
- Zhou, Y., Jin, N., Zhang, H., & Zhai, L. (2020). Method based on parallel-wire conductivity probe for measuring water hold-up in near-horizontal oil–water two-phase flow pipes. *IET Science, Measurement and Technology*, 14(6), 676–683. <https://doi.org/10.1049/iet-smt.2019.0308>