

DAFTAR PUSTAKA

- Abbas, T. F., Othman, F. M., & Ali, H. B. (2018). *Influence of Layer Thickness on Impact Property of 3D-Printed PLA*. 1–4.
- Andrade, T. F., Abreu, P., Restivo, M. T., Chouzal, M. F., Santos, B. F., & Rodrigues, J. (2017). Enhancing a 3D printer with online access. *International Journal of Interactive Mobile Technologies*, 11(5), 44–55. <https://doi.org/10.3991/ijim.v11i5.7069>
- Arifianto. (2008). *Analisis Karakteristik Termal Pada Kabel Berisolasi dan Berselubung PVC Tegangan Pengenal 300/500 Volt*. 4–27.
- Bhosale, V., Gaikwad, P., Dhere, S., Sutar, C., & Raykar, S. J. (2022). Analysis of process parameters of 3D printing for surface finish, printing time and tensile strength. *Materials Today: Proceedings*, 59, 841–846. <https://doi.org/10.1016/j.matpr.2022.01.210>
- Birosz, M. T., Ledenyák, D., & Andó, M. (2022). Effect of FDM infill patterns on mechanical properties. *Polymer Testing*, 113(June). <https://doi.org/10.1016/j.polymertesting.2022.107654>
- Cardarelli, F. (2000). Materials Handbook. In *Materials Handbook*. <https://doi.org/10.1007/978-1-4471-3648-4>
- Carneiro, O. S., Silva, A. F., & Gomes, R. (2015). Fused deposition modeling with polypropylene. *Materials and Design*, 83, 768–776. <https://doi.org/10.1016/j.matdes.2015.06.053>
- Cataldi, A., Rigotti, D., Nguyen, V. D. H., & Pegoretti, A. (2018). Polyvinyl alcohol reinforced with crystalline nanocellulose for 3D printing application. *Materials Today Communications*, 15(February), 236–244. <https://doi.org/10.1016/j.mtcomm.2018.02.007>
- Chalgham, A., Ehrmann, A., & Wickenkamp, I. (2021). Mechanical properties of fdm printed pla parts before and after thermal treatment. *Polymers*, 13(8). <https://doi.org/10.3390/polym13081239>
- Christiyan, K. G. J., Chandrasekhar, U., & Venkateswarlu, K. (2014). *Influence of Raster Orientation and Layer Thickness on Mechanical Properties of Abs Material Using Fdm Process*. 8354(3), 1–83.
- Christiyan, K. G. J., Chandrasekhar, U., & Venkateswarlu, K. (2016). A study on the influence of process parameters on the Mechanical Properties of 3D printed ABS composite. *IOP Conference Series: Materials Science and Engineering*, 114(1). <https://doi.org/10.1088/1757-899X/114/1/012109>
- Custompartnet. (2010). *Additive Fabrication*. <http://www.custompartnet.com/>

- Darsin, M., Mauludy, R. R., Hardiatama, I., Fachri, B. A., Ramadhan, M. E., & Parningotan, D. (2022). Analysis of the effect 3D printing parameters on tensile strength using Copper-PLA filament. *Sinergi*, 26(1), 99. <https://doi.org/10.22441/sinergi.2022.1.013>
- Ding, S., Zou, B., Wang, P., & Ding, H. (2019). Effects of nosel temperature and building orientation on mechanical properties and microstructure of PEEK and PEI printed by 3D-FDM. *Polymer Testing*, 78(June), 105948. <https://doi.org/10.1016/j.polymertesting.2019.105948>
- Fountas, N. A., Papantoniou, I., Kechagias, J. D., Manolacos, D. E., & Vaxevanidis, N. M. (2022). Modeling and optimization of flexural properties of FDM-processed PET-G specimens using RSM and GWO algorithm. *Engineering Failure Analysis*, 138(December 2021), 106340. <https://doi.org/10.1016/j.engfailanal.2022.106340>
- Giordano, R. A., Wu, B. M., Borland, S. W., Cima, L. G., Sachs, E. M., & Cima, M. J. (1997). Mechanical properties of dense polylactic acid structures fabricated by three dimensional printing. *Journal of Biomaterials Science, Polymer Edition*, 8(1), 63–75. <https://doi.org/10.1163/156856297X00588>
- Guo, J., Xiao, R., Tian, C., & Jiang, M. (2018). Optimizing physical aging in poly(ethylene terephthalate)-glycol (PETG). *Journal of Non-Crystalline Solids*, 502(October), 15–21. <https://doi.org/10.1016/j.jnoncrysol.2018.10.021>
- Harsojuwono, B. A., & Arnata, I. W. (2015). Teknologi Polimer Industri Pertanian. *Teknologi Polimer*, 108.
- Karayel, E., & Bozkurt, Y. (2020). Additive manufacturing method and different welding applications. *Journal of Materials Research and Technology*, 9(5), 11424–11438. <https://doi.org/10.1016/j.jmrt.2020.08.039>
- Lubis, S., Djamil, S., & Yolanda, Y. (2016). Pengaruh Orientasi Objek Pada Proses 3D Printing Bahan Polymer Pla Dan Abs Terhadap Kekuatan Tarik Dan Ketelitian Dimensi Produk. *Sinergi*, 20(1), 27. <https://doi.org/10.22441/sinergi.2016.1.005>
- Lundberg, O., Afriyie, R., Aronsson, D., Sas, G., Shanmugam, V., Jiang, L., Qiang, X., Michael, F., Hedenqvist, M., & Das, O. (2022). The effect of infill density on the fire properties of polylactic acid 3D printed parts : A short communication. 111(April), 0–2. <https://doi.org/10.1016/j.polymertesting.2022.107594>
- Matmatch. (2019). What is Tensile Strength? Matmatch. <https://matmatch.com/learn/property/tensile-strength>
- Mohamed, O. A., Masood, S. H., & Bhowmik, J. L. (2015). Optimization of fused deposition modeling process parameters: a review of current research and

future prospects. *Advances in Manufacturing*, 3(1), 42–53.
<https://doi.org/10.1007/s40436-014-0097-7>

N.Mohammed Raffic, Babu, D. K. G., Venkatramanan, P. P. L., P, R., & S, S. N. (2017). Effect of Fdm Process Parameters in Abs Plastic Material. *International Journal on Mechanical and Production Engineering*, 3(1), 14–23.

Pal, T., Pramanik, S., Verma, K. D., Naqvi, S. Z., Manna, P. K., & Kar, K. K. (2022). 6 - *Fly ash-reinforced polypropylene composites* (K. K. B. T.-H. of F. A. Kar (ed.); pp. 243–270). Butterworth-Heinemann.
<https://doi.org/https://doi.org/10.1016/B978-0-12-817686-3.00021-9>

Saba, N., Jawaaid, M., & Sultan, M. T. H. (2018). An overview of mechanical and physical testing of composite materials. In *Mechanical and Physical Testing of Biocomposites, Fibre-Reinforced Composites and Hybrid Composites*. Elsevier Ltd. <https://doi.org/10.1016/B978-0-08-102292-4.00001-1>

Singh, S., Ramakrishna, S., & Singh, R. (2017). Material issues in additive manufacturing: A review. *Journal of Manufacturing Processes*, 25, 185–200.
<https://doi.org/10.1016/j.jmapro.2016.11.006>

Sumantri, D. (2012). Peningkatan Kinerja Mesin RAPID Prototyping Berbasis Fused Deposition Modelling. *Skripsi Teknik Mesin, Fakultas Teknologi Industri, Universitas Islam Indonesia*, 1–151.

Suzen, Z. S., Hasdiansah, & Yuliyanto. (2020). Pengaruh Tipe Infill dan Temperatur Nosel Terhadap Kekuatan Tarik Produk 3D Printing Filamen Pla+ Esun. *Manutech : Jurnal Teknologi Manufaktur*, 12(02).

Tagami, T., Fukushige, K., Ogawa, E., Hayashi, N., & Ozeki, T. (2017). 3D printing factors important for the fabrication of polyvinylalcohol filament-based tablets. *Biological and Pharmaceutical Bulletin*, 40(3), 357–364.
<https://doi.org/10.1248/bpb.b16-00878>

Wojnowski, W., Marć, M., Kalinowska, K., Kosmela, P., & Zabiegała, B. (2022). Emission Profiles of Volatiles during 3D Printing with ABS, ASA, Nylon, and PETG Polymer Filaments. *Molecules*, 27(12), 1–9.
<https://doi.org/10.3390/molecules27123814>

Zubaidi, A. B. (2012). *Analisis Perancangan Bejana Tekan (Shell thickness , Nosel neck) pada Shell and Tube Heat Exchanger Tipe BEM*.