

DAFTAR PUSTAKA

- Abbas, J. A., Said, I. H., Mohamed, M. A., Yasin, S. A., Ali, Z. A., & Ahmed, I. (2018). Electrospinning of polyethylene terephthalate (PET) nanofibers: optimization study using taguchi design of experiment. *IOP Conference Series: Materials Science and Engineering*, 454, 012130. <https://doi.org/10.1088/1757-899x/454/1/012130>
- Abbasi, A., & Shakeri, A. (2018). Effect of the flame-retardant 3-hydroxyphenylphosphinyl-propanoic acid on the mechanical, thermal, and flammability properties of poly(ethylene terephthalate) nanofiber mats. *High Performance Polymers*, 31(8), 919–927. <https://doi.org/10.1177/0954008318805530>
- Afshari, M., & Ojha, S. (2016). *Electrospun Nanofibers (Woodhead Publishing Series in Textiles)* (1st ed.). Woodhead Publishing.
- Al-Hazeem, N. Z. (2020). Effect of the Distance between the Needle Tip and the Collector on Nanofibers Morphology. *Nanomedicine & Nanotechnology Open Access*, 5(3). <https://doi.org/10.23880/nnoa-16000195>
- Amariei, N., Manea, L. R., Berteau, A. P., Berteau, A. P., & Popa, A. F. (2017). The Influence of Polymer Solution on the Properties of Electrospun 3D Nanostructures. *IOP Conference Series: Materials Science and Engineering*, 209, 012092. <https://doi.org/10.1088/1757-899x/209/1/012092>
- Bakar, S. S. S., Foong, K. M., Halif, N. A., & Yahud, S. (2019). Effect of solution concentration and applied voltage on electrospun polyacrylonitrile fibers. *IOP Conference Series: Materials Science and Engineering*, 701(1), 012018. <https://doi.org/10.1088/1757-899x/701/1/012018>
- Barbosa, M. C., Razzino, C. D. A., Stocco, T. D., Santana, M. D. V., Ghosh, A., Pereira, L. F., Tierra-Criollo, C. J., & Lobo, A. O. (2022). Production of rGO-Based Electrospinning Nanocomposites Incorporated in Recycled PET as an Alternative Dry Electrode. *Polymers*, 14(20), 4288. <https://doi.org/10.3390/polym14204288>
- Bell, B. (2015). *Systems Approach to Producing Electrospun Polyvinylidene Difluoride Fiber Webs with Controlled Fiber Structure and Functionality* [Graduate Dissertation, University of South Florida]. <https://digitalcommons.usf.edu/cgi/viewcontent.cgi?article=7052&context>

=etd

- Bonfim, D. P. F., Cruz, F., Bretas, R. E. S., Guerra, V. G., & Aguiar, M. L. (2021). A Sustainable Recycling Alternative: Electrospun PET-Membranes for Air Nanofiltration. *Polymers*, 13(7), 1166. <https://doi.org/10.3390/polym13071166>
- Bruce, P., Bruce, A., & Gedeck, P. (2020). *Practical Statistics for Data Scientists: 50+ Essential Concepts Using R and Python* (2nd ed.). O'Reilly Media.
- Cai, Y., & Gevelber, M. (2013). The effect of relative humidity and evaporation rate on electrospinning: fiber diameter and measurement for control implications. *Journal of Materials Science*, 48(22), 7812–7826. <https://doi.org/10.1007/s10853-013-7544-x>
- Coleman, M. M., & Painter, P. C. (1998). *Fundamentals of Polymer Science: An Introductory Text, Second Edition*. CRC Press.
- Colmenares-Roldan, G. J., Quintero-Martinez, Y., Agudelo-Gomez, L. M., Rodriguez-Vinasco, L. F., & Palacio, L. M. H. (2017). Influence of the molecular weight of polymer, solvents and operational condition in the electrospinning of polycaprolactone. *Revista Facultad De Ingenieria Universidad De Antioquia*, 84, 35–45. <https://doi.org/10.17533/udea.redin.n84a05>
- David, I. J., Adubisi, O. D., Ogbaji, O., Eghwerido, J. T., & Umar, Z. A. (2020). Resistant measures in assessing the adequacy of regression models. *Scientific African*, 8, e00437. <https://doi.org/10.1016/j.sciaf.2020.e00437>
- De Vrieze, S., Van Camp, T., Nelvig, A., Hagström, B., Westbroek, P., & De Clerck, K. (2009). The effect of temperature and humidity on electrospinning. *Journal of Materials Science*, 44(5), 1357–1362. <https://doi.org/10.1007/s10853-008-3010-6>
- Guo, Y., Wang, X., Shen, Y., Dong, K., Shen, L., & Alzalab, A. a. A. (2021). Research progress, models and simulation of electrospinning technology: a review. *Journal of Materials Science*, 57(1), 58–104. <https://doi.org/10.1007/s10853-021-06575-w>
- Hadjizadeh, A., Ajji, A., & Bureau, M. N. (2011). Nano/micro electro-spun polyethylene terephthalate fibrous mat preparation and characterization. *Journal of the Mechanical Behavior of Biomedical Materials*, 4(3), 340–351. <https://doi.org/10.1016/j.jmbbm.2010.10.014>
- Haider, A., Haider, S., & Kang, I. K. (2018). A comprehensive review summarizing the effect of electrospinning parameters and potential applications of nanofibers in biomedical and biotechnology. *Arabian Journal of Chemistry*, 11(8), 1165–1188. <https://doi.org/10.1016/j.arabjc.2015.11.015>

- Hastie, T., Tibshirani, R., & Friedman, J. (2009). *The Elements of Statistical Learning: Data Mining, Inference, and Prediction, Second Edition*. Springer Science & Business Media.
- Ibrahim, H. M., & Klingner, A. (2020). A review on electrospun polymeric nanofibers: Production parameters and potential applications. *Polymer Testing*, 90, 106647. <https://doi.org/10.1016/j.polymertesting.2020.106647>
- Jalali, S., Montazer, M., & Mahmoudi Rad, M. (2021). Biologically active PET/polysaccharide-based nanofibers post-treated with selenium/Tragacanth Gum nanobiocomposites. *Carbohydrate Polymers*, 251, 117125. <https://doi.org/10.1016/j.carbpol.2020.117125>
- Jalali, S., Montazer, M., & Malek, R. M. A. (2018). A Novel Semi-bionanofibers through Introducing Tragacanth Gum into PET Attaining Rapid Wetting and Degradation. *Fibers and Polymers*, 19(10), 2088–2096. <https://doi.org/10.1007/s12221-018-8276-y>
- Javazmi, L., Ravandi, S. a. H., & Ghareaghaji, A. A. (2014). Fabrication and characterization of PET nanofiber hollow yarn. *Fibers and Polymers*, 15(5), 954–960. <https://doi.org/10.1007/s12221-014-0954-9>
- Jog, J. P. (1995). Crystallization of Polyethyleneterephthalate. *Journal of Macromolecular Science, Part A*, 35(3), 531–553. <https://doi.org/10.1080/15321799508014598>
- Kayaci, F., Aytac, Z., & Uyar, T. (2013). Surface modification of electrospun polyester nanofibers with cyclodextrin polymer for the removal of phenanthrene from aqueous solution. *Journal of Hazardous Materials*, 261, 286–294. <https://doi.org/10.1016/j.jhazmat.2013.07.041>
- Kayaci, F., & Uyar, T. (2014). Electrospun polyester/cyclodextrin nanofibers for entrapment of volatile organic compounds. *Polymer Engineering & Science*, 54(12), 2970–2978. <https://doi.org/10.1002/pen.23858>
- Khorram, M., Mousavi, A., & Mehranbod, N. (2017). Chromium removal using adsorptive membranes composed of electrospun plasma-treated functionalized polyethylene terephthalate (PET) with chitosan. *Journal of Environmental Chemical Engineering*, 5(3), 2366–2377. <https://doi.org/10.1016/j.jece.2017.04.010>
- Kim, S. C., Kang, S., Lee, H., Kwak, D. B., Ou, Q., Pei, C., & Pui, D. Y. (2020). Nanofiber Filter Performance Improvement: Nanofiber Layer Uniformity and Branched Nanofiber. *Aerosol and Air Quality Research*, 20(1), 80–88. <https://doi.org/10.4209/aaqr.2019.07.0343>
- Kong, L., & Ziegler, G. R. (2013). Quantitative relationship between electrospinning parameters and starch fiber diameter. *Carbohydrate*

- Polymers*, 92(2), 1416–1422. <https://doi.org/10.1016/j.carbpol.2012.09.026>
- Kuhn, M., & Johnson, K. (2019). *Feature Engineering and Selection: A Practical Approach for Predictive Models (Chapman & Hall/CRC Data Science Series)* (1st ed.). Chapman and Hall/CRC.
- Li, D., & Xia, Y. (2004). Electrospinning of Nanofibers: Reinventing the Wheel? *Advanced Materials*, 16(14), 1151–1170. <https://doi.org/10.1002/adma.200400719>
- Li, Z., & Wang, C. (2013). Effects of Working Parameters on Electrospinning. In *SpringerBriefs in materials* (pp. 15–28). Springer Nature. https://doi.org/10.1007/978-3-642-36427-3_2
- Lim, C., Jankovic, J., & Ng, S. Y. (2008). Effects of crystalline morphology on the tensile properties of electrospun polymer nanofibers. *Applied Physics Letters*, 92(14), 141908. <https://doi.org/10.1063/1.2857478>
- Lin, Y., Gaebler, J., Reiter, F., Tan, T. R., Bowler, R. P., Sørensen, A. S., Leibfried, D., & Wineland, D. J. (2013). Dissipative production of a maximally entangled steady state of two quantum bits. *Nature*, 504(7480), 415–418. <https://doi.org/10.1038/nature12801>
- Lopes-da-Silva, J. A., Veleirinho, B., & Delgadillo, I. (2009). Preparation and Characterization of Electrospun Mats Made of PET/Chitosan Hybrid Nanofibers. *Journal of Nanoscience and Nanotechnology*, 9(6), 3798–3804. <https://doi.org/10.1166/jnn.2009.ns70>
- Maeda, T., Kim, Y. H., Aoyagi, T., & Ebara, M. (2017). The Design of Temperature-Responsive Nanofiber Meshes for Cell Storage Applications. *Fibers*, 5(1), 13. <https://doi.org/10.3390/fib5010013>
- Mahalingam, S., Raimi-Abraham, B. T., Craig, D. Q., & Edirisinghe, M. (2015). Solubility–spinnability map and model for the preparation of fibres of polyethylene (terephthalate) using gyration and pressure. *Chemical Engineering Journal*, 280, 344–353. <https://doi.org/10.1016/j.cej.2015.05.114>
- Mahdavi, H., & Moslehi, M. (2016). A new thin film composite nanofiltration membrane based on PET nanofiber support and polyamide top layer: preparation and characterization. *Journal of Polymer Research*, 23(12). <https://doi.org/10.1007/s10965-016-1157-4>
- Marcus, Y. (1998). *The Properties of Solvents*. John Wiley & Sons.
- Patra, S. N., Lin, R. J. T., & Bhattacharyya, D. (2010). Regression analysis of manufacturing electrospun nonwoven nanotextiles. *Journal of Materials Science*, 45(14), 3938–3946. <https://doi.org/10.1007/s10853-010-4459-7>
- Pérez, C. F., Paredes, J. G., Valencia, R. X., Vaca, W. H., & Vásquez, E. P. (2018).

- Logistic regression model for the grooving process of hybrid polyester resin composite materials reinforced with natural fibers and fiberglass. *IOP Conference Series: Materials Science and Engineering*, 446, 012003. <https://doi.org/10.1088/1757-899x/446/1/012003>
- Pisani, S., Genta, I., Dorati, R., Modena, T., Chiesa, E., Bruni, G., Benazzo, M., & Conti, B. (2022). A design of experiment (DOE) approach to correlate PLA-PCL electrospun fibers diameter and mechanical properties for soft tissue regeneration purposes. *Journal of Drug Delivery Science and Technology*, 68, 103060. <https://doi.org/10.1016/j.jddst.2021.103060>
- Salehi Shahrabi, S., Barzin, J., & Shokrollahi, P. (2018). Statistical approach to estimate fiber diameter of PET/PVP blend electrospun using Taguchi method and fitting regression model. *Materials Research Express*, 6(2), 025306. <https://doi.org/10.1088/2053-1591/aaeaf6>
- Shahreen, L., & Chase, G. G. (2015). Effects of Electrospinning Solution Properties on Formation of Beads in Tio₂ Fibers with PdO Particles. *Journal of Engineered Fibers and Fabrics*, 10(3), 155892501501000. <https://doi.org/10.1177/155892501501000308>
- Siegemund, G., Schwertfeger, W. D., Feiring, A. E., Smart, B. E., Behr, F. E., Vogel, H., & McKusick, B. C. (2000). Fluorine Compounds, Organic. *Ullmann's Encyclopedia of Industrial Chemistry*. https://doi.org/10.1002/14356007.a11_349
- Smółka, K., Firyach-Nowacka, A., & Lefik, M. (2017). Three-dimensional computer models of electrospinning systems. *Open Physics*, 15(1), 777–789. <https://doi.org/10.1515/phys-2017-0091>
- Strain, I. N., Wu, Q., Pourrahimi, A. M., Hedenqvist, M. S., Olsson, R. F., & Andersson, R. (2015). Electrospinning of recycled PET to generate tough mesomorphic fibre membranes for smoke filtration. *Journal of Materials Chemistry. A, Materials for Energy and Sustainability*, 3(4), 1632–1640. <https://doi.org/10.1039/c4ta06191h>
- Suzuki, J. (2021). *Statistical Learning with Math and Python: 100 Exercises for Building Logic*. Springer Nature.
- Tarus, B. K., Fadel, N., Al-Oufy, A., & El-Messiry, M. (2020). Investigation of mechanical properties of electrospun poly (vinyl chloride) polymer nanoengineered composite. *Journal of Engineered Fibers and Fabrics*, 15, 155892502098256. <https://doi.org/10.1177/1558925020982569>
- Topuz, F., Oldal, D. G., & Szekely, G. (2022). Valorization of Polyethylene Terephthalate (PET) Plastic Wastes as Nanofibrous Membranes for Oil Removal: Sustainable Solution for Plastic Waste and Oil Pollution.

Industrial & Engineering Chemistry Research, 61(25), 9077–9086.

<https://doi.org/10.1021/acs.iecr.2c01431>

Veleirinho, B., Rei, M. F., & Lopes-DA-Silva, J. A. (2008). Solvent and concentration effects on the properties of electrospun poly(ethylene terephthalate) nanofiber mats. *Journal of Polymer Science Part B: Polymer Physics*, 46(5), 460–471. <https://doi.org/10.1002/polb.21380>

Wang, A. C., Murdock, R. J., Kauwe, S. K., Oliynyk, A. O., Gurlo, A., Brgoch, J., Persson, K. A., & Sparks, T. D. (2020). Machine Learning for Materials Scientists: An Introductory Guide Towards Best Practices. *ChemRxiv*. <https://doi.org/10.26434/chemrxiv.12249752.v1>

Wang, C. C., Lee, M., & Wu, Y. (2012). Solution-Electrospun Poly(ethylene terephthalate) Fibers: Processing and Characterization. *Macromolecules*, 45(19), 7939–7947. <https://doi.org/10.1021/ma300121k>

Xue, J., Wu, T., Dai, Y., & Xia, Y. (2019). Electrospinning and Electrospun Nanofibers: Methods, Materials, and Applications. *Chemical Reviews*, 119(8), 5298–5415. <https://doi.org/10.1021/acs.chemrev.8b00593>

Zaman, M. H., Sooriyaarachchi, D., Zhou, Y., Tan, G. Z., & Du, D. (2021). Modeling the density gradient of 3D nanofiber scaffolds fabricated by divergence electrospinning. *Advances in Manufacturing*. <https://doi.org/10.1007/s40436-020-00307-0>

Zou, N., Zhang, C., Wang, Y., & Zhang, L. (2021). Recognition and Diagnosis Method of Accelerated Aging of Lithium-Ion Battery Based on Logistic Regression. *World Electric Vehicle Journal*, 12(3), 143. <https://doi.org/10.3390/wevj12030143>