

DAFTAR PUSTAKA

- [1] Saripah Sobah, Hary Sulisty, and Siti Syamsiah, “Pengolahan Gas CO₂ Hasil Samping Industri Amoniak Melalui Gasifikasi Batubara yang Telah dipirolisis dengan Menambahkan Ca(OH)₂,” *J. Rekayasa Proses*, vol. 7, no. 1, pp. 25–29, 2013.
- [2] V. Pattabathula and J. Richardson, “Introduction to ammonia production,” *Chem. Eng. Prog.*, vol. 112, no. 9, pp. 69–75, 2016.
- [3] A. I. Amhamed *et al.*, “Ammonia Production Plants—A Review,” *Fuels*, vol. 3, no. 3, pp. 408–435, 2022, doi: 10.3390/fuels3030026.
- [4] A. E. Yüzbaşıoğlu, A. H. Tatarhan, and A. O. Gezerman, “Decarbonization in ammonia production, new technological methods in industrial scale ammonia production and critical evaluations,” *Heliyon*, vol. 7, no. 10, 2021, doi: 10.1016/j.heliyon.2021.e08257.
- [5] R. H. Perry, “PERRY’s Chemical Engineering Handbook,” *Perrys’ Chem. Eng. Handb.*, p. 21, 2007, [Online]. Available: <http://books.google.com/books?id=X1wIW9TrqXMC&pgis=1>.
- [6] R. S. Ulrich, “View through a window may influence recovery from surgery,” *Science (80-.)*, vol. 224, no. 4647, pp. 420–421, 1984, doi: 10.1126/science.6143402.
- [7] M. S. Peters, K. D. Timmerhaus, and R. E. West, *Plant Design and Economics for Chemical Engineers*, 5 th. New York: McGraw-Hill Book Company, Inc., 2003.
- [8] R. S. Aries and R. D. Newton, “Chemical Engineering Cost Estimation.” McGraw-Hill Book Company, Inc., New York, pp. 1–16; 52; 97–119, 1955.
- [9] C. Yang, F. Du, H. Zheng, and K. H. Chung, “Hydroconversion characteristics and kinetics of residue narrow fractions,” *Fuel*, vol. 84, no. 6 SPEC. ISS., pp. 675–684, 2005, doi: 10.1016/j.fuel.2004.03.018.
- [10] R. Chacón, A. Canale, A. Bouza, and Y. Sánchez, “Modeling of a three-phase reactor for bitumen-derived gas oil hydrotreating,” *Brazilian J. Chem. Eng.*, vol. 29, no. 1, pp. 135–146, 2012, doi: 10.1590/S0104-66322012000100015.
- [11] J. Xu and G. F. Froment, “Methane steam reforming, methanation and water-gas shift: I. Intrinsic kinetics,” *AIChE J.*, vol. 35, no. 1, pp. 88–96, 1989, doi: 10.1002/aic.690350109.
- [12] J. M. Smith, I. J. C. N. Van, M. M. Abbott, and I. N. T. Ioi, “Introduction to Chemical Engineering Thermodynamics.”
- [13] C. L. Yaws, *Chemical Properties Handbook*, vol. 5, no. 3. 1999.
- [14] A. A. AL-Dhfeery and A. A. Jassem, “Modeling and simulation of an industrial secondary reformer reactor in the fertilizer plants,” *Int. J. Ind. Chem.*, vol. 3, no. 1, pp. 1–8, 2012, doi: 10.1186/2228-5547-3-14.
- [15] Y. H. Yu, “Simulation of secondary reformer in industrial ammonia plant,” *Chem. Eng. Technol.*, vol. 25, no. 3, pp. 307–314, 2002, doi: 10.1002/1521-4125(200203)25:3<307::AID-CEAT307>3.0.CO;2-C.
- [16] Bird R.B.; Stewart W. E.; Lightfoot E. N, *Transport phenomena*, vol. 36, no. 11. 1980.



- [17] R. L. Keiski, O. Desponds, Y. F. Chang, and G. A. Somorjai, "Kinetics of the water-gas shift reaction over several alkane activation and water-gas shift catalysts," *Appl. Catal. A, Gen.*, vol. 101, no. 2, pp. 317–338, 1993, doi: 10.1016/0926-860X(93)80277-W.
- [18] N. E. Amadeo and M. A. Laborde, "Hydrogen production from the low-temperature water-gas shift reaction: Kinetics and simulation of the industrial reactor," *Int. J. Hydrogen Energy*, vol. 20, no. 12, pp. 949–956, 1995, doi: 10.1016/0360-3199(94)00130-R.
- [19] D. C. Dyson and J. M. Simon, "A kinetic expression with diffusion correction for ammonia synthesis on industrial catalyst," *Ind. Eng. Chem. Fundam.*, vol. 7, no. 4, pp. 605–610, 1968, doi: 10.1021/i160028a013.
- [20] R. Sinnott and G. Towler, "Chemical Engineering Design," *Chem. Eng. Des. SI Ed.*, pp. 1–1262, 2019, doi: 10.1016/B978-0-08-102599-4.09980-X.
- [21] Brownell, "Process Equipment Design Handbook," *Advances in Applied Science Research*, vol. 3, no. 3. p. 408, 1959, [Online]. Available: <https://books.google.com/books?id=QtQWiZSkBzMC&pgis=1>.
- [22] J. R. Couper, W. R. Penney, and P. Fair James R., *Chemical Process Equipment. [electronic resource] : Selection and Design*. 2012.
- [23] R. E. Treybal, *Mass Transfer Operations*, 3rd ed. New York: McGraw-Hill Book Company, Inc., 1981.
- [24] J. M. Coulson and J. F. Richardson, *Chemical Engineering Design*, vol. 6, no. August. 2005.
- [25] H. A. Al-Ghawas, G. Ruiz-Ibanez, and O. C. Sandall, "Absorption of Carbonyl Sulfide in Aqueous Methyl-diethanolamine," *Chem. Eng. Sci.*, vol. 44, no. 3, pp. 631–639, 1989, doi: 10.1016/S0009-2509(00)00420-6.
- [26] T. N. G. Borhani, V. Akbari, M. K. A. Hamid, and Z. A. Manan, "Rate-based simulation and comparison of various promoters for CO₂ capture in industrial DEA-promoted potassium carbonate absorption unit," *J. Ind. Eng. Chem.*, vol. 22, pp. 306–316, 2015, doi: 10.1016/j.jiec.2014.07.024.
- [27] C. Jataí Cavalcante Júnior and P. de A. Pessoa Filho, "Modeling and simulation of an industrial adsorption process of dehydration of natural gas in 4A molecular sieves: Effect of adsorbent aging," *Results Eng.*, vol. 18, no. January, 2023, doi: 10.1016/j.rineng.2023.101144.
- [28] D. M. Ruthven, "Principles of Adsorption and Adsorption Processes," *Wiley Intersci.*, vol. 1, pp. 1–31, 1984.
- [29] G. Kolios, J. Frauhammer, and G. Eigenberger, "Autothermal fixed-bed reactor concepts," *Chem. Eng. Sci.*, vol. 55, no. 24, pp. 5945–5967, 2000, doi: 10.1016/S0009-2509(00)00183-4.
- [30] J. R. BACKHURST and J. H. HARKER, "Flow of Fluids — Energy and Momentum Relationships," *Chem. Eng.*, pp. 16–18, 2001, doi: 10.1016/b978-0-08-049422-7.50006-7.
- [31] D. Q. Kern, "Procces Heat Transfer." pp. 820–845, 1965.



Prarancangan Pabrik Blue Ammonia dari Gas Alam dengan Proses KBR Purifier™ Kapasitas 500.000 Ton/Tahun

Alvin Arkhanul Agung Putra, Ir. Muhammad Mufti Azis, S.T., M.Sc., Ph.D., IPM.

Universitas Gadjah Mada, 2023 | Diunduh dari <http://etd.repository.ugm.ac.id/>

UNIVERSITAS
GADJAH MADA

- [32] L. E. Brownell and E. H. Young, *Process Equipment Design*. Michigan: John Wiley & Sons, 1959.
- [33] J. R. Couper, J. R. Fair, and W. R. Penney, *Chemical Process Engineering Design 3rd Edition*, 3rd ed. Oxford: Elsevier Inc., 2012.