



## DAFTAR PUSTAKA

- Anderson, J. P., & Altan, M. C. (2012). Properties of composite cylinders fabricated by bladder assisted composite manufacturing. *Journal of Engineering Materials and Technology*, 134(4), 5–7. <https://doi.org/10.1115/1.4007017>
- Barney, J. A. (2003). Natural Rubber Production, di dalam Lecture de Notes. *Bogor, Balai Penelitian Perkebunan*.
- Blackley, D. C. (1997). Polymer Latices. In *Polymer Latices*. <https://doi.org/10.1007/978-94-011-5848-0>
- Cataldo, F. (2023). Thermochemistry of Sulfur-Based Vulcanization and of Devulcanized and Recycled Natural Rubber Compounds. *International Journal of Molecular Sciences*, 24(3). <https://doi.org/10.3390/ijms24032623>
- Catauro, M., Dal Poggetto, G., Cicala, G., Saitta, L., Tosto, C., & Blanco, I. (2022). Thermo-oxidative investigation on SiO<sub>2</sub> and SiO<sub>2</sub>–ZrO<sub>2</sub> composites prepared by sol–gel route. *Journal of Thermal Analysis and Calorimetry*, 147(9), 5401–5412. <https://doi.org/10.1007/s10973-021-11139-w>
- Dafader, N. C., Jolly, Y. N., Haque, M. E., Akhtar, F., & Ahmad, M. U. (1999). The role of coagulants on the preparation of dipped film from radiation vulcanized natural rubber latex. *Polymer - Plastics Technology and Engineering*, 38(2), 267–274. <https://doi.org/10.1080/03602559909351576>
- Dewi, I. R., & Herminiawati. (2014). *Lateks Karet Alam Untuk Sol Sepatu: Metode Pembuatan, Sifat Mekanik Dan Morfologi Natural Rubber Latex for Shoe Sole: Manufacturing Method, Mechanical and Morphological Properties*. 61–70.
- Dewi, R. S., & Parjono. (2017). Peningkatan Penguasaan Fitur Cad Inventor Melalui Penerapan Metode Problem Solving Di Smk N 2 Depok. *Jurnal Pendidikan Vokasional Teknik Mesin*, 151–160. <http://journal.student.uny.ac.id/ojs/ojs/index.php/mesin/article/view/7104/0>
- Fachry, A. R., Sari, T. I., Putra, B. A., & Kristanto, D. A. (2012). Pengaruh Penambahan Filler Kaolin Terhadap Elastisitas dan Kekerasan Produk Souvenir dari Karet Alam (*Havea Brasiliensis*). In *Prosiding SNTK TOPI* (pp. 205–210).
- Hamill, L., Centea, T., & Nutt, S. (2015). Surface porosity during vacuum bag-only prepreg processing: Causes and mitigation strategies. *Composites Part A: Applied Science and Manufacturing*, 75, 1–10. <https://doi.org/10.1016/j.compositesa.2015.04.009>
- Harahap, H. (2008). Pengaruh Pengisi CaCO<sub>3</sub> dan Temperatur Vulkanisasi Terhadap Sifat-Sifat Mekanikal Film Latex Karet. *J. Penelitian Rekayasa.*, Vol. 1((2)), 43–46.
- Hill, D. M. (2019). Latex dipping: Science and technology. In *Latex Dipping: Science and Technology*. <https://doi.org/10.1515/9783110638097>



- Hou, T., & Jensen, B. (2018). *Evaluation of Double-Vacuum-Bag Process For Composite Fabrication T. H. Hou and B. J. Jensen NASA Langley Research Center, Hampton, Virginia 23681.* 1–16.
- Hutahean, L. S., & Untung, P. (2020). Silika Sebagai Filler Rubber Seal. *JURNAL TEKNOLOGI Dan MANAJEMEN*, 18(1), 49–57.
- Indrajati, I. N., & Dewi, I. R. (2014). STATISTICAL REVIEW OF CALCIUM NITRATE COAGULANT ON THE NATURAL RUBBER LATEX FILM STRENGTH. *Prosiding Seminar Nasional Kulit, Karet, Dan Plastik Ke-3 Yogyakarta, 29 Oktober 2014 STATISTICAL*.
- Izquierdo, A., Ono, S. S., Voegel, J. C., Schaaf, P., & Decher, G. (2005). Dipping versus spraying: Exploring the deposition conditions for speeding up layer-by-layer assembly. *Langmuir*, 21(16), 7558–7567. <https://doi.org/10.1021/la047407s>
- Junlapong, K., Suwanboon, S., & Khaokong, C. (2019). Effects of zinc oxide particle shape on properties of a prevulcanized latex. *Iranian Polymer Journal (English Edition)*, 28(4), 325–335. <https://doi.org/10.1007/s13726-019-00702-w>
- Kohjiya, S., & Ikeda, Y. (2014). Chemistry, Manufacture and Applications of Natural Rubber. *Woodhead Publishing of Elsevier*. WWW.elsivier.com
- Lindley, P. B. (1974). Engineering Design With Natural Rubber. *The Malaysian Rubber Producers Research Association*, 48.
- Loadman, M. J. R. (1985). The glass transition temperature of natural rubber. *Journal of Thermal Analysis*, 30(4), 929–941. <https://doi.org/10.1007/BF01913321>
- Mazumdar, S. K. (2001). Composites manufacturing: Materials, product, and process engineering. In *Composites Manufacturing: Materials, Product, and Process Engineering*.
- Meronda, R. G. (2008). *Rahma g. meronda*.
- Nugroho, G., & Wantogia, M. S. R. R. (2019). Proses Fabrikasi dan Sifat Mekanik Komposit Polimer dengan Metode Bladder Compression Moulding. *Journal of Mechanical Design and Testing*, 1(2), 95. <https://doi.org/10.22146/jmdt.53047>
- On, N. K., Rashid, A. A., Nazlan, M. M. M., & Hamdan, H. (2012). Thermal and mechanical behavior of natural rubber latex-silica aerogel film. *Journal of Applied Polymer Science*, 124(4), 3108–3116.
- Phomrak, S., Nimpairoon, A., Newby, B. M. Z., & Phisalaphong, M. (2020). Natural rubber latex foam reinforced with micro-and nanofibrillated cellulose via dunlop method. *Polymers*, 12(9), 1–16. <https://doi.org/10.3390/polym12091959>
- Prihatin, S., Utama, M., & Andreiyanti, W. (2018). a Review on the Rubber Products From Irradiation Vulcanization Natural Latex. *Prosiding Seminar Nasional Kulit, Karet, Dan Plastik*, 3(1), 19–54.



<https://www.researchgate.net/publication/322635671>

- Putra, M. I., & Nugroho, G. (2021). Pengaruh Curing Time Terhadap Sifat Mekanis Komposit Epoxy/Carbon Fiber dan Epoxy/ Glass Fiber dengan Metode Manufaktur Bladder Compression Moulding. *Journal of Mechanical Design and Testing*, 3(1), 20. <https://doi.org/10.22146/jmdt.57205>
- Qamarina, M. S. N., & Hashim, M. Y. A. (2009). Zinc-complexes in natural rubber latex sulphur vulcanisation system. *Journal of Rubber Research*, 12(2), 80–92.
- Rodgers, B. (2015). RubbeR Compounding Chemistry and Applications. In *CRC Press is an imprint of Taylor & Francis Group, an Informa business* (Vol. 2, Issue july). CRC Press is an imprint of Taylor & Francis Group, an Informa business.
- Saiwari, S., Hayeemasae, N., Soontaranon, S., Kalkornsurapranee, E., Jaratrotkamjorn, R., & Masa, A. (2022). Structure-Property relationships in natural rubber representing several clonal varieties of Hevea Brasiliensis. *Progress in Rubber, Plastics and Recycling Technology*, 38(4), 295–310. <https://doi.org/10.1177/14777606221127372>
- Sudhakaran, G., & Avirah, S. A. (2022). The application of nano silica as a potential, cost-efficient green filler in acrylonitrile butadiene rubber vulcanizates containing carboxy-terminated liquid natural rubber. *Journal of Elastomers and Plastics*, 54(5), 815–827. <https://doi.org/10.1177/00952443221102586>
- Tamási, K., & Kollár, M. S. (2018). Effect of different sulfur content in Natural Rubber mixtures on their thermo-mechanical and surface properties. *International Journal of Engineering Research & Science*, 4(2), 28–37.
- Tambunan, F. E., & Harahap, H. (2015). Pengaruh Suhu Vulkanisasi Dan Komposisi Bentonite Clay Yang Dimodifikasi Dengan Alkanolamida Dari Bahan Baku Rbdpko Pada Produk Lateks Karet Alam. *Jurnal Teknik Kimia USU*, 4(4), 64–70. <https://doi.org/10.32734/jtk.v4i4.1515>
- Yang, L., Zhou, S., Gu, G., & Wu, L. (2013). Film-forming behavior and mechanical properties of colloidal silica/polymer latex blends with high silica load. *Journal of Applied Polymer Science*, 129(3), 1434–1445. <https://doi.org/10.1002/app.38827>
- Yip, E., & Cacioli, P. (2002). The manufacture of gloves from natural rubber latex. *Journal of Allergy and Clinical Immunology*, 110(2), S3–S14. <https://doi.org/10.1067/mai.2002.124499>