

## REFERENCES

- Abubakar, M., Muthuraja, A., Rajak, D.K., Ahmad, N., Pruncu, C.I., Lamberti, L., Kumar, A., 2020. Influence of Firing Temperature on the Physical, Thermal and Microstructural Properties of Kankara Kaolin Clay: A Preliminary Investigation. *Materials* 13, 1872. <https://doi.org/10.3390/ma13081872>
- Ali, Md.H., Issayev, G., Shehab, E., Sarfraz, S., 2022. A critical review of 3D printing and digital manufacturing in construction engineering. *Rapid Prototyp. J.* 28, 1312–1324. <https://doi.org/10.1108/RPJ-07-2021-0160>
- Carr, M.M., Wang, Y., Ghayoomi, M., Newell, P., 2023. Effects of 3D Printing on Clay Permeability and Strength. *Transp. Porous Media* 148, 499–518. <https://doi.org/10.1007/s11242-023-01955-z>
- Castelein, O., Soulestin, B., Bonnet, J.P., Blanchart, P., 2001. The influence of heating rate on the thermal behaviour and mullite formation from a kaolin raw material. *Ceram. Int.* [https://doi.org/10.1016/S0272-8842\(00\)00110-3](https://doi.org/10.1016/S0272-8842(00)00110-3)
- Chan, S.S.L., Pennings, R.M., Edwards, L., Franks, G.V., 2020. 3D printing of clay for decorative architectural applications: Effect of solids volume fraction on rheology and printability. *Addit. Manuf.* 35, 101335. <https://doi.org/10.1016/j.addma.2020.101335>
- Detellier, C., 2018. Functional Kaolinite. *Chem. Rec.* 18, 868–877. <https://doi.org/10.1002/tcr.201700072>
- Ismiati, N., Darwis, D., 2021. The effect of sintering temperature on the mechanical properties of ceramic. *J. Phys. Conf. Ser.* 1763, 012094. <https://doi.org/10.1088/1742-6596/1763/1/012094>
- ISO/ASTM 52900:2021(en), Additive manufacturing — General principles — Fundamentals and vocabulary [WWW Document], n.d. URL <https://www.iso.org/obp/ui/en/#iso:std:iso-astm:52900:ed-2:v1:en> (accessed 8.31.23).
- Jadhav, A., Jadhav, V.S., 2022. A review on 3D printing: An additive manufacturing technology. *Mater. Today Proc., International Conference on Design, Manufacturing and Materials Engineering* 62, 2094–2099. <https://doi.org/10.1016/j.matpr.2022.02.558>
- Kim, N.P., Cho, D., Zielewski, M., 2019. Optimization of 3D printing parameters of Screw Type Extrusion (STE) for ceramics using the Taguchi method. *Ceram. Int.* 45, 2351–2360. <https://doi.org/10.1016/j.ceramint.2018.10.152>
- Mouiya, M., Bouazizi, A., Abourriche, A., El Khessaimi, Y., Benhammou, A., El Hafiane, Y., Taha, Y., Oumam, M., Abouliatim, Y., Smith, A., Hannache, H., 2019. Effect of sintering temperature on the microstructure and mechanical behavior of porous ceramics made from clay and banana peel powder. *Results Mater.* 4, 100028. <https://doi.org/10.1016/j.rinma.2019.100028>
- Precedence Research, 2023. Kaolin Market Size To Attain Around USD 6.74 Billion By 2032 (Market Analysis). Precedence Research.
- Revelo, C.F., Colorado, H.A., 2018. 3D printing of kaolinite clay ceramics using the Direct Ink Writing (DIW) technique. *Ceram. Int.* 44, 5673–5682. <https://doi.org/10.1016/j.ceramint.2017.12.219>



- Rosenthal, M., Henneberger, C., Gutkes, A., Bues, C.-T., 2018. Liquid Deposition Modeling: a promising approach for 3D printing of wood. *Eur. J. Wood Wood Prod.* 76. <https://doi.org/10.1007/s00107-017-1274-8>
- Ruscitti, A., Tapia, C., Rendtorff, N.M., 2020. A review on additive manufacturing of ceramic materials based on extrusion processes of clay pastes. *Cerâmica* 66, 354–366. <https://doi.org/10.1590/0366-69132020663802918>
- Wi, K., Suresh, V., Wang, K., Li, B., Qin, H., 2020. Quantifying quality of 3D printed clay objects using a 3D structured light scanning system. *Addit. Manuf.* 32, 100987. <https://doi.org/10.1016/j.addma.2019.100987>