

## DAFTAR PUSTAKA

- Abraham, A., Soloman, P.A., Rejini, V.O. (2016). Preparation of chitosan-polyvinyl alcohol blends and studies on thermal and mechanical properties. *Procedia Technology*, 24: 741-748. <https://doi.org/10.1016/j.protcy>.
- Abraham, A., Soloman, P.A., Rejini, V.O. (2016). Preparation of chitosan-polyvinyl alcohol blends and studies on thermal and mechanical properties. *Procedia Technology*.
- Anggraini, T.; Ulfimarjan, A.F.; Yenrina, R. (2017). The effect of chitosan concentration on the characteristics of sago (metroxylon sp) starch bioplastics. *Res. J. Pharm. Biol. Chem. Sci.* 1339–1351.
- Berdichevsky, M.N. dan V.I. Dmitriev. (2008). *Models and Methods of Magnetotellurics*. Springer, Berlin, Jerman, 31–33. Blakely, R.J. 1996
- Britannica, T. Editor Ensiklopedia (2023, 20 Maret). *alkohol polivinil*. *Ensiklopedia Britannica*. <https://www.britannica.com/science/polyvinyl-alcohol>
- Budiawanti Sri. (2007). Perbaikan Sifat Sensitif Kelembaban dari Film PVA Elektrolit dengan Cr<sub>2</sub>O<sub>3</sub> sebagai Modifikator. Tesis Pascasarjana UI.
- C.A. Finch. (1992). *Polivinyil Alcohol-Development*. Wiley, New York.
- Callister, W.D. (1997). *Material Science and Engineering*, Fourth edition, John Wiley & Sons, Inc., New York.
- DC Chemical Co., Ltd. (2006). *Poli Vinyl Alcohol: PVA*, 10 hlm. [http://www.dcchem.co.kr/english/product/p\\_petr/p\\_petr8.htm](http://www.dcchem.co.kr/english/product/p_petr/p_petr8.htm).
- Ioelovich, M. (2014). Crystallinity and hydrophility of chitin and chitosan. *Journal of Chemistry*, 3(3): 7-14
- Kusmono, Wildan, M.W., Lubis, F.I. (2021). Fabrication and characterization of chitosan/cellulose nanocrystal/glycerol bio-composite films. *Polymers*, 13(7): 1096. <https://doi.org/10.3390/polym13071>
- Lopez, O.; Garcia, M.A.; Villar, M.A.; Gentili, A.; Rodriguez, M.; Albertengo, L. (2014). Thermo-compression of biodegradable thermoplastic corn starch films containing chitin and chitosan. *LWT-Food Sci. Technol.*
- MUT Muttaqin H.S. Afdhal. (2005). Sifat Listrik Film Polivinil Alkohol (PVA) yang dengan NaCl serta aplikasinya sebagai Sensor. Tesis Pascasarjana UI.

- Narudin, N.A.H., Mahadi, A.H., Kusri, E., Usman, A.(2020). Chitin, chitosan and submicron-sized chitosan particles prepared from *Scylla serrata* shells. *Materials International*, 2(2): 139-149. <https://doi.org/10.33263/Materials22>
- Parning, Horale dan Tiopan. (2006). *Kimia*. Cetakan Pertama. Yudhistira. Jkt. Hal: 188
- Pereira, P.F.; Andrade, C.T. (2017). Optimized pH-responsive film based on a eutectic mixture-plasticized chitosan. *Carbohydr. Polym.* 165, 238–246.
- Queiroz, M.F., Teodosio Melo, K.R., Sabry, D.A., Sassaki, G.L., Rocha, H.A.O. (2014). Does the use of chitosan contribute to oxalate kidney stone formation? *Marine Drugs*, 13(1): 141-158. <https://doi.org/10.3390/md130>.
- RAJ, Sachin S., et al. Philosophy of selecting ASTM standards for mechanical characterization of polymers and polymer composites. *Materiale Plastice*, 2021, 58.3: 247-256.
- Sakai Y., Sadaoka Y., Matsuguchi M. Humidity Sensors Based on Polymer Thin Films, *Sensors & Actuators B*, 35-36, 1996, 85-90
- Sirotkin, N., Khlyustova, A., Costerin, D., Naumova, I., Kalazhokov, Z., Kalazhokov, K., Titov, V., Agafonov, A. (2022). Synthesis of chitosan/PVA/metal oxide nanocomposite using underwater discharge plasma: characterization and antibacterial activities. *Polymer Bulletin*, 1-20. <https://doi.org/10.1007/s00289-022-04348-2>
- Soebianto, Yanti.S. Karakteristik Pencangkakan Asam Akrilat Dan Akrilamida Pada Serbuk Selulosa Dengan Inisiasi Sinar Gamma. Puslitbang Teknologi Isotop dan Radiasi (P3TIR)- Batan.
- Van Vlack, L H. (2001). *Elemen-elemen Ilmu dan Rekayasa Material*, edisi keenam. Erlangga, Jakarta.
- Voronova, M. I., O. V. Surov, S. S. Guseinov, V. P. Barannikov, and A. G. Zakharov. (2015). Thermal stability of composites of polyvinyl alcohol with nanocrystalline cellulose in its acid and neutralized forms. *Carbohydrate Polymers* 130:440–47.
- Yang Mu-Rong, Chen Ko-Shao. (1998). Humidity Sensors Using Polyvinyl Alcohol Mixed with Electrolyte, *Sensors & Actuators B*, 49, 240-247.