DAFTAR PUSTAKA

[1] I. I. R. Salma, D. K. Syabana, Y. Satria, and R. Christianto, "Diversifikasi desain produk tenun ikat nusa tenggara timur dengan paduan teknik tenun dan teknik batik," *Din. Kerajinan dan Batik Maj. Ilm.*, vol. 35, no. 2, p. 85, Dec. 2018, doi: 10.22322/dkb.v35i2.4174.

[2] D. L. Nadek, Yersi Florida, "Minat konsumen pada tenun ikat NTT di sentra tenunn ikat Ina Ndao kota kupang," *e-Journal. Vol. 07 Nomor 02 Tahun 2018*, vol. 07, pp. 100–105, 2018.

[3] I. Pemerintah Republik, "Undang-Undang Nomor 28 Tahun 2014 Tentang Hak Cipta," no. 1, 2014.

[4] KEMENTRIAN HUKUM DAN HAM RI, "Peraturan Menteri Hukum Dan Hak Asasi Manusia Republik Indonesia Nomor 10 Tahun 2022 Tentang Perubahan Atas Peraturan Menteri Hukum Dan Hak Asasi Manusia Nomor 12 Tahun 2019 Tentang Indikasi Geografis," *Peratur. Menteri Kesehat. Republik Indones. Nomor 4 Tahun 2018*, vol. 151, no. 2, pp. 10–17, 2018.

[5] M. I. J. Lamabelawa and T. Informatika, "Perbandingan ekstraksi fitur tenun ikat NTT berbasis analisis tekstur," *J. HOAQ -Teknologi Inf.*, vol. 7, no. 1, pp. 481–488, 2016.

[6] B. Baso and N. Suciati, "Temu Kembali Citra Tenun Nusa Tenggara Timur menggunakan Esktraksi Fitur yang Robust terhadap Perubahan Skala, Rotasi, dan Pencahayaan," *J. Teknol. Inf. dan Ilmu Komput.*, vol. 7, no. 2, p. 349, Feb. 2020, doi: 10.25126/jtiik.2020722002.

[7] A. B. Seran, A. Y. Rahman, and I. Istiadi, "Temu Kembali Kemiripan Motif Citra Tenun Menggunakan Transformasi Wavelet Diskrit Dan GLCM," *J. RESTI (Rekayasa Sist. dan Teknol. Informasi)*, vol. 5, no. 5, pp. 958–966, 2021, doi: 10.29207/resti.v5i5.3484.

[8] A. S. Prabuwono, W. Usino, A. Bramantoro, K. H. S. Allehaibi, H. A., and T. Defisa, "Content based image retrieval and support vector machine methods for face recognition," *TEM J.*, vol. 8, no. 2, pp. 389–395, 2019, doi: 10.18421/TEM82-10.

[9] J. Xiang, N. Zhang, R. Pan, and W. Gao, "Fabric image retrieval system using hierarchical search based on deep convolutional neural network," *IEEE Access*, vol. 7, pp. 35405–35417, 2019, doi: 10.1109/ACCESS.2019.2898906.

[10] J. Xiang, N. Zhang, R. Pan, and W. Gao, "Fabric retrieval based on multi-task learning," *IEEE Trans. Image Process.*, vol. 30, no. 2, pp. 1570–1582, 2021, doi: 10.1109/TIP.2020.3043877.

[11] N. Zhang, R. Shamey, J. Xiang, R. Pan, and W. Gao, "A novel image retrieval strategy based on transfer learning and hand-crafted features for wool fabric," *Expert Syst. Appl.*, vol. 191, no. November 2021, p. 116229, 2022, doi: 10.1016/j.eswa.2021.116229.

[12] H. Prasetyo and B. A. Putra Akardihas, "Batik image retrieval using convolutional neural network," *TELKOMNIKA (Telecommunication Comput. Electron. Control.*, vol. 17, no. 6, p. 3010, Dec. 2019, doi: 10.12928/telkomnika.v17i6.12701.

[13] O. García-Olalla, E. Alegre, L. Fernández-Robles, E. Fidalgo, and S. Saikia, "Textile retrieval based on image content from CDC and webcam cameras in indoor environments," *Sensors (Switzerland)*, vol. 18, no. 5, pp. 1–20, 2018, doi: 10.3390/s18051329.

[14] I. Nurhaida, H. Wei, R. A. M. Zen, R. Manurung, and A. M. Arymurthy, "Texture fusion for batik motif retrieval system," *Int. J. Electr. Comput. Eng.*, vol. 6, no. 6,

pp. 3174–3187, 2016, doi: 10.11591/ijece.v6i6.12049.

[15] C. Mutia, F. Arnia, and R. Muharar, "Improving the performance of CBIR on islamic women apparels using normalized PHOG," *Bull. Electr. Eng. Informatics*, vol. 6, no. 3, pp. 271–280, 2017, doi: 10.11591/eei.v6i3.657.

[16] A. A. Kasim, R. Wardoyo, and A. Harjoko, "Batik classification with artificial neural network based ontexture-shape feature of main ornament," *Int. J. Intell. Syst. Appl.*, vol. 9, no. 6, pp. 55–65, 2017, doi: 10.5815/ijisa.2017.06.06.

[17] N. Zhang, J. Xiang, L. Wang, W. Gao, and R. Pan, "Image retrieval of wool fabric. Part I: Based on low-level texture features," *Text. Res. J.*, vol. 89, no. 19–20, pp. 4195–4207, Oct. 2019, doi: 10.1177/0040517519829003.

[18] N. Zhang, J. Xiang, L. Wang, N. Xiong, W. Gao, and R. Pan, "Image retrieval of wool fabric. Part II: based on low-level color features," *Text. Res. J.*, vol. 90, no. 7–8, pp. 797–808, 2020, doi: 10.1177/0040517519881819.

[19] J. Wang *et al.*, "Automatic Assessment of Fabric Smoothness Appearance Based on a Compact Convolutional Neural Network with Label Smoothing," *IEEE Access*, vol. 8, pp. 26966–26974, 2020, doi: 10.1109/ACCESS.2020.2971506.

[20] A. Nazir, R. Ashraf, T. Hamdani, and N. Ali, "Content based image retrieval system by using HSV color histogram, discrete wavelet transform and edge histogram descriptor," *2018 Int. Conf. Comput. Math. Eng. Technol. Inven. Innov. Integr. Socioecon. Dev. iCoMET 2018 - Proc.*, vol. 2018-Janua, pp. 1–6, 2018, doi: 10.1109/ICOMET.2018.8346343.

[21] I. Nasita, K. Muchtar, K. Saddami, and F. Arnia, "Cross-domain clothing image retrieval based on hybrid shape feature," *Proc. Cybern. 2019 - 2019 IEEE Int. Conf. Cybern. Comput. Intell. Towar. a Smart Human-Centered Cyber World*, pp. 98–102, 2019, doi: 10.1109/CYBERNETICSCOM.2019.8875676.

[22] A. F. Dewi, F. Arnia, and R. Muharar, "Effectiveness of MPEG-7 color features in clothing retrieval," *Bull. Electr. Eng. Informatics*, vol. 6, no. 2, pp. 166–173, 2017, doi: 10.11591/eei.v6i2.619.

[23] N. Aulia, F. Arnia, and K. Munadi, "HOG of region of interest for improving clothing retrieval performance," *Proc. Cybern. 2019 - 2019 IEEE Int. Conf. Cybern. Comput. Intell. Towar. a Smart Human-Centered Cyber World*, pp. 7–12, 2019, doi: 10.1109/CYBERNETICSCOM.2019.8875636.

[24] R. Ashraf *et al.*, "Content Based Image Retrieval by Using Color Descriptor and Discrete Wavelet Transform," *J. Med. Syst.*, vol. 42, no. 3, 2018, doi: 10.1007/s10916-017-0880-7.

[25] Z. Wang, Y. Gu, Y. Zhang, J. Zhou, and X. Gu, "Clothing retrieval with visual attention model," *2017 IEEE Vis. Commun. Image Process. VCIP 2017*, vol. 2018-Janua, pp. 1–4, 2018, doi: 10.1109/VCIP.2017.8305144.

[26] Y. Li, J. Zhang, M. Chen, H. Lei, G. Luo, and Y. Huang, "Shape based local affine invariant texture characteristics for fabric image retrieval," *Multimed. Tools Appl.*, vol. 78, no. 11, pp. 15433–15453, 2019, doi: 10.1007/s11042-018-6936-y.

[27] R. T. Wahyuningrum and I. A. Siradjuddin, "An efficient batik image retrieval system based on color and texture features," *J. Theor. Appl. Inf. Technol.*, vol. 81, no. 2, pp. 349–354, 2015.

[28] J. Jing, Q. Li, P. Li, and L. Zhang, "A new method of printed fabric image retrieval based on color moments and gist feature description," *Text. Res. J.*, vol. 86, no. 11, pp. 1137–1150, 2016, doi: 10.1177/0040517515606378.

[29] F. Shen *et al.*, "A large benchmark for fabric image retrieval," in *2019 IEEE 4th International Conference on Image, Vision and Computing (ICIVC)*, 2019, pp. 247–251, doi: 10.1109/ICIVC47709.2019.8981065.

[30] D. Deng, R. Wang, H. Wu, H. He, Q. Li, and X. Luo, "Learning deep similarity models with focus ranking for fabric image retrieval," *Image Vis. Comput.*, vol. 70, pp. 11–20, Feb. 2018, doi: 10.1016/j.imavis.2017.12.005.

[31] L. Xiao and X. Yichao, "Exact clothing retrieval approach based on deep neural network," *Proc. 2016 IEEE Inf. Technol. Networking, Electron. Autom. Control Conf. ITNEC 2016*, no. 1, pp. 396–400, 2016, doi: 10.1109/ITNEC.2016.7560389.

[32] X. Wang, Z. Xie, and S. Hao, "Clothing identification based on fused key points," *ACM Int. Conf. Proceeding Ser.*, vol. Part F1481, pp. 116–120, 2019, doi: 10.1145/3319921.3319949.

[33] H. Tariq, S. Sheikh, U. A. Mohsin Ali, and A. Ali, "Domain Specific Content Based Image Retrieval (CBIR) for Feminine Textile Designs," *Ijcsns*, vol. 19, no. 2, p. 88, 2019.

[34] L. Yao and H. Ke, "Robust image retrieval for lacy and embroidered fabric," *Text. Res. J.*, vol. 89, no. 13, pp. 2616–2625, 2019, doi: 10.1177/0040517518798648.

[35] C.-F. J. Kuo, C.-L. Lee, and C.-Y. Shih, "Image database of printed fabric with repeating dot patterns part (I) – image archiving," *Text. Res. J.*, vol. 87, no. 17, pp. 2089–2105, Oct. 2017, doi: 10.1177/0040517516663160.

[36] H. Lei, Y. Yi, Y. Li, G. Luo, and M. Wang, "A new clothing image retrieval algorithm based on sketch component segmentation in mobile visual sensors," *Int. J. Distrib. Sens. Networks*, vol. 14, no. 11, 2018, doi: 10.1177/1550147718815627.

[37] N. Suciati, D. Herumurti, and A. Y. Wijaya, "Fractal-based texture and HSV color features for fabric image retrieval," *Proc. - 5th IEEE Int. Conf. Control Syst. Comput. Eng. ICCSCE 2015*, no. November, pp. 178–182, 2016, doi: 10.1109/ICCSCE.2015.7482180.

[38] Rangkuti, "Content Based Batik Image Retrieval," *J. Comput. Sci.*, vol. 10, no. 6, pp. 925–934, 2014, doi: 10.3844/jcssp.2014.925.934.

[39] Y. Bi, R. Bhatia, and S. Kapoor, "Frontiers in Intelligent Computing: Theory and Applications," in *Proceedings of the 7th International Conference on FICTA*, 2018, vol. 104, pp. 304–314.

[40] Y. W. Chen, X. Huang, D. Chen, and X. H. Han, "Generic and Specific Impressions Estimation and Their Application to KANSEI-Based Clothing Fabric Image Retrieval," *Int. J. Pattern Recognit. Artif. Intell.*, vol. 32, no. 10, pp. 1–18, 2018, doi: 10.1142/S0218001418540241.

[41] K. Yildiz, "Dimensionality reduction-based feature extraction and classification on fleece fabric images," *Signal, Image Video Process.*, vol. 11, no. 2, pp. 317–323, 2017, doi: 10.1007/s11760-016-0939-9.

[42] S. Singh and S. Batra, "An efficient bi-layer content based image retrieval system," *Multimed. Tools Appl.*, vol. 79, no. 25–26, pp. 17731–17759, 2020, doi: 10.1007/s11042-019-08401-7.

[43] D. Latha and Y. Jacob Vetha Raj, "Hybrid CBIR method using statistical, DWT-Entropy and POPMV-based feature sets," *IET Image Process.*, vol. 13, no. 12, pp. 2031–2044, Oct. 2019, doi: 10.1049/iet-ipr.2018.5797.

[44] S. Fadaei, R. Amirfattahi, and M. R. Ahmadzadeh, "New content-based image retrieval system based on optimised integration of DCD, wavelet and curvelet features," *IET Image Process.*, vol. 11, no. 2, pp. 89–98, 2017, doi: 10.1049/iet-ipr.2016.0542.

[45] H. Prasetyo and J. W. Simatupang, "Batik Image Retrieval Using Maximum Run Length LBP and Sine-Cosine Optimizer," *ICSECC 2019 - Int. Conf. Sustain. Eng. Creat. Comput. New Idea, New Innov. Proc.*, pp. 265–269, 2019, doi: 10.1109/ICSECC.2019.8907190.

[46] W. Heri Prasetyo and Winarno, "Statistical modeling of gabor filtered magnitude for batik image retrieval," *J. Telecommun. Electron. Comput. Eng.*, vol. 10, no. 2–4, pp. 85–89, 2018.

[47] Q. Feng, Q. Hao, Y. Chen, Y. Yi, Y. Wei, and J. Dai, "Hybrid Histogram Descriptor: A Fusion Feature Representation for Image Retrieval," *Sensors*, vol. 18, no. 6, p. 1943, Jun. 2018, doi: 10.3390/s18061943.

[48] H. Zhang, Y. Sun, L. Liu, and X. Xu, "CascadeGAN: A category-supervised cascading generative adversarial network for clothes translation from the human body to tiled images," *Neurocomputing*, vol. 382, pp. 148–161, 2020, doi: 10.1016/j.neucom.2019.11.085.

[49] F. I. Chou, Y. K. Tsai, Y. M. Chen, J. T. Tsai, and C. C. Kuo, "Optimizing Parameters of Multi-Layer Convolutional Neural Network by Modeling and Optimization Method," *IEEE Access*, vol. 7, pp. 68316–68330, 2019, doi: 10.1109/ACCESS.2019.2918563.

[50] Z. Cai, W. Gao, Z. Yu, J. Huang, and Z. Cai, "Feature extraction with triplet convolutional neural network for content-based image retrieval," in *2017 12th IEEE Conference on Industrial Electronics and Applications (ICIEA)*, 2017, vol. 2018-Febru, pp. 337–342, doi: 10.1109/ICIEA.2017.8282867.

[51] Y. Xiong, N. Liu, Z. Xu, and Y. Zhang, "A parameter partial-sharing CNN architecture for cross-domain clothing retrieval," *VCIP 2016 - 30th Anniv. Vis. Commun. Image Process.*, pp. 1–4, 2017, doi: 10.1109/VCIP.2016.7805463.

[52] K. Lin, H. F. Yang, K. H. Liu, J. H. Hsiao, and C. S. Chen, "Rapid clothing retrieval via deep learning of binary codes and hierarchical search," *ICMR 2015 - Proc. 2015 ACM Int. Conf. Multimed. Retr.*, pp. 499–502, 2015, doi: 10.1145/2671188.2749318.

[53] D. D. Pukale, S. G. Bhirud, and V. D. Katkar, "Content-based Image Retrieval using Deep Convolution Neural Network," *2017 Int. Conf. Comput. Commun. Control Autom. ICCUBEA 2017*, vol. 6, no. 8, pp. 199–203, 2018, doi: 10.1109/ICCUBEA.2017.8463691.

[54] L. Zhou, Z. Zhou, and L. Z. B, "Deep Part-Based Image Feature," pp. 340–347, 2017.

[55] J. Zhu, Y. Yang, J. Cao, E. Chak, and F. Mei, "Artificial Intelligence on Fashion and Textiles," vol. 849, no. January, pp. 121–128, 2019, doi: 10.1007/978-3-319-99695-0.

[56] Y. Yang, S. Jiao, J. He, B. Xia, J. Li, and R. Xiao, "Image retrieval via learning content-based deep quality model towards big data," *Futur. Gener. Comput. Syst.*, vol. 112, pp. 243–249, 2020, doi: 10.1016/j.future.2020.05.016.

[57] S. Wei, L. Liao, J. Li, Q. Zheng, F. Yang, and Y. Zhao, "Saliency Inside: Learning Attentive CNNs for Content-Based Image Retrieval," *IEEE Trans. Image Process.*, vol. 28, no. 9, pp. 4580–4593, Sep. 2019, doi: 10.1109/TIP.2019.2913513.

[58] S. Park, M. Shin, S. Ham, S. Choe, and Y. Kang, "Study on fashion image retrieval methods for efficient fashion visual search," *IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit. Work.*, vol. 2019-June, pp. 316–319, 2019, doi: 10.1109/CVPRW.2019.00042.

[59] Z. Luo, J. Yuan, J. Yang, and W. Wen, "Spatial constraint multiple granularity attention network for clothes retrieval", Jiahui Yuan Jie Yang Wei Wen Samsung Research China-Beijing (SRC-B), Beijing, China Institute of Automation, Chinese Academy of Sciences," *2019 IEEE Int. Conf. Image Process.*, pp. 859–863, 2019.

[60] R. Li, F. Feng, I. Ahmad, and X. Wang, "Retrieving real world clothing images via multi-weight deep convolutional neural networks," *Cluster Comput.*, vol. 22, no. s3, pp. 7123–7134, 2019, doi: 10.1007/s10586-017-1052-8.

[61] W. Wei and Y. Wang, "Color Image Retrieval Based on Quaternion and Deep Features," *IEEE Access*, vol. 7, pp. 126430–126438, 2019, doi: 10.1109/ACCESS.2019.2938000.

[62] Y. Liu, Y. Peng, D. Hu, D. Li, K. P. Lim, and N. Ling, "Image Retrieval using CNN and Low-level Feature Fusion for Crime Scene Investigation Image Database," *2018 Asia-Pacific Signal Inf. Process. Assoc. Annu. Summit Conf. APSIPA ASC 2018 - Proc.*, no. November, pp. 1208–1214, 2019, doi: 10.23919/APSIPA.2018.8659471.

[63] X. Zheng, Y. Zhang, and X. Lu, "Deep Balanced discrete hashing for image retrieval," *Neurocomputing*, vol. 403, pp. 224–236, 2020, doi: 10.1016/j.neucom.2020.04.037.

[64] X. Xie *et al.*, "An Infectious cDNA Clone of SARS-CoV-2," *Cell Host Microbe*, vol. 27, no. 5, pp. 841-848.e3, May 2020, doi: 10.1016/j.chom.2020.04.004.

[65] F. Ye, H. Xiao, X. Zhao, M. Dong, W. Luo, and W. Min, "Remote sensing image retrieval using convolutional neural network features and weighted distance," *IEEE Geosci. Remote Sens. Lett.*, vol. 15, no. 10, pp. 1535–1539, 2018, doi: 10.1109/LGRS.2018.2847303.

[66] I. C. Amitha and N. K. Narayanan, "Object Retrieval in Images using SIFT and R-CNN," *2020 Int. Conf. Innov. Trends Inf. Technol. ICITIIT 2020*, 2020, doi: 10.1109/ICITIIT49094.2020.9071557.

[67] D. Varga and T. Sziranyi, "Fast content-based image retrieval using convolutional neural network and hash function," *2016 IEEE Int. Conf. Syst. Man, Cybern. SMC 2016 - Conf. Proc.*, pp. 2636–2640, 2017, doi: 10.1109/SMC.2016.7844637.

[68] T. Jenicek and O. Chum, "No fear of the dark: Image retrieval under varying illumination conditions," *Proc. IEEE Int. Conf. Comput. Vis.*, vol. 2019-Octob, pp. 9695–9703, 2019, doi: 10.1109/ICCV.2019.00979.

[69] J. S. Gill, R. Singh, P. Palta, T. Sharma, and G. Goel, "CBIR of Trademark Images in different color spaces using XYZ and HSI," vol. 6, no. 5, pp. 84–91, 2016.

[70] R. Kapoor, D. Sharma, and T. Gulati, "State of the art content based image retrieval techniques using deep learning: a survey," *Multimed. Tools Appl.*, vol. 80, no. 19, pp. 29561–29583, 2021, doi: 10.1007/s11042-021-11045-1.

[71] A. R. Nagar, N. S. Sushmitha, and M. K. Nalini, "Content Based Image Retrieval for the Medical Domain," vol. 8, no. 06, pp. 1345–1351, 2019.

[72] P. Sadeghi-Tehran, P. Angelov, N. Virlet, and M. Hawkesford, "Scalable Database Indexing and Fast Image Retrieval Based on Deep Learning and Hierarchically Nested Structure Applied to Remote Sensing and Plant Biology," *J. Imaging*, vol. 5, no. 3, p. 33, Mar. 2019, doi: 10.3390/jimaging5030033.

[73] S. Ting and G. Guohua, "Image Retrieval Method for Deep Neural Network," *Int. J. Signal Process. Image Process. Pattern Recognit.*, vol. 9, no. 7, pp. 33–42, 2016, doi: 10.14257/ijsip.2016.9.7.04.

[74] S. Khan, H. Rahmani, S. A. A. Shah, and M. Bennamoun, "A Guide to Convolutional Neural Networks for Computer Vision," *Synth. Lect. Comput. Vis.*, vol. 8, no. 1, pp. 1–207, Feb. 2018, doi: 10.2200/S00822ED1V01Y201712COV015.

[75] A. Qayyum, S. M. Anwar, M. Awais, and M. Majid, "Medical image retrieval using deep convolutional neural network," *Neurocomputing*, vol. 266, pp. 8–20, 2017, doi: 10.1016/j.neucom.2017.05.025.

[76]   H. El-kaime, M. Hanoune, and A. Eddaoui, *Lecture Notes in Real-Time Intelligent Systems*, vol. 756, no. December 2018. Springer International Publishing, 2019.

[77]   S. Wang, J. Cao, and P. S. Yu, "Deep Learning for Spatio-Temporal Data Mining: A Survey," pp. 1–21, 2019, doi: 10.48550/arXiv.1906.04928.

[78]   Z. Li, X. Zhang, H. Müller, and S. Zhang, "Large-scale retrieval for medical image analytics: A comprehensive review," *Med. Image Anal.*, vol. 43, pp. 66–84, 2018, doi: 10.1016/j.media.2017.09.007.

[79]   M. Z. Alom *et al.*, "A State-of-the-Art Survey on Deep Learning Theory and Architectures," *Electronics*, vol. 8, no. 3, p. 292, Mar. 2019, doi: 10.3390/electronics8030292.

[80]   Gonzalez C.R and Woods R., *Digital Image Processing*, Second Edi. New Jersey: Prentice Hall, 2002.

[81]   P. Tschandl, G. Argenziano, M. Razmara, and J. Yap, "Diagnostic accuracy of content-based dermatoscopic image retrieval with deep classification features," *Br. J. Dermatol.*, vol. 181, no. 1, pp. 155–165, Jul. 2019, doi: 10.1111/bjd.17189.

[82]   A. Zafar *et al.*, "A Comparison of Pooling Methods for Convolutional Neural Networks," *Appl. Sci.*, vol. 12, no. 17, p. 8643, Aug. 2022, doi: 10.3390/app12178643.

[83]   W. Liu, Z. Wang, X. Liu, N. Zeng, Y. Liu, and F. E. Alsaadi, "A survey of deep neural network architectures and their applications," *Neurocomputing*, vol. 234, pp. 11–26, Apr. 2017, doi: 10.1016/j.neucom.2016.12.038.

[84]   A. K. dan A. Susanto, *Teori dan Aplikasi Pengolahan Citra*. Yogyakarta: Penerbit ANDI, 2013.

[85]   D. Cai, "A Revisit of Hashing Algorithms for Approximate Nearest Neighbor Search," *IEEE Trans. Knowl. Data Eng.*, vol. 33, no. 6, pp. 2337–2348, 2019, doi: 10.1109/tkde.2019.2953897.

[86]   Y. Luo, W. Li, X. Ma, and K. Zhang, "Image retrieval algorithm based on locality-sensitive hash using convolutional neural network and attention mechanism," *Information*, vol. 13, no. 10, p. 446, Sep. 2022, doi: 10.3390/info13100446.

[87]   I. H. Witten, E. Frank, and Mark A. Hall, *Data Mining: Practical Machine learning 3rd ed.* 2011.

[88]   X. Li, J. Yang, and J. Ma, "Recent developments of content-based image retrieval (CBIR)," *Neurocomputing*, vol. 452, pp. 675–689, 2021, doi: 10.1016/j.neucom.2020.07.139.

[89]   B. A. Krizhevsky, I. Sutskever, and G. E. Hinton, "ImageNet Classification with Deep Convolutional Neural Networks," *Commun. ACM*, vol. 60, no. 6, pp. 84–90, 2012.

[90]   H. Rastegar and D. Giveki, "Designing a new deep convolutional neural network for content-based image retrieval with relevance feedback," *Comput. Electr. Eng.*, vol. 106, no. January, p. 108593, Mar. 2023, doi: 10.1016/j.compeleceng.2023.108593.

[91]   Y. Meir, O. Tevet, Y. Tzach, S. Hodassman, R. D. Gross, and I. Kanter, "Efficient shallow learning as an alternative to deep learning," *Sci. Rep.*, vol. 13, no. 1, pp. 1–7, 2023, doi: 10.1038/s41598-023-32559-8.

[92]   A. Suryarasmi, C. C. Chang, R. Akhmalia, M. Marshallia, W. J. Wang, and D. Liang, "FN-Net: A lightweight CNN-based architecture for fabric defect detection with adaptive threshold-based class determination," *Displays*, vol. 73, no. April, p. 102241, 2022, doi: 10.1016/j.displa.2022.102241.

[93]   G. G. Dario *et al.*, "On the behavior of convolutional nets for feature extraction," *J. Artif. Intell. Res.*, vol. 61, pp. 563–592, 2018, doi: 10.1613/jair.5756.

[94]   W. S. Ahmed and A. A. A. Karim, "The impact of filter size and number of filters on classification accuracy in CNN," *Proc. 2020 Int. Conf. Comput. Sci. Softw. Eng. CSASE 2020*, pp. 88–93, 2020, doi: 10.1109/CSASE48920.2020.9142089.

[95]   V. Suárez-Paniagua and I. Segura-Bedmar, "Evaluation of pooling operations in convolutional architectures for drug-drug interaction extraction," *BMC Bioinformatics*, vol. 19, no. Suppl 8, 2018, doi: 10.1186/s12859-018-2195-1.

[96]   C. L. Yang, Y. Harjoseputro, Y. C. Hu, and Y. Y. Chen, "An Improved Transfer-learning for Image-based Species Classification of Protected Indonesians Birds," *Comput. Mater. Contin.*, vol. 73, no. 3, pp. 4577–4593, 2022, doi: 10.32604/cmc.2022.031305.

[97]   A. G. Howard *et al.*, "MobileNets: efficient convolutional neural networks for mobile vision applications," Apr. 2017, doi: 10.48550/arXiv.1704.04861.

[98]   J. Yang and G. Yang, "Modified convolutional neural network based on dropout and the stochastic gradient descent optimizer," *Algorithms*, vol. 11, no. 3, pp. 1–15, 2018, doi: 10.3390/a11030028.

[99]   M. Liu *et al.*, "Focused dropout for convolutional neural network," *Appl. Sci.*, vol. 12, no. 15, p. 7682, 2022, doi: 10.3390/app12157682.

[100] T. Agrawal, *Hyperparameter Optimization in Machine Learning: Make Your Machine Learning and Deep Learning Models More Efficient*. Apress, 2021.

[101] R. Siddiqi, "Effectiveness of transfer learning and fine tuning in automated fruit image classification," *ACM Int. Conf. Proceeding Ser.*, no. i, pp. 91–100, 2019, doi: 10.1145/3342999.3343002.

[102] A. Canziani, A. Paszke, and E. Culurciello, "An Analysis of Deep Neural Network Models for Practical Applications," pp. 1–7, 2016.

[103] K. Simonyan and A. Zisserman, "Very deep convolutional networks for large-scale image recognition," *3rd Int. Conf. Learn. Represent. ICLR 2015 - Conf. Track Proc.*, pp. 1–14, 2015.

[104] K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," in *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, vol. 2016-December, pp. 770–778, doi: 10.1109/CVPR.2016.90.

[105] C. Szegedy *et al.*, "Going deeper with convolutions," *Proc. IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit.*, vol. 07-12-June, pp. 1–9, 2015, doi: 10.1109/CVPR.2015.7298594.

[106] F. Chollet, "Xception: Deep Learning with Depthwise Separable Convolutions," *2017 IEEE Conf. Comput. Vis. Pattern Recognit.*, vol. 2017-January, pp. 1800–1807, Oct. 2016.

[107] C. R. Edwin Selva Rex, J. Annrose, and J. Jenifer Jose, "Comparative analysis of deep convolution neural network models on small scale datasets," *Optik (Stuttg).*, vol. 271, no. October, p. 170238, 2022, doi: 10.1016/j.ijleo.2022.170238.

[108] S. Tena, R. Hartanto, and I. Ardiyanto, "East nusa tenggara weaving image retrieval using convolutional neural network," in *2021 4th International Seminar on Research of Information Technology and Intelligent Systems (ISRITI)*, 2021, pp. 150–154, doi: 10.1109/ISRITI54043.2021.9702843.

[109] M. Lin, Q. Chen, and S. Yan, "Network in network," *2nd Int. Conf. Learn. Represent. ICLR 2014 - Conf. Track Proc.*, pp. 1–10, 2014.

[110] A. Gordo, J. Almazán, J. Revaud, and D. Larlus, "End-to-End Learning of Deep Visual Representations for Image Retrieval," *Int. J. Comput. Vis.*, vol. 124, no. 2, pp. 237–254, Sep. 2017, doi: 10.1007/s11263-017-1016-8.

[111] C. Szegedy, S. Ioffe, V. Vanhoucke, and A. A. Alemi, "Inception-v4, inception-

ResNet and the impact of residual connections on learning," *31st AAAI Conf. Artif. Intell. AAAI 2017*, pp. 4278–4284, 2017.

[112] W. Yang, L. Xu, X. Chen, F. Zheng, and Y. Liu, "Chi-squared distance metric learning for histogram data," *Math. Probl. Eng.*, vol. 2015, 2015, doi: 10.1155/2015/352849.

[113] P. Isola, A. A. Efros, B. Ai, and U. C. Berkeley, "Image-to-Image Translation with Conditional Adversarial Networks."

[114] D. W. Prabowo, H. A. Nugroho, N. A. Setiawan, and J. Debayle, "An Advanced Data Augmentation Scheme on Limited EEG Signals for Human Emotion Recognition," *Lect. Notes Electr. Eng.*, vol. 1008, pp. 391–409, 2023, doi: 10.1007/978-981-99-0248-4_27.

[115] S. Tena, R. Hartanto, and I. Ardiyanto, "Content-based image retrieval for fabric images: A survey," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 23, no. 3, p. 1861, Sep. 2021, doi: 10.11591/ijeecs.v23.i3.pp1861-1872.