



## REFERENCES

- Ahn, S.-H., Montero, M., Odell, D., Roundy, S., Wright, P.K., 2002. Anisotropic material properties of fused deposition modeling ABS. *Rapid Prototyp. J.* 8, 248–257.
- Akbas, O.E., Hira, O., Hervan, S.Z., Samankan, S., Altinkaynak, A., 2019. Dimensional accuracy of FDM-printed polymer parts. *Rapid Prototyp. J.*
- Álvarez, K., Lagos, R.F., Aizpun, M., 2016. Investigating the influence of infill percentage on the mechanical properties of fused deposition modelled ABS parts. *Ing. e Investig.* 36, 110.
- American Society for Testing and Materials, 2016. ASTM D638-14, Standard Practice for Preparation of Metallographic Specimens. *ASTM Int.* 82, 1–15.
- Arifvianto, B., Wirawan, Y.B., Salim, U.A., Suyitno, S., Mahardika, M., 2021. Effects of extruder temperatures and raster orientations on mechanical properties of the FFF-processed polylactic-acid (PLA) material. *Rapid Prototyp. J.* 27, 1761–1775.
- Averett, R.D., Realff, M.L., Jacob, K., Cakmak, M., Yalcin, B., 2011. The mechanical behavior of poly(lactic acid) unreinforced and nanocomposite films subjected to monotonic and fatigue loading conditions. *J. Compos. Mater.* 45, 2717–2726.
- Bahadur W, Y., Mahardika, M., 2019. Pengaruh Temperatur Ekstrusi dan Orientasi Raster Terhadap Sifat Mekanis dan Perambatan Retak Lelah Material Polylactic-Acid (PLA) yang Difabrikasi dengan Fused Deposition Modelling (FDM). Universitas Gadjah Mada.
- Bähr, F., Westkämper, E., 2018. Correlations between Influencing Parameters and Quality Properties of Components Produced by Fused Deposition Modeling. *Procedia CIRP* 72, 1214–1219.
- Bandeira, C.F., Montoro, S.R., Espindola, E.L., Botelho, E.C., Costa, M.L., Cioffi, M.O.H., 2015. Comparison of Glass Transition Temperature Values of Composite Polymer Obtained by TMA and DSC. *Appl. Mech. Mater.* 719–720, 91–95.
- Behzadnasab, M., Yousefi, A.A., Ebrahimibagha, D., Nasiri, F., 2019. Effects of



- processing conditions on mechanical properties of PLA printed parts. *Rapid Prototyp.* J. 26, 381–389.
- Bellini, A., Güceri, S., 2003. Mechanical characterization of parts fabricated using fused deposition modeling. *Rapid Prototyp. J.* 9, 252–264.
- Beran, T., Mulholland, T., Henning, F., Rudolph, N., Osswald, T.A., 2018. Nozzle clogging factors during fused filament fabrication of spherical particle filled polymers. *Addit. Manuf.* 23, 206–214.
- Bhudolia, S.K., Fischer, S., He, P.G., Yue, C.Y., Joshi, S.C., Yang, J.L., 2015. Design, manufacturing and testing of filament wound composite risers for marine and offshore applications. In: *Materials Science Forum*. pp. 337–343.
- Braconnier, D.J., Jensen, R.E., Peterson, A.M., 2020. Processing parameter correlations in material extrusion additive manufacturing. *Addit. Manuf.* 31, 100924.
- Campbell, T.W., 2012. Technologies, Potential, and Implications of Additive Manufacturing. [Cbpp.Uaa.Alaska.Edu](http://Cbpp.Uaa.Alaska.Edu).
- Çanti, E., Aydin, M., 2018. Effects of micro particle reinforcement on mechanical properties of 3D printed parts. *Rapid Prototyp. J.*
- Çanti, E., Aydin, M., 2018. Effects of micro particle reinforcement on mechanical properties of 3D printed parts. *Rapid Prototyp. J.* 24, 171–176.
- Cantrell, J.T., Rohde, S., Damiani, D., Gurnani, R., DiSandro, L., Anton, J., Young, A., Jerez, A., Steinbach, D., Kroese, C., Ifju, P.G., 2017. Experimental characterization of the mechanical properties of 3D-printed ABS and polycarbonate parts. *Rapid Prototyp. J.* 23, 811–824.
- Carneiro, Olga S, Silva, A.F., Gomes, R., 2015. Fused deposition modeling with polypropylene. *Mater. Des.* 83, 768–776.
- Carneiro, O. S., Silva, A.F., Gomes, R., 2015. Fused deposition modeling with polypropylene. *Mater. Des.* 83, 768–776.
- Castro-Aguirre, E., Iniguez-Franco, F., Samsudin, H., Fang, X., Auras, R., 2016. Poly (lactic acid)—Mass production, processing, industrial applications, and end of life. *Adv. Drug Deliv. Rev.* 107, 333–366.
- Chacón, J.M., Caminero, M.A., García-Plaza, E., Núñez, P.J., 2017. Additive

manufacturing of PLA structures using fused deposition modelling: Effect of process parameters on mechanical properties and their optimal selection. *Mater. Des.* 124, 143–157.

Chang, D.-Y., Huang, B.-H., 2011. Studies on profile error and extruding aperture for the RP parts using the fused deposition modeling process. *Int. J. Adv. Manuf. Technol.* 53, 1027–1037.

Cheng, L., Zhang, P., Biyikli, E., Bai, J., Robbins, J., To, A., 2017. Efficient design optimization of variable-density cellular structures for additive manufacturing: theory and experimental validation. *Rapid Prototyp. J.* 23, 660–677.

Cho, H., Choi, Y.-J., Lee, S., Koo, J., Huang, T., 2016. Comparison of hollow fiber membranes in direct contact and air gap membrane distillation (MD). *Desalin. Water Treat.* 57, 10012–10019.

Chua, C.K., Vadakke Matham, M., Kim, Y.-J., 2017. Lasers in 3D printing and manufacturing. World Scientific.

Costa, S.F., Duarte, F.M., Covas, J.A., 2015. Thermal conditions affecting heat transfer in FDM/FFE: a contribution towards the numerical modelling of the process: This paper investigates convection, conduction and radiation phenomena in the filament deposition process. *Virtual Phys. Prototyp.* 10, 35–46.

Dawoud, M., Taha, I., Ebeid, S.J., 2016. Mechanical behaviour of ABS: An experimental study using FDM and injection moulding techniques. *J. Manuf. Process.* 21, 39–45.

Dickson, A.N., Barry, J.N., McDonnell, K.A., Dowling, D.P., 2017. Fabrication of continuous carbon, glass and Kevlar fibre reinforced polymer composites using additive manufacturing. *Addit. Manuf.* 16, 146–152.

Dizon, J.R.C., Espera, A.H., Chen, Q., Advincula, R.C., 2018. Mechanical characterization of 3D-printed polymers. *Addit. Manuf.* 20, 44–67.

Dul, S., Fambri, L., Pegoretti, A., 2016. Fused deposition modelling with ABS-graphene nanocomposites. *Compos. Part A Appl. Sci. Manuf.* 85, 181–191.



- Durgun, I., Ertan, R., 2014. Experimental investigation of FDM process for improvement of mechanical properties and production cost. *Rapid Prototyp.* J. 20, 228–235.
- Ecker, J.V., Haider, A., Burzic, I., Huber, A., Eder, G., Hild, S., 2019. Mechanical properties and water absorption behaviour of PLA and PLA/wood composites prepared by 3D printing and injection moulding. *Rapid Prototyp.* J. 25, 672–678.
- Es-Said, O.S., Foyos, J., Noorani, R., Mendelson, M., Marloth, R., Pregger, B.A., 2000. Effect of Layer Orientation on Mechanical Properties of Rapid Prototyped Samples. *Mater. Manuf. Process.* 15, 107–122.
- Gamze Karsli, N., Yilmaz, T., Aytac, A., Ozkoc, G., 2013. Investigation of erosive wear behavior and physical properties of SGF and/or calcite reinforced ABS/PA6 composites. *Compos. Part B Eng.* 44, 385–393.
- Gebhardt, A., Schmidt, F.-M., Höller, J.-S., Sokalla, W., Sokalla, P., 2010. Additive manufacturing by selective laser melting the realizer desktop machine and its application for the dental industry. *Phys. Procedia* 5, 543–549.
- Gibson, I., Rosen, D., Stucker, B., 2015. *Additive Manufacturing Technologies*. Springer New York, New York, NY.
- Grasso, M., Azzouz, L., Ruiz-Hincapie, P., Zarrelli, M., Ren, G., 2018. Effect of temperature on the mechanical properties of 3D-printed PLA tensile specimens. *Rapid Prototyp. J.* 24, 1337–1346.
- Gunawan, L., Mahardika, M., 2020. PENGAMATAN KEKUATAN TARIK POLIMER POLYLACTIC ACID DENGAN SERBUK NANOTUBE KARBON MENGGUNAKAN METODE AIRFLOW EJECTION PADA MESIN 3D PRINTER. Universitas Gadjah Mada.
- Guo, N., Leu, M.C., 2013. Additive manufacturing: technology, applications and research needs. *Front. Mech. Eng.* 8, 215–243.
- Gurr, M., Mülhaupt, R., 2012. Rapid Prototyping. In: *Polymer Science: A Comprehensive Reference*. Elsevier, pp. 77–99.
- Halápi, D., Kovács, S.E., Bodnár, Z., Palotás, Á.B., Varga, L., 2018. Tensile



- analysis of 3D printer filaments. In: The Publications of the MultiScience - XXXII. MicroCAD International Scientific Conference. University of Miskolc, pp. 5–6.
- Halápi, D., Kovács, S.E., Hudák, H., Bodnár, Z., Palotás, Á.B., Varga, L., 2019. TENSILE ANALYSIS OF 3D PRINTER FILAMENTS. *Mater. Sci. Eng.* 44, 14–23.
- Heidari-Rarani, M., Rafiee-Afarani, M., Zahedi, A.M., 2019. Mechanical characterization of FDM 3D printing of continuous carbon fiber reinforced PLA composites. *Compos. Part B Eng.* 175, 107147.
- Huang, B., Masood, S.H., Nikzad, M., Venugopal, P.R., Arivazhagan, A., 2016. Dynamic Mechanical Properties of Fused Deposition Modelling Processed Polyphenylsulfone Material. *Am. J. Eng. Appl. Sci.* 9, 1–11.
- Huang, Z., Dantan, J.-Y., Etienne, A., Rivette, M., Bonnet, N., 2018. Geometrical deviation identification and prediction method for additive manufacturing. *Rapid Prototyp. J.*
- Hutmacher, D.W., 2015. Bioprinting, biofabrication, biomanufacturing? The need for definitions and norms in additive manufacturing in the biomedical sciences.
- Ivey, M., Melenka, G.W., Carey, J.P., Ayrancı, C., 2017. Characterizing short-fiber-reinforced composites produced using additive manufacturing. *Adv. Manuf. Polym. Compos. Sci.* 3, 81–91.
- Jami, H., Masood, S.H., Song, W.Q., 2013. Dynamic Response of FDM Made ABS Parts in Different Part Orientations. *Adv. Mater. Res.* 748, 291–294.
- Jiang, S., Siyajeu, Y., Shi, Y., Zhu, S., Li, H., 2020. Improving the forming quality of fused filament fabrication parts by applied vibration. *Rapid Prototyp. J.* 26, 202–212.
- Jinghua, S., Xin, H., 2015. Research on the Review of 3D Printing Technology in Construction [J]. *Huazhong Archit.* 2.
- Jo, W., Kwon, O.-C., Moon, M.-W., 2018. Investigation of influence of heat treatment on mechanical strength of FDM printed 3D objects. *Rapid Prototyp. J.* 24, 637–644.



- Jones, J.B., Wimpenny, D.I., Gibbons, G.J., 2015. Additive manufacturing under pressure. *Rapid Prototyp. J.* 21, 89–97.
- Keleş, Ö., Anderson, E.H., Huynh, J., 2018. Mechanical reliability of short carbon fiber reinforced ABS produced via vibration assisted fused deposition modeling. *Rapid Prototyp. J.* 24, 1572–1578.
- Keleş, Ö., Blevins, C.W., Bowman, K.J., 2017. Effect of build orientation on the mechanical reliability of 3D printed ABS. *Rapid Prototyp. J.* 23, 320–328.
- Kim, H., Lin, Y., Tseng, T.-L.B., 2018. A review on quality control in additive manufacturing. *Rapid Prototyp. J.*
- Kosinar, M., Kuric, I., 2011. Geometric Errors in CNC Machine Tools 21–26.
- Kruth, J., Mercelis, P., Van Vaerenbergh, J., Froyen, L., Rombouts, M., 2005. Binding mechanisms in selective laser sintering and selective laser melting. *Rapid Prototyp. J.* 11, 26–36.
- Kruth, J.P., Leu, M.C., Nakagawa, T., 1998. Progress in additive manufacturing and rapid prototyping. *CIRP Ann. - Manuf. Technol.* 47, 525–540.
- Kuznetsov, V.E., Solonin, A.N., Tavitov, A., Urzhumtsev, O., Vakulik, A., 2020. Increasing strength of FFF three-dimensional printed parts by influencing on temperature-related parameters of the process. *Rapid Prototyp. J.* 26, 107–121.
- Kuznetsov, V.E., Solonin, A.N., Urzhumtsev, O.D., Schilling, R., Tavitov, A.G., 2018. Strength of PLA components fabricated with fused deposition technology using a desktop 3D printer as a function of geometrical parameters of the process. *Polymers (Basel).* 10.
- Lanzotti, A., Grasso, M., Staiano, G., Martorelli, M., 2015. The impact of process parameters on mechanical properties of parts fabricated in PLA with an open-source 3-D printer. *Rapid Prototyp. J.* 21, 604–617.
- Le Duigou, A., Barbé, A., Guillou, E., Castro, M., 2019. 3D printing of continuous flax fibre reinforced biocomposites for structural applications. *Mater. Des.* 180, 107884.
- Lee, C.-Y., Liu, C.-Y., 2019. The influence of forced-air cooling on a 3D printed PLA part manufactured by fused filament fabrication. *Addit. Manuf.* 25,

196–203.

- Lee, C.S., Kim, S.G., Kim, H.J., Ahn, S.H., 2007. Measurement of anisotropic compressive strength of rapid prototyping parts. *J. Mater. Process. Technol.* 187–188, 627–630.
- Lee, J.Y., Tan, W.S., An, J., Chua, C.K., Tang, C.Y., Fane, A.G., Chong, T.H., 2016. The potential to enhance membrane module design with 3D printing technology. *J. Memb. Sci.* 499, 480–490.
- Li, H., Wang, T., Joshi, S., Yu, Z., 2019. The quantitative analysis of tensile strength of additively manufactured continuous carbon fiber reinforced polylactic acid (PLA). *Rapid Prototyp. J.* 25, 1624–1636.
- Li, H., Zhang, X., Duan, Y., Wang, D., Li, L., Yan, S., 2004. Influence of crystallization temperature on the morphologies of isotactic polypropylene single-polymer composite. *Polymer (Guildf.)*. 45, 8059–8065.
- Li, N., Li, Y., Liu, S., 2016. Rapid prototyping of continuous carbon fiber reinforced polylactic acid composites by 3D printing. *J. Mater. Process. Technol.* 238, 218–225.
- Lipton, J.I., Cutler, M., Nigl, F., Cohen, D., Lipson, H., 2015. Additive manufacturing for the food industry. *Trends food Sci. Technol.* 43, 114–123.
- Lyu, J., Manoochehri, S., 2019. Error modeling and compensation for FDM machines. *Rapid Prototyp. J.*
- Mae, H., Omiya, M., Kishimoto, K., 2008. Tensile behavior of polypropylene blended with bimodal distribution of styrene-ethylene-butadiene-styrene particle size. *J. Appl. Polym. Sci.* 107, 3520–3528.
- Mangat, A.S., Singh, S., Gupta, M., Sharma, R., 2018. Experimental investigations on natural fiber embedded additive manufacturing-based biodegradable structures for biomedical applications. *Rapid Prototyp. J.* 24, 1221–1234.
- Marga, F., Jakab, K., Khatiwala, C., Shepherd, B., Dorfman, S., Hubbard, B., Colbert, S., Forgacs, G., 2012. Toward engineering functional organ modules by additive manufacturing. *Biofabrication* 4, 22001.
- Masood, S., Song, W., 2004. Development of new metal/polymer materials for

- rapid tooling using Fused deposition modelling. *Mater. Des.* 25, 587–594.
- Mathew, A.P., Oksman, K., Sain, M., 2006. The effect of morphology and chemical characteristics of cellulose reinforcements on the crystallinity of polylactic acid. *J. Appl. Polym. Sci.* 101, 300–310.
- Matsuzaki, R., Ueda, M., Namiki, M., Jeong, T.-K., Asahara, H., Horiguchi, K., Nakamura, T., Todoroki, A., Hirano, Y., 2016. Three-dimensional printing of continuous-fiber composites by in-nozzle impregnation. *Sci. Rep.* 6, 23058.
- Melchels, F.P.W., Feijen, J., Grijpma, D.W., 2010. A review on stereolithography and its applications in biomedical engineering. *Biomaterials* 31, 6121–6130.
- Messiry, M. El, 2013. Theoretical analysis of natural fiber volume fraction of reinforced composites. *Alexandria Eng. J.* 52, 301–306.
- Mueller, B., Kochan, D., 1999. Laminated object manufacturing for rapid tooling and patternmaking in foundry industry. *Comput. Ind.* 39, 47–53.
- Muzakki, I.F., Mahardika, M., 2019. PENGUATAN KEKUATAN TARIK SPESIMEN POLYLACTIC ACID HASIL PENCETAKAN MESIN 3D PRINTER DENGAN PENAMBAHAN SERBUK SILIKON KARBIDA MELALUI METODE AIR BLOW ADDITION. Universitas Gadjah Mada.
- Naranjo-Lozada, J., Ahuett-Garza, H., Orta-Castañón, P., Verbeeten, W.M.H., Sáiz-González, D., 2019. Tensile properties and failure behavior of chopped and continuous carbon fiber composites produced by additive manufacturing. *Addit. Manuf.* 26, 227–241.
- Nikzad, M., Masood, S.H., Sbarski, I., 2011. Thermo-mechanical properties of a highly filled polymeric composites for Fused Deposition Modeling. *Mater. Des.* 32, 3448–3456.
- Ning, F., Cong, W., Qiu, J., Wei, J., Wang, S., 2015. Additive manufacturing of carbon fiber reinforced thermoplastic composites using fused deposition modeling. *Compos. Part B Eng.* 80, 369–378.
- Nsengimana, J., Van der Walt, J., Pei, E., Miah, M., 2019. Effect of post-processing on the dimensional accuracy of small plastic additive manufactured parts. *Rapid Prototyp. J.* 25, 1–12.
- Osman, M.A., Atia, M.R.A., 2018. Investigation of ABS-rice straw composite

- feedstock filament for FDM. *Rapid Prototyp. J.* 24, 1067–1075.
- Pedersen, D.B., 2013. Additive manufacturing: multi material processing and part quality control.
- Perkins, I., Skitmore, M., 2015. Three-dimensional printing in the construction industry: A review. *Int. J. Constr. Manag.* 15, 1–9.
- Petousis, M., Moutsopoulou, A., Korlos, A., Papadakis, V., Mountakis, N., Tsikritzis, D., Ntintakis, I., Vidakis, N., 2023a. The Effect of Nano Zirconium Dioxide ( $ZrO_2$ )-Optimized Content in Polyamide 12 (PA12) and Polylactic Acid (PLA) Matrices on Their Thermomechanical Response in 3D Printing. *Nanomaterials* 13, 1906.
- Petousis, M., Vidakis, N., Mountakis, N., Moutsopoulou, A., Papadakis, V., Maravelakis, E., 2023b. On the substantial mechanical reinforcement of Polylactic Acid with Titanium Nitride ceramic nanofillers in material extrusion 3D printing. *Ceram. Int.* 49, 16397–16411.
- Pratama, J., Cahyono, S.I., Suyitno, S., Muflikhun, M.A., Salim, U.A., Mahardika, M., Arifvianto, B., 2021. A Review on Reinforcement Methods for Polymeric Materials Processed Using Fused Filament Fabrication (FFF). *Polymers (Basel)*. 13, 4022.
- Rahim, S.L., Maidin, S., 2014. Feasibility study of additive manufacturing technology implementation in Malaysian automotive industry using analytic hierarchy process. In: *Advanced Materials Research*. pp. 450–454.
- Rajpurohit, S.R., Dave, H.K., 2018. Effect of process parameters on tensile strength of FDM printed PLA part. *Rapid Prototyp. J.* 24, 1317–1324.
- Rankouhi, B., Javadpour, S., Delfanian, F., Letcher, T., 2016. Failure Analysis and Mechanical Characterization of 3D Printed ABS With Respect to Layer Thickness and Orientation. *J. Fail. Anal. Prev.* 16, 467–481.
- Rodríguez, J.F., Thomas, J.P., Renaud, J.E., 2001. Mechanical behavior of acrylonitrile butadiene styrene (ABS) fused deposition materials. Experimental investigation. *Rapid Prototyp. J.* 7, 148–158.
- Rodríguez, J.F., Thomas, J.P., Renaud, J.E., 2003. Mechanical behavior of acrylonitrile butadiene styrene fused deposition materials modeling. *Rapid*



Prototyp. J. 9, 219–230.

Saboori, A., Gallo, D., Biamino, S., Fino, P., Lombardi, M., 2017. An overview of additive manufacturing of titanium components by directed energy deposition: microstructure and mechanical properties. Appl. Sci. 7, 883.

Sezer, H Kürcsad, Eren, O., 2019. FDM 3D printing of MWCNT re-inforced ABS nano-composite parts with enhanced mechanical and electrical properties. J. Manuf. Process. 37, 339–347.

Sezer, H. Kürşad, Eren, O., 2019. FDM 3D printing of MWCNT re-inforced ABS nano-composite parts with enhanced mechanical and electrical properties. J. Manuf. Process. 37, 339–347.

Shearer, C., Shearer, B., Matijasevic, G., Gandhi, P., 1999. Transient liquid phase sintering composites: Polymer adhesives with metallurgical bonds. J. Electron. Mater. 28, 1319–1326.

Shenzhen Esun Industrial Co., L., 2012. Safety Data Sheet. Mater. Saf. Data Sheet 4(2), 8–10.

Slonov, A.L., Khashirov, A.A., Zhansitov, A.A., Rzhevskaya, E.V., Khashirova, S.Y., 2018. The influence of the 3D-printing technology on the physical and mechanical properties of polyphenylene sulfone. Rapid Prototyp. J. 24, 1124–1130.

Sood, A.K., Ohdar, R.K., Mahapatra, S.S., 2010. Parametric appraisal of mechanical property of fused deposition modelling processed parts. Mater. Des. 31, 287–295.

Sood, A.K., Ohdar, R.K., Mahapatra, S.S., 2012. Experimental investigation and empirical modelling of FDM process for compressive strength improvement. J. Adv. Res. 3, 81–90.

Sudiyarto, A.Z., Mahardika, M., 2019. PENGARUH PENAMBAHAN SERBUK MIKRO ALUMINIUM PADA POLIMER PLA DENGAN MENGGUNAKAN 3D PRINTER MELALUI METODE BLOW UDARA BERTEKANAN ARIEF ZULFAUZI SUDIYARTO, Muslim Mahardika, S.T., M.Eng., Ph.D. Universitas Gadjah Mada.

Sun, B., Qin, Y., Xu, Y., Sun, Y., Wang, B., Dai, K., Zheng, G., Liu, C., Chen, J.,



2013. Study of shear-induced interfacial crystallization in polymer-based composite through in situ monitoring interfacial shear stress. *J. Mater. Sci.* 48, 5354–5360.
- Sun, J., Peng, Z., Yan, L., Fuh, J.Y.H., Hong, G.S., 2015a. 3D food printing an innovative way of mass customization in food fabrication. *Int. J. Bioprinting* 1.
- Sun, J., Zhou, W., Huang, D., Fuh, J.Y.H., Hong, G.S., 2015b. An overview of 3D printing technologies for food fabrication. *Food bioprocess Technol.* 8, 1605–1615.
- Sun, Q., Rizvi, G.M., Bellehumeur, C.T., Gu, P., 2008. Effect of processing conditions on the bonding quality of FDM polymer filaments. *Rapid Prototyp. J.* 14, 72–80.
- Tanikella, N.G., Wittbrodt, B., Pearce, J.M., 2017. Tensile strength of commercial polymer materials for fused filament fabrication 3D printing. *Addit. Manuf.* 15, 40–47.
- Tekinalp, H.L., Kunc, V., Velez-Garcia, G.M., Duty, C.E., Love, L.J., Naskar, A.K., Blue, C.A., Ozcan, S., 2014. Highly oriented carbon fiber–polymer composites via additive manufacturing. *Compos. Sci. Technol.* 105, 144–150.
- Tham, K.-M., Laurello, V.P., Lee, C.-P., Azad, G.S., Martin, N.F., Sansom, D.G., Hitchman, N., others, 2015. Turbine abradable layer with progressive wear zone multi level ridge arrays.
- Tian, X., Liu, T., Yang, C., Wang, Q., Li, D., 2016. Interface and performance of 3D printed continuous carbon fiber reinforced PLA composites. *Compos. Part A Appl. Sci. Manuf.* 88, 198–205.
- Tiwary, V.K., P., A., Deshpande, A.S., Rangaswamy, N., 2019. Surface enhancement of FDM patterns to be used in rapid investment casting for making medical implants. *Rapid Prototyp. J.* 25, 904–914.
- Too, M.H., Leong, K.F., Chua, C.K., Du, Z.H., Yang, S.F., Cheah, C.M., Ho, S.L., 2002. Investigation of 3D non-random porous structures by fused deposition modelling. *Int. J. Adv. Manuf. Technol.* 19, 217–223.



- Torrado Perez, A.R., Roberson, D.A., Wicker, R.B., 2014. Fracture surface analysis of 3D-printed tensile specimens of novel ABS-based materials. *J. Fail. Anal. Prev.* 14, 343–353.
- Tymrak, B.M., Kreiger, M., Pearce, J.M., 2014. Mechanical properties of components fabricated with open-source 3-D printers under realistic environmental conditions. *Mater. Des.* 58, 242–246.
- Valkenaers, H., Jansen, D., Voet, A., Van Gysel, A., Ferraris, E., 2014. Additive manufacturing for concrete: A 3D printing principle. In: Proceedings of the 14th Euspen International Conference. pp. 139–142.
- Vidakis, N., Petousis, M., Michailidis, N., Papadakis, V., Mountakis, N., Argyros, A., Dimitriou, E., Charou, C., Moutsopoulou, A., 2023a. Polylactic acid/silicon nitride biodegradable and biomedical Nanocomposites with optimized rheological and thermomechanical response for material extrusion additive manufacturing. *Biomed. Eng. Adv.* 6, 100103.
- Vidakis, N., Petousis, M., Mountakis, N., Papadakis, V., Charou, C., Rousos, V., Bastas, P., 2023b. Glass Fillers in Three Different Forms Used as Reinforcement Agents of Polylactic Acid in Material Extrusion Additive Manufacturing. *Appl. Sci.* 13, 6471.
- Vidakis, N., Petousis, M., Moutsopoulou, A., Papadakis, V., Spiridaki, M., Mountakis, N., Charou, C., Tsikritzis, D., Maravelakis, E., 2023c. Nanocomposites with Optimized Polytetrafluoroethylene Content as a Reinforcement Agent in PA12 and PLA for Material Extrusion Additive Manufacturing. *Polymers (Basel)*. 15, 2786.
- Volpato, N., Foggiatto, J.A., Schwarz, D.C., 2014. The influence of support base on FDM accuracy in Z. *Rapid Prototyp. J.*
- Walker, J.S., Arnold, J., Shrestha, C., Smith, D., 2020. Antibacterial silver submicron wire-polylactic acid composites for fused filament fabrication. *Rapid Prototyp. J.* 26, 32–38.
- Wang, J.Y., Xu, D.D., Sun, W., Du, S.M., Guo, J.J., Xu, G.J., 2019. Effects of nozzle-bed distance on the surface quality and mechanical properties of fused filament fabrication parts. *IOP Conf. Ser. Mater. Sci. Eng.* 479,



- Weng, Z., Wang, J., Senthil, T., Wu, L., 2016. Mechanical and thermal properties of ABS/montmorillonite nanocomposites for fused deposition modeling 3D printing. *Mater. Des.* 102, 276–283.
- Wijaya, R., Mahardika, M., 2019. PENGARUH PENAMBAHAN SERBUK NANO MAGNETITE PADA POLIMER PLA DENGAN MENGGUNAKAN 3D PRINTER MELALUI METODE COMPRESSED-AIR-ASSISTED. Universitas Gadjah Mada.
- Williams, N.X., Noyce, S., Cardenas, J.A., Catenacci, M., Wiley, B.J., Franklin, A.D., 2019. Silver nanowire inks for direct-write electronic tattoo applications. *Nanoscale* 11, 14294–14302.
- Xiang, S., Feng, L., Bian, X., Li, G., Chen, X., 2020. Evaluation of PLA content in PLA/PBAT blends using TGA. *Polym. Test.* 81, 106211.
- Yang, L., Li, S., Zhou, X., Liu, J., Li, Y., Yang, M., Yuan, Q., Zhang, W., 2019. Effects of carbon nanotube on the thermal, mechanical, and electrical properties of PLA/CNT printed parts in the FDM process. *Synth. Met.* 253, 122–130.
- Yu, B., Wang, M., Sun, H., Zhu, F., Han, J., Bhat, G., 2017. Preparation and properties of poly (lactic acid)/magnetic Fe<sub>3</sub>O<sub>4</sub> composites and nonwovens. *RSC Adv.* 7, 41929–41935.
- Ziemian, S., Okwara, M., Ziemian, C.W., 2015. Tensile and fatigue behavior of layered acrylonitrile butadiene styrene. *Rapid Prototyp. J.* 21, 270–278.