REFERENCES

[1] M. Borgestig, J. Sandqvist, G. Ahlsten, T. Falkmer, and H. Hemmingsson, "Gaze-based assistive technology in daily activities in children with severe physical impairments–an intervention study," *Developmental Neurorehabilitation*, vol. 20, no. 3, pp. 129–141, 2017.

[2] K. Holmqvist, M. Nyström, R. Andersson, R. Dewhurst, H. Jarodzka, and J. Van de Weijer, *Eye tracking: A comprehensive guide to methods and measures*. United Kingdom: Oxford University Press, 2011.

[3] M. Braun, M. Wölfel, G. Renner, and C. Menschik, "Accessibility of different natural user interfaces for people with intellectual disabilities," in *2020 International Conference on Cyberworlds (CW)*. IEEE, 2020, pp. 211–218.

[4] M. Vidal, J. Turner, A. Bulling, and H. Gellersen, "Wearable eye tracking for mental health monitoring," *Computer Communications*, vol. 35, no. 11, pp. 1306–1311, 2012.

[5] J. Gonzalez-Sanchez, M. Baydogan, M. E. Chavez-Echeagaray, R. K. Atkinson, and W. Burleson, "Affect measurement: A roadmap through approaches, technologies, and data analysis," in *Emotions and affect in human factors and human-computer interaction*, M. Jeon, Ed. San Diego: Academic Press, 2017, pp. 255–288.

[6] M. Startsev, I. Agtzidis, and M. Dorr, "1D CNN with BLSTM for automated classification of fixations, saccades, and smooth pursuits," *Behavior Research Methods*, vol. 51, no. 2, pp. 556–572, 2019.

[7] A. Hyrskykari, H. Istance, and S. Vickers, "Gaze gestures or dwell-based interaction?" in *Proceedings of the Symposium on Eye Tracking Research and Applications*. ACM, 2012, pp. 229–232.

[8] P. Majaranta and K.-J. Räihä, "Twenty years of eye typing: systems and design issues," in *Proceedings of the 2002 symposium on Eye tracking research & applications*, 2002, pp. 15–22.

[9] D. D. Salvucci and J. R. Anderson, "Intelligent gaze-added interfaces," in *Proceedings of the SIGCHI conference on Human factors in computing systems*. ACM, 2000, pp. 273–280.

[10] H. Drewes and A. Schmidt, "Interacting with the computer using gaze gestures," in *IFIP Conference on Human-Computer Interaction*. Springer, 2007, pp. 475–488.

[11] M. L. Dybdal, J. S. Agustin, and J. P. Hansen, "Gaze input for mobile devices by dwell and gestures," in *Proceedings of the Symposium on Eye Tracking Research and Applications*. ACM, 2012, pp. 225–228.

[12] J. Kangas, D. Akkil, J. Rantala, P. Isokoski, P. Majaranta, and R. Raisamo, "Gaze gestures and haptic feedback in mobile devices," in *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*. ACM, 2014, pp. 435–438.

[13] A. R. Suhari, R. Hartanto, and S. Wibirama, "Improving performance of eye movements classification using cnn-transformer model," in *2023 International Conference on Advanced Mechatronics, Intelligent Manufacture and Industrial Automation (ICAMIMIA)*. IEEE, 2023, pp. 751–756.

[14] A. Nuraini, S. Murnani, I. Ardiyanto, and S. Wibirama, "Machine learning in gaze-based interaction: A survey of eye movements events detection," in *2021 International Conference on Computer System, Information Technology, and Electrical Engineering (COSITE)*. IEEE, 2021, pp. 150–155.

[15] M. Vidal, A. Bulling, and H. Gellersen, "Pursuits: spontaneous interaction with displays based on smooth pursuit eye movement and moving targets," in *Proceedings of the 2013 ACM international joint conference on Pervasive and ubiquitous computing*. ACM, 2013, pp. 439–448.

[16] M. Vidal, A. Bulling, and Gellersen, "Detection of smooth pursuits using eye movement shape features," in *Proceedings of the Symposium on Eye Tracking Research and Applications*. ACM, 2012, p. 177–180.

[17] K. Pfeuffer, M. Vidal, J. Turner, A. Bulling, and H. Gellersen, "Pursuit calibration: Making gaze calibration less tedious and more flexible," in *Proceedings of the 26th annual ACM symposium on User interface software and technology*. ACM, 2013, pp. 261–270.

[18] A. Esteves, E. Velloso, A. Bulling, and H. Gellersen, "Orbits: Gaze interaction for smart watches using smooth pursuit eye movements," in *Proceedings of the 28th annual ACM symposium on user interface software & technology*. ACM, 2015, pp. 457–466.

[19] S. Wibirama, S. Murnani, and N. A. Setiawan, "Spontaneous gaze gesture interaction in the presence of noises and various types of eye movements," in *ACM Symposium on Eye Tracking Research and Applications*. ACM, 2020, pp. 1–5.

[20] S. Wibirama, S. Murnani, N. A. Setiawan, and H. Nurlatifa, "A survey of event detection methods for eye movements classification in smooth-pursuit-based interactive applications," in *2020 International Symposium on Community-centric Systems (CcS)*. IEEE, 2020, pp. 1–6.

[21] J. Pekkanen and O. Lappi, "A new and general approach to signal denoising and eye movement classification based on segmented linear regression," *Scientific reports*, vol. 7, no. 1, p. 17726, 2017.

[22] R. Zemblys, "Eye-movement event detection meets machine learning," in *Biomedical Engineering*, 11 2016, pp. 98–101.

[23] T. Santini, W. Fuhl, T. Kübler, and E. Kasneci, "Bayesian identification of fixations, saccades, and smooth pursuits," in *Proceedings of the Ninth Biennial ACM Symposium on Eye Tracking Research & Applications.* ACM, 2016, pp. 163–170.

[24] Y. Bengio, I. Goodfellow, and A. Courville, *Deep learning.* Massachusetts, MA, USA: MIT press Cambridge, 2017, vol. 1.

[25] C. Elmadjian, C. Gonzales, and C. H. Morimoto, "Eye movement classification with temporal convolutional networks," in *Pattern Recognition. ICPR International Workshops and Challenges: Virtual Event, January 10–15, 2021, Proceedings, Part III.* Springer, 2021, pp. 390–404.

[26] S. Hoppe and A. Bulling, "End-to-end eye movement detection using convolutional neural networks," *arXiv preprint arXiv:1609.02452*, 2016.

[27] R. Zemblys, D. C. Niehorster, and K. Holmqvist, "gazenet: End-to-end eye-movement event detection with deep neural networks," *Behavior research methods*, vol. 51, pp. 840–864, 2019.

[28] J. Goltz, M. Grossberg, and R. Etemadpour, "Exploring simple neural network architectures for eye movement classification," in *Proceedings of the 11th ACM symposium on eye tracking research & Applications.* ACM, 2019, pp. 1–5.

[29] K. Anusree and J. Amudha, "Eye movement event detection with deep neural networks," in *Computational Vision and Bio-Inspired Computing: ICCVBIC 2019.* Springer, 2020, pp. 921–930.

[30] T. Yu and H. Zhu, "Hyper-parameter optimization: A review of algorithms and applications," *arXiv preprint arXiv:2003.05689*, 2020.

[31] M. Feurer and F. Hutter, "Hyperparameter optimization," *Automated machine learning: Methods, systems, challenges*, pp. 3–33, 2019.

[32] L. Yang and A. Shami, "On hyperparameter optimization of machine learning algorithms: Theory and practice," *Neurocomputing*, vol. 415, pp. 295–316, 2020.

[33] J. Bergstra, D. Yamins, and D. Cox, "Making a science of model search: Hyperparameter optimization in hundreds of dimensions for vision architectures," in *International conference on machine learning.* PMLR, 2013, pp. 115–123.

[34] M. Dzieżyc, M. Gjoreski, P. Kazienko, S. Saganowski, and M. Gams, "Can we ditch feature engineering? end-to-end deep learning for affect recognition from physiological sensor data," *Sensors*, vol. 20, no. 22, 2020.

[35] M. Tahkola and Z. Guangrong, "Atsc-nex: Automated time series classification with sequential model-based optimization and nested cross-validation," *IEEE Access*, vol. 10, pp. 39 299–39 312, 2022.

[36] S. Khessiba, A. G. Blaiech, A. Manzanera, K. Ben Khalifa, A. Ben Abdallah, and M. H. Bedoui, "Hyperparameter optimization of deep learning models for eeg-based vigilance detection," in *International Conference on Computational Collective Intelligence*. Cham: Springer, 2022, pp. 200–210.

[37] M. Riyad, M. Khalil, and A. Adib, "Hyperparameter bayesian optimisation applied to convnets for motor imagery tasks," in *2021 International Conference on INnovations in Intelligent SysTems and Applications (INISTA)*. IEEE, 2021, pp. 1–6.

[38] V. Sood, D. Kumar, V. A. Athavale, and S. C. Gupta, "Epilepsy seizure detection by using bayesian optimize bi-lstm model," in *2020 Sixth International Conference on Parallel, Distributed and Grid Computing (PDGC)*. IEEE, 2020, pp. 291–296.

[39] K. Xu, S. Xia, and G. Li, "Automatic classification of sleep stages based on raw single-channel eeg," in *Third Chinese Conference on Pattern Recognition and Computer Vision*. Cham: Springer, 2020, pp. 356–368.

[40] G. C. Jana, A. Sabath, and A. Agrawal, "Capsule neural networks on spatio-temporal eeg frames for cross-subject emotion recognition," *Biomedical Signal Processing and Control*, vol. 72, p. 103361, 2022.

[41] A. Nair, K. S. S. S. Srujan, S. R. Kulkarni, K. Alwadhi, N. Jain, H. Kodamana, S. Sandeep, and V. O. John, "A deep learning framework for the detection of tropical cyclones from satellite images," *IEEE Geoscience and Remote Sensing Letters*, vol. 19, pp. 1–5, 2022.

[42] H. Li, Z. Lin, Z. An, S. Zuo, W. Zhu, Z. Zhang, Y. Mu, L. Cao, and J. D. P. García, "Automatic electrocardiogram detection and classification using bidirectional long short-term memory network improved by bayesian optimization," *Biomedical Signal Processing and Control*, vol. 73, p. 103424, 2022.

[43] S. Murnani, N. A. Setiawan, and S. Wibirama, "Spontaneous gaze interaction based on smooth pursuit eye movement using difference gaze pattern method," *Communications in Science and Technology*, vol. 7, no. 1, pp. 8–14, 2022.

[44] R. Zemblys, D. C. Niehorster, O. Komogortsev, and K. Holmqvist, "Using machine learning to detect events in eye-tracking data," *Behavior research methods*, vol. 50, pp. 160–181, 2018.

[45] A. H. Fristiana, S. A. I. Alfarozi, A. E. Permanasari, and S. Wibirama, "Improving deep learning-based eye movements classification using bayesian optimization," in *2023 IEEE International Biomedical Instrumentation and Technology Conference (IBITeC)*.   IEEE, 2023, pp. 197–202.

[46] W. Tang, G. Long, L. Liu, T. Zhou, J. Jiang, and M. Blumenstein, "Rethinking 1d-cnn for time series classification: A stronger baseline," *arXiv preprint arXiv:2002.10061*, pp. 1–7, 2020.

[47] S. R. Dubey, S. K. Singh, and B. B. Chaudhuri, "Activation functions in deep learning: A comprehensive survey and benchmark," *Neurocomputing*, 2022.

[48] C. Cooney, A. Korik, R. Folli, and D. Coyle, "Evaluation of hyperparameter optimization in machine and deep learning methods for decoding imagined speech eeg," *Sensors*, vol. 20, no. 16, 2020.

[49] A. Pauls and J. Yoder, "Determining optimum drop-out rate for neural networks," in *Midwest Instructional Computing Symposium (MICS)*, 2018.

[50] D. H. Koh, S. Munikrishne Gowda, and O. V. Komogortsev, "Real time eye movement identification protocol," in *CHI'10 Extended Abstracts on Human Factors in Computing Systems*, 2010, pp. 3499–3504.

[51] M. Startsev, I. Agtzidis, and M. Dorr, "Smooth pursuit," http://michaeldorr. de/smoothpursuit/, 2016.

[52] L. Larsson, "Event detection in eye-tracking data for use in applications with dynamic stimuli," Ph.D. dissertation, Lund University, Lund, Sweden, 2016.

[53] X. Zhang, X. Chen, L. Yao, C. Ge, and M. Dong, "Deep neural network hyperparameter optimization with orthogonal array tuning," in *International Conference on Neural Information Processing, ICONIP 2019*.   Cham: Springer, 2019, pp. 287–295.

[54] J. Bergstra and Y. Bengio, "Random search for hyper-parameter optimization." *Journal of machine learning research*, vol. 13, no. 2, 2012.

[55] L. Li, K. Jamieson, G. DeSalvo, A. Rostamizadeh, and A. Talwalkar, "Hyperband: A novel bandit-based approach to hyperparameter optimization," *Journal of Machine Learning Research*, vol. 18, no. 185, pp. 1–52, 2018.

[56] J. Wang, J. Xu, and X. Wang, "Combination of hyperband and bayesian optimization for hyperparameter optimization in deep learning," *arXiv preprint arXiv:1801.01596*, 2018.

[57] J. Bergstra, R. Bardenet, Y. Bengio, and B. Kégl, "Algorithms for hyperparameter optimization," *Advances in neural information processing systems*, vol. 24, 2011.

[58] J. Wu, X.-Y. Chen, H. Zhang, L.-D. Xiong, H. Lei, and S.-H. Deng, "Hyperparameter optimization for machine learning models based on bayesian optimization," *Journal of Electronic Science and Technology*, vol. 17, no. 1, pp. 26–40, 2019.

[59] X. Wang, Y. Jin, S. Schmitt, and M. Olhofer, "Recent advances in bayesian optimization," *ACM Computing Surveys*, vol. 55, no. 13s, pp. 1–36, 2023.

[60] N. Hnoohom, A. Jitpattanakul, and S. Mekruksavanich, "Real-life human activity recognition with tri-axial accelerometer data from smartphone using hybrid long short-term memory networks," in *2020 15th International Joint Symposium on Artificial Intelligence and Natural Language Processing (iSAI-NLP)*. IEEE, 2020, pp. 1–6.

[61] J. Wang, J. Shi, Y. Xu, H. Zhong, G. Li, J. Tian, W. Xu, Z. Gao, Y. Jiang, W. Jiao *et al.*, "A new strategy for mental fatigue detection based on deep learning and respiratory signal," in *Proceedings of the 11th International Conference on Computer Engineering and Networks*. Springer, 2022, pp. 543–552.

[62] L. Zhu, F. Zhu, and J. Price, "Topographynet: a deep learning model for eeg-based mind wandering detection," in *Proceedings of the 13th ACM International Conference on Bioinformatics, Computational Biology and Health Informatics*. ACM, 2022, pp. 1–10.

[63] B. E. Olivas-Padilla and M. I. Chacon-Murguia, "Classification of multiple motor imagery using deep convolutional neural networks and spatial filters," *Applied Soft Computing*, vol. 75, pp. 461–472, 2019.

[64] C. V. San Buenaventura, N. M. C. Tiglao, and R. O. Atienza, "Deep learning for smartphone-based human activity recognition using multi-sensor fusion," in *International Wireless Internet Conference (WICON 2018)*. Springer, 2019, pp. 65–75.

[65] H. Ke, D. Chen, B. Shi, J. Zhang, X. Liu, X. Zhang, and X. Li, "Improving brain e-health services via high-performance eeg classification with grouping bayesian optimization," *IEEE Transactions on Services Computing*, vol. 13, no. 4, pp. 696–708, 2019.

[66] D. Siekierski and K. Siwek, "Heart beats classification method using a multi-signal ecg spectrogram and convolutional neural network with residual blocks," *Computer Methods and Programs in Biomedicine Update*, vol. 2, p. 100075, 2022.

[67] J. N. Stember, H. Celik, D. Gutman, N. Swinburne, R. Young, S. Eskreis-Winkler, A. Holodny, S. Jambawalikar, B. J. Wood, P. D. Chang *et al.*, "Integrating eye tracking and speech recognition accurately annotates mr brain

images for deep learning: proof of principle," *Radiology: Artificial Intelligence*, vol. 3, no. 1, p. e200047, 2020.

[68] P. A. Punde, M. E. Jadhav, and R. R. Manza, "A study of eye tracking technology and its applications," in *2017 1st International Conference on Intelligent Systems and Information Management (ICISIM)*. IEEE, 2017, pp. 86–90.

[69] D. D. Salvucci and J. H. Goldberg, "Identifying fixations and saccades in eye-tracking protocols," in *Proceedings of the 2000 symposium on Eye tracking research & applications*. ACM, 2000, pp. 71–78.

[70] O. V. Komogortsev and A. Karpov, "Automated classification and scoring of smooth pursuit eye movements in the presence of fixations and saccades," *Behavior research methods*, vol. 45, pp. 203–215, 2013.

[71] M. Nyström and K. Holmqvist, "An adaptive algorithm for fixation, saccade, and glissade detection in eyetracking data," *Behavior research methods*, vol. 42, no. 1, pp. 188–204, 2010.

[72] L. Larsson, M. Nyström, and M. Stridh, "Detection of saccades and postsaccadic oscillations in the presence of smooth pursuit," *IEEE Transactions on biomedical engineering*, vol. 60, no. 9, pp. 2484–2493, 2013.

[73] J. M. Bland and D. G. Altman, "Statistics notes: measurement error," *BMJ*, vol. 312, no. 7047, p. 1654, 1996.

[74] I. H. Sarker, "Deep learning: a comprehensive overview on techniques, taxonomy, applications and research directions," *SN Computer Science*, vol. 2, no. 6, p. 420, 2021.

[75] S. A. Ebrahim, J. Poshtan, S. M. Jamali, and N. A. Ebrahim, "Quantitative and qualitative analysis of time-series classification using deep learning," *IEEE Access*, vol. 8, pp. 90 202–90 215, 2020.

[76] H. Ismail Fawaz, G. Forestier, J. Weber, L. Idoumghar, and P.-A. Muller, "Deep learning for time series classification: a review," *Data mining and knowledge discovery*, vol. 33, no. 4, pp. 917–963, 2019.

[77] S. Bai, J. Z. Kolter, and V. Koltun, "An empirical evaluation of generic convolutional and recurrent networks for sequence modeling," *arXiv preprint arXiv:1803.01271*, 2018.

[78] C. Pelletier, G. I. Webb, and F. Petitjean, "Temporal convolutional neural network for the classification of satellite image time series," *Remote Sensing*, vol. 11, no. 5, p. 523, 2019.

[79] R. C. Staudemeyer and E. R. Morris, "Understanding lstm–a tutorial into long short-term memory recurrent neural networks," *arXiv preprint arXiv:1909.09586*, 2019.

[80] K. Janocha and W. M. Czarnecki, "On loss functions for deep neural networks in classification," *arXiv preprint arXiv:1702.05659*, 2017.

[81] S. Jadon, "A survey of loss functions for semantic segmentation," in *2020 IEEE conference on computational intelligence in bioinformatics and computational biology (CIBCB)*.   IEEE, 2020, pp. 1–7.

[82] J. Wang, D. R. Salem, and R. K. Sani, "Two new exopolysaccharides from a thermophilic bacterium geobacillus sp. wsucf1: Characterization and bioactivities," *New Biotechnology*, vol. 61, pp. 29–39, 2021.

[83] C. M. Bishop, *Pattern Recognition and Machine Learning*, softcover reprint of the original 1st edition 2006 (corrected at 8th printing 2009) ed., ser. Information Science and Statistics.   New York, NY: Springer New York, 2016.

[84] Y. Tian, D. Su, S. Lauria, and X. Liu, "Recent advances on loss functions in deep learning for computer vision," *Neurocomputing*, vol. 497, pp. 129–158, 2022.

[85] U. Ruby and V. Yendapalli, "Binary cross entropy with deep learning technique for image classification," *International Journal of Advanced Trends in Computer Science and Engineering*, vol. 9, no. 10, 2020.

[86] R. Ward, X. Wu, and L. Bottou, "Adagrad stepsizes: Sharp convergence over nonconvex landscapes," *The Journal of Machine Learning Research*, vol. 21, no. 1, pp. 9047–9076, 2020.

[87] M. D. Zeiler, "Adadelta: an adaptive learning rate method," *arXiv preprint arXiv:1212.5701*, 2012.

[88] Y. Dauphin, H. De Vries, and Y. Bengio, "Equilibrated adaptive learning rates for non-convex optimization," *Advances in neural information processing systems*, vol. 28, 2015.

[89] S. Bock, J. Goppold, and M. Weiß, "An improvement of the convergence proof of the adam-optimizer," *arXiv preprint arXiv:1804.10587*, 2018.

[90] T. Leen and G. Orr, "Optimal stochastic search and adaptive momentum," *Advances in neural information processing systems*, vol. 6, 1993.

[91] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," *arXiv preprint arXiv:1412.6980*, 2014.

[92] S. Y. ŞEN and N. ÖZKURT, "Convolutional neural network hyperparameter tuning with adam optimizer for ecg classification," in *2020 innovations in intelligent systems and applications conference (ASYU)*.   IEEE, 2020, pp. 1–6.

[93] R. S. Srinivasamurthy, "Understanding 1d convolutional neural networks using multiclass time-varying signalss," Ph.D. dissertation, Clemson University, Clemson, SC, USA, 2018.

[94] S. Cornegruta, R. Bakewell, S. Withey, and G. Montana, "Modelling radiological language with bidirectional long short-term memory networks," *arXiv preprint arXiv:1609.08409*, 2016.

[95] F. Yu and V. Koltun, "Multi-scale context aggregation by dilated convolutions," *arXiv preprint arXiv:1511.07122*, 2015.

[96] K. A. A. Weiss, F. Concatto, R. C. G. Teive, and A. R. G. Ramirez, "On-line recognition of emotions via electroencephalography," *IEEE Latin America Transactions*, vol. 20, no. 5, pp. 806–812, 2022.

[97] J. J. Bird, D. R. Faria, L. J. Manso, A. Ekárt, and C. D. Buckingham, "A deep evolutionary approach to bioinspired classifier optimisation for brain-machine interaction," *Complexity*, vol. 2019, 2019.

[98] J. J. Bird, J. Kobylarz, D. R. Faria, A. Ekárt, and E. P. Ribeiro, "Cross-domain mlp and cnn transfer learning for biological signal processing: Eeg and emg," *IEEE Access*, vol. 8, pp. 54 789–54 801, 2020.

[99] S. Kaliyapillai and S. Krishnamurthy, "Differential Evolution based Hyperparameters Tuned Deep Learning Models for Disease Diagnosis and Classification," *Advances in Science, Technology and Engineering Systems Journal*, vol. 5, no. 5, pp. 253–261, 2020.

[100] E. Kıymaç and Y. Kaya, "A novel automated cnn arrhythmia classifier with memory-enhanced artificial hummingbird algorithm," *Expert Systems with Applications*, 2022, advance online publication.

[101] J. Escorcia-Gutierrez, K. Beleno, J. Jimenez-Cabas, M. Elhoseny, M. D. Alshehri, and M. M. Selim, "An automated deep learning enabled brain signal classification for epileptic seizure detection on complex measurement systems," *Measurement*, vol. 196, p. 111226, 2022.

[102] T. M. Ingolfsson, M. Hersche, X. Wang, N. Kobayashi, L. Cavigelli, and L. Benini, "Eeg-tcnet: An accurate temporal convolutional network for embedded motor-imagery brain–machine interfaces," in *2020 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*. IEEE, 2020, pp. 2958–2965.

[103] K. Zhou, W. Wang, T. Hu, and K. Deng, "Time series forecasting and classification models based on recurrent with attention mechanism and generative adversarial networks," *Sensors*, vol. 20, no. 24, 2020.

[104] S. Paisarnsrisomsuk, C. Ruiz, and S. Alvarez, "Improved deep learning clas-
sification of human sleep stages," in *2020 IEEE 33rd International Sympo-
sium on Computer-Based Medical Systems (CBMS)*. IEEE, 2020, pp. 338–
343.

[105] B. Abibullaev, I. Dolzhikova, and A. Zollanvari, "A brute-force cnn model
selection for accurate classification of sensorimotor rhythms in bcis," *IEEE
Access*, vol. 8, pp. 101 014–101 023, 2020.

[106] M. Debella-Gilo and A. K. Gjertsen, "Mapping seasonal agricultural land use
types using deep learning on sentinel-2 image time series," *Remote Sensing*,
vol. 13, no. 2, p. 289, 2021.

[107] D. Thakur and S. Biswas, "Optimization of hyperparameters in convolutional
neural network for human activity recognition," in *Proceedings of the 2nd
International Conference on Recent Trends in Machine Learning, IoT, Smart
Cities and Applications: ICMISC 2021*. Springer, 2022, pp. 535–546.

[108] E. Maghawry, T. F. Gharib, R. Ismail, and M. J. Zaki, "An efficient heartbeats
classifier based on optimizing convolutional neural network model," *IEEE
Access*, vol. 9, pp. 153 266–153 275, 2021.

[109] S. Tsokov, M. Lazarova, and A. Aleksieva-Petrova, "Evolving 1d convolu-
tional neural networks for human activity recognition," in *Proceedings of
the 22nd International Conference on Computer Systems and Technologies*.
ACM, 2021, pp. 49–54.

[110] D. Aquino-Brítez, A. Ortiz, J. Ortega, J. León, M. Formoso, J. Q. Gan, and
J. J. Escobar, "Optimization of deep architectures for eeg signal classifica-
tion: An automl approach using evolutionary algorithms," *Sensors*, vol. 21,
no. 6, p. 2096, 2021.

[111] X. Zhang, H. Peng, J. Zhang, and Y. Wang, "A cost-sensitive attention tem-
poral convolutional network based on adaptive top-k differential evolution
for imbalanced time-series classification," *Expert Systems with Applications*,
2022, advance online publication.

[112] S. Raziani and M. Azimbagirad, "Deep cnn hyperparameter optimization al-
gorithms for sensor-based human activity recognition," *Neuroscience Infor-
matics*, vol. 2, no. 3, p. 100078, 2022.

[113] I. Shahin, A. B. Nassif, and M. B. Alsabek, "Covid-19 electrocardiograms
classification using cnn models," in *2021 14th International Conference on
Developments in eSystems Engineering (DeSE)*. IEEE, 2021, pp. 448–452.

[114] H. Xie, L. Zhang, and C. P. Lim, "Evolving cnn-lstm models for time series
prediction using enhanced grey wolf optimizer," *IEEE access*, vol. 8, pp.
161 519–161 541, 2020.

[115] V. Guleva, A. Calcagno, P. Reali, and A. M. Bianchi, "Personality traits classification from eeg signals using eegnet," in *2022 IEEE 21st Mediterranean Electrotechnical Conference (MELECON)*. IEEE, 2022, pp. 590–594.

[116] E. Phaisangittisagul, "An analysis of the regularization between l2 and dropout in single hidden layer neural network," in *2016 7th International Conference on Intelligent Systems, Modelling and Simulation (ISMS)*. IEEE, 2016, pp. 174–179.

[117] E. Wu, K. Islam, J. Li, M. C. Lebrasse, V. Hill, and R. Zimmerman, "An active learning model for seagrass detection in remote senseing imagery," in *2021 IEEE 12th Annual Information Technology, Electronics and Mobile Communication Conference (IEMCON)*. IEEE, 2021, pp. 0113–0118.

[118] C. Nwankpa, W. Ijomah, A. Gachagan, and S. Marshall, "Activation functions: Comparison of trends in practice and research for deep learning," *arXiv preprint arXiv:1811.03378*, 2018.

[119] X. Li, Z. Hu, and X. Huang, "Combine relu with tanh," in *2020 IEEE 4th Information Technology, Networking, Electronic and Automation Control Conference (ITNEC)*, vol. 1. IEEE, 2020, pp. 51–55.

[120] C. Sun, J. Sharma, and M. Maiti, "Investigating the relationship between dropout regularization and model complexity in neural networks," *arXiv preprint arXiv:2108.06628*, 2021.

[121] S. Salman and X. Liu, "Overfitting mechanism and avoidance in deep neural networks," *arXiv preprint arXiv:1901.06566*, 2019.

[122] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, "Dropout: a simple way to prevent neural networks from overfitting," *The journal of machine learning research*, vol. 15, no. 1, pp. 1929–1958, 2014.

[123] V. Pham, T. Bluche, C. Kermorvant, and J. Louradour, "Dropout improves recurrent neural networks for handwriting recognition," in *2014 14th international conference on frontiers in handwriting recognition*. IEEE, 2014, pp. 285–290.

[124] P. M. Radiuk, "Impact of training set batch size on the performance of convolutional neural networks for diverse datasets," *Information Technology and Management Science*, vol. 20, no. 1, pp. 20–24, 2017.

[125] S. Afaq and S. Rao, "Significance of epochs on training a neural network," *Int. J. Sci. Technol. Res*, vol. 9, no. 06, pp. 485–488, 2020.

[126] R. Elshawi, M. Maher, and S. Sakr, "Automated machine learning: State-of-the-art and open challenges," *arXiv preprint arXiv:1906.02287*, 2019.

[127] G. Luo, "A review of automatic selection methods for machine learning algorithms and hyper-parameter values," *Network Modeling Analysis in Health Informatics and Bioinformatics*, vol. 5, pp. 1–16, 2016.

[128] N. DeCastro-García, A. L. Munoz Castaneda, D. Escudero Garcia, and M. V. Carriegos, "Effect of the sampling of a dataset in the hyperparameter optimization phase over the efficiency of a machine learning algorithm," *Complexity*, vol. 2019, 2019.

[129] Y. Li, S. Fang, X. Bai, L. Jiao, and N. Marturi, "Parallel design of sparse deep belief network with multi-objective optimization," *Information Sciences*, vol. 533, pp. 24–42, 2020.

[130] T. Maumela, F. Nelwamondo, and T. Marwala, "Population based training and federated learning frameworks for hyperparameter optimisation and ml unfairness using ulimisana optimisation algorithm," *Information Sciences*, vol. 612, pp. 132–150, 2022.

[131] M. Feurer, J. Springenberg, and F. Hutter, "Initializing bayesian hyperparameter optimization via meta-learning," in *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*. AAAI, 2015, pp. 1128–1135.

[132] E. Alba, *Parallel metaheuristics: a new class of algorithms*. Hoboken, New Jersey: John Wiley & Sons, 2005.

[133] B. Shahriari, K. Swersky, Z. Wang, R. P. Adams, and N. de Freitas, "Taking the human out of the loop: A review of bayesian optimization," *Proceedings of the IEEE*, vol. 104, no. 1, pp. 148–175, 2016.

[134] E. Brochu, V. M. Cora, and N. De Freitas, "A tutorial on bayesian optimization of expensive cost functions, with application to active user modeling and hierarchical reinforcement learning," *arXiv preprint arXiv:1012.2599*, 2010.

[135] V. Cerqueira, L. Torgo, and I. Mozetič, "Evaluating time series forecasting models: An empirical study on performance estimation methods," *Machine Learning*, vol. 109, pp. 1997–2028, 2020.

[136] M. Hanafy and R. Ming, "Classification of the insureds using integrated machine learning algorithms: A comparative study," *Applied Artificial Intelligence*, vol. 36, no. 1, p. 2020489, 2022.

[137] M. Bekkar, H. K. Djemaa, and T. A. Alitouche, "Evaluation measures for models assessment over imbalanced data sets," *J Inf Eng Appl*, vol. 3, no. 10, 2013.

[138] L. A. Jeni, J. F. Cohn, and F. De La Torre, "Facing imbalanced data–recommendations for the use of performance metrics," in *2013 Humaine association conference on affective computing and intelligent interaction*. IEEE, 2013, pp. 245–251.

[139] G. Haixiang, L. Yijing, J. Shang, G. Mingyun, H. Yuanyue, and G. Bing, "Learning from class-imbalanced data: Review of methods and applications," *Expert systems with applications*, vol. 73, pp. 220–239, 2017.

[140] G. Menghani, "Efficient deep learning: A survey on making deep learning models smaller, faster, and better," *ACM Computing Surveys*, vol. 55, no. 12, pp. 1–37, 2023.

[141] A. Benavoli, G. Corani, and F. Mangili, "Should we really use post-hoc tests based on mean-ranks?" *The Journal of Machine Learning Research*, vol. 17, no. 1, pp. 152–161, 2016.

[142] L. Ott and M. Longnecker, *An introduction to statistical methods and data analysis*. Boston, Massachusetts, USA: Cengage Learning, 2015.

[143] P. Mishra, C. M. Pandey, U. Singh, A. Gupta, C. Sahu, and A. Keshri, "Descriptive statistics and normality tests for statistical data," *Annals of cardiac anaesthesia*, vol. 22, no. 1, p. 67, 2019.

[144] M. Azizjon, A. Jumabek, and W. Kim, "1d cnn based network intrusion detection with normalization on imbalanced data," in *2020 international conference on artificial intelligence in information and communication (ICAIIC)*. IEEE, 2020, pp. 218–224.

[145] M. Alfaroby E., S. Wibirama, and I. Ardiyanto, "Accuracy improvement of object selection in gaze gesture application using deep learning," in *2020 12th International Conference on Information Technology and Electrical Engineering (ICITEE)*. IEEE, 2020, pp. 307–311.

[146] M. A. Fikri, I. K. A. Putra, and S. Wibirama, "Object selection using lstm networks for spontaneous gaze-based interaction," in *2022 14th International Conference on Information Technology and Electrical Engineering (ICITEE)*. IEEE, 2022, pp. 1–5.

[147] J. Zhu, H. Chen, and W. Ye, "Classification of human activities based on radar signals using 1d-cnn and lstm," in *2020 IEEE International Symposium on Circuits and Systems (ISCAS)*. IEEE, 2020, pp. 1–5.

[148] P. Tsinganos, B. Jansen, J. Cornelis, and A. Skodras, "Real-time analysis of hand gesture recognition with temporal convolutional networks," *Sensors*, vol. 22, no. 5, p. 1694, 2022.

[149] A. Sawada, T. Miyagawa, A. Ebihara, S. Yachida, and T. Hosoi, "Convolutional neural networks for time-dependent classification of variable-length time series," in *2022 International joint conference on neural networks (IJCNN)*. IEEE, 2022, pp. 1–8.

[150] C.-H. Wang, K.-Y. Huang, Y. Yao, J.-C. Chen, H.-H. Shuai, and W.-H. Cheng, "Lightweight deep learning: An overview," *IEEE consumer electronics magazine*, 2022.

[151] A. Burrello, M. Zanghieri, C. Sarti, L. Ravaglia, S. Benatti, and L. Benini, "Tackling time-variability in semg-based gesture recognition with on-device incremental learning and temporal convolutional networks," in *2021 IEEE Sensors Applications Symposium (SAS)*. IEEE, 2021, pp. 1–6.

[152] C. Elmadjian, C. Gonzales, R. L. d. Costa, and C. H. Morimoto, "Online eye-movement classification with temporal convolutional networks," *Behavior Research Methods*, pp. 1–19, 2022.

[153] S. Wibirama, S. Murnani, I. D. Sukowati, and R. Ferdiana, "Gaze-controlled digital signage for public health education during covid-19 pandemic," in *2021 9th International Conference on Information and Communication Technology (ICoICT)*. IEEE, 2021, pp. 7–12.

[154] D. A. Suryakusuma, A. Wicaksono, R. Hartanto, S. Wibirama *et al.*, "Implementing design thinking in the development of digital signage user interface for public health education," in *2022 8th International Conference on Science and Technology (ICST)*, vol. 1. IEEE, 2022, pp. 1–6.