



DAFTAR PUSTAKA

Al Issa, S., & MacIan, R. (2011). A review of CCFL phenomenon. *Annals of Nuclear Energy*, 38 (9), 1795–1819.

<https://doi.org/10.1016/j.anucene.2011.04.021>

ANSYS. (2021). *Ansyst Fluent Theory Guide*.

Astyanto, A. H., Indarto, Kirkland, K. V., & Deendarlianto. (2022). An experimental study on the effect of liquid properties on the counter-current flow limitation (CCFL) during gas/liquid counter-current two-phase flow in a 1/30 scaled-down of Pressurized Water Reactor (PWR) hot leg geometry. *Nuclear Engineering and Design*, 399(2), 112052.

<https://doi.org/10.1016/j.nucengdes.2022.112052>

Astyanto, A. H., Rahman, Y., Medha, A. Y. A., Deendarlianto, & Indarto. (2021). Time-series differential pressure fluctuations of a flooding regime: A preliminary experimental results investigation on a 1/30 down-scaled PWR hot leg geometry. *AIP Conference Proceedings*, 2403(December).

<https://doi.org/10.1063/5.0070772>

Deendarlianto, Ousaka, A., Kariyasaki, A., Lucas, D., Vierow, K., Vallee, C., & Hogan, K. (2010). The effects of surface tension on flooding in counter-current two-phase flow in an inclined tube. *Experimental Thermal and Fluid Science*, 34 (7), 813–826.

<https://doi.org/10.1016/j.expthermflusci.2010.01.010>

Deendarlianto, D., Höhne, T., Lucas, D., Vallée, C., & Zabala, G. A. M. (2011). CFD studies on the phenomena around counter-current flow limitations of gas/liquid two-phase flow in a model of a PWR hot leg. *Nuclear Engineering and Design*, 241 (12), 5138–5148.

<https://doi.org/10.1016/j.nucengdes.2011.08.071>



Deendarlianto, Höhne, T., Lucas, D., & Vierow, K. (2012). Gas-liquid countercurrent two-phase flow in a PWR hot leg: A comprehensive research review. *Nuclear Engineering and Design*, 243(2), 214–233.
<https://doi.org/10.1016/j.nucengdes.2011.11.015>

Deendarlianto, Ousaka, A., Kariyasaki, A., & Fukano, T. (2006). *Prediction of flooding gas velocity in gas – liquid counter-current two-phase flow in inclined pipes*. 236, 1282–1292.
<https://doi.org/10.1016/j.nucengdes.2005.12.001>

Greenshields, C. J., Weller, H. G., Gasparini, L., & Reese, J. M. (2010). Implementation of semi-discrete, non-staggered central schemes in a colocated, polyhedral, finite volume framework, for high-speed viscous flows. *International Journal for Numerical Methods in Fluids*, 63(1), 1–21.

H K Versteeg and W Malalasekera. (2007). *An Introduction to Computational Fluid Dynamics* (Vol. 2). Pearson Education Limited.

KINOSHITA, I., NRIAI, T., TOMIYAMA, A., LUCAS, D., & MURASE, M. (2011). Effects of Liquid Properties on CCFL in a Scaled-Down Model of a PWR Hot Leg. *Journal of Power and Energy Systems*, 5(3), 316–329.
<https://doi.org/10.1299/jpes.5.316>

Kuron, M., 2015, 3 Criteria for Assessing CFD Convergence,
<https://www.engineering.com/story/3-criteria-for-assessing-cfd-convergence>
(Diakses: 25 Desember 2023)

Murase, M., Tomiyama, A., Lucas, D., Kinoshita, I., Utanohara, Y., & Yanagi, C. (2012). Correlation for countercurrent flow limitation in a PWR hot leg. *Journal of Nuclear Science and Technology*, 49 (4), 398–407.
<https://doi.org/10.1080/00223131.2012.669241>

Navarro, M. A. (2005). Study of countercurrent flow limitation in a horizontal pipe connected to an inclined one. *Nuclear Engineering and Design*,



235(10–12), 1139–1148. <https://doi.org/10.1016/j.nucengdes.2005.02.010>

NuclearTourist (2005) Pressurized Water Reactor (PWR)

<https://www.nucleartourist.com/type/pwr.htm>. (Diakses: 25 Desember 2023)

Pantzali, M. N., Mouza, A. A., & Paras, S. V. (2007). Study of hydrodynamic characteristics of the liquid layer during counter-current flow in inclined small diameter tubes : the effect of liquid properties. *6th International Conference on Multiphase Flow, Leipzig, Germany., July.*

Pratama, A. S., Indarto, I., & Deendarlianto, D. (2021). Studi CFD mengenai Pengaruh Sifat Fisis Fluida terhadap Karakteristik Counter-Current Flow Limitation pada Pipa Horizontal. *Journal of Mechanical Design and Testing*, 3(2), 118. <https://doi.org/10.22146/jmdt.66408>

Samal, K., & Ghosh, S. (2020). Characterization and prediction of flow-conditions in the hot-leg of PWR during loss of coolant accident. *Nuclear Engineering and Design*, 359 (February 2019), 110446.
<https://doi.org/10.1016/j.nucengdes.2019.110446>

Suzuki, S., & Ueda, T. (1977). Behaviour of liquid films and flooding in counter-current two-phase flow-part 1.flow in circular tubes. 3(6), 517–532.

Utanohara, Y., Kinoshita, I., Murase, M., Lucas, D., Vallée, C., & Tomiyama, A. (2012). Numerical simulations for steam-water CCFL tests using the 1/3 scale rectangular channel simulating a PWR hot leg. *Nuclear Engineering and Design*, 249, 14–23. <https://doi.org/10.1016/j.nucengdes.2011.05.041>

Wallis, G. B., 1969, One-dimensional Two-phase Flow, McGraw-Hill, New York.