

DAFTAR PUSTAKA

- Barros, F., Aguiar, S., Sousa, P. J., Cachaço, A., Ramos, N. V., Tavares, P. J., Moreira, P. M. G. P., Xu, M., Santos, L. O., & Franco, E. (2021). Displacement monitoring of crossbeams in an airport runway extension using digital image correlation. *Procedia Structural Integrity*, 37(C), 159–166. <https://doi.org/10.1016/j.prostr.2022.01.072>
- Fei, G., Nie, L., Zhong, L., Shi, Q., Hu, K., Parra-Cabrera, C., Oprins, H., Ameloot, R., & Yang, S. (2022). Photocurable resin-silica composites with low thermal expansion for 3D printing microfluidic components onto printed circuit boards. *Materials Today Communications*, 31. <https://doi.org/10.1016/j.mtcomm.2022.103482>
- Gairola, S., & Jayaganthan, R. (2021). Xfem simulation of tensile and fracture behavior of ultrafine-grained al 6061 alloy. *Metals*, 11(11). <https://doi.org/10.3390/met11111761>
- Ghandriz, R., Hart, K., & Li, J. (2020). Extended finite element method (XFEM) modeling of fracture in additively manufactured polymers. *Additive Manufacturing*, 31. <https://doi.org/10.1016/j.addma.2019.100945>
- Goodyear, S. R., & Aspden, R. M. (2012). Mechanical properties of bone ex vivo. *Methods in Molecular Biology*, 816, 555–571. https://doi.org/10.1007/978-1-61779-415-5_35
- Huang, Y., Guan, Y., Wang, L., Zhou, J., Ge, Z., & Hou, Y. (2018). Characterization of mortar fracture based on three point bending test and XFEM. *International Journal of Pavement Research and Technology*, 11(4), 339–344. <https://doi.org/10.1016/j.ijprt.2017.09.005>
- Khosravani, M. R., Frohn-Sörensen, P., Engel, B., & Reinicke, T. (2023). Mixed mode brittle fracture of stereolithographic 3D-printed parts.

Journal of Materials Research and Technology, 25, 3177–3188.

<https://doi.org/10.1016/j.jmrt.2023.06.175>

Khosravani, M. R., & Reinicke, T. (2023). Effects of printing parameters on the fracture toughness of 3D-printed polymer parts. *Procedia Structural Integrity*, 47, 454–459. <https://doi.org/10.1016/j.prostr.2023.07.079>

Kumar, S. L., Aravind, H. B., & Hossiney, N. (2019). Digital image correlation (DIC) for measuring strain in brick masonry specimen using Ncorr open source 2D MATLAB program. *Results in Engineering*, 4. <https://doi.org/10.1016/j.rineng.2019.100061>

Miedzińska, D., Gieleta, R., & Popławski, A. (2020). Experimental study on influence of curing time on strength behavior of sla-printed samples loaded with different strain rates. *Materials*, 13(24), 1–16. <https://doi.org/10.3390/ma13245825>

Shirodkar, N., Cheng, S., & Seidel, G. D. (2021). Enhancement of Mode I fracture toughness properties of epoxy reinforced with graphene nanoplatelets and carbon nanotubes. *Composites Part B: Engineering*, 224. <https://doi.org/10.1016/j.compositesb.2021.109177>

Silva, R. V., Spinelli, D., Bose Filho, W. W., Claro Neto, S., Chierice, G. O., & Tarpani, J. R. (2006). Fracture toughness of natural fibers/castor oil polyurethane composites. *Composites Science and Technology*, 66(10), 1328–1335. <https://doi.org/10.1016/j.compscitech.2005.10.012>

SOFU, M. M., VAROL ÖZKAVAK, H., BACAK, S., & FENKLİ, M. (2023). Comparison of Strength, Surface Quality and Cost of Different Additive Manufacturing Methods. *İmalat Teknolojileri ve Uygulamaları*, 4(1), 25–36. <https://doi.org/10.52795/mateca.1265509>

Zhao, T., Yu, R., Li, X., Cheng, B., Zhang, Y., Yang, X., Zhao, X., Zhao, Y., & Huang, W. (2018). 4D printing of shape memory polyurethane via

stereolithography. *European Polymer Journal*, 101, 120–126.

<https://doi.org/10.1016/j.eurpolymj.2018.02.021>