

DAFTAR PUSTAKA

3D Flex 100 & FIRMFLEX (3D Semi Flexibel Resin) MSDS (2022).

Borrello, J. *et al.* (2018) ‘3D printing a mechanically-tunable acrylate resin on a commercial DLP-SLA printer’, *Additive Manufacturing*, 23(February), pp. 374–380. doi: 10.1016/j.addma.2018.08.019.

Callister, W. D. and Rethwisch, D. G. (2015) *Fundamentals of Materials Science and Engineering: An Integrated Approach*. 5th edn, Wiley. 5th edn.

Godec, D. *et al.* (2022) *A Guide to Additive Manufacturing*. Cham: Springer Tracts in Additive Manufacturing Damir. doi: 10.1007/978-3-031-05863-9.

Lim, W. Bin *et al.* (2022) ‘A novel UV-curable acryl-polyurethane for flexural 3D printing architectures’, *Additive Manufacturing*, 51(October 2021), p. 102625. doi: 10.1016/j.addma.2022.102625.

Pagac, M. *et al.* (2021) ‘A Review of Vat Photopolymerization Technology : Materials’, *Polymers*, 13(13), p. 598.

Piroonpan, T., Booncharoen, K. and Pasanphan, W. (2022) ‘Sugar-Core Synthesized Multibranched Polylactic Acid and Its Diacrylate Blends as a UV LED-Curable Coating with Enhanced Toughness and Performance’, *ACS Sustainable Chemistry and Engineering*, 10(51), pp. 17027–17042. doi: 10.1021/acssuschemeng.2c02958.

‘Safety Data Sheet of ANYCUBIC 3D Printing UV Sensitive Resin’ (2021) *Anycubic*, pp. 1–15.

Standard Terminology for Additive Manufacturing Technologies (2013) *ASTM INTERNATIONAL*. doi: 10.1520/F2792-12A.2.

Standard Test Method for Rubber Property - Durometer Hardness (2015). ASTM International. doi: 10.1520/D2240-15E01.mendations.

Standard Test Method for Tensile Properties of Plastics (2010). ASTM International. doi: 10.1520/D0638-10.1.

Tri(propylene glycol) diacrylate Safety Data Sheet (2023).

Weigel, N., Männel, M. J. and Thiele, J. (2021) ‘Flexible Materials for High-Resolution 3D Printing of Microfluidic Devices with Integrated Droplet Size Regulation’, *ACS Applied Materials and Interfaces*, 13(26), pp. 31086–31101. doi: 10.1021/acsami.1c05547.