

DAFTAR PUSTAKA

- Abdellah, M. Y., Sadek, M. G., Alharthi, H., Abdel-Jaber, G. T., & Backar, A. H. (2023). Characteristic properties of date-palm fibre/sheep wool reinforced polyester composites. *Journal of Bioresources and Bioproducts*, 8(4), 430–443. <https://doi.org/10.1016/j.jobab.2023.09.003>
- Abdul Khalil, H. P. S., Davoudpour, Y., Islam, M. N., Mustapha, A., Sudesh, K., Dungani, R., & Jawaid, M. (2014). Production and modification of nanofibrillated cellulose using various mechanical processes: A review. *Carbohydrate Polymers*, 99, 649–665. <https://doi.org/10.1016/j.carbpol.2013.08.069>
- Abdul Khalil, H. P. S., Ismail, H., Ahmad, M. N., Ariffin, A., & Hassan, K. (2001). The effect of various anhydride modifications on mechanical properties and water absorption of oil palm empty fruit bunches reinforced polyester composites. *Polymer International*, 50(4), 395–402. <https://doi.org/https://doi.org/10.1002/pi.642>
- Abdul Khalil, H. P. S., Jawaid, M., & Abu Bakar, A. (2011). Woven hybrid composites: Water absorption and thickness swelling behaviours. *BioResources*, 6(2), 1043–1052.
- Abdurohman, K., Satrio, T., Muzayadah, N. L., & Teten. (2018). A comparison process between hand lay-up, vacuum infusion and vacuum bagging method toward e-glass EW 185/lycal composites. *Journal of Physics: Conference Series*, 1130(1). <https://doi.org/10.1088/1742-6596/1130/1/012018>
- Adugna Ayalew, A., & Fenta Wodage, A. (2022). Characterization of Chemically Treated Sisal Fiber/Polyester Composites. *Journal of Engineering (United Kingdom)*, 2022. <https://doi.org/10.1155/2022/8583213>
- Ahmad, J., & Zhou, Z. (2022). Mechanical Properties of Natural as well as Synthetic Fiber Reinforced Concrete: A Review. *Construction and Building Materials*, 333(December 2021), 127353. <https://doi.org/10.1016/j.conbuildmat.2022.127353>
- Ahmadijokani, F., Shojaei, A., Dordanihaghighi, S., Jafarpour, E., Mohammadi, S., & Arjmand, M. (2020). Effects of hybrid carbon-aramid fiber on performance of non-asbestos organic brake friction composites. *Wear*, 452–453(March), 203280. <https://doi.org/10.1016/j.wear.2020.203280>
- Ahvazi, B., Danumah, C., Ngo, T. D., Zhu, Z., & Lorenz, H. (2022). The Impact of Fibre Oxidation on the Preparation of Cellulose Nanocrystals (CNC). *Biomass (Switzerland)*, 2(4), 316–333. <https://doi.org/10.3390/biomass2040021>
- Akhil, U. V, Radhika, N., Saleh, B., Aravind Krishna, S., Noble, N., & Rajeshkumar, L. (2023). A comprehensive review on plant-based natural

- fiber reinforced polymer composites: Fabrication, properties, and applications. *Polymer Composites*, 44(5), 2598–2633.
<https://doi.org/https://doi.org/10.1002/pc.27274>
- Akil, H. M., Santulli, C., Sarasini, F., Tirillò, J., & Valente, T. (2014). Environmental effects on the mechanical behaviour of pultruded jute/glass fibre-reinforced polyester hybrid composites. *Composites Science and Technology*, 94, 62–70. <https://doi.org/10.1016/j.compscitech.2014.01.017>
- Al-Maharma, A. Y., & Al-Huniti, N. (2019). Critical review of the parameters affecting the effectiveness of moisture absorption treatments used for natural composites. *Journal of Composites Science*, 3(1).
<https://doi.org/10.3390/jcs3010027>
- Ali, S., Khan, A. S., Anjum, M. A., Nawaz, A., Naz, S., Ejaz, S., & Hussain, S. (2020). Effect of postharvest oxalic acid application on enzymatic browning and quality of lotus (*Nelumbo nucifera* Gaertn.) root slices. *Food Chemistry*, 312, 126051. <https://doi.org/10.1016/j.foodchem.2019.126051>
- Alshahrani, H., & Arun Prakash, V. R. (2022). Mechanical, fatigue and DMA behaviour of high content cellulosic corn husk fibre and orange peel biochar epoxy biocomposite: A greener material for cleaner production. *Journal of Cleaner Production*, 374(May), 133931.
<https://doi.org/10.1016/j.jclepro.2022.133931>
- Altenbach, H., Altenbach, J., & Kissing, W. (2018). Classification of Composite Materials. *Mechanics of Composite Structural Elements*, 3–18.
https://doi.org/10.1007/978-981-10-8935-0_1
- Amiandamhen, S. O., Meincken, M., & Tyhoda, L. (2020). Natural Fibre Modification and Its Influence on Fibre-matrix Interfacial Properties in Biocomposite Materials. *Fibers and Polymers*, 21(4), 677–689.
<https://doi.org/10.1007/s12221-020-9362-5>
- Amrollahi, S., Ramezanzadeh, B., Yari, H., Ramezanzadeh, M., & Mahdavian, M. (2019). Synthesis of polyaniline-modified graphene oxide for obtaining a high performance epoxy nanocomposite film with excellent UV blocking/anti-oxidant/ anti-corrosion capabilities. *Composites Part B: Engineering*, 173, 106804.
<https://doi.org/https://doi.org/10.1016/j.compositesb.2019.05.015>
- Anand, P. B., Nagaraja, S., Jayaram, N., Sreenivasa, S. P., Almakayeel, N., Khan, T. M. Y., Kumar, R., Kumar, R., & Ammarullah, M. I. (2023). Kenaf Fiber and Hemp Fiber Multi-Walled Carbon Nanotube Filler-Reinforced Epoxy-Based Hybrid Composites for Biomedical Applications: Morphological and Mechanical Characterization. *Journal of Composites Science*, 7(8).
<https://doi.org/10.3390/jcs7080324>
- Ansari, F., Skrifvars, M., & Berglund, L. (2015). Nanostructured biocomposites based on unsaturated polyester resin and a cellulose nanofiber network.

Composites Science and Technology, 117, 298–306.
<https://doi.org/10.1016/j.compscitech.2015.07.004>

Arabpour, A., Shockravi, A., Rezania, H., & Farahati, R. (2020). Investigation of anticorrosive properties of novel silane-functionalized polyamide/GO nanocomposite as steel coatings. *Surfaces and Interfaces*, 18(December 2019), 100453. <https://doi.org/10.1016/j.surfin.2020.100453>

Araki, J., Wada, M., Kuga, S., & Okano, T. (1998). Flow properties of microcrystalline cellulose suspension prepared by acid treatment of native cellulose. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 142(1), 75–82. [https://doi.org/10.1016/S0927-7757\(98\)00404-X](https://doi.org/10.1016/S0927-7757(98)00404-X)

Arola, S., Malho, J., Laaksonen, P., Lille, M., & Linder, M. B. (2013). The role of hemicellulose in nanofibrillated cellulose networks. *Soft Matter*, 9(4), 1319–1326. <https://doi.org/10.1039/C2SM26932E>

Arul Marcel Moshi, A., Ravindran, D., Sundara Bharathi, S. R., Padma, S. R., Indran, S., & Divya, D. (2020). Characterization of natural cellulosic fiber extracted from *Grewia damine* flowering plant's stem. *International Journal of Biological Macromolecules*, 164, 1246–1255. <https://doi.org/10.1016/j.ijbiomac.2020.07.225>

Arulmurugan, S., & Venkateshwaran, N. (2016). Vibration analysis of nanoclay filled natural fiber composites. *Polymers and Polymer Composites*, 24(7), 507–516. <https://doi.org/10.1177/096739111602400709>

Arun Prakash, V. R., & Viswanthan, R. (2019). Fabrication and characterization of echinoidea spike particles and kenaf natural fibre-reinforced *Azadirachta-Indica* blended epoxy multi-hybrid bio composite. *Composites Part A: Applied Science and Manufacturing*, 118(January), 317–326. <https://doi.org/10.1016/j.compositesa.2019.01.008>

Arun, R., Shruthy, R., Preetha, R., & Sreejit, V. (2022). Biodegradable nano composite reinforced with cellulose nano fiber from coconut industry waste for replacing synthetic plastic food packaging. *Chemosphere*, 291(P1), 132786. <https://doi.org/10.1016/j.chemosphere.2021.132786>

Aryasena, R., Kusmono, & Umami, N. (2022). Production of cellulose nanocrystals extracted from *Pennisetum purpureum* fibers and its application as a lubricating additive in engine oil. *Heliyon*, 8(11), e11315. <https://doi.org/https://doi.org/10.1016/j.heliyon.2022.e11315>

Ashby, M. F. (2008). The CES EduPack Database of Natural and Man-Made Materials. *Cambridge University*, 1, 1–26. Cambridge

Ashori, A., & Sheshmani, S. (2010). Hybrid composites made from recycled materials: Moisture absorption and thickness swelling behavior. *Bioresource Technology*, 101(12), 4717–4720. <https://doi.org/https://doi.org/10.1016/j.biortech.2010.01.060>

- Asim, M., Jawaid, M., Nasir, M., & Saba, N. (2018). Effect of Fiber Loadings and Treatment on Dynamic Mechanical, Thermal and Flammability Properties of Pineapple Leaf Fiber and Kenaf Phenolic Composites. *Journal of Renewable Materials*, 6(4), 383–393. <https://doi.org/10.7569/JRM.2017.634162>
- Asim, M., Saba, N., Jawaid, M., Nasir, M., Pervaiz, M., & Alothman, O. (2017). A review on Phenolic resin and its Composites. *Current Analytical Chemistry*, 13. <https://doi.org/10.2174/1573411013666171003154410>
- Athijayamani, A., Thiruchitrabalam, M., Natarajan, U., & Pazhanivel, B. (2009). Effect of moisture absorption on the mechanical properties of randomly oriented natural fibers/polyester hybrid composite. *Materials Science and Engineering: A*, 517(1), 344–353. <https://doi.org/https://doi.org/10.1016/j.msea.2009.04.027>
- Azhary, T., Kusmono, Wildan, M. W., & Herianto. (2022). Mechanical, morphological, and thermal characteristics of epoxy/glass fiber/cellulose nanofiber hybrid composites. *Polymer Testing*, 110(March), 107560. <https://doi.org/10.1016/j.polymertesting.2022.107560>
- Babu, B., Muruganandhan, P., Girimurugan, R., Sakthi, S., Nanthakumar, S., & Vignesh, S. (2023). Influence of powdered chick eggshell (PECS) on mechanical and wear properties of kenaf fiber (KF) reinforced composites. *Materials Today: Proceedings*, xxx. <https://doi.org/10.1016/j.matpr.2023.03.009>
- Baek, Y. M., Shin, P. S., Kim, J. H., Park, H. S., DeVries, K. L., & Park, J. M. (2020). Thermal transfer, interfacial, and mechanical properties of carbon fiber/polycarbonate-CNT composites using infrared thermography. *Polymer Testing*, 81(May 2019), 106247. <https://doi.org/10.1016/j.polymertesting.2019.106247>
- Balaji, & Nagarajan. (2017). Characterization of alkali treated and untreated new cellulosic fiber from Saharan aloe vera cactus leaves. *Carbohydrate Polymers*, 174, 200–208. <https://doi.org/10.1016/j.carbpol.2017.06.065>
- Barros, T. P. D. S., Cavalcante, D. G. D. L., De Oliveira, D. F., Caluête, R. E., & De Lima, S. J. G. (2019). Study of the surface properties of the epoxy/quasicrystal composite. *Journal of Materials Research and Technology*, 8(1), 590–598. <https://doi.org/10.1016/j.jmrt.2018.04.015>
- Bartoli, M., Rosi, L., & Frediani, M. (2019). Chapter 22. Synthesis and Applications of Unsaturated Polyester Composites. In *Unsaturated Polyester Resins*. Elsevier Inc. <https://doi.org/10.1016/B978-0-12-816129-6.00022-3>
- Basavaraj, Y., & Raghavendra, H. (2014). Experimental and Numerical Study of the Influence of Volume Fraction on Tensile and Flexural Strength of E-Glass Epoxy Cross Ply Laminates. *International Journal of Mechanical and Industrial Technology*, 2(1), 39–44.

- Battisti, A., Skordos, A. A., & Partridge, I. K. (2009). Monitoring dispersion of carbon nanotubes in a thermosetting polyester resin. *Composites Science and Technology*, 69(10), 1516–1520.
<https://doi.org/https://doi.org/10.1016/j.compscitech.2008.05.012>
- Beckermann, G. W., & Pickering, K. L. (2008). Engineering and evaluation of hemp fibre reinforced polypropylene composites: Fibre treatment and matrix modification. *Composites Part A: Applied Science and Manufacturing*, 39(6), 979–988.
<https://doi.org/https://doi.org/10.1016/j.compositesa.2008.03.010>
- Belbekhouche, S., Bras, J., Siqueira, G., Chappey, C., Lebrun, L., Khelifi, B., Marais, S., & Dufresne, A. (2011). Water sorption behavior and gas barrier properties of cellulose whiskers and microfibrils films. *Carbohydrate Polymers*, 83(4), 1740–1748.
<https://doi.org/https://doi.org/10.1016/j.carbpol.2010.10.036>
- Binti Mohd Hafidz, N. S., Bin Mohamed Rehan, M. S., & Binti Mokhtar, H. (2021). Effect of alkaline treatment on water absorption and thickness swelling of natural fibre reinforced unsaturated polyester composites. *Materials Today: Proceedings*, 48, 720–727.
<https://doi.org/10.1016/j.matpr.2021.02.209>
- Bledzki, A. K., & Gassan, J. (1999). Composites reinforced with cellulose based fibres. *Progress in Polymer Science*, 24(2), 221–274.
[https://doi.org/https://doi.org/10.1016/S0079-6700\(98\)00018-5](https://doi.org/https://doi.org/10.1016/S0079-6700(98)00018-5)
- Braun, B., & Dorgan, J. R. (2009). Single-Step Method for the Isolation and Surface Functionalization of Cellulosic Nanowhiskers. *Biomacromolecules*, 10(2), 334–341. <https://doi.org/10.1021/bm8011117>
- Burgert, I., Frühmann, K., Keckes, J., Fratzl, P., & Stanzl-Tschegg, S. (2005). Properties of chemically and mechanically isolated fibres of spruce (*Picea abies* [L.] Karst.). Part 2: Twisting phenomena. *Holzforschung*, 59(2), 247–251. <https://doi.org/10.1515/HF.2005.039>
- Cai, M., Takagi, H., Nakagaito, A. N., Katoh, M., Ueki, T., Waterhouse, G. I. N., & Li, Y. (2015). Influence of alkali treatment on internal microstructure and tensile properties of abaca fibers. *Industrial Crops and Products*, 65, 27–35.
<https://doi.org/10.1016/j.indcrop.2014.11.048>
- Cai, Y., Xiong, J., Huang, X., Pervez, M. N., Lin, L., Xiong, X., & Wang, L. (2024). Improving the dyeability of ramie fibre by sequential alkaline and alcohol pretreatments. *Industrial Crops and Products*, 212(December 2023), 118381. <https://doi.org/10.1016/j.indcrop.2024.118381>
- Callister, W. D., & Rethwisch, D. G. (2010). *Materials science and engineering : an introduction*.
- Camarero Espinosa, S., Kuhnt, T., Foster, E. J., & Weder, C. (2013). Isolation of

- Thermally Stable Cellulose Nanocrystals by Phosphoric Acid Hydrolysis. *Biomacromolecules*, 14(4), 1223–1230. <https://doi.org/10.1021/bm400219u>
- Cao, L., Fu, X., Xu, C., Yin, S., & Chen, Y. (2017). High-performance natural rubber nanocomposites with marine biomass (tunicate cellulose). *Cellulose*, 24(7), 2849–2860. <https://doi.org/10.1007/s10570-017-1293-y>
- Chand, N., & Fahim, M. (2021). Green tribology and tribological characterization of biocomposites. In N. Chand & M. Fahim (Eds.), *Tribology of Natural Fiber Polymer Composites (Second Edition)* (Second Edi, pp. 207–212). Woodhead Publishing. [https://doi.org/https://doi.org/10.1016/B978-0-12-818983-2.00009-8](https://doi.org/10.1016/B978-0-12-818983-2.00009-8)
- Chandran, M. S., & Padmanabhan, K. (2019). Microbond fibre bundle pullout technique to evaluate the interfacial adhesion of polyethylene and polypropylene self reinforced composites. *Applied Adhesion Science*. <https://doi.org/10.1186/s40563-019-0121-z>
- Charoenvai, S., Khedari, J., Hirunlabh, J., Daguinet, M., & Quenard, D. (2005). Impact of rice husk ash on the performance of durian fiberbased construction materials. *10DBMC International Conference On Durability of Building Materials and Components, April*. <http://www.cstb.fr/fileadmin/documents/publicationsScientifiques/DOC00003448.pdf>
- Chauhan, V. S., & Chakrabarti, S. K. (2012). Use of nanotechnology for high performance cellulosic and papermaking products. *Cellulose Chemistry and Technology*, 46(5–6), 389–400.
- Chen, H., Zhang, W., Wang, X., Wang, H., Wu, Y., Zhong, T., & Fei, B. (2018). Effect of alkali treatment on wettability and thermal stability of individual bamboo fibers. *Journal of Wood Science*, 64(4), 398–405. <https://doi.org/10.1007/s10086-018-1713-0>
- Chen, L., Wang, Q., Hirth, K., Baez, C., Agarwal, U. P., & Zhu, J. Y. (2015). Tailoring the yield and characteristics of wood cellulose nanocrystals (CNC) using concentrated acid hydrolysis. *Cellulose*, 22(3), 1753–1762. <https://doi.org/10.1007/s10570-015-0615-1>
- Chen, L., Zhu, J. Y., Baez, C., Kitin, P., & Elder, T. (2016). Highly thermal-stable and functional cellulose nanocrystals and nanofibrils produced using fully recyclable organic acids. *Green Chemistry*, 18(13), 3835–3843. <https://doi.org/10.1039/c6gc00687f>
- Chen, P., Yu, H., Liu, Y., Chen, W., Wang, X., & Ouyang, M. (2013). Concentration effects on the isolation and dynamic rheological behavior of cellulose nanofibers via ultrasonic processing. *Cellulose*, 20(1), 149–157. <https://doi.org/10.1007/s10570-012-9829-7>
- Chen, W., Yu, H., Liu, Y., Chen, P., Zhang, M., & Hai, Y. (2011).

- Individualization of cellulose nanofibers from wood using high-intensity ultrasonication combined with chemical pretreatments. *Carbohydrate Polymers*, 83(4), 1804–1811.
<https://doi.org/https://doi.org/10.1016/j.carbpol.2010.10.040>
- Cheng, M., Qin, Z., Liu, Y., Qin, Y., & Li, T. (2014). Efficient extraction of carboxylated spherical cellulose nanocrystals with narrow distribution through hydrolysis of lyocell fibers by using ammonium persulfate as an oxidant. 251–258. <https://doi.org/10.1039/c3ta13653a>
- Cheng, M., Qin, Z., Liu, Y., Qin, Y., Li, T., Chen, L., & Zhu, M. (2014). Efficient extraction of carboxylated spherical cellulose nanocrystals with narrow distribution through hydrolysis of lyocell fibers by using ammonium persulfate as an oxidant. *Journal of Materials Chemistry A*, 2(1), 251–258. <https://doi.org/10.1039/c3ta13653a>
- Cheng, Q., Jiang, H., & Li, Y. (2020). Effect of fiber content and orientation on the scratch behavior of short glass fiber reinforced PBT composites. *Tribology International*, 146(January), 106221. <https://doi.org/10.1016/j.triboint.2020.106221>
- Cherian, B. M., Leão, A. L., de Souza, S. F., Thomas, S., Pothan, L. A., & Kottaisamy, M. (2010). Isolation of nanocellulose from pineapple leaf fibres by steam explosion. *Carbohydrate Polymers*, 81(3), 720–725. <https://doi.org/10.1016/j.carbpol.2010.03.046>
- Chin, S. C., Tee, K. F., Tong, F. S., Ong, H. R., & Gimbin, J. (2020). Thermal and mechanical properties of bamboo fiber reinforced composites. *Materials Today Communications*, 23(December 2019), 100876. <https://doi.org/10.1016/j.mtcomm.2019.100876>
- Choi, H. Y., & Lee, J. S. (2012). Effects of surface treatment of ramie fibers in a ramie/poly(lactic acid) composite. *Fibers and Polymers*, 13(2), 217–223. <https://doi.org/10.1007/s12221-012-0217-6>
- Christensen, R. M. (2005). *Mechanics of Composite Materials*. Dover Publications.
- Corrêa, A. C., de Teixeira, E. M., Pessan, L. A., & Mattoso, L. H. C. (2010). Cellulose nanofibers from curaua fibers. *Cellulose*, 17(6), 1183–1192. <https://doi.org/10.1007/s10570-010-9453-3>
- Dagdag, O., Hsissou, R., El Harfi, A., Safi, Z., Berisha, A., Verma, C., Ebenso, E. E., Quraishi, M. A., Wazzan, N., Jodeh, S., & El Gouri, M. (2020). Epoxy resins and their zinc composites as novel anti-corrosive materials for copper in 3% sodium chloride solution: Experimental and computational studies. *Journal of Molecular Liquids*, 315, 113757. <https://doi.org/https://doi.org/10.1016/j.molliq.2020.113757>
- Dagdag, O., Safi, Z., Hsissou, R., Erramli, H., El Bouchti, M., Wazzan, N., Guo,

- L., Verma, C., Ebenso, E. E., & El Harfi, A. (2019). Epoxy pre-polymers as new and effective materials for corrosion inhibition of carbon steel in acidic medium: Computational and experimental studies. *Scientific Reports*, 9(1), 11715. <https://doi.org/10.1038/s41598-019-48284-0>
- Dai, D., & Fan, M. (2010). Characteristic and Performance of Elementary Hemp Fibre. *Materials Sciences and Applications*, 01(06), 336–342. <https://doi.org/10.4236/msa.2010.16049>
- Dai, H., Huang, Y., Zhang, H., Ma, L., Huang, H., Wu, J., & Zhang, Y. (2020). Direct fabrication of hierarchically processed pineapple peel hydrogels for efficient Congo red adsorption. *Carbohydrate Polymers*, 230, 115599. <https://doi.org/https://doi.org/10.1016/j.carbpol.2019.115599>
- Dai, H., Ou, S., Huang, Y., & Huang, H. (2018). Utilization of pineapple peel for production of nanocellulose and film application. *Cellulose*, 25(3), 1743–1756. <https://doi.org/10.1007/s10570-018-1671-0>
- Dang, C. Y., Shen, X. J., Nie, H. J., Yang, S., Shen, J. X., Yang, X. H., & Fu, S. Y. (2019). Enhanced interlaminar shear strength of ramie fiber/polypropylene composites by optimal combination of graphene oxide size and content. *Composites Part B: Engineering*, 168(April), 488–495. <https://doi.org/10.1016/j.compositesb.2019.03.080>
- Dantas, L. G., De Castro Motta, L. A., Pasquini, D., & Vieira, J. G. (2019). Surface esterification of sisal fibres for use as reinforcement in cementitious matrix. *Materials Research*, 22(4). <https://doi.org/10.1590/1980-5373-MR-2018-0585>
- Das, P., & Tiwari, P. (2019). Thermal degradation study of waste polyethylene terephthalate (PET) under inert and oxidative environments. *Thermochimica Acta*, 679(April), 178340. <https://doi.org/10.1016/j.tca.2019.178340>
- Das, S. (2017a). Mechanical and water swelling properties of waste paper reinforced unsaturated polyester composites. *Construction and Building Materials*, 138, 469–478. <https://doi.org/https://doi.org/10.1016/j.conbuildmat.2017.02.041>
- Das, S. (2017b). Mechanical properties of waste paper/jute fabric reinforced polyester resin matrix hybrid composites. *Carbohydrate Polymers*, 172, 60–67. <https://doi.org/10.1016/j.carbpol.2017.05.036>
- Datsyuk, V., Trotsenko, S., Trakakis, G., Boden, A., Vyzas-Asimakopoulos, K., Parthenios, J., Galiotis, C., Reich, S., & Papagelis, K. (2020). Thermal properties enhancement of epoxy resins by incorporating polybenzimidazole nanofibers filled with graphene and carbon nanotubes as reinforcing material. *Polymer Testing*, 82(August 2019), 106317. <https://doi.org/10.1016/j.polymertesting.2019.106317>
- Dayo, A. Q., Wang, A. ran, Kiran, S., Wang, J., Qureshi, K., Xu, Y. le, Zegaoui,

- A., Derradji, M., Babar, A. A., & Liu, W. bin. (2018). Impacts of hemp fiber diameter on mechanical and water uptake properties of polybenzoxazine composites. *Industrial Crops and Products*, *111*(July 2017), 277–284. <https://doi.org/10.1016/j.indcrop.2017.10.039>
- de Araujo Alves Lima, R., Kawasaki Cavalcanti, D., de Souza e Silva Neto, J., Meneses da Costa, H., & Banea, M. D. (2020). Effect of surface treatments on interfacial properties of natural intralaminar hybrid composites. *Polymer Composites*, *41*(1), 314–325. <https://doi.org/10.1002/pc.25371>
- De, S., Fulmali, A. O., Shivangi, P. N., Choudhury, S., Prusty, R. K., & Ray, B. C. (2020). Interface modification of carbon fiber reinforced epoxy composite by hydroxyl/carboxyl functionalized carbon nanotube. *Materials Today: Proceedings*, *27*, 1473–1478. <https://doi.org/10.1016/j.matpr.2020.02.970>
- Deepa, B., Abraham, E., Cordeiro, N., Mozetic, M., Mathew, A. P., Oksman, K., Faria, M., Thomas, S., & Pothan, L. A. (2015). Utilization of various lignocellulosic biomass for the production of nanocellulose: a comparative study. *Cellulose*, *22*(2), 1075–1090. <https://doi.org/10.1007/s10570-015-0554-x>
- Devnani, G. L., & Sinha, S. (2019). Extraction, characterization and thermal degradation kinetics with activation energy of untreated and alkali treated *Saccharum spontaneum* (Kans grass) fiber. *Composites Part B: Engineering*, *166*(October 2018), 436–445. <https://doi.org/10.1016/j.compositesb.2019.02.042>
- Dhakal, H. N., Zhang, Z. Y., & Bennett, N. (2012). Influence of fibre treatment and glass fibre hybridisation on thermal degradation and surface energy characteristics of hemp/unsaturated polyester composites. *Composites Part B: Engineering*, *43*(7), 2757–2761. <https://doi.org/10.1016/j.compositesb.2012.04.036>
- Dhali, K., Ghasemlou, M., Daver, F., Cass, P., & Adhikari, B. (2021). A review of nanocellulose as a new material towards environmental sustainability. *Science of the Total Environment*, *775*, 145871. <https://doi.org/10.1016/j.scitotenv.2021.145871>
- Dimas, A. A., Kusmono, Muhammad, W. W., & Mochammad, N. I. (2020). Extraction and characterization of nanocrystalline cellulose (Ncc) from ramie fiber by hydrochloric acid hydrolysis. *Key Engineering Materials*, *867* *KEM*(October), 109–116. <https://doi.org/10.4028/www.scientific.net/KEM.867.109>
- Ding, Y., Ye, Q., Liu, M., Shi, Z., & Liang, Y. (2021). Reductive release of Fe mineral-associated organic matter accelerated by oxalic acid. *Science of the Total Environment*, *763*(xxxx), 142937. <https://doi.org/10.1016/j.scitotenv.2020.142937>
- Djafari Petroudy, S. R. (2017). *3 - Physical and mechanical properties of natural*

- fibers* (M. Fan & F. B. T.-A. H. S. N. F. C. in C. Fu (eds.); pp. 59–83). Woodhead Publishing. <https://doi.org/https://doi.org/10.1016/B978-0-08-100411-1.00003-0>
- Dong, Z. jiao, Zhou, T., Luan, H., Williams, R. C., Wang, P., & Leng, Z. (2019). Composite modification mechanism of blended bio-asphalt combining styrene-butadiene-styrene with crumb rubber: A sustainable and environmental-friendly solution for wastes. *Journal of Cleaner Production*, 214, 593–605. <https://doi.org/10.1016/j.jclepro.2019.01.004>
- Druzhinina, I. S., & Kubicek, C. P. (2017). Genetic engineering of *Trichoderma reesei* cellulases and their production. *Microbial Biotechnology*, 10(6), 1485–1499. <https://doi.org/10.1111/1751-7915.12726>
- Du, H., Liu, C., Zhang, Y., Yu, G., Si, C., & Li, B. (2016). Preparation and characterization of functional cellulose nanofibrils via formic acid hydrolysis pretreatment and the followed high-pressure homogenization. *Industrial Crops and Products*, 94, 736–745. <https://doi.org/10.1016/j.indcrop.2016.09.059>
- Du, Y., Yan, N., & Kortschot, M. T. (2015). 4 - *The use of ramie fibers as reinforcements in composites* (O. Faruk & M. B. T.-B. R. in C. M. Sain (eds.); pp. 104–137). Woodhead Publishing. <https://doi.org/https://doi.org/10.1533/9781782421276.1.104>
- Duan, Y., Tan, Z., Zhao, Y., & Sun, J. (2008). Compression responses of preform in vacuum infusion process. *Chinese Journal of Aeronautics*, 21(4), 370–377. [https://doi.org/10.1016/S1000-9361\(08\)60048-5](https://doi.org/10.1016/S1000-9361(08)60048-5)
- El Gouri, M., El Bachiri, A., Hegazi, S. E., Rafik, M., & El Harfi, A. (2009). Thermal degradation of a reactive flame retardant based on cyclotriphosphazene and its blend with DGEBA epoxy resin. *Polymer Degradation and Stability*, 94(11), 2101–2106. <https://doi.org/10.1016/j.polymdegradstab.2009.08.009>
- Elfaleh, I., Abbassi, F., Habibi, M., Ahmad, F., Guedri, M., Nasri, M., & Garnier, C. (2023). A comprehensive review of natural fibers and their composites: An eco-friendly alternative to conventional materials. *Results in Engineering*, 19(July), 101271. <https://doi.org/10.1016/j.rineng.2023.101271>
- Espert, A., Vilaplana, F., & Karlsson, S. (2004). Comparison of water absorption in natural cellulosic fibres from wood and one-year crops in polypropylene composites and its influence on their mechanical properties. *Composites Part A: Applied Science and Manufacturing*, 35(11), 1267–1276. <https://doi.org/https://doi.org/10.1016/j.compositesa.2004.04.004>
- Espinosa, S. C., Kuhnt, T., Johan Foster, E., & Weder, C. (2020). Isolation of thermally stable cellulose nanocrystals from spent coffee grounds via phosphoric acid hydrolysis. *Journal of Renewable Materials*, 8(2), 187–203. <https://doi.org/10.32604/jrm.2020.07940>

- Fakhrurrozi, I. F. (2024). Studi sifat mekanis, penyerapan air, kelarutan dan keausan dari komposit PLA/acetylated cellulose nanocrystal untuk aplikasi material mahkota gigi yang difabrikasi dengan fused deposition modeling. In *Thesis* (Vol. 1, Issue April). Universitas Gadjah Mada.
- Ferrer, A., Pal, L., & Hubbe, M. A. (2017). Nanocellulose in packaging: Advances in barrier layer technologies. *Industrial Crops and Products*, *95*, 574–582. <https://doi.org/10.1016/j.indcrop.2016.11.012>
- Filipova, I., Fridrihsone, V., Cabulis, U., & Berzins, A. (2018). Synthesis of Nanofibrillated Cellulose by Combined Ammonium Persulfate Treatment with Ultrasound and Mechanical Processing. *Nanomaterials*, *8*(9). <https://doi.org/10.3390/nano8090640>
- Filson, P. B., & Dawson-Andoh, B. E. (2009). Sono-chemical preparation of cellulose nanocrystals from lignocellulose derived materials. *Bioresource Technology*, *100*(7), 2259–2264. <https://doi.org/10.1016/j.biortech.2008.09.062>
- Frone, A. N., Panaitescu, D. M., & Donescu, D. (2011). Some aspects concerning the isolation of cellulose micro- and nano-fibers. *UPB Scientific Bulletin, Series B: Chemistry and Materials Science*, *73*(2), 133–152.
- Fukuzumi, H., Saito, T., & Isogai, A. (2012). Influence of TEMPO-oxidized cellulose nanofibril length on film properties. *Carbohydrate Polymers*. <https://doi.org/10.1016/j.carbpol.2012.04.069>
- Fukuzumi, H., Saito, T., Iwata, T., Kumamoto, Y., & Isogai, A. (2009). Transparent and High Gas Barrier Films of Cellulose Nanofibers Prepared by TEMPO-Mediated Oxidation. *Biomacromolecules*, *10*(1), 162–165. <https://doi.org/10.1021/bm801065u>
- Gajjar, T., Shah, D. B., Joshi, S. J., & Patel, K. M. (2020). Analysis of process parameters for composites manufacturing using vacuum infusion process. *Materials Today: Proceedings*, *21*, 1244–1249. <https://doi.org/10.1016/j.matpr.2020.01.112>
- Gall, J. F., Church, G. L., & Brown, R. L. (1943). Solubility of Ammonium Persulfate in Water and in Solutions of Sulfuric Acid and Ammonium Sulfate. *The Journal of Physical Chemistry*, *47*(9), 645–649. <https://doi.org/10.1021/j150432a003>
- Gapsari, F., Purnowidodo, A., Hidayatullah, S., & Suteja, S. (2021). Characterization of Timoho Fiber as a reinforcement in green composite. *Journal of Materials Research and Technology*, *13*, 1305–1315. <https://doi.org/10.1016/j.jmrt.2021.05.049>
- Gatenholm, P., & Klemm, D. (2010). Bacterial nanocellulose as a renewable material for biomedical applications. *MRS Bulletin*, *35*(3), 208–213. <https://doi.org/10.1557/mrs2010.653>

- Ghozali, M., Ariawan, D., & Surojo, E. (2021). The Effect of Alkali Treatment And Microcrystalline Cellulose Addition on Density Value of Cantala Fiber Reinforced Unsaturated Polyester Composites. *Mekanika: Majalah Ilmiah Mekanika*, 20(1), 1. <https://doi.org/10.20961/mechanika.v20i1.47460>
- Goh, K. Y., Ching, Y. C., Chuah, C. H., Abdullah, L. C., & Liou, N.-S. (2016). Individualization of microfibrillated celluloses from oil palm empty fruit bunch: comparative studies between acid hydrolysis and ammonium persulfate oxidation. *Cellulose*, 23(1), 379–390. <https://doi.org/10.1007/s10570-015-0812-y>
- Guimarães, J. L., Frollini, E., da Silva, C. G., Wypych, F., & Satyanarayana, K. G. (2009). Characterization of banana, sugarcane bagasse and sponge gourd fibers of Brazil. *Industrial Crops and Products*, 30(3), 407–415. <https://doi.org/10.1016/j.indcrop.2009.07.013>
- Gupta, M., & Gond, R. (2017). Influence of Concentrations of Alkali Treatment on Mechanical and Dynamic. *American Journal of Polymer Science & Engineering*, 5(1), 24–33.
- Haafiz, M. K. M., Hassan, A., Zakaria, Z., & Inuwa, I. M. (2014). Isolation and characterization of cellulose nanowhiskers from oil palm biomass microcrystalline cellulose. *Carbohydrate Polymers*, 103, 119–125. <https://doi.org/https://doi.org/10.1016/j.carbpol.2013.11.055>
- Habibi, Y., Chanzy, H., & Vignon, M. R. (2006). TEMPO-mediated surface oxidation of cellulose whiskers. *Cellulose*, 13(6), 679–687. <https://doi.org/10.1007/s10570-006-9075-y>
- Habibi, Y., Goffin, A.-L., Schiltz, N., Duquesne, E., Dubois, P., & Dufresne, A. (2008). Bionanocomposites based on poly(ϵ -caprolactone)-grafted cellulose nanocrystals by ring-opening polymerization. *J. Mater. Chem.*, 18(41), 5002–5010. <https://doi.org/10.1039/B809212E>
- Habibi, Y., Lucia, L. A., & Rojas, O. J. (2010). Cellulose nanocrystals: Chemistry, self-assembly, and applications. *Chemical Reviews*, 110(6), 3479–3500. <https://doi.org/10.1021/cr900339w>
- Hadlhalli, P., & Nagarajachari, U. (2024). Synergistic effects of sisal / glass fiber hybridization and eggshell powder filler on the performance of eco-friendly polymer composites. *August*, 1–15. <https://doi.org/10.1002/pc.29041>
- Hajiha, H., Sain, M., & Mei, L. H. (2014). Modification and Characterization of Hemp and Sisal Fibers. *Journal of Natural Fibers*, 11(2), 144–168. <https://doi.org/10.1080/15440478.2013.861779>
- Han, C. L., Wang, G. D., Li, N., Wang, M., Liu, X. liang, & Ma, J. he. (2021). Study on interlaminar performance of CNTs/epoxy film enhanced GFRP under low-temperature cycle. *Composite Structures*, 272(May), 114191. <https://doi.org/10.1016/j.compstruct.2021.114191>

- Hasan, M. H., Mollik, M. S., & Rashid, M. M. (2018). Effect of nanoclay on thermal behavior of jute reinforced composite. *International Journal of Advanced Manufacturing Technology*, 94(5–8), 1863–1871. <https://doi.org/10.1007/s00170-017-0883-z>
- Haunreiter, K. J., Dichiara, A. B., & Gustafson, R. (2022). Nanocellulose by Ammonium Persulfate Oxidation: An Alternative to TEMPO-Mediated Oxidation. *ACS Sustainable Chemistry & Engineering*. <https://doi.org/10.1021/acssuschemeng.1c07814>
- He, T., Jiang, Z., Wu, P., Yi, J., Li, J., & Hu, C. (2016). Fractionation for further conversion: from raw corn stover to lactic acid. *Scientific Reports*, 6(1), 38623. <https://doi.org/10.1038/srep38623>
- Hemmati, F., Jafari, S. M., & Taheri, R. A. (2019). Optimization of homogenization-sonication technique for the production of cellulose nanocrystals from cotton linter. *International Journal of Biological Macromolecules*, 137, 374–381. <https://doi.org/https://doi.org/10.1016/j.ijbiomac.2019.06.241>
- Henschen, J., Li, D., & Ek, M. (2019). Preparation of cellulose nanomaterials via cellulose oxalates. *Carbohydrate Polymers*, 213(November 2018), 208–216. <https://doi.org/10.1016/j.carbpol.2019.02.056>
- Hernandez, C. C., Ferreira, F. F., & Rosa, D. S. (2018). X-ray powder diffraction and other analyses of cellulose nanocrystals obtained from corn straw by chemical treatments. *Carbohydrate Polymers*, 193(January), 39–44. <https://doi.org/10.1016/j.carbpol.2018.03.085>
- Hestiawan, H., Jamasri, & Kusmono. (2016). A Preliminary Study: Influence of Alkali Treatment on Physical and Mechanical Properties of Agel Leaf Fiber (*Corypha gebanga*). *Applied Mechanics and Materials*, 842, 61–66. <https://doi.org/10.4028/www.scientific.net/amm.842.61>
- Hindeleh, A. M., & Johnson, D. J. (1980). An empirical estimation of Scherrer parameters for the evaluation of true crystallite size in fibrous polymers. *Polymer*, 21(8), 929–935. [https://doi.org/https://doi.org/10.1016/0032-3861\(80\)90250-5](https://doi.org/https://doi.org/10.1016/0032-3861(80)90250-5)
- Hsissou, R., About, S., Berisha, A., Berradi, M., Assouag, M., Hajjaji, N., & Elharfi, A. (2019). Experimental, DFT and molecular dynamics simulation on the inhibition performance of the DGDCBA epoxy polymer against the corrosion of the E24 carbon steel in 1.0 M HCl solution. *Journal of Molecular Structure*, 1182, 340–351. <https://doi.org/https://doi.org/10.1016/j.molstruc.2018.12.030>
- Hsissou, R., About, S., Safi, Z., Benhiba, F., Wazzan, N., Guo, L., Nouneh, K., Briche, S., Erramli, H., Ebn Touhami, M., Assouag, M., & Elharfi, A. (2021). Synthesis and anticorrosive properties of epoxy polymer for CS in [1 M] HCl solution: Electrochemical, AFM, DFT and MD simulations.

Construction and Building Materials, 270, 121454.
<https://doi.org/https://doi.org/10.1016/j.conbuildmat.2020.121454>

Hsissou, R., About, S., Seghiri, R., Rehioui, M., Berisha, A., Erramli, H., Assouag, M., & Elharfi, A. (2020). Evaluation of corrosion inhibition performance of phosphorus polymer for carbon steel in [1 M] HCl: Computational studies (DFT, MC and MD simulations). *Journal of Materials Research and Technology*, 9(3), 2691–2703.
<https://doi.org/https://doi.org/10.1016/j.jmrt.2020.01.002>

Hsissou, R., El Bouchti, M., & El Harfi, A. (2017). Elaboration and viscosimetric, viscoelastic and rheological studies of a new hexafunctional polyepoxide polymer : Hexaglycidyl ethylene of methylene dianiline. *Journal of Materials and Environmental Science*, 8(12), 4349–4361.
<https://doi.org/10.26872/jmes.2017.8.12.458>

Hu, Y., Tang, L., Lu, Q., Wang, S., Chen, X., & Huang, B. (2014). Preparation of cellulose nanocrystals and carboxylated cellulose nanocrystals from borer powder of bamboo. *Cellulose*, 21(3), 1611–1618.
<https://doi.org/10.1007/s10570-014-0236-0>

Ilangovan, M., Guna, V., Prajwal, B., Jiang, Q., & Reddy, N. (2020). Extraction and characterisation of natural cellulose fibers from *Kigelia africana*. *Carbohydrate Polymers*, 236(February), 115996.
<https://doi.org/10.1016/j.carbpol.2020.115996>

Indirasetyo, N. L., & Kusmono. (2022). Isolation and Properties of Cellulose Nanocrystals Fabricated by Ammonium Persulfate Oxidation from *Sansevieria trifasciata* Fibers. *Fibers*, 10(7).
<https://doi.org/10.3390/fib10070061>

Indran, S., & Raj, R. E. (2015). Characterization of new natural cellulosic fiber from *Cissus quadrangularis* stem. *Carbohydrate Polymers*, 117, 392–399.
<https://doi.org/https://doi.org/10.1016/j.carbpol.2014.09.072>

Ioelovich, M. (2014). Peculiarities of cellulose nanoparticles. *Tappi Journal*, 13(5), 45–51. <https://doi.org/10.32964/tj13.5.45>

Iwamoto, S., Nakagaito, A. N., & Yano, H. (2007). Nano-fibrillation of pulp fibers for the processing of transparent nanocomposites. *Applied Physics A: Materials Science and Processing*, 89(2), 461–466.
<https://doi.org/10.1007/s00339-007-4175-6>

Jabbar, A., Militký, J., Wiener, J., Kale, B. M., Ali, U., & Rwawiire, S. (2017). Nanocellulose coated woven jute/green epoxy composites: Characterization of mechanical and dynamic mechanical behavior. *Composite Structures*, 161, 340–349. <https://doi.org/10.1016/j.compstruct.2016.11.062>

Jaiswal, D., Devnani, G. L., Rajeshkumar, G., Sanjay, M. R., & Siengchin, S. (2022). Review on extraction, characterization, surface treatment and thermal

- degradation analysis of new cellulosic fibers as sustainable reinforcement in polymer composites. *Current Research in Green and Sustainable Chemistry*, 5(November 2021), 100271. <https://doi.org/10.1016/j.crgsc.2022.100271>
- Jamasri, & Yudhanto, F. (2022). The Effect of Alkali Treatment and Addition of Microcrystalline Cellulose (MCC) on Physical and Tensile Properties of Ramie/Polyester Laminated Composites. *Revue Des Composites et Des Materiaux Avances*, 32(2), 77–84. <https://doi.org/10.18280/rcma.320204>
- Jamilah, U. L., & Sujito, S. (2021). The improvement of ramie fiber properties as composite materials using alkalization treatment: NaOH concentration. *Jurnal Sains Materi Indonesia*, 22(2), 62. <https://doi.org/10.17146/jsmi.2021.22.3.6182>
- Jawaid, M., Abdul Khalil, H. P. S., Noorunnisa Khanam, P., & Abu Bakar, A. (2011). Hybrid Composites Made from Oil Palm Empty Fruit Bunches/Jute Fibres: Water Absorption, Thickness Swelling and Density Behaviours. *Journal of Polymers and the Environment*, 19(1), 106–109. <https://doi.org/10.1007/s10924-010-0203-2>
- Jawaid, M., Kian, L. K., Fouad, H., Saba, N., Alothman, O. Y., & Hashem, M. (2021). Morphological, structural, and thermal analysis of three part of Conocarpus cellulosic fibres. *Journal of Materials Research and Technology*, 10, 24–33. <https://doi.org/10.1016/j.jmrt.2020.11.108>
- Jayabalakrishnan, D., Prabhu, P., Mohamed Iqbal, S., Mugendiran, V., Ravi, S., & Arun Prakash, V. R. (2022). Mechanical, dielectric, and hydrophobicity behavior of coconut shell biochar toughened Caryota urens natural fiber reinforced epoxy composite. *Polymer Composites*, 43(1), 493–502. <https://doi.org/10.1002/pc.26393>
- Jiang, H., Wu, Y., Han, B., & Zhang, Y. (2017). Effect of oxidation time on the properties of cellulose nanocrystals from hybrid poplar residues using the ammonium persulfate. *Carbohydrate Polymers*, 174, 291–298. <https://doi.org/10.1016/j.carbpol.2017.06.080>
- John, M. J., & Anandjiwala, R. D. (2008). Recent developments in chemical modification and characterization of natural fiber-reinforced composites. *Polymer Composites*, 29(2), 187–207. <https://doi.org/10.1002/pc.20461>
- Jonoobi, M., Oladi, R., Davoudpour, Y., Oksman, K., Dufresne, A., Hamzeh, Y., & Davoodi, R. (2015). Different preparation methods and properties of nanostructured cellulose from various natural resources and residues: a review. *Cellulose*, 22(2), 935–969. <https://doi.org/10.1007/s10570-015-0551-0>
- Joseph, P. V., Joseph, K., Thomas, S., Pillai, C. K. S., Prasad, V. S., Groeninckx, G., & Sarkissova, M. (2003). The thermal and crystallisation studies of short sisal fibre reinforced polypropylene composites. *Composites Part A: Applied*

Science and Manufacturing, 34(3), 253–266.

[https://doi.org/https://doi.org/10.1016/S1359-835X\(02\)00185-9](https://doi.org/https://doi.org/10.1016/S1359-835X(02)00185-9)

Kabir, M. M. (2012). *Effects of Chemical Treatments on Hemp Fibre Reinforced Polyester Composites* (Issue September). University of Southern Queensland Toowoomba, Queensland, Australia.

Kabir, M. M., Wang, H., Lau, K. T., & Cardona, F. (2012). Chemical treatments on plant-based natural fibre reinforced polymer composites: An overview. *Composites Part B: Engineering*, 43(7), 2883–2892.

<https://doi.org/https://doi.org/10.1016/j.compositesb.2012.04.053>

Kabir, M. M., Wang, H., Lau, K. T., & Cardona, F. (2013a). Effects of chemical treatments on hemp fibre structure. *Applied Surface Science*, 276, 13–23.

<https://doi.org/https://doi.org/10.1016/j.apsusc.2013.02.086>

Kabir, M. M., Wang, H., Lau, K. T., & Cardona, F. (2013b). Tensile properties of chemically treated hemp fibres as reinforcement for composites. *Composites Part B: Engineering*, 53, 362–368.

<https://doi.org/https://doi.org/10.1016/j.compositesb.2013.05.048>

Kamble, Z., Behera, B. K., Kimura, T., & Haruhiro, I. (2022). Development and characterization of thermoset nanocomposites reinforced with cotton fibres recovered from textile waste. *Journal of Industrial Textiles*, 51(2), 2026S-2052S. <https://doi.org/10.1177/1528083720913535>

Kamble, Z., Behera, B. K., Mishra, R., & Behera, P. K. (2021). Influence of cellulosic and non-cellulosic particle fillers on mechanical, dynamic mechanical, and thermogravimetric properties of waste cotton fibre reinforced green composites. *Composites Part B: Engineering*, 207(December 2020), 108595.

<https://doi.org/10.1016/j.compositesb.2020.108595>

Kargarzadeh, H., Sheltami, R. M., Ahmad, I., Abdullah, I., & Dufresne, A. (2015). Cellulose nanocrystal: A promising toughening agent for unsaturated polyester nanocomposite. *Polymer*, 56, 346–357.

<https://doi.org/10.1016/j.polymer.2014.11.054>

Karimi, K., & Taherzadeh, M. J. (2016). A critical review of analytical methods in pretreatment of lignocelluloses: Composition, imaging, and crystallinity. *Bioresource Technology*, 200, 1008–1018.

<https://doi.org/10.1016/j.biortech.2015.11.022>

Karthi, N., Kumaresan, K., Sathish, S., Gokulkumar, S., Prabhu, L., & Vigneshkumar, N. (2019). An overview: Natural fiber reinforced hybrid composites, chemical treatments and application areas. *Materials Today: Proceedings*, 27(xxxx), 2828–2834.

<https://doi.org/10.1016/j.matpr.2020.01.011>

Kathirselvam, M., Kumaravel, A., Arthanarieswaran, V. P., & Saravanakumar, S.

- S. (2019). Characterization of cellulose fibers in *Thespesia populnea* barks: Influence of alkali treatment. *Carbohydrate Polymers*, 217(April), 178–189. <https://doi.org/10.1016/j.carbpol.2019.04.063>
- Kaur, P., Sharma, N., Munagala, M., Rajkhowa, R., Aallardyce, B., Shastri, Y., & Agrawal, R. (2021). Nanocellulose: Resources, Physio-Chemical Properties, Current Uses and Future Applications. *Frontiers in Nanotechnology*, 3(November), 1–17. <https://doi.org/10.3389/fnano.2021.747329>
- Kaushik, A., Singh, M., & Verma, G. (2010). Green nanocomposites based on thermoplastic starch and steam exploded cellulose nanofibrils from wheat straw. *Carbohydrate Polymers*, 82(2), 337–345. <https://doi.org/https://doi.org/10.1016/j.carbpol.2010.04.063>
- Kaushik, V. K., Kumar, A., & Kalia, S. (2012). *Effect of Mercerization and Benzoyl Peroxide Treatment on Morphology, Thermal Stability and Crystallinity of Sisal Fibers*. 1(6), 101–105. <https://doi.org/10.5923/j.textile.20120106.07>
- Keerati-U-Rai, M., & Corredig, M. (2009). Effect of dynamic high pressure homogenization on the aggregation state of soy protein. *Journal of Agricultural and Food Chemistry*, 57(9), 3556–3562. <https://doi.org/10.1021/jf803562q>
- Khalil, H. P. S. A., Tehrani, M. A., Davoudpour, Y., Bhat, A. H., Jawaid, M., & Hassan, A. (2012). Natural fiber reinforced poly(vinyl chloride) composites: A review. *Journal of Reinforced Plastics and Composites*, 32(5), 330–356. <https://doi.org/10.1177/0731684412458553>
- Khan, A., Asiri, A. M., Jawaid, M., Saba, N., & Inamuddin. (2020). Effect of cellulose nano fibers and nano clays on the mechanical, morphological, thermal and dynamic mechanical performance of kenaf/epoxy composites. *Carbohydrate Polymers*, 239(December 2019), 116248. <https://doi.org/10.1016/j.carbpol.2020.116248>
- Khan, A., Jagdale, P., Castellino, M., Rovere, M., Jehangir, Q., Mandracci, P., Rosso, C., & Tagliaferro, A. (2018). Innovative functionalized carbon fibers from waste: How to enhance polymer composites properties. *Composites Part B: Engineering*, 139(November 2017), 31–39. <https://doi.org/10.1016/j.compositesb.2017.11.064>
- Khanjanzadeh, H., & Park, B. D. (2020). Characterization of carboxylated cellulose nanocrystals from recycled fiberboard fibers using ammonium persulfate oxidation. *Journal of the Korean Wood Science and Technology*, 48(2), 231–244. <https://doi.org/10.5658/WOOD.2020.48.2.231>
- Khanjanzadeh, H., & Park, B. D. (2021). Optimum oxidation for direct and efficient extraction of carboxylated cellulose nanocrystals from recycled MDF fibers by ammonium persulfate. *Carbohydrate Polymers*, 251(June 2020), 117029. <https://doi.org/10.1016/j.carbpol.2020.117029>

- Kirubakaran, G., & SenthamaraiKannan, C. (2024). Mechanical, wear, and water absorption behavior of polyester biocomposite using jackfruit seed husk cellulose and pineapple fiber. *Biomass Conversion and Biorefinery*, *14*(9), 10759–10769. <https://doi.org/10.1007/s13399-024-05268-z>
- Kiziltas, A., Gardner, D. J., Han, Y., & Yang, H. S. (2010). Determining the mechanical properties of microcrystalline cellulose (MCC)-Filled PET-PTT blend composites. *Wood and Fiber Science*, *42*(2), 165–176. <https://www.scopus.com/inward/record.uri?eid=2-s2.0-78649784304&partnerID=40&md5=afbc1bff34ce3083cc2178ef5c43dc98>
- Klemm, D., Heublein, B., Fink, H.-P., & Bohn, A. (2005). Cellulose: Fascinating Biopolymer and Sustainable Raw Material. *Angewandte Chemie International Edition*, *44*(22), 3358–3393. <https://doi.org/https://doi.org/10.1002/anie.200460587>
- Kolthoff, I. M., & Miller, I. K. (1951). The Chemistry of Persulfate. I. The Kinetics and Mechanism of the Decomposition of the Persulfate Ion in Aqueous Medium1. *Journal of the American Chemical Society*, *73*(7), 3055–3059. <https://doi.org/10.1021/ja01151a024>
- Kommula, V. P., Reddy, K. O., Shukla, M., Marwala, T., & Rajulu, A. V. (2013). Physico-chemical, Tensile, and Thermal Characterization of Napier Grass (Native African) Fiber Strands. *International Journal of Polymer Analysis and Characterization*, *18*(4), 303–314. <https://doi.org/10.1080/1023666X.2013.784935>
- Kontturi, E., Laaksonen, P., Linder, M. B., Nonappa, Gröschel, A. H., Rojas, O. J., & Ikkala, O. (2018). Advanced Materials through Assembly of Nanocelluloses. *Advanced Materials*, *30*(24), 1703779. <https://doi.org/https://doi.org/10.1002/adma.201703779>
- Kumar, R. D. S., Gurusamy, P., & Dinesh, D. (2024). Hybrid effect of neem seed and groundnut shell bio-fillers on the mechanical, water absorption and thermal properties of jute fiber reinforced epoxy composites. *International Journal of Materials Research*, *115*(7), 517–528. <https://doi.org/doi:10.1515/ijmr-2023-0301>
- Kumar, S., Graninger, G., Hawkins, S. C., & Falzon, B. G. (2021). A nanostructured cellulose-based interphase layer to enhance the mechanical performance of glass fibre-reinforced polymer composites. *Composites Part A: Applied Science and Manufacturing*, *148*(July 2020), 106475. <https://doi.org/10.1016/j.compositesa.2021.106475>
- Kushwaha, P. K., & Kumar, R. (2010). Studies on water absorption of bamboo-epoxy composites: Effect of silane treatment of mercerized bamboo. *Journal of Applied Polymer Science*, *115*(3), 1846–1852. <https://doi.org/https://doi.org/10.1002/app.31317>
- Kusmono, & Affan, M. N. (2020). Isolation and Characterization of

Nanocrystalline Cellulose from Ramie Fibers via Phosphoric Acid Hydrolysis. *Journal of Natural Fibers*, 00(00), 1–12.
<https://doi.org/10.1080/15440478.2020.1821292>

- Kusmono, Listyanda, R. F., Wildan, M. W., & Ilman, M. N. (2020). Preparation and characterization of cellulose nanocrystal extracted from ramie fibers by sulfuric acid hydrolysis. *Heliyon*, 6(11), e05486.
<https://doi.org/10.1016/j.heliyon.2020.e05486>
- Lam, E., Leung, A. C. W., Liu, Y., Majid, E., Hrapovic, S., Male, K. B., & Luong, J. H. T. (2013). Green Strategy Guided by Raman Spectroscopy for the Synthesis of Ammonium Carboxylated Nanocrystalline Cellulose and the Recovery of Byproducts. *ACS Sustainable Chemistry & Engineering*, 1(2), 278–283. <https://doi.org/10.1021/sc3001367>
- Latief, F. H., Chafidz, A., Junaedi, H., Alfozan, A., & Khan, R. (2019). Effect of alumina contents on the physicomechanical properties of alumina (Al₂O₃) reinforced polyester composites. *Advances in Polymer Technology*, 2019, 1–9. <https://doi.org/10.1155/2019/5173537>
- Le Guen, M. J., Newman, R. H., Fernyhough, A., Emms, G. W., & Staiger, M. P. (2016). The damping-modulus relationship in flax-carbon fibre hybrid composites. *Composites Part B: Engineering*, 89, 27–33.
<https://doi.org/10.1016/j.compositesb.2015.10.046>
- Lee, J. M., Mohd Ishak, Z. A., Mat Taib, R., Law, T. T., & Ahmad Thirmezir, M. Z. (2013). Mechanical, Thermal and Water Absorption Properties of Kenaf-Fiber-Based Polypropylene and Poly(Butylene Succinate) Composites. *Journal of Polymers and the Environment*, 21(1), 293–302.
<https://doi.org/10.1007/s10924-012-0516-4>
- Lee, K. Y., Tammelin, T., Schulfte, K., Kiiskinen, H., Samela, J., & Bismarck, A. (2012). High performance cellulose nanocomposites: Comparing the reinforcing ability of bacterial cellulose and nanofibrillated cellulose. *ACS Applied Materials and Interfaces*, 4(8), 4078–4086.
<https://doi.org/10.1021/am300852a>
- Lee, S. O., Rhee, K. Y., & Park, S. J. (2015). Influence of chemical surface treatment of basalt fibers on interlaminar shear strength and fracture toughness of epoxy-based composites. *Journal of Industrial and Engineering Chemistry*, 32, 153–156. <https://doi.org/10.1016/j.jiec.2015.08.009>
- Lee, S. Y., Chun, S. J., Kang, I. A., & Park, J. Y. (2009). Preparation of cellulose nanofibrils by high-pressure homogenizer and cellulose-based composite films. *Journal of Industrial and Engineering Chemistry*, 15(1), 50–55.
<https://doi.org/10.1016/j.jiec.2008.07.008>
- Lee, H. V., Hamid, S. B. A., & Zain, S. K. (2014). Conversion of Lignocellulosic Biomass to Nanocellulose: Structure and Chemical Process. *The Scientific World Journal*, 2014, 631013. <https://doi.org/10.1155/2014/631013>

- Lefranc, E. (1869). The Ramie: Its Origin, Its Value, Its Advantages, Its Culture, Its Extracting Process. In *Imprimerie de la Renaissance louisianaise, Nouvelle Orléans (New Orleans), USA*.
- Lehrhofer, A. F., Goto, T., Kawada, T., Rosenau, T., & Hettegger, H. (2022). The in vitro synthesis of cellulose – A mini-review. *Carbohydrate Polymers*, 285(February), 119222. <https://doi.org/10.1016/j.carbpol.2022.119222>
- Leung, A. C. W., Hrapovic, S., Lam, E., Liu, Y., Male, K. B., Mahmoud, K. A., & Luong, J. H. T. (2011). Characteristics and properties of carboxylated cellulose nanocrystals prepared from a novel one-step procedure. *Small*, 7(3), 302–305. <https://doi.org/10.1002/sml.201001715>
- Li, B., Xu, W., Kronlund, D., Määttänen, A., Liu, J., Smått, J. H., Peltonen, J., Willför, S., Mu, X., & Xu, C. (2015). Cellulose nanocrystals prepared via formic acid hydrolysis followed by TEMPO-mediated oxidation. *Carbohydrate Polymers*, 133, 605–612. <https://doi.org/10.1016/j.carbpol.2015.07.033>
- Li, D., Henschen, J., & Ek, M. (2017). Esterification and hydrolysis of cellulose using oxalic acid dihydrate in a solvent-free reaction suitable for preparation of surface-functionalised cellulose nanocrystals with high yield. *Green Chemistry*, 19(23), 5564–5567. <https://doi.org/10.1039/c7gc02489d>
- Li, S., Li, C., Li, C., Yan, M., Wu, Y., Cao, J., & He, S. (2013). Fabrication of nano-crystalline cellulose with phosphoric acid and its full application in a modified polyurethane foam. *Polymer Degradation and Stability*, 98(9), 1940–1944. <https://doi.org/10.1016/j.polymdegradstab.2013.06.017>
- Li, W., Wang, R., & Liu, S. (2011). Nanocrystalline cellulose prepared from softwood kraft pulp via ultrasonic-assisted acid hydrolysis. *BioResources*, 6(4), 4271–4281. <https://doi.org/10.15376/biores.6.4.4271-4281>
- Li, W., Yue, J., & Liu, S. (2012). Preparation of nanocrystalline cellulose via ultrasound and its reinforcement capability for poly(vinyl alcohol) composites. *Ultrasonics Sonochemistry*, 19(3), 479–485. <https://doi.org/10.1016/j.ultsonch.2011.11.007>
- Li, X., Tabil, L. G., & Panigrahi, S. (2007). Chemical Treatments of Natural Fiber for Use in Natural Fiber-Reinforced Composites: A Review. *Journal of Polymers and the Environment*, 15(1), 25–33. <https://doi.org/10.1007/s10924-006-0042-3>
- Liu, C., Li, B., Du, H., Lv, D., Zhang, Y., Yu, G., Mu, X., & Peng, H. (2016). Properties of nanocellulose isolated from corncob residue using sulfuric acid, formic acid, oxidative and mechanical methods. *Carbohydrate Polymers*, 151, 716–724. <https://doi.org/10.1016/j.carbpol.2016.06.025>
- Liu, Q., Lu, Y., Aguedo, M., Jacquet, N., Ouyang, C., He, W., Yan, C., Bai, W., Guo, R., Goffin, D., Song, J., & Richel, A. (2017). Isolation of High-Purity

- Cellulose Nanofibers from Wheat Straw through the Combined Environmentally Friendly Methods of Steam Explosion, Microwave-Assisted Hydrolysis, and Microfluidization. *ACS Sustainable Chemistry & Engineering*, 5(7), 6183–6191.
<https://doi.org/10.1021/acssuschemeng.7b01108>
- Liu, W., Mohanty, A. K., Drzal, L. T., Askel, P., & Misra, M. (2004). Effects of alkali treatment on the structure, morphology and thermal properties of native grass fibers as reinforcements for polymer matrix composites. *Journal of Materials Science*, 39(3), 1051–1054.
<https://doi.org/10.1023/B:JMISC.0000012942.83614.75>
- Liu, Y., Ma, Y., Yu, J., Zhuang, J., Wu, S., & Tong, J. (2019). Development and characterization of alkali treated abaca fiber reinforced friction composites. *Composite Interfaces*, 26(1), 67–82.
<https://doi.org/10.1080/09276440.2018.1472456>
- Lotfi, A., Li, H., Dao, D. V., & Prusty, G. (2021). Natural fiber–reinforced composites: A review on material, manufacturing, and machinability. *Journal of Thermoplastic Composite Materials*, 34(2), 238–284.
<https://doi.org/10.1177/0892705719844546>
- Lu, Q., Agriculture, F., Lin, F., & Wang, S. (2016). *Extraction of Cellulose Nanocrystals with a High Yield of 88% by Simultaneous Mechanochemical Activation and Phosphotungstic Acid Hydrolysis*. March.
<https://doi.org/10.1021/acssuschemeng.5b01620>
- Lu, Z., Fan, L., Zheng, H., Lu, Q., Liao, Y., & Huang, B. (2013). Preparation, characterization and optimization of nanocellulose whiskers by simultaneously ultrasonic wave and microwave assisted. *Bioresource Technology*, 146, 82–88. <https://doi.org/10.1016/j.biortech.2013.07.047>
- Ma, P. C., Siddiqui, N. A., Marom, G., & Kim, J. K. (2010). Dispersion and functionalization of carbon nanotubes for polymer-based nanocomposites: A review. *Composites Part A: Applied Science and Manufacturing*, 41(10), 1345–1367. <https://doi.org/10.1016/j.compositesa.2010.07.003>
- Maache, M., Bezazi, A., Amroune, S., Scarpa, F., & Dufresne, A. (2017). Characterization of a novel natural cellulosic fiber from *Juncus effusus* L. *Carbohydrate Polymers*, 171, 163–172.
<https://doi.org/https://doi.org/10.1016/j.carbpol.2017.04.096>
- Magagula, S. I., Sefadi, J. S., Mochane, M. J., Mokhothu, T. H., Mokhena, T. C., & Lenetha, G. G. (2022). 2 - The effect of alkaline treatment on natural fibers/biopolymer composites. In A. Shahzad, F. Tanasa, & C.-A. Teaca (Eds.), *Surface Treatment Methods of Natural Fibres and their Effects on Biocomposites* (pp. 19–45). Woodhead Publishing.
<https://doi.org/https://doi.org/10.1016/B978-0-12-821863-1.00002-8>
- Maiti, S., Jayaramudu, J., Das, K., Reddy, S. M., Sadiku, R., Ray, S. S., & Liu, D.

- (2013). Preparation and characterization of nano-cellulose with new shape from different precursor. *Carbohydrate Polymers*, 98(1), 562–567. <https://doi.org/https://doi.org/10.1016/j.carbpol.2013.06.029>
- Malainine, M. E., Dufresne, A., Dupeyre, D., Mahrouz, M., Vuong, R., & Vignon, M. R. (2003). Structure and morphology of cladodes and spines of *Opuntia ficus-indica*. Cellulose extraction and characterisation. *Carbohydrate Polymers*, 51(1), 77–83. [https://doi.org/https://doi.org/10.1016/S0144-8617\(02\)00157-1](https://doi.org/https://doi.org/10.1016/S0144-8617(02)00157-1)
- Manalo, A. C., Wani, E., Zukarnain, N. A., Karunasena, W., & Lau, K. T. (2015). Effects of alkali treatment and elevated temperature on the mechanical properties of bamboo fibre-polyester composites. *Composites Part B: Engineering*, 80, 73–83. <https://doi.org/10.1016/j.compositesb.2015.05.033>
- Manimaran, P., Sentharamaikkannan, P., Sanjay, M. R., Marichelvam, M. K., & Jawaid, M. (2018). Study on characterization of *Furcraea foetida* new natural fiber as composite reinforcement for lightweight applications. *Carbohydrate Polymers*, 181(July 2017), 650–658. <https://doi.org/10.1016/j.carbpol.2017.11.099>
- Maniraj, J., Venkat Raman, R., Felix Sahayaraj, A., Tamil Selvan, M., Jayant, G., Sathish, T., & Mohammed Rafi, S. (2024). Enhancing performance of *Prosopis juliflora* fiber reinforced epoxy composites with silane treatment and *Syzygium cumini* filler. *Journal of Materials Research and Technology*, 31(June), 93–108. <https://doi.org/10.1016/j.jmrt.2024.06.058>
- Maradini, G. da S., Oliveira, M. P., Guanaes, G. M. da S., Passamani, G. Z., Carreira, L. G., Boschetti, W. T. N., Monteiro, S. N., Pereira, A. C., & de Oliveira, B. F. (2020). Characterization of polyester nanocomposites reinforced with conifer fiber cellulose nanocrystals. *Polymers*, 12(12), 1–19. <https://doi.org/10.3390/polym12122838>
- Marsyahyo, E., Jamasri, Rochardjo, H. S. B., & Soekrisno. (2009). Preliminary Investigation on Bulletproof Panels Made from Ramie Fiber Reinforced Composites for NIJ Level II, IIA, and IV. *Journal of Industrial Textiles*, 39(1), 13–26. <https://doi.org/10.1177/1528083708098913>
- Marwan, M., Indarti, E., Bairwan, R. D., Khalil, H. P. S. A., Abdullah, C. K., & Ahmad, A. (2024). Enhancement micro filler spent coffee grounds in catalyst - chemically modified bast fibers reinforced biodegradable materials. *Bioresource Technology Reports*, 25(October 2023), 101723. <https://doi.org/10.1016/j.biteb.2023.101723>
- Marwanto, M., Maulana, M. I., Febrianto, F., Wistara, N. J., Nikmatin, S., Masruchin, N., Zaini, L. H., Lee, S. H., & Kim, N. H. (2021). Effect of oxidation time on the properties of cellulose nanocrystals prepared from balsa and kapok fibers using ammonium persulfate. *Polymers*, 13(11). <https://doi.org/10.3390/polym13111894>

- Mascheroni, E., Rampazzo, R., Ortenzi, M. A., Piva, G., Bonetti, S., & Piergiovanni, L. (2016). Comparison of cellulose nanocrystals obtained by sulfuric acid hydrolysis and ammonium persulfate, to be used as coating on flexible food-packaging materials. *Cellulose*, 23(1), 779–793. <https://doi.org/10.1007/s10570-015-0853-2>
- Mawardi, I., Jufriadi, J., & Hanif, H. (2018). Effect of fiber fibrillation on impact and flexural strength of coir fiber reinforced epoxy hybrid composites. *IOP Conference Series: Materials Science and Engineering*, 334(1). <https://doi.org/10.1088/1757-899X/334/1/012079>
- Melo, E. C. R. de, Camillo, M. de O., Marcelino, P. R. C., Barbosa dos Santos da Silva, R., Colares Firmino, T., Ferreira de Oliveira, B., Profeti, D., Campos Pereira, A., Neves Monteiro, S., & Picanço Oliveira, M. (2022). Influence of Silanization Treatment of Sponge Gourd (*Luffa cylindrica*) Fibers on the Reinforcement of Polyester Composites: A Brief Report. *Polymers*, 14(16). <https://doi.org/10.3390/polym14163311>
- Mitra, B. C., Basak, R. K., & Sarkar, M. (1998). Studies on jute-reinforced composites, its limitations, and some solutions through chemical modifications of fibers. *Journal of Applied Polymer Science*, 67(6), 1093–1100. [https://doi.org/10.1002/\(SICI\)1097-4628\(19980207\)67:6<1093::AID-APP17>3.0.CO;2-1](https://doi.org/10.1002/(SICI)1097-4628(19980207)67:6<1093::AID-APP17>3.0.CO;2-1)
- Mohan Gift, M. D., Raghuram, K. S., Suryanarayana Raju, J. N. S., Ravi, D., Venkata Rao, M., Subbiah, R., & Chandrakasu, M. (2022). Study on influence of nano-filler content on the performance of natural fibre reinforced epoxy composites. *Materials Today: Proceedings*, xxx, 1–5. <https://doi.org/10.1016/j.matpr.2022.01.304>
- Mohan Kumar, K., Naik, V., Waddar, S. S., Santhosh, N., Kaup, V., & Harish, H. V. (2023). Mechanical and Water Absorption Characterization of Mango Seed Shell/Epoxy Composite for Low Load Carrying Structures. *International Journal of Polymer Science*, 2023. <https://doi.org/10.1155/2023/9976409>
- Mohanty, A. K., Misra, M., & Hinrichsen, G. (2000). Biofibres, biodegradable polymers and biocomposites: An overview. *Macromolecular Materials and Engineering*, 276–277(1), 1–24. [https://doi.org/https://doi.org/10.1002/\(SICI\)1439-2054\(20000301\)276:1<1::AID-MAME1>3.0.CO;2-W](https://doi.org/https://doi.org/10.1002/(SICI)1439-2054(20000301)276:1<1::AID-MAME1>3.0.CO;2-W)
- Moon, R. J., Martini, A., Nairn, J., Simonsen, J., & Youngblood, J. (2011). Cellulose nanomaterials review: structure, properties and nanocomposites. *Chem. Soc. Rev.*, 40(7), 3941–3994. <https://doi.org/10.1039/C0CS00108B>
- Moshi, A. A. M., Ravindran, D., Bharathi, S. R. S., Indran, S., Saravanakumar, S. S., & Liu, Y. (2020). Characterization of a new cellulosic natural fiber extracted from the root of *Ficus religiosa* tree. *International Journal of*

- Biological Macromolecules*, 142, 212–221.
<https://doi.org/10.1016/j.ijbiomac.2019.09.094>
- Mouritz, A. P. B. T.-I. to A. M. (Ed.). (2012). *15 - Fibre-polymer composites for aerospace structures and engines* (pp. 338–393). Woodhead Publishing.
<https://doi.org/https://doi.org/10.1533/9780857095152.338>
- Mubarak, Y. A., & Abdulsamad, R. T. (2019). Effects of microcrystalline cellulose on the mechanical properties of low-density polyethylene composites. *Journal of Thermoplastic Composite Materials*, 32(3), 297–311.
<https://doi.org/10.1177/0892705717753056>
- Mulinari, D. R., Baptista, C. A. R. P., Souza, J. V. C., & Voorwald, H. J. C. (2011). Mechanical properties of coconut fibers reinforced polyester composites. *Procedia Engineering*, 10, 2074–2079.
<https://doi.org/10.1016/j.proeng.2011.04.343>
- Muller, J., & Beer, F. (1962). Process for the production of caro's acid salts and solutions thereof. *United States Patent Ofilice*.
<https://doi.org/10.1145/178951.178972>
- Muralidaran, V. M., Natrayan, L., Kaliappan, S., & Patil, P. P. (2023). Grape stalk cellulose toughened plain weaved bamboo fiber-reinforced epoxy composite: load bearing and time-dependent behavior. *Biomass Conversion and Biorefinery*, 14(13), 14317–14324. <https://doi.org/10.1007/s13399-022-03702-8>
- Mwaikambo, L. Y., & Ansell, M. P. (2002). Chemical modification of hemp, sisal, jute, and kapok fibers by alkalization. *Journal of Applied Polymer Science*, 84(12), 2222–2234. <https://doi.org/10.1002/app.10460>
- Mwaikambo, L. Y., Tucker, N., & Clark, A. J. (2007). Mechanical Properties of Hemp-Fibre-Reinforced Euphorbia Composites. *Macromolecular Materials and Engineering*, 292(9), 993–1000.
<https://doi.org/https://doi.org/10.1002/mame.200700092>
- Nagarajan, B., Arshad, M., Ullah, A., Mertiny, P., & Qureshi, A. J. (2019). Additive manufacturing ferromagnetic polymers using stereolithography – Materials and process development. *Manufacturing Letters*, 21, 12–16.
<https://doi.org/10.1016/j.mfglet.2019.06.003>
- Nair, S. S., Zhu, J. Y., Deng, Y., & Ragauskas, A. J. (2014). Characterization of cellulose nanofibrillation by micro grinding. *Journal of Nanoparticle Research*, 16(4), 2349. <https://doi.org/10.1007/s11051-014-2349-7>
- Narayanan, L., & Muthukumar, S. (2024). Development of silane-treated corn husk fiber and agro-waste biofiller-reinforced epoxy composite: effects on wear, mechanical, thermal, and water absorption properties. *Biomass Conversion and Biorefinery*, 0123456789. <https://doi.org/10.1007/s13399-024-05837-2>

- Nechyporchuk, O., Belgacem, M. N., & Bras, J. (2016). Production of cellulose nanofibrils: A review of recent advances. *Industrial Crops and Products*, 93, 2–25. <https://doi.org/https://doi.org/10.1016/j.indcrop.2016.02.016>
- Neenu, K. V., Midhun Dominic, C. D., Begum, P. M. S., Parameswaranpillai, J., Kanoth, B. P., David, D. A., Sajadi, S. M., Dhanyasree, P., Ajithkumar, T. G., & Badawi, M. (2022). Effect of oxalic acid and sulphuric acid hydrolysis on the preparation and properties of pineapple pomace derived cellulose nanofibers and nanopapers. *International Journal of Biological Macromolecules*, 209(PB), 1745–1759. <https://doi.org/10.1016/j.ijbiomac.2022.04.138>
- Niu, F., Li, M., Huang, Q., Zhang, X., Pan, W., Yang, J., & Li, J. (2017). The characteristic and dispersion stability of nanocellulose produced by mixed acid hydrolysis and ultrasonic assistance. *Carbohydrate Polymers*, 165, 197–204. <https://doi.org/https://doi.org/10.1016/j.carbpol.2017.02.048>
- Nobile, M. R. (2011). 15 - Rheology of polymer–carbon nanotube composites melts. In T. McNally & P. B. T.-P. N. C. Pötschke (Eds.), *Woodhead Publishing Series in Composites Science and Engineering* (pp. 428–481). Woodhead Publishing. <https://doi.org/https://doi.org/10.1533/9780857091390.2.428>
- Nogi, M., Iwamoto, S., Nakagaito, A. N., & Yano, H. (2009). Optically Transparent Nanofiber Paper. *Advanced Materials*, 21(16), 1595–1598. <https://doi.org/https://doi.org/10.1002/adma.200803174>
- Nur Aimi, M. N., Anuar, H., Maizirwan, M., Sapuan, S. M., Wahit, M. U., & Zakaria, S. (2015). Preparation of durian skin nanofibre (DSNF) and its effect on the properties of polylactic acid (PLA) biocomposites. *Sains Malaysiana*, 44(11), 1551–1559.
- Nurazzi, N. M., Asyraf, M. R. M., Fatimah Athiyah, S., Shazleen, S. S., Rafiqah, S. A., Harussani, M. M., Kamarudin, S. H., Razman, M. R., Rahmah, M., Zainudin, E. S., Ilyas, R. A., Aisyah, H. A., Norrrahim, M. N. F., Abdullah, N., Sapuan, S. M., & Khalina, A. (2021). A review on mechanical performance of hybrid natural fiber polymer composites for structural applications. *Polymers*, 13(13). <https://doi.org/10.3390/polym13132170>
- Nurazzi, N. M., Khalina, A., Sapuan, S. M., Ilyas, R. A., Rafiqah, S. A., & Hanafee, Z. M. (2020). Thermal properties of treated sugar palm yarn/glass fiber reinforced unsaturated polyester hybrid composites. *Journal of Materials Research and Technology*, 9(2), 1606–1618. <https://doi.org/10.1016/j.jmrt.2019.11.086>
- Oudiani, A. El, Chaabouni, Y., Msahli, S., & Sakli, F. (2011). Crystal transition from cellulose I to cellulose II in NaOH treated Agave americana L. fibre. *Carbohydrate Polymers*, 86(3), 1221–1229. <https://doi.org/10.1016/j.carbpol.2011.06.037>

- Oun, A. A., & Rhim, J. W. (2015). Effect of post-treatments and concentration of cotton linter cellulose nanocrystals on the properties of agar-based nanocomposite films. *Carbohydrate Polymers*, *134*, 20–29. <https://doi.org/10.1016/j.carbpol.2015.07.053>
- Oun, A. A., & Rhim, J. W. (2017). Characterization of carboxymethyl cellulose-based nanocomposite films reinforced with oxidized nanocellulose isolated using ammonium persulfate method. *Carbohydrate Polymers*, *174*, 484–492. <https://doi.org/10.1016/j.carbpol.2017.06.121>
- Padhi, S., & Behera, A. (2022). Chapter 17 - Biosynthesis of Silver Nanoparticles: Synthesis, mechanism, and characterization. In K. A. Abd-Elsalam, R. Periakaruppan, & S. B. T.-A.-W. and M. for P. of S. N. Rajeshkumar (Eds.), *Nanobiotechnology for Plant Protection* (pp. 397–440). Elsevier. <https://doi.org/https://doi.org/10.1016/B978-0-12-823575-1.00008-1>
- Pahr, D. H., Rammerstorfer, F. G., Rosenkranz, P., Humer, K., & Weber, H. W. (2002). A study of short-beam-shear and double-lap-shear specimens of glass fabric/epoxy composites. *Composites Part B:Engineering*, *33*(2), 125–132. [https://doi.org/10.1016/S1359-8368\(01\)00063-4](https://doi.org/10.1016/S1359-8368(01)00063-4)
- Parveen, S., Pichandi, S., Goswami, P., & Rana, S. (2020). Novel glass fibre reinforced hierarchical composites with improved interfacial, mechanical and dynamic mechanical properties developed using cellulose microcrystals. *Materials and Design*, *188*, 108448. <https://doi.org/10.1016/j.matdes.2019.108448>
- Pasquini, D., Belgacem, M. N., Gandini, A., & Curvelo, A. A. D. S. (2006). Surface esterification of cellulose fibers: Characterization by DRIFT and contact angle measurements. *Journal of Colloid and Interface Science*, *295*(1), 79–83. <https://doi.org/10.1016/j.jcis.2005.07.074>
- Pasquini, D., Teixeira, E. de M., Curvelo, A. A. da S., Belgacem, M. N., & Dufresne, A. (2008). Surface esterification of cellulose fibres: Processing and characterisation of low-density polyethylene/cellulose fibres composites. *Composites Science and Technology*, *68*(1), 193–201. <https://doi.org/10.1016/j.compscitech.2007.05.009>
- Patterson, A. L. (1939). The Scherrer Formula for X-Ray Particle Size Determination. *Phys. Rev.*, *56*(10), 978–982. <https://doi.org/10.1103/PhysRev.56.978>
- Penttilä, P. A., Várnai, A., Pere, J., Tammelin, T., Salmén, L., Siika-aho, M., Viikari, L., & Serimaa, R. (2013). Xylan as limiting factor in enzymatic hydrolysis of nanocellulose. *Bioresource Technology*, *129*, 135–141. <https://doi.org/10.1016/j.biortech.2012.11.017>
- Pichandi, S., Rana, S., Parveen, S., & Figueiro, R. (2018). A green approach of improving interface and performance of plant fibre composites using microcrystalline cellulose. *Carbohydrate Polymers*, *197*(May), 137–146.

<https://doi.org/10.1016/j.carbpol.2018.05.074>

Pitchayya Pillai, G., Manimaran, P., & Vignesh, V. (2021). Physico-chemical and Mechanical Properties of Alkali-Treated Red Banana Peduncle Fiber.

Journal of Natural Fibers, 18(12), 2102–2111.

<https://doi.org/10.1080/15440478.2020.1723777>

Plermjai, K., Boonyarattanakalin, K., Mekprasart, W., Pavasupree, S., Phoothkong, W., & Pecharapa, W. (2018). Extraction and characterization of nanocellulose from sugarcane bagasse by ball-milling-assisted acid hydrolysis. *AIP Conference Proceedings*, 2010(September).

<https://doi.org/10.1063/1.5053181>

Pratiwi, H., Kusmono, & Wildan, M. W. (2024). Influences of sodium hydroxide and oxalic acid treatments on physical, mechanical, thermal properties, and morphology of ramie fibers. *Journal of Materials Research and Technology*, 30(May), 8648–8660. <https://doi.org/10.1016/j.jmrt.2024.05.233>

Prithiviraj, M., & Muralikannan, R. (2022). Investigation of Optimal Alkali-treated Perotis indica Plant Fibers on Physical, Chemical, and Morphological Properties. *Journal of Natural Fibers*, 19(7), 2730–2743.

<https://doi.org/10.1080/15440478.2020.1821291>

Purkait, B. S., Ray, D., Sengupta, S., Kar, T., Mohanty, A., & Misra, M. (2011). Isolation of cellulose nanoparticles from sesame husk. *Industrial and Engineering Chemistry Research*, 50(2), 871–876.

<https://doi.org/10.1021/ie101797d>

Rajakumar, I. P. T., Raguraman, D., Isaac, J. S., Suthan, R., Bhattacharya, S., Seikh, A. H., Khan, S. M. A., & Raghavan, I. K. (2022). Mechanical Properties of Polymer Composites Reinforced with Alkaline-Treated Natural Fibre. *Advances in Polymer Technology*, 2022.

<https://doi.org/10.1155/2022/1458547>

Rajesh, G., Ratna Prasad, A. V., & Gupta, A. (2015). Mechanical and degradation properties of successive alkali treated completely biodegradable sisal fiber reinforced poly lactic acid composites. *Journal of Reinforced Plastics and Composites*, 34(12), 951–961. <https://doi.org/10.1177/0731684415584784>

Rajisha, K. R., Deepa, B., Pothan, L. A., & Thomas, S. (2011). 9 - Thermomechanical and spectroscopic characterization of natural fibre composites. In N. E. B. T.-I. E. of N. F. C. for M. P. Zafeiropoulos (Ed.), *Woodhead Publishing Series in Composites Science and Engineering* (pp. 241–274). Woodhead Publishing.

<https://doi.org/https://doi.org/10.1533/9780857092281.2.241>

Raju, A., & Shanmugaraja, M. (2019). Recent researches in fiber reinforced composite materials: A review. *Materials Today: Proceedings*, 46(XXXX), 9291–9296. <https://doi.org/10.1016/j.matpr.2020.02.141>

- Raju, J. S. N., Depoures, M. V., & Kumaran, P. (2021). Comprehensive characterization of raw and alkali (NaOH) treated natural fibers from *Symphirema involucratum* stem. *International Journal of Biological Macromolecules*, 186(July), 886–896.
<https://doi.org/10.1016/j.ijbiomac.2021.07.061>
- Ramakrishnan, S., Krishnamurthy, K., Rajasekar, R., & Rajeshkumar, G. (2019). An experimental study on the effect of nano-clay addition on mechanical and water absorption behaviour of jute fibre reinforced epoxy composites. *Journal of Industrial Textiles*, 49(5), 597–620.
<https://doi.org/10.1177/1528083718792915>
- Ramamoorthy, S. K., Bakare, F., Herrmann, R., & Skrifvars, M. (2015). Performance of biocomposites from surface modified regenerated cellulose fibers and lactic acid thermoset bioresin. *Cellulose*, 22(4), 2507–2528.
<https://doi.org/10.1007/s10570-015-0643-x>
- Ramesh, M., Deepa, C., Arpitha, G. R., & Gopinath, V. (2019). Effect of hybridization on properties of hemp-carbon fibre-reinforced hybrid polymer composites using experimental and finite element analysis. *World Journal of Engineering*, 16(2), 248–259. <https://doi.org/10.1108/WJE-04-2018-0125>
- Rashid, B., Leman, Z., Jawaid, M., Ghazali, M. J., & Ishak, M. R. (2016). Physicochemical and thermal properties of lignocellulosic fiber from sugar palm fibers: effect of treatment. *Cellulose*, 23(5), 2905–2916.
<https://doi.org/10.1007/s10570-016-1005-z>
- Reddy, K. O., Reddy, K. R. N., Zhang, J., Zhang, J., & Varada Rajulu, A. (2013). Effect of Alkali Treatment on the Properties of Century Fiber. *Journal of Natural Fibers*, 10(3), 282–296.
<https://doi.org/10.1080/15440478.2013.800812>
- Reddy, R. V. S., Mohana Krishnudu, D., Rajendra Prasad, P., & Reddy, P. V. (2020). Alkali Treatment Influence on Characterization of *Setaria Italic* (Foxtail Millet) Fiber Reinforced Polymer Composites Using Vacuum Bagging. *Journal of Natural Fibers*, 19(5), 1–13.
<https://doi.org/10.1080/15440478.2020.1788494>
- Reshmy, R., Philip, E., Paul, S. A., Madhavan, A., Sindhu, R., Binod, P., Pandey, A., & Sirohi, R. (2020). Nanocellulose-based products for sustainable applications-recent trends and possibilities. *Reviews in Environmental Science and Biotechnology*, 19(4), 779–806. <https://doi.org/10.1007/s11157-020-09551-z>
- Ridzuan, M. J. M., Abdul Majid, M. S., Afendi, M., Aqmariah Kanafiah, S. N., Zahri, J. M., & Gibson, A. G. (2016). Characterisation of natural cellulosic fibre from *Pennisetum purpureum* stem as potential reinforcement of polymer composites. *Materials and Design*, 89, 839–847.
<https://doi.org/10.1016/j.matdes.2015.10.052>

- Robinson, B. B. (1940). Ramie fiber production. *United States Department of Agriculture*, 585, 1–15. <http://hdl.handle.net/10113/33573>
- Rochardjo, H., Fatkhurrohman, & Kusumaatmaja, Ahmad Yudhanto, F. (2021). Fabrication of Nanofiltration Membrane based on Polyvinyl Alcohol Nanofibers Reinforced with Cellulose Nanocrystal using Electrospinning Techniques. *International Journal of Technology*, 12(2), 329–338. <https://doi.org/https://doi.org/10.14716/ijtech.v12i2.4173>
- Rod, K. A., Nguyen, M.-T., Elbakhshwan, M., Gills, S., Kutchko, B., Varga, T., Mckinney, A. M., Roosendaal, T. J., Childers, M. I., Zhao, C., Chen-Wiegart, Y. K., Thieme, J., Koech, P. K., Um, W., Chun, J., Rousseau, R., Glezakou, V.-A., & Fernandez, C. A. (2019). Insights into the physical and chemical properties of a cement-polymer composite developed for geothermal wellbore applications. *Cement and Concrete Composites*, 97, 279–287. <https://doi.org/https://doi.org/10.1016/j.cemconcomp.2018.12.022>
- Romanov, V., Lomov, S. V., Verpoest, I., & Gorbatiikh, L. (2015). Inter-fiber stresses in composites with carbon nanotube grafted and coated fibers. *Composites Science and Technology*, 114, 79–86. <https://doi.org/https://doi.org/10.1016/j.compscitech.2015.04.013>
- Roy, A., Chakraborty, S., Kundu, S. P., Basak, R. K., Basu Majumder, S., & Adhikari, B. (2012). Improvement in mechanical properties of jute fibres through mild alkali treatment as demonstrated by utilisation of the Weibull distribution model. *Bioresource Technology*, 107, 222–228. <https://doi.org/10.1016/j.biortech.2011.11.073>
- Saba, N., Paridah, M. T., Abdan, K., & Ibrahim, N. A. (2016a). Effect of oil palm nano filler on mechanical and morphological properties of kenaf reinforced epoxy composites. *Construction and Building Materials*, 123, 15–26. <https://doi.org/10.1016/j.conbuildmat.2016.06.131>
- Saba, N., Paridah, M. T., Abdan, K., & Ibrahim, N. A. (2016b). Thermal properties of oil palm nano filler/kenaf reinforced epoxy hybrid nanocomposites. *AIP Conference Proceedings*, 1787. <https://doi.org/10.1063/1.4968118>
- Sacui, I. A., Nieuwendaal, R. C., Burnett, D. J., Stranick, S. J., Jorfi, M., Weder, C., Foster, E. J., Olsson, R. T., & Gilman, J. W. (2014). Comparison of the Properties of Cellulose Nanocrystals and Cellulose Nanofibrils Isolated from Bacteria, Tunicate, and Wood Processed Using Acid, Enzymatic, Mechanical, and Oxidative Methods. *ACS Applied Materials & Interfaces*, 6(9), 6127–6138. <https://doi.org/10.1021/am500359f>
- Sadeghifar, H., Filpponen, I., Clarke, S., Brougham, D., & Argyropoulos, D. (2011). Production of cellulose nanocrystals using hydrobromic acid and click reactions on their surface. *Journal of Materials Science*, 46, 7344–7355. <https://doi.org/10.1007/s10853-011-5696-0>

- Saelee, K., Yingkamhaeng, N., Nimchua, T., & Sukyai, P. (2016). An environmentally friendly xylanase-assisted pretreatment for cellulose nanofibrils isolation from sugarcane bagasse by high-pressure homogenization. *Industrial Crops and Products*, 82, 149–160. <https://doi.org/https://doi.org/10.1016/j.indcrop.2015.11.064>
- Safaei, M., Pourbandari, D., Karimi, M. R., Baghani, M., Abrinia, K., Wang, K., & Baniassadi, M. (2024). Developing a multiscale approach for damage analysis of functionalized-GNP/PET nanocomposite. *Journal of Materials Science*, 59(7), 2907–2923. <https://doi.org/10.1007/s10853-024-09364-3>
- Sahayaraj, A. F., Muthukrishnan, M., & Ramesh, M. (2022). Influence of Tamarindus indica seed nano-powder on properties of Luffa cylindrica (L.) fruit waste fiber reinforced polymer composites. *Polymer Composites*, 43(9), 6442–6452. <https://doi.org/10.1002/pc.26957>
- Salinas, O. A., Benítez Benítez, R., & Martin Franco, J. (2022). Chemical Modification of Figue Fiber by Alkalization and Esterification Utilizing Figue Fiber Dust as Residue of the Fiquera Industry. *Journal of Natural Fibers*, 19(9), 3186–3194. <https://doi.org/10.1080/15440478.2020.1841061>
- Sampath Kumar, T. S. (2013). *Chapter 2 - Physical and Chemical Characterization of Biomaterials* (A. Bandyopadhyay & S. B. T.-C. of B. Bose (Eds.); pp. 11–47). Academic Press. <https://doi.org/https://doi.org/10.1016/B978-0-12-415800-9.00002-4>
- Sánchez, M. L., Morales, L. Y., & Caicedo, J. D. (2017). Physical and mechanical properties of agglomerated panels made from bamboo fiber and vegetable resin. *Construction and Building Materials*, 156, 330–339. <https://doi.org/10.1016/j.conbuildmat.2017.09.003>
- Saravanakumar, S. S., Kumaravel, A., Nagarajan, T., & Moorthy, I. G. (2014). Investigation of Physico-Chemical Properties of Alkali-Treated Prosopis juliflora Fibers. *International Journal of Polymer Analysis and Characterization*, 19(4), 309–317. <https://doi.org/10.1080/1023666X.2014.902527>
- Sarker, F., Potluri, P., Afroj, S., Koncherry, V., Novoselov, K. S., & Karim, N. (2019). Ultrahigh Performance of Nanoengineered Graphene-Based Natural Jute Fiber Composites. *ACS Applied Materials and Interfaces*, 11(23), 21166–21176. <https://doi.org/10.1021/acsami.9b04696>
- Sathishkumar, T. P., Navaneethakrishnan, P., Shivaram, S. V., Kanna, S. S., Rajeshkumar, L., & Rajeshkumar, G. (2023). Characterization of New Cellulose Fiber Extracted from Pithecellobium dulce Tree. *Applied Science and Engineering Progress*, 16(3), 1–11. <https://doi.org/10.14416/j.asep.2023.05.002>
- Sathishkumar, T. P., Shah, M. A., Panchal, H., Sharma, K., Gopinath, R., Sanjay, M. R., Siengchin, S., Rajesh Kumar, L., & Rampradheep, G. S. (2024).

- Characterization of new cellulose fiber extracted from second generation Bitter Albizia tree. *Scientific Reports*, 14(1), 1–12.
<https://doi.org/10.1038/s41598-024-51719-y>
- Saw, S. K., Akhtar, K., Yadav, N., & Singh, A. K. (2014a). Hybrid Composites Made from Jute/Coir Fibers: Water Absorption, Thickness Swelling, Density, Morphology, and Mechanical Properties. *Journal of Natural Fibers*, 11(1), 39–53. <https://doi.org/10.1080/15440478.2013.825067>
- Saw, S. K., Akhtar, K., Yadav, N., & Singh, A. K. (2014b). Hybrid Composites Made from Jute/Coir Fibers: Water Absorption, Thickness Swelling, Density, Morphology, and Mechanical Properties. *Journal of Natural Fibers*, 11(1), 39–53. <https://doi.org/10.1080/15440478.2013.825067>
- Segal, L., Creely, J. J., Martin, A. E., & Conrad, C. M. (1959). An Empirical Method for Estimating the Degree of Crystallinity of Native Cellulose Using the X-Ray Diffractometer. *Textile Research Journal*, 29(10), 786–794.
<https://doi.org/10.1177/004051755902901003>
- Seki, Y., Kılınç, A. Ç., Dalmis, R., Atagür, M., Köktaş, S., Göktaş, A. A., Çelik, E., Seydibeyoğlu, M. Ö., & Öney, A. B. (2018). Surface modification of new cellulose fiber extracted from Conium maculatum plant: a comparative study. *Cellulose*, 25(6), 3267–3280. <https://doi.org/10.1007/s10570-018-1797-0>
- Sen, T., & Reddy, H. N. J. (2011). Various Industrial Applications of Hemp , Kinaf , Flax and Ramie Natural Fibres. *International Journal of Innovation, Management and Technology*, 2(3), 192 – 198.
- Senthamaraikannan, P., & Kathiresan, M. (2018). Characterization of raw and alkali treated new natural cellulosic fiber from Coccinia grandis.L. *Carbohydrate Polymers*, 186(January), 332–343.
<https://doi.org/10.1016/j.carbpol.2018.01.072>
- Shahril, S. M., Ridzuan, M. J. M., Majid, M. S. A., Bariah, A. M. N., Rahman, M. T. A., & Narayanasamy, P. (2022). Alkali treatment influence on cellulosic fiber from Furcraea foetida leaves as potential reinforcement of polymeric composites. *Journal of Materials Research and Technology*, 19, 2567–2583.
<https://doi.org/10.1016/j.jmrt.2022.06.002>
- Shanmugasundaram, N., Rajendran, I., & Ramkumar, T. (2018). Characterization of untreated and alkali treated new cellulosic fiber from an Areca palm leaf stalk as potential reinforcement in polymer composites. *Carbohydrate Polymers*, 195(April), 566–575.
<https://doi.org/10.1016/j.carbpol.2018.04.127>
- Sharma, C., & Bhardwaj, N. K. (2019). Bacterial nanocellulose: Present status, biomedical applications and future perspectives. *Materials Science and Engineering C*, 104(July), 109963.
<https://doi.org/10.1016/j.msec.2019.109963>

- Sharma, P., Joshi, R., & Hsiao, B. (2017). A Simple Approach to Prepare Carboxycellulose Nanofibers from Untreated Biomass. *Biomacromolecules*, *18*. <https://doi.org/10.1021/acs.biomac.7b00544>
- Shen, F., Xiao, W., Lin, L., Yang, G., Zhang, Y., & Deng, S. (2013). Enzymatic saccharification coupling with polyester recovery from cotton-based waste textiles by phosphoric acid pretreatment. *Bioresource Technology*, *130*, 248–255. <https://doi.org/10.1016/j.biortech.2012.12.025>
- Shen, X. J., Dang, C. Y., Tang, B. L., Yang, X. H., Nie, H. J., Lu, J. J., Zhang, T. T., & Friedrich, K. (2020). The reinforcing effect of oriented graphene on the interlaminar shear strength of carbon fabric/epoxy composites. *Materials and Design*, *185*, 108257. <https://doi.org/10.1016/j.matdes.2019.108257>
- Siakeng, R., Jawaid, M., Asim, M., Saba, N., Sanjay, M. R., Siengchin, S., & Fouad, H. (2020). Alkali treated coir/pineapple leaf fibres reinforced pla hybrid composites: Evaluation of mechanical, morphological, thermal and physical properties. *Express Polymer Letters*, *14*(8), 717–730. <https://doi.org/10.3144/expresspolymlett.2020.59>
- Simonassi, N. T., Pereira, A. C., Monteiro, S. N., Margem, F. M., Rodríguez, R. J. S., De Deus, J. F., Vieira, C. M. F., & Drelich, J. (2017). Reinforcement of polyester with renewable ramie fibers. *Materials Research*, *20*, 51–59. <https://doi.org/10.1590/1980-5373-mr-2016-1046>
- Sionkowska, A., Mężykowska, O., & Piątek, J. (2019). Bacterial nanocellulose in biomedical applications: a review. *Polymer International*, *68*(11), 1841–1847. <https://doi.org/https://doi.org/10.1002/pi.5882>
- Siró, I., & Plackett, D. (2010). Microfibrillated cellulose and new nanocomposite materials: A review. *Cellulose*, *17*(3), 459–494. <https://doi.org/10.1007/s10570-010-9405-y>
- Sisti, L., Totaro, G., Vannini, M., Fabbri, P., Kalia, S., Zatta, A., & Celli, A. (2016). Evaluation of the retting process as a pre-treatment of vegetable fibers for the preparation of high-performance polymer biocomposites. *Industrial Crops and Products*, *81*, 56–65. <https://doi.org/https://doi.org/10.1016/j.indcrop.2015.11.045>
- Sokołowska, K., Konieczna-Molenda, A., & Witek, E. (2016). Hydroliza odpadów celulozowych katalizowana enzymami celulolitycznymi immobilizowanymi na nośniku polimerowym. *Polimery*, *61*(9), 633–641.
- Springer, E., & Minor, J. (1991). *Delignification of lignocellulosic materials with monoperoxysulfuric acid*.
- Sreenivasan, V. S., Ravindran, D., Manikandan, V., & Narayanasamy, R. (2012). Influence of fibre treatments on mechanical properties of short *Sansevieria cylindrica*/polyester composites. *Materials and Design*, *37*, 111–121. <https://doi.org/10.1016/j.matdes.2012.01.004>

- Srinivasan, D. V., & Vassilopoulos, A. P. (2023). Fatigue performance of wind turbine rotor blade epoxy adhesives. *Polymer Testing*, *121*, 107975. <https://doi.org/https://doi.org/10.1016/j.polymertesting.2023.107975>
- Sullins, T., Pillay, S., Komus, A., & Ning, H. (2017). Hemp fiber reinforced polypropylene composites: The effects of material treatments. *Composites Part B*, *114*, 15–22. <https://doi.org/10.1016/j.compositesb.2017.02.001>
- Sumita, M., Sakata, K., Asai, S., Miyasaka, K., & Nakagawa, H. (1991). Dispersion of fillers and the electrical conductivity of polymer blends filled with carbon black. *Polymer Bulletin*, *25*(2), 265–271. <https://doi.org/10.1007/BF00310802>
- Suwan, T., Maichin, P., Fan, M., Jitsangiam, P., Tangchirapat, W., & Chindaprasirt, P. (2022). Influence of alkalinity on self-treatment process of natural fiber and properties of its geopolymeric composites. *Construction and Building Materials*, *316*(December 2021), 125817. <https://doi.org/10.1016/j.conbuildmat.2021.125817>
- Swain, P. T. R., & Biswas, S. (2018). A comparative analysis of physico-mechanical, water absorption, and morphological behaviour of surface modified woven jute fiber composites. *Polymer Composites*, *39*(8), 2952–2960. <https://doi.org/https://doi.org/10.1002/pc.24294>
- Syukran Alhelmy Seri Buana, M., Pasbakhsh, P., Goh, K. L., Bateni, F., & Haris, M. R. H. M. (2013). Elasticity, microstructure and thermal stability of foliage and fruit fibres from four tropical crops. *Fibers and Polymers*, *14*(4), 623–629. <https://doi.org/10.1007/s12221-013-0623-4>
- Tang, Y., Shen, X., Zhang, J., Guo, D., Kong, F., & Zhang, N. (2015). Extraction of cellulose nano-crystals from old corrugated container fiber using phosphoric acid and enzymatic hydrolysis followed by sonication. *Carbohydrate Polymers*, *125*, 360–366. <https://doi.org/10.1016/j.carbpol.2015.02.063>
- Tang, Z., Chen, D., Wang, X., Han, Z., Tao, R., Zhang, G., Hou, D., Wu, D., & Ding, Q. (2023). Impact of polyethylene fiber on the ductility and durability of magnesium phosphate cement. *Journal of Building Engineering*, *68*, 106123. <https://doi.org/10.1016/j.jobbe.2023.106123>
- Tarchoun, A. F., Trache, D., & Klapötke, T. M. (2019). Microcrystalline cellulose from *Posidonia oceanica* brown algae: Extraction and characterization. *International Journal of Biological Macromolecules*, *138*, 837–845. <https://doi.org/https://doi.org/10.1016/j.ijbiomac.2019.07.176>
- Tawakkal, I. S. M. A., Cran, M. J., & Bigger, S. W. (2018). The influence of chemically treated natural fibers in poly(lactic acid) composites containing thymol. *Polymer Composites*, *39*(4), 1261–1272. <https://doi.org/https://doi.org/10.1002/pc.24062>

- Thakur, V. K., Thakur, M. K., Raghavan, P., & Kessler, M. R. (2014). Progress in Green Polymer Composites from Lignin for Multifunctional Applications: A Review. *ACS Sustainable Chemistry & Engineering*, 2(5), 1072–1092. <https://doi.org/10.1021/sc500087z>
- Thapa, S., Mishra, J., Arora, N., Mishra, P., Li, H., O'Hair, J., Bhatti, S., & Zhou, S. (2020). Microbial cellulolytic enzymes: diversity and biotechnology with reference to lignocellulosic biomass degradation. *Reviews in Environmental Science and Bio/Technology*, 19(3), 621–648. <https://doi.org/10.1007/s11157-020-09536-y>
- Thirmizir, M. Z. A., Ishak, Z. A. M., Taib, R. M., Sudin, R., & Leong, Y. W. (2011). Mechanical, Water Absorption and Dimensional Stability Studies of Kenaf Bast Fibre-Filled Poly(butylene succinate) Composites. *Polymer-Plastics Technology and Engineering*, 50(4), 339–348. <https://doi.org/10.1080/03602559.2010.531871>
- Tian, C., Yi, J., Wu, Y., Wu, Q., Qing, Y., & Wang, L. (2016). Preparation of highly charged cellulose nanofibrils using high-pressure homogenization coupled with strong acid hydrolysis pretreatments. *Carbohydrate Polymers*, 136, 485–492. <https://doi.org/https://doi.org/10.1016/j.carbpol.2015.09.055>
- Torquato, S. (2002). Microstructure and Macroscopic Properties. In *Random Heterogeneous Materials* (Interdisci). Springer New York, NY.
- Trache, D., Hussin, M. H., Haafiz, M. K. M., & Thakur, V. K. (2017). Recent progress in cellulose nanocrystals: sources and production. *Nanoscale*, 9(5), 1763–1786. <https://doi.org/10.1039/C6NR09494E>
- Um, B. H., Karim, M. N., & Henk, L. L. (2003). Effect of sulfuric and phosphoric acid pretreatments on enzymatic hydrolysis of corn stover. *Applied Biochemistry and Biotechnology - Part A Enzyme Engineering and Biotechnology*, 105(1–3), 115–125. <https://doi.org/10.1385/ABAB:105:1-3:115>
- Uribe, B. E. B., Chiromito, E. M. S., Carvalho, A. J. F., Arenal, R., & Tarpani, J. R. (2017). TEMPO-oxidized cellulose nanofibers as interfacial strengthener in continuous-fiber reinforced polymer composites. *Materials and Design*, 133, 340–348. <https://doi.org/10.1016/j.matdes.2017.08.004>
- van de Werken, N., Tekinalp, H., Khanbolouki, P., Ozcan, S., Williams, A., & Tehrani, M. (2020). Additively manufactured carbon fiber-reinforced composites: State of the art and perspective. *Additive Manufacturing*, 31, 100962. <https://doi.org/https://doi.org/10.1016/j.addma.2019.100962>
- Velmurugan, G., Chohan, J. S., Muhammed Abraar, S. A., Sathish, R., Senthil Murugan, S., Nagaraj, M., Suresh Kumar, S., Siva Shankar, V., & Elil Raja, D. (2023). Investigation of Nano SiO₂ Filler Loading on Mechanical and Flammability Properties of Jute-Based Hybrid Polypropylene Composites. *Silicon*, 15(17), 7247–7263. <https://doi.org/10.1007/s12633-023-02578-1>

- Venkateshwaran, N., & Elayaperumal, A. (2010). Banana Fiber Reinforced Polymer Composites - A Review. *Journal of Reinforced Plastics and Composites*, 29(15), 2387–2396. <https://doi.org/10.1177/0731684409360578>
- Ventura-Cruz, S., & Tecante, A. (2021). Nanocellulose and microcrystalline cellulose from agricultural waste: Review on isolation and application as reinforcement in polymeric matrices. *Food Hydrocolloids*, 118(March), 106771. <https://doi.org/10.1016/j.foodhyd.2021.106771>
- Vijay, R., Lenin Singaravelu, D., Vinod, A., Sanjay, M. R., Siengchin, S., Jawaid, M., Khan, A., & Parameswaranpillai, J. (2019). Characterization of raw and alkali treated new natural cellulosic fibers from *Tridax procumbens*. *International Journal of Biological Macromolecules*, 125, 99–108. <https://doi.org/10.1016/j.ijbiomac.2018.12.056>
- Vijay, R., Vinod, A., Lenin Singaravelu, D., Sanjay, M. R., & Siengchin, S. (2021). Characterization of chemical treated and untreated natural fibers from *Pennisetum orientale* grass- A potential reinforcement for lightweight polymeric applications. *International Journal of Lightweight Materials and Manufacture*, 4(1), 43–49. <https://doi.org/10.1016/j.ijlmm.2020.06.008>
- Vinod, A., Sanjay, M. R., Siengchin, S., & Fischer, S. (2021). Fully bio-based agro-waste soy stem fiber reinforced bio-epoxy composites for lightweight structural applications: Influence of surface modification techniques. *Construction and Building Materials*, 303(January), 124509. <https://doi.org/10.1016/j.conbuildmat.2021.124509>
- Walker, J. C. F. (2006). Sawmilling. In *Primary Wood Processing: Principles and Practice* (Vol. 9781402043). https://doi.org/10.1007/1-4020-4393-7_7
- Wang, B., Panigrahi, S., Tabil, L., & Crerar, W. (2007). Pre-treatment of Flax Fibers for use in Rotationally Molded Biocomposites. *Journal of Reinforced Plastics and Composites*, 26(5), 447–463. <https://doi.org/10.1177/0731684406072526>
- Wang, B., & Sain, M. (2007). Dispersion of soybean stock-based nanofiber in a plastic matrix. *Polymer International*, 56(4), 538–546. <https://doi.org/https://doi.org/10.1002/pi.2167>
- Wang, C., Ren, Z., Li, S., & Yi, X. (2018). Effect of ramie fabric chemical treatments on the physical properties of thermoset polylactic acid (PLA) composites. *Aerospace*, 5(3). <https://doi.org/10.3390/aerospace5030093>
- Wang, H., Du, H., Liu, K., Liu, H., Xu, T., Zhang, S., Chen, X., Zhang, R., Li, H., Xie, H., Zhang, X., & Si, C. (2021). Sustainable preparation of bifunctional cellulose nanocrystals via mixed H₂SO₄/formic acid hydrolysis. *Carbohydrate Polymers*, 266(February), 118107. <https://doi.org/10.1016/j.carbpol.2021.118107>
- Wang, H., Xie, H., Du, H., Wang, X., Liu, W., Duan, Y., Zhang, X., Sun, L.,

- Zhang, X., & Si, C. (2020). Highly Efficient Preparation of Functional and Thermostable Cellulose Nanocrystals via H₂SO₄ Intensified Acetic Acid Hydrolysis. *Carbohydrate Polymers*, 239(March), 116233. <https://doi.org/10.1016/j.carbpol.2020.116233>
- Williams, T., Hosur, M., Theodore, M., Netravali, A., Rangari, V., & Jeelani, S. (2011). Time effects on morphology and bonding ability in mercerized natural fibers for composite reinforcement. *International Journal of Polymer Science*, 2011. <https://doi.org/10.1155/2011/192865>
- Wise, L. E., Murphy, M., & Adieco, A. A. D. (1946). *A chlorite holocellulose, its fractionation and bearing on summative wood analysis and studies on the hemicelluloses.*
- Wu, Z. Y., Liang, H. W., Chen, L. F., Hu, B. C., & Yu, S. H. (2016). Bacterial Cellulose: A Robust Platform for Design of Three Dimensional Carbon-Based Functional Nanomaterials. *Accounts of Chemical Research*, 49(1), 96–105. <https://doi.org/10.1021/acs.accounts.5b00380>
- Xia, L., Zhang, C., Wang, A., Wang, Y., & Xu, W. (2020). Morphologies and properties of *Juncus effusus* fiber after alkali treatment. *Cellulose*, 27(4), 1909–1920. <https://doi.org/10.1007/s10570-019-02933-9>
- Xie, H., Zou, Z., Du, H., Zhang, X., Wang, X., Yang, X., Wang, H., Li, G., Li, L., & Si, C. (2019). Preparation of thermally stable and surface-functionalized cellulose nanocrystals via mixed H₂SO₄/Oxalic acid hydrolysis. *Carbohydrate Polymers*, 223(May), 115116. <https://doi.org/10.1016/j.carbpol.2019.115116>
- Yan, C.-F., Yu, H.-Y., & Yao, J.-M. (2015). One-step extraction and functionalization of cellulose nanospheres from lyocell fibers with cellulose II crystal structure. *Cellulose*, 22(6), 3773–3788. <https://doi.org/10.1007/s10570-015-0761-5>
- Yan, L., Chouw, N., Huang, L., & Kasal, B. (2016). Effect of alkali treatment on microstructure and mechanical properties of coir fibres, coir fibre reinforced-polymer composites and reinforced-cementitious composites. *Construction and Building Materials*, 112, 168–182. <https://doi.org/10.1016/j.conbuildmat.2016.02.182>
- Yang, H., Yan, R., Chen, H., Zheng, C., Lee, D. H., & Liang, D. T. (2006). In-Depth Investigation of Biomass Pyrolysis Based on Three Major Components: Hemicellulose, Cellulose and Lignin. *Energy & Fuels*, 20(1), 388–393. <https://doi.org/10.1021/ef0580117>
- Yang, H., Zhang, Y., Kato, R., & Rowan, S. J. (2019). Preparation of cellulose nanofibers from *Miscanthus x. Giganteus* by ammonium persulfate oxidation. *Carbohydrate Polymers*, 212(February), 30–39. <https://doi.org/10.1016/j.carbpol.2019.02.008>

- Yu, H., Qin, Z., Liang, B., Liu, N., Zhou, Z., & Chen, L. (2013). Facile extraction of thermally stable cellulose nanocrystals with a high yield of 93% through hydrochloric acid hydrolysis under hydrothermal conditions. *Journal of Materials Chemistry A*, 1(12), 3938–3944.
<https://doi.org/10.1039/c3ta01150j>
- Yuan, Y., & Lee, T. R. (2013). *Contact Angle and Wetting Properties BT - Surface Science Techniques* (G. Bracco & B. Holst (Eds.); pp. 3–34). Springer Berlin Heidelberg. https://doi.org/10.1007/978-3-642-34243-1_1
- Yudhanto, F., Yudha, V., Jamasri, & Wisnujati, A. (2022). Effect of Alkali Soaking Time on Physical and Morphological Properties of Agave Cantala Fiber. *AIP Conference Proceedings*, 2499(November).
<https://doi.org/10.1063/5.0104998>
- Zaini, L. H., Febrianto, F., Wistara, I. N. J., Marwanto, N., Maulana, M. I., Lee, S. H., & Kim, N. H. (2019). Effect of ammonium persulfate concentration on characteristics of cellulose nanocrystals from oil palm frond. *Journal of the Korean Wood Science and Technology*, 47(5), 597–606.
<https://doi.org/10.5658/WOOD.2019.47.5.597>
- Zamboni Schiavon, J., & de Oliveira Andrade, J. J. (2023). Comparison between alternative chemical treatments on coir fibers for application in cementitious materials. *Journal of Materials Research and Technology*, 25, 4634–4649.
<https://doi.org/10.1016/j.jmrt.2023.06.210>
- Zhang, H., Chen, Y., Wang, S., Ma, L., Yu, Y., Dai, H., & Zhang, Y. (2020). Extraction and comparison of cellulose nanocrystals from lemon (*Citrus limon*) seeds using sulfuric acid hydrolysis and oxidation methods. *Carbohydrate Polymers*, 238(2), 116180.
<https://doi.org/10.1016/j.carbpol.2020.116180>
- Zhang, K., Sun, P., Liu, H., Shang, S., Song, J., & Wang, D. (2016). Extraction and comparison of carboxylated cellulose nanocrystals from bleached sugarcane bagasse pulp using two different oxidation methods. *Carbohydrate Polymers*, 138, 237–243. <https://doi.org/10.1016/j.carbpol.2015.11.038>
- Zhang, K., Wang, F., Liang, W., Wang, Z., Duan, Z., & Yang, B. (2018). Thermal and mechanical properties of bamboo fiber reinforced epoxy composites. *Polymers*, 8(6). <https://doi.org/10.3390/polym10060608>
- Zhao, F., Huang, Y., Liu, L., Bai, Y., & Xu, L. (2011). Formation of a carbon fiber/polyhedral oligomeric silsesquioxane/carbon nanotube hybrid reinforcement and its effect on the interfacial properties of carbon fiber/epoxy composites. *Carbon*, 49(8), 2624–2632.
<https://doi.org/https://doi.org/10.1016/j.carbon.2011.02.026>
- Zhao, J., Zhang, W., Zhang, X., Zhang, X., Lu, C., & Deng, Y. (2013). Extraction of cellulose nanofibrils from dry softwood pulp using high shear homogenization. *Carbohydrate Polymers*, 97(2), 695–702.

<https://doi.org/https://doi.org/10.1016/j.carbpol.2013.05.050>

- Zheng, J., Liu, Y., Wang, Q., Cheng, L., Zhang, C., Zhang, T., Shao, J., & Dai, F. (2024). Mechanical properties and thermal characteristics of three nano-filler/silk fiber reinforced hybrid composites: A comparative study using a ductile epoxy resin matrix. *Polymer Testing*, *130*(January), 108319. <https://doi.org/10.1016/j.polymeresting.2023.108319>
- Zhou, W., Kou, Y., Yuan, M., Li, B., Cai, H., Li, Z., Chen, F., Liu, X., Wang, G., Chen, Q., & Dang, Z. M. (2019). Polymer composites filled with core@double-shell structured fillers: Effects of multiple shells on dielectric and thermal properties. *Composites Science and Technology*, *181*(June). <https://doi.org/10.1016/j.compscitech.2019.107686>
- Zhou, Y., Saito, T., Bergström, L., & Isogai, A. (2018). Acid-Free Preparation of Cellulose Nanocrystals by TEMPO Oxidation and Subsequent Cavitation. *Biomacromolecules*, *19*(2), 633–639. <https://doi.org/https://doi.org/10.1021/acs.biomac.7b01730>
- Zuluaga, R., Putaux, J. L., Restrepo, A., Mondragon, I., & Gañán, P. (2007). Cellulose microfibrils from banana farming residues: Isolation and characterization. *Cellulose*, *14*(6), 585–592. <https://doi.org/10.1007/s10570-007-9118-z>
- Żygo, M., & Prochoń, M. (2017). Enzymatyczne metody otrzymywania nanowłóknien celulozowych. *Eliksir*, *1*(5), 26–29.