

## TABLE OF CONTENTS

<b>FOREWORD</b>	<b>i</b>
<b>TABLE OF CONTENTS</b>	<b>iii</b>
<b>LIST OF FIGURES</b>	<b>vi</b>
<b>LIST OF TABLES</b>	<b>viii</b>
<b>NOMENCLATURE</b>	<b>ix</b>
<b>ABSTRAK</b>	<b>xi</b>
<b>ABSTRACT</b>	<b>xii</b>
<b>CHAPTER I INTRODUCTION</b>	<b>1</b>
1.1. Background	1
1.2. Problem Formulation	3
1.3. Research Scope	3
1.4. Research Objectives	4
1.5. Benefit of Research	4
<b>CHAPTER II LITERATURE STUDY</b>	<b>5</b>
2.1. Polyethylene Glycol (PEG) as PCM	5
2.2. Encapsulation of Low Temperature PCM	6
2.3. Variation of PCM Positions	8
2.4. Research Gap	10
<b>CHAPTER III FUNDAMENTAL THEORY</b>	<b>15</b>
3.1. Food Preservation of Vegetables and Fruits	15
3.2. Cold Storage	16
3.1.1. Product Load	17
3.1.2. Respiration Load	18
3.1.3. Transmission Load	18
3.1.4. Infiltration Load	20
3.1.5. Internal Load	20
3.3. Thermodynamics of Thermal Energy Storage	20
3.4. Phase Change Material (PCM)	22
3.3.1. Requirement Properties	24
3.3.2. Properties Test	25

3.5. Thermocouple for Temperature Measurement	27
<b>CHAPTER IV RESEARCH METHODOLOGY</b>	<b>30</b>
4.1. Research Flowchart	30
4.2. Experimental Setup	31
4.2.1. Chest Freezer	32
4.2.2. Phase Change Material (PCM)	32
4.2.3. PCM Packs	32
4.2.4. Cold Storage Container	32
4.2.5. Magnetic Stirrer	32
4.3. Measurements	33
4.3.1. Laptop/PC	34
4.3.2. Data Acquisition	34
4.3.3. Thermocouples	35
4.3.4. Measurement Points	35
4.3.5. LabVIEW	36
4.4. Experimental Procedures	38
4.4.1. Thermal Expansion Test	38
4.4.2. Leakage Test	38
4.4.3. Temperature Validation	38
4.4.4. Determining Melting Point of Eutectic Mixtures	39
4.4.5. Variations of PCM Positions	39
4.4.6. Combination of PCM Mixtures	41
4.5. Data Analysis	42
4.5.1. Melting Point Eutectic PCM	42
4.5.2. Threshold Duration	42
4.5.3. Uniformity Temperature	43
4.5.4. Cooling Load	43
<b>CHAPTER V RESULTS AND DISCUSSION</b>	<b>44</b>
5.1. Melting point of Phase Change Material (PCM)	44
5.2. The Effect of PCM Configurations within Portable Cold Storage	45

5.3. Cold Storage Performance Using Eutectic PCM at Various Different Mixtures	53
5.4. The Impact of Eutectic PEG and Pure Water Combinations as PCM on Altered Performance	59
<b>CHAPTER VI CONCLUSION</b>	<b>66</b>
<b>REFERENCES</b>	<b>68</b>

## LIST OF FIGURES

<b>Fig. 1.1.</b>	Melting Temperature of PCMs against latent heat of fusion.	2
<b>Fig. 2.1.</b>	Experimental of PEG 1540 with different wt% in water utilizing DSC (a) heating curves (b) phase diagram.	6
<b>Fig. 2.2.</b>	Corrosion rate vs time in (a) salt solution (b) general PCM.	7
<b>Fig. 2.3.</b>	Discharging performance of different PCM layouts by (a) Burgess et al. (2022) (b) Du et al. (2020)	9
<b>Fig. 2.4.</b>	Temperature at various positions inside an insulated container from 6 h to 72 h by experimental data.	10
<b>Fig. 3.1.</b>	Typical contribution of each type of cooling load to the energy consumption of transportation refrigeration system.	17
<b>Fig. 3.3.</b>	Potential of latent heat thermal energy.	21
<b>Fig. 3.4.</b>	Classification of PCM.	22
<b>Fig. 3.5.</b>	Thermophysical properties test by T-history method.	25
<b>Fig. 3.6.</b>	Experimental Apparatus of PCM properties test at ZAE Bayern.	26
<b>Fig. 3.7.</b>	Schematic design of a disc-type hf-DSC and commercial hf-DSC	26
<b>Fig. 3.8.</b>	Operating range of thermocouples	28
<b>Fig. 3.9.</b>	Conventional method for thermocouple reference temperature	29
<b>Fig. 4.1.</b>	Research Flowchart	30
<b>Fig. 4.2.</b>	Experimental Setup (a) main equipments, (b) schematic diagram	31
<b>Fig. 4.3.</b>	Tools and equipment (a) Chest freezer (b) PCM (c) PEG 600 (d) PEG 6000 (e) Cold storage Container (f) Magnetic stirrer	33
<b>Fig. 4.4.</b>	Thermocouple Type-T	35
<b>Fig. 4.6.</b>	LABVIEW Program (a) dashboard interface (b) program	37
<b>Fig. 4.7.</b>	Configuration of PCMs and temperature measurements in (a) V1 (b) V2 (c) V3 (d) V4	40
<b>Fig. 4.8.</b>	Description of PCM combinations	41
<b>Fig. 5.1.</b>	Average storage temperature within portable cold storage over time in different water PCM configurations.	46

<b>Fig. 5.2.</b>	Disparity of temperature within cold storage at certain average storage temperature in different water PCM configurations	47
<b>Fig. 5.3.</b>	Total heat rate through the wall over duration in different water PCM configurations	48
<b>Fig. 5.4.</b>	Heat rate through the wall over cold storage temperature in different water PCM configurations from (a) bottom side, (b) top side	50
<b>Fig. 5.5.</b>	Heat rate through the wall over cold storage temperature in different water PCM configurations from (a) short side, (b) long side	51
<b>Fig. 5.6.</b>	Cooling load over cold storage temperature in different water PCM configurations	52
<b>Fig. 5.7.</b>	Average storage temperature over duration with V2 configurations using various mixture of (a) eutectic PEG600, (b) eutectic PEG6000	54
<b>Fig. 5.8.</b>	Threshold time from -2°C to 5°C at various PCM mixtures with V2 configurations	56
<b>Fig. 5.9.</b>	Cooling load over cold storage temperature with V2 configurations using various mixture of (a) eutectic PEG600, (b) eutectic PEG6000	57
<b>Fig. 5.10.</b>	Temperature uniformity at certain storage temperature with V2 configuration using various mixture of (a) eutectic PEG600, (b) eutectic PEG6000	58
<b>Fig. 5.11.</b>	Average storage temperature over time with V2 configurations using water PCM and (a) 30 wt% eutectic PEG600, (b) 40 wt% eutectic PEG6000	60
<b>Fig. 5.12.</b>	Cooling load over cold storage temperature with V2 configurations using water PCM and (a) 30 wt% eutectic PEG600, (b) 40 wt% eutectic PEG6000	62
<b>Fig. 5.13.</b>	Threshold time from -2°C to 5°C with V2 configuration at various combination of 30 wt% eutectic PEG600 or 40 wt% eutectic PEG6000 with water PCM	63
<b>Fig. 5.14.</b>	Temperature inhomogeneity in cold storage with V2 configuration under different combination of water PCM and (a) 30 wt% eutectic PEG600 (b) 40 wt% eutectic PEG6000	64

## LIST OF TABLES

<b>Table 2.1.</b> Thermophysical properties of several forms of PEG	5
<b>Table 2.2.</b> Overview of research on portable cold storage with PCM	12
<b>Table 3.1.</b> Fruits and vegetables with recommended storage temperature	15
<b>Table 3.2.</b> Calculation values of conductivity coefficient for EPS specimen	19
<b>Table 3.3.</b> Advantages and disadvantages of PCM	23
<b>Table 3.4.</b> Required properties of PCM	24
<b>Table 4.1.</b> Laptop Specifications	34
<b>Table 4.2.</b> Specifications of NI-9213	34
<b>Table 4.3.</b> PCM compositions	39
<b>Table 5.1.</b> Melting point of different mixtures	44