



TABLE OF CONTENTS

APPROVAL PAGE	i
STATEMENT OF ANTI-PLAGIARISM	ii
PREFACE	iii
TABLE OF CONTENTS	v
LIST OF FIGURES	vii
LIST OF TABLES	x
ABSTRACT	xi
INTISARI.....	xii
CHAPTER I INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	2
1.3 Problem Limitations.....	2
1.4 Purpose of Research.....	3
1.5 Benefit of Research	3
1.6 Research Methodology.....	3
1.7 Systematic of Writing	4
CHAPTER II LITERATURE REVIEW.....	6
CHAPTER III THEORETICAL FOUNDATION.....	9
3.1 Global Navigation Satellite System (GNSS)	9
3.1.1 GNSS Positioning	9
3.2 Real-Time Kinematic (RTK)	12
3.3 Dilution of Precision (DOP).....	16
CHAPTER IV RESEARCH METHODOLOGY	19
4.1 Tools and Materials.....	19
4.2 Research Stages.....	21
4.3 Analysis of System.....	22
4.4 Block Diagram Design.....	22
4.5 Hardware Design.....	23
4.6 Algorithm Design.....	39
4.7 System Testing Design.....	49



4.8	System Testing Scheme	51
CHAPTER V IMPLEMENTATION		54
5.1	Implementation of System	54
5.1.1	Hardware Implementation.....	54
5.1.2	Software Implementation	58
CHAPTER VI RESULT AND DISCUSSION		65
6.1	Results of Obtaining Data from Receiver Module.....	65
6.2	Results of Obtaining Correction Data from Base Station	67
6.3	Results of Positioning Accuracy	68
6.3.1	Static Positioning	69
6.3.2	Dynamic Positioning.....	81
6.3.3	Further Analysis of Positioning Accuracy	86
6.3.4	Performance Comparison of Static Positioning	91
6.3.5	Performance Comparison of Dynamic Positioning	93
CHAPTER VII CONCLUSION AND RECOMMENDATION		95
7.1	Conclusion	95
7.2	Recommendation.....	96
REFERENCES.....		97



LIST OF FIGURES

Figure 3.1 GNSS positioning on space and ground segment (Petrovski, 2014).....	9
Figure 3.2 GNSS positioning (Petrovski, 2014)	10
Figure 3.3 GNSS receiver functional diagram (Petrovski, 2014)	12
Figure 3.4 Geometric representation of RTK (Kaleev <i>et al.</i> , 2021)	14
Figure 3.5 Position and measurement error on satellite geometry (DOP) (Hofmann-Wellenhof <i>et al.</i> , 2008).....	16
Figure 3.6 Satellite visibility and DOP in Graz, Austria with 400 m elevation and mask angle of 10° (Hofmann-Wellenhof <i>et al.</i> , 2008).....	18
Figure 4.1 General working principle of RTK technique	22
Figure 4.2 Block diagram of RTK GNSS receiver module	23
Figure 4.3 Hardware design	24
Figure 4.4 ESP32-WROOM-32 schematics	25
Figure 4.5 ZED-F9P schematics	26
Figure 4.6 Power regulator schematics	27
Figure 4.7 USB to UART converter schematics.....	29
Figure 4.8 Active antenna circuit on the receiver module schematics.....	30
Figure 4.9 Active antenna	31
Figure 4.10 Push button circuit schematics.....	32
Figure 4.11 Micro USB ports and clamping diode array schematics	33
Figure 4.12 LED status with external power pin schematics.....	35
Figure 4.13 PCB design of the receiver module	37
Figure 4.14 Wiring block diagram of base station.....	39
Figure 4.15 Software design	41
Figure 4.16 Flowchart for NMEA data processing algorithm	43
Figure 4.17 Flowchart for sending RTCM correction data to ZED-F9P	45
Figure 4.18 RTK2go NTRIP caster status at 12 June 2025	47
Figure 4.19 Ardusimple WiFi NTRIP Master ESP32 XBee firmware.....	47
Figure 4.20 Block diagram of the process of sending correction data.....	48



Figure 4.21 Flowchart for RTK GNSS module (left) and RTK base station (right)	53
Figure 5.1 RTK GNSS receiver module with active antenna	56
Figure 5.2 RTK GNSS receiver module without active antenna	56
Figure 5.3 Base station with active antenna	57
Figure 5.4 Program for declaring the objects and libraries	58
Figure 5.5 Program for initializing and configuring the system	59
Figure 5.6 Program of the main loop	61
Figure 5.7 Program to pass NMEA messages to parser	61
Figure 5.8 Program to declare the libraries and network credentials	62
Figure 5.9 Program to connect to network and NTRIP caster	64
Figure 5.10 Program to connect to network and NTRIP caster	64
Figure 6.1 Static positioning without RTK	69
Figure 6.2 Line graph for error of positioning without RTK	71
Figure 6.3 Scatter plot of no RTK fix with reference point	72
Figure 6.4 Static positioning with RTK	73
Figure 6.5 Scatter plot of RTK fix with reference point	74
Figure 6.6 Static positioning no RTK with new reference point	75
Figure 6.7 Line graph for error of positioning without RTK in new reference point	77
Figure 6.8 Scatter plot without RTK to new reference point	77
Figure 6.9 Static positioning with RTK to new reference point	78
Figure 6.10 Line graph for error of positioning with RTK in new reference point	79
Figure 6.11 Scatter plot with RTK to new reference point	80
Figure 6.12 Dynamic positioning coordinates with RTK	81
Figure 6.13 Dynamic positioning path with RTK	82
Figure 6.14 Dynamic positioning coordinates without RTK	84
Figure 6.15 Dynamic positioning path without RTK	85
Figure 6.16 Static positioning results	87



Figure 6.17 Line graph for error of positioning with RTK in fixed reference point	89
Figure 6.18 Scatter plot for data comparison with fixed reference point.....	90
Figure 6.19 Scatter plot for data comparison with previous reference points	91
Figure 6.20 Line graph for error of positioning with both methods	92
Figure 6.21 Dynamic path comparison	94



LIST OF TABLES

Table 2.1 Research Correlation.....	8
Table 4.1 List of Components.....	19
Table 4.2 List of Tools.....	20
Table 4.3 Research Stages.....	21
Table 4.4 NMEA sentences and the descriptions (Shoab <i>et al.</i> , 2013).....	40
Table 4.5 System Testing Design.....	49
Table 6.1 u-center example text console output.....	65
Table 6.2 u-center UBX-NAV-PVT output.....	66
Table 6.3 Example Arduino IDE serial monitor output with RTK.....	68
Table 6.4 Static without RTK positioning error.....	70
Table 6.5 Static with RTK positioning error.....	73
Table 6.6 Static positioning error with new reference point.....	76
Table 6.7 Static positioning error with new reference point.....	79
Table 6.8 Output of coordinates for dynamic positioning with RTK.....	83
Table 6.9 Output of coordinates for dynamic positioning without RTK.....	85
Table 6.10 Static positioning error with fixed reference point.....	88
Table 6.11 Root mean square error of the static positioning.....	93
Table 6.12 Error between start and end points.....	94