

DAFTAR PUSTAKA

- Akinyede O., Ram M., Ajit K., Jagannathan S., 2007, *“Static and Dynamic Loading Behavior of Hybrid Epoxy Composite With Alumina Nanoparticles”*, International Conference on Composite Materials, Kyoto, Japan.
- Alcoa Inc, 2011, *“Aluminum Oxide (alumina, calcinated alumina)”*.
- Astruc, A., Joliff, E., Chailan, J.F., Aragon, E., Petter, C.O., Sampaio, C.H., 2009, *“Incorporation of Kaolin Fillers into an Epoxy/Polyamidoamine Matrix for Coating”*, Progress in Organic Coatings 65 158-168, Elsevier B.V.
- Barsoum, M.W., 1997, *“Fundamentals of Ceramics”*, McGraw-Hill.
- Chow, W.S, and Yap, Y.P, 2008, *Optimization of process variables on Flexural Properties of Epoxy/Organo-Montmorillonite Nanocomposites by Response Surface Methodology*, Express Polymer Letter Vol.2, No.1.
- Cook, MC., Boesl, Burris DL., and Sawyer WG., 2006, *“Epoxy, ZnO, and PTFE Nanocomposite: Friction and Wear Optimization”*, Tribology Letters, Vol. 22, No. 3.
- Harrison, K., 2007, *“Epoxy Resin”*, (Molecule of the Month for March).
- Kornmann, X., Lindberg H., Berglund LA., 2001, *“Synthesis of Epoxy-Clay Nanocomposites, Influence of the Nature of the Curing Agent on Structure”*, Polymer, 42:4493–9.
- Marur PR., Batra, Garcia G., Loos AC., 2004, *“Static and Dynamic Fracture Toughness of Epoxy/Alumina Composite with Submicron Inclusions”*, Journal of Materials Science 39, 1437 – 1440.
- Padmanabhan and Kishore, 1990, *“Role of Alumina in Flexure of Glass/Epoxy Composites”*, Bull. Mater. Sci., Vol. 13, No. 4, pp. 245-253.
- Philipp, M., Gervais, Sanctuary R., Müller, Baller J., Wetzels, Krüger JK., 2008, *“Effect of Mixing Sequence on the Curing of Amine-Hardened*



- Epoxy/Alumina Nanocomposites as Assessed by Optical Refractometry*”, Express Polymer Letters Vol.2, No.8, 546–552.
- Shi H, Liu F, Han E, Wei Y., 2007, “*Effects of Nano Pigments on the Corrosion Resistance of Alkyd Coatings*”, J Mater Sci Technol, 23(4):551–8.
- Shukla, A., 2005, “*Practical Fracture Mechanics in Design*”, Second Edition, Revised and Expanded, Marcel Dekker.
- Wise, C.W., Cook W.D., Goodwin A.A., 2000, “*CT□N Rubber Phase Separation in Model Epoxy Resins*”, Polymer 41, pp. 4625 – 4633.
- Xia L., Riester BW., Sheldon, Curtin, Liang, Yin and Xu JM., 2004, “*Mechanical Properties of Highly Ordered Nanoporous Anodic Alumina Membranes*”, Rev Adv.Mater.Sci., 6, 131-139.
- Zhanhu, G., Tony, P., Oyoung, C., Ying W., and Thomas H., 2006, “*Surface Functionalized Alumina Nanoparticle Filled Polymeric Nanocomposites with Enhanced Mechanical Properties*”, Journal of Materials Chemistry.
- Zhou, Q, Jung, H.C., Yuhong, H., Rui, Z., Wenwu, C., and Kirk, S., 2009, “*Alumina/Epoxy Nanocomposite Matching Layers for High□ Frequency Ultrasound Transducer Application, IEEE Trans Ultrason Ferroelectr Freq Control*”, 56(1): 213–219.