

DAFTAR PUSTAKA

- Abdar, M., Pourpanah, F., Hussain, S., Rezazadegan, D., Liu, L., Ghavamzadeh, M., Fieguth, P., Cao, X., Khosravi, A., Acharya, U. R., Makarenkov, V., & Nahavandi, S. (2021). A review of uncertainty quantification in deep learning: Techniques, applications and challenges. *Information Fusion*, 76, 243–297. <https://doi.org/10.1016/j.inffus.2021.05.008>
- Abeykoon, C., Sri-Amphorn, P., & Fernando, A. (2020a). Optimization of fused deposition modeling parameters for improved PLA and ABS 3D printed structures. *International Journal of Lightweight Materials and Manufacture*, 3(3), 284–297. <https://doi.org/10.1016/j.ijlmm.2020.03.003>
- Abeykoon, C., Sri-Amphorn, P., & Fernando, A. (2020b). Optimization of fused deposition modeling parameters for improved PLA and ABS 3D printed structures. *International Journal of Lightweight Materials and Manufacture*, 3(3), 284–297. <https://doi.org/10.1016/j.ijlmm.2020.03.003>
- Abiodun, O. I., Jantan, A., Omolara, A. E., Dada, K. V., Mohamed, N. A., & Arshad, H. (2018). State-of-the-art in artificial neural network applications: A survey. *Heliyon*, 4(11), e00938. <https://doi.org/10.1016/j.heliyon.2018.e00938>
- Ahmad, N. N., Wong, Y. H., & Ghazali, N. N. N. (2022). A systematic review of fused deposition modeling process parameters. *Soft Science*, 2(3), 11. <https://doi.org/10.20517/ss.2022.08>
- Ahn, S., Montero, M., Odell, D., Roundy, S., & Wright, P. K. (2002). Anisotropic material properties of fused deposition modeling ABS. *Rapid Prototyping Journal*, 8(4), 248–257. <https://doi.org/10.1108/13552540210441166>
- Aihemaiti, P., Jiang, H., Aiyiti, W., & Kasimu, A. (2021a). Optimization of 3D Printing Parameters of Biodegradable Polylactic Acid/Hydroxyapatite Composite Bone Plates. *International Journal of Bioprinting*, 8(1), 490. <https://doi.org/10.18063/ijb.v8i1.490>
- Aihemaiti, P., Jiang, H., Aiyiti, W., & Kasimu, A. (2021b). Optimization of 3D Printing Parameters of Biodegradable Polylactic Acid/Hydroxyapatite

- Composite Bone Plates. *International Journal of Bioprinting*, 8(1), 490.
<https://doi.org/10.18063/ijb.v8i1.490>
- Alafaghani, A., Qattawi, A., Alrawi, B., & Guzman, A. (2017). Experimental Optimization of Fused Deposition Modelling Processing Parameters: A Design-for-Manufacturing Approach. *Procedia Manufacturing*, 10, 791–803.
<https://doi.org/10.1016/j.promfg.2017.07.079>
- Al-Ahmari, A., Mian, S. H., Advanced Manufacturing Institute, King Saud University, Riyadh 11421, Saudi Arabia, Ameen, W., & Industrial Engineering Department, College of Engineering and Architecture, Al Yamamah University, Riyadh 11512, Saudi Arabia. (2021). Performance assessment of fused deposition modeling process. *Journal of Engineering Research*, 9(1). <https://doi.org/10.36909/jer.v9i1.8725>
- Andriyansyah, D. (2018a). *OPTIMASI PARAMETER PROSES 3D PRINTING TERHADAP KUAT TARIK FILAMEN POLYLACTIC ACID MENGGUNAKAN METODE TAGUCHI*.
- Andriyansyah, D. (2018b). *OPTIMASI PARAMETER PROSES 3D PRINTING TERHADAP KUAT TARIK FILAMEN POLYLACTIC ACID MENGGUNAKAN METODE TAGUCHI*.
- Arivazhagan, A., & Masood, S. H. (2012). Dynamic Mechanical Properties of ABS Material Processed by Fused Deposition Modelling. *International Journal of Engineering Research And*, 2(3).
- Armiliotta, A., Bellotti, M., & Cavallaro, M. (2018). Warpage of FDM parts: Experimental tests and analytic model. *Robotics and Computer-Integrated Manufacturing*, 50, 140–152. <https://doi.org/10.1016/j.rcim.2017.09.007>
- Baca, D., & Ahmad, R. (2020a). The impact on the mechanical properties of multi-material polymers fabricated with a single mixing nozzle and multi-nozzle systems via fused deposition modeling. *The International Journal of Advanced Manufacturing Technology*, 106(9–10), 4509–4520.
<https://doi.org/10.1007/s00170-020-04937-3>
- Baca, D., & Ahmad, R. (2020b). The impact on the mechanical properties of multi-material polymers fabricated with a single mixing nozzle and multi-nozzle

- systems via fused deposition modeling. *International Journal of Advanced Manufacturing Technology*, 106(9–10), 4509–4520. Scopus. <https://doi.org/10.1007/s00170-020-04937-3>
- Baca Lopez, D. M., & Ahmad, R. (2020). Tensile Mechanical Behaviour of Multi-Polymer Sandwich Structures via Fused Deposition Modelling. *Polymers*, 12(3), 651. <https://doi.org/10.3390/polym12030651>
- Bernardez, L. D. (2022). Effects of infill patterns on part performances and energy consumption in acrylonitrile butadiene styrene fused filament fabrication via industrial-grade machine. *Progress in Additive Manufacturing*.
- Bilowo, G., & Hardjono, B. (2025). 3D print orientation optimization and comparative analysis of NSGA-II versus NSGA-II with Q-learning. *International Journal on Smart Sensing and Intelligent Systems*, 18(1). <https://doi.org/10.2478/ijssis-2025-0035>
- Birosz, M. T., Ledenyák, D., & Andó, M. (2022). Effect of FDM infill patterns on mechanical properties. *Polymer Testing*, 113, 107654. <https://doi.org/10.1016/j.polymertesting.2022.107654>
- Brejcha, V., Böhm, M., Holeček, T., Jerman, M., Kobetičová, K., Burianová, I., Černý, R., & Pavlík, Z. (2025). Comparison of Bending Properties of Sandwich Structures Using Conventional and 3D-Printed Core with Flax Fiber Reinforcement. *Journal of Composites Science*, 9(4), 182. <https://doi.org/10.3390/jcs9040182>
- Calabrese, L., Marabello, G., Chairi, M., & Di Bella, G. (2025). Optimization of Deposition Temperature and Gyroid Infill to Improve Flexural Performance of PLA and PLA–Flax Fiber Composite Sandwich Structures. *Journal of Manufacturing and Materials Processing*, 9(2), 31. <https://doi.org/10.3390/jmmp9020031>
- Camara, M. V. O., Ferrari, T., & Ribeiro, G. M. (2024). Modified NSGA-II for solving Bi-objective support unit location problem to assist roadside traffic survey with multi-stages. *Expert Systems with Applications*, 249, 123448. <https://doi.org/10.1016/j.eswa.2024.123448>

- Cantrell, J. T., Rohde, S., Damiani, D., Gurnani, R., DiSandro, L., Anton, J., Young, A., Jerez, A., Steinbach, D., Kroese, C., & Ifju, P. G. (2017). Experimental characterization of the mechanical properties of 3D-printed ABS and polycarbonate parts. *Rapid Prototyping Journal*, 23(4), 811–824. <https://doi.org/10.1108/RPJ-03-2016-0042>
- Cao, X., Yan, H., Huang, Z., Ai, S., Xu, Y., Fu, R., & Zou, X. (2021). A Multi-Objective Particle Swarm Optimization for Trajectory Planning of Fruit Picking Manipulator. *Agronomy*, 11(11), 2286. <https://doi.org/10.3390/agronomy11112286>
- Chai, T., & Draxler, R. R. (2014). Root mean square error (RMSE) or mean absolute error (MAE)? – Arguments against avoiding RMSE in the literature. *Geoscientific Model Development*, 7(3), 1247–1250. <https://doi.org/10.5194/gmd-7-1247-2014>
- Chicco, D., Warrens, M. J., & Jurman, G. (2021). The coefficient of determination R-squared is more informative than SMAPE, MAE, MAPE, MSE and RMSE in regression analysis evaluation. *PeerJ Computer Science*, 7, e623. <https://doi.org/10.7717/peerj-cs.623>
- Chin Ang, K., Fai Leong, K., Kai Chua, C., & Chandrasekaran, M. (2006). Investigation of the mechanical properties and porosity relationships in fused deposition modelling-fabricated porous structures. *Rapid Prototyping Journal*, 12(2), 100–105. <https://doi.org/10.1108/13552540610652447>
- Coello Coello, C. A., & Lechuga, M. S. (2002). MOPSO: A proposal for multiple objective particle swarm optimization. *Proceedings of the 2002 Congress on Evolutionary Computation. CEC'02 (Cat. No.02TH8600)*, 1051–1056 vol.2. <https://doi.org/10.1109/CEC.2002.1004388>
- Crapnell, R. D., Bernalte, E., Ferrari, A. G.-M., Whittingham, M. J., Williams, R. J., Hurst, N. J., & Banks, C. E. (2022). *All-in-One Single-Print Additively Manufactured Electroanalytical Sensing Platforms*.
- De Bernardez, L., Campana, G., Mele, M., Sanguineti, J., Sandre, C., & Mur, S. M. (2023). Effects of infill patterns on part performances and energy consumption in acrylonitrile butadiene styrene fused filament fabrication via

- industrial-grade machine. *Progress in Additive Manufacturing*, 8(2), 117–129. <https://doi.org/10.1007/s40964-022-00316-4>
- Deb, J., Ahsan, N., & Majumder, S. (2022). Modeling the Interplay Between Process Parameters and Part Attributes in Additive Manufacturing Process With Artificial Neural Network. *Volume 2A: Advanced Manufacturing*, V02AT02A015. <https://doi.org/10.1115/IMECE2022-95120>
- Deb, K. (2002). A Fast and Elitist Multiobjective Genetic Algorithm: *IEEE TRANSACTIONS ON EVOLUTIONARY COMPUTATION*, 6(2).
- Deng, X., Zeng, Z., Peng, B., Yan, S., & Ke, W. (2018). Mechanical Properties Optimization of Poly-Ether-Ether-Ketone via Fused Deposition Modeling. *Materials*, 11(2), 216. <https://doi.org/10.3390/ma11020216>
- Desai, K. M., Survase, S. A., Saudagar, P. S., Lele, S. S., & Singhal, R. S. (2008). Comparison of artificial neural network (ANN) and response surface methodology (RSM) in fermentation media optimization: Case study of fermentative production of scleroglucan. *Biochemical Engineering Journal*, 41(3), 266–273. <https://doi.org/10.1016/j.bej.2008.05.009>
- Deshwal, S., Kumar, A., & Chhabra, D. (2020). Exercising hybrid statistical tools GA-RSM, GA-ANN and GA-ANFIS to optimize FDM process parameters for tensile strength improvement. *CIRP Journal of Manufacturing Science and Technology*, 31, 189–199. <https://doi.org/10.1016/j.cirpj.2020.05.009>
- Dev, S., & Srivastava, R. (2020). Experimental investigation and optimization of FDM process parameters for material and mechanical strength. *Materials Today: Proceedings*, 26, 1995–1999. <https://doi.org/10.1016/j.matpr.2020.02.435>
- Dey, A., & Yodo, N. (2019). A Systematic Survey of FDM Process Parameter Optimization and Their Influence on Part Characteristics. *Journal of Manufacturing and Materials Processing*, 3(3), 64. <https://doi.org/10.3390/jmmp3030064>
- Ding, M., Li, X., Hassler, R., & Barnett, E. (2021). Understanding the properties of operations: A cross-cultural analysis. *International Journal of Mathematical*

- Education in Science and Technology*, 52(1), 39–64.
<https://doi.org/10.1080/0020739X.2019.1657595>
- Ding, S., Su, C., & Yu, J. (2011). An optimizing BP neural network algorithm based on genetic algorithm. *Artificial Intelligence Review*, 36(2), 153–162.
<https://doi.org/10.1007/s10462-011-9208-z>
- Dudek, P., & Zagórski, K. (2017). Cost, resources, and energy efficiency of additive manufacturing. *E3S Web of Conferences*, 14, 01040.
<https://doi.org/10.1051/e3sconf/20171401040>
- E. Tontowi, A., Anggraeni, D., Tssg Saragih, H., P.N. Raharjo, K., & Utami, P. (2017). Experimental study of 3D-printable biocomposite of [HA/PMMA/Sericin] materials. *Advanced Materials Letters*, 8(8), 857–861.
<https://doi.org/10.5185/amlett.2017.1640>
- El Youbi El Idrissi, M. A., Laaouina, L., Jeghal, A., Tairi, H., & Zaki, M. (2023). Modeling of Energy Consumption and Print Time for FDM 3D Printing Using Multilayer Perceptron Network. *Journal of Manufacturing and Materials Processing*, 7(4), 128. <https://doi.org/10.3390/jmmp7040128>
- Elhoone, H., Zhang, T., Anwar, M., & Desai, S. (2020). Cyber-based design for additive manufacturing using artificial neural networks for Industry 4.0. *International Journal of Production Research*, 58(9), 2841–2861.
<https://doi.org/10.1080/00207543.2019.1671627>
- Elkholy, A., & Kempers, R. (2018). Investigation into the Influence of Fused Deposition Modeling (FDM) Process Parameters on the Thermal Properties of 3D-Printed Parts. *Progress in Canadian Mechanical Engineering*. 2018 Canadian Society for Mechanical Engineering (CSME) International Congress. <https://doi.org/10.25071/10315/35337>
- Enemuoh, E. U., Duginski, S., Feyen, C., & Menta, V. G. (2021a). Effect of Process Parameters on Energy Consumption, Physical, and Mechanical Properties of Fused Deposition Modeling. *Polymers*, 13(15), 2406.
<https://doi.org/10.3390/polym13152406>
- Enemuoh, E. U., Duginski, S., Feyen, C., & Menta, V. G. (2021b). Effect of Process Parameters on Energy Consumption, Physical, and Mechanical Properties of

- Fused Deposition Modeling. *Polymers*, 13(15), 2406.
<https://doi.org/10.3390/polym13152406>
- Ercanlı, İ., Günlü, A., Şenyurt, M., & Keleş, S. (2018). Artificial neural network models predicting the leaf area index: A case study in pure even-aged Crimean pine forests from Turkey. *Forest Ecosystems*, 5(1), 29.
<https://doi.org/10.1186/s40663-018-0149-8>
- Espalin, D., Ramirez, J. A., Medina, F., & Wicker, R. (2014). Multi-material, multi-technology FDM: exploring build process variations. *Rapid Prototyping Journal*, 20(3).
- Fatimatuzahraa, A. W., Farahaina, B., & Yusoff, W. A. Y. (2011). The effect of employing different raster orientations on the mechanical properties and microstructure of Fused Deposition Modeling parts. *2011 IEEE Symposium on Business, Engineering and Industrial Applications (ISBEIA)*, 22–27.
<https://doi.org/10.1109/ISBEIA.2011.6088811>
- Feng, C., Zhang, M., & Bhandari, B. (2019). Materials Properties of Printable Edible Inks and Printing Parameters Optimization during 3D Printing: A review. *Critical Reviews in Food Science and Nutrition*, 59(19), 3074–3081.
<https://doi.org/10.1080/10408398.2018.1481823>
- Fernandes, J. F. M. (2018). *Study of the Influence of 3D Printing Parameters on the Mechanical Properties of PLA*.
- Filippis, L. A. C. D., Serio, L. M., Facchini, F., & Mummolo, G. (2018). ANN Modelling to Optimize Manufacturing Process. In A. El-Shahat (Ed.), *Advanced Applications for Artificial Neural Networks*. InTech.
<https://doi.org/10.5772/intechopen.71237>
- Fitas, R. (2024). *A new simplified MOPSO based on Swarm Elitism and Swarm Memory: MO-ETPSO (Version 1)*. arXiv.
<https://doi.org/10.48550/ARXIV.2402.12856>
- Fountas, N. A., Kechagias, J. D., Manolakos, D. E., & Vaxevanidis, N. M. (2020a). Single and multi-objective optimization of FDM-based additive manufacturing using metaheuristic algorithms. *Procedia Manufacturing*, 51, 740–747. <https://doi.org/10.1016/j.promfg.2020.10.104>

- Fountas, N. A., Kechagias, J. D., Manolakos, D. E., & Vaxevanidis, N. M. (2020b). Single and multi-objective optimization of FDM-based additive manufacturing using metaheuristic algorithms. *Procedia Manufacturing*, *51*, 740–747. <https://doi.org/10.1016/j.promfg.2020.10.104>
- Fountas, N. A., & Vaxevanidis, N. M. (2021). Optimization of fused deposition modeling process using a virus-evolutionary genetic algorithm. *Computers in Industry*, *125*, 103371. <https://doi.org/10.1016/j.compind.2020.103371>
- Gajjar, T., Yang, R., Ye, L., & Zhang, Y. X. (2025). Effects of key process parameters on tensile properties and interlayer bonding behavior of 3D printed PLA using fused filament fabrication. *Progress in Additive Manufacturing*, *10*(2), 1261–1280. <https://doi.org/10.1007/s40964-024-00704-y>
- Gao, J. (2024). R-Squared (R^2) – How much variation is explained? *Research Methods in Medicine & Health Sciences*, *5*(4), 104–109. <https://doi.org/10.1177/26320843231186398>
- Garg, N., & Kumar, P. (2017). *Multi-objective optimization of 3D printing parameters to fabricate TPU for tribological applications*.
- Giri, J., Shahane, P., Jachak, S., Chadge, R., & Giri, P. (2021a). Optimization of FDM process parameters for dual extruder 3d printer using Artificial Neural network. *Materials Today: Proceedings*, *43*, 3242–3249. <https://doi.org/10.1016/j.matpr.2021.01.899>
- Giri, J., Shahane, P., Jachak, S., Chadge, R., & Giri, P. (2021b). Optimization of FDM process parameters for dual extruder 3d printer using Artificial Neural network. *Materials Today: Proceedings*, *43*, 3242–3249. <https://doi.org/10.1016/j.matpr.2021.01.899>
- Głowacki, M., Skórczewska, K., Lewandowski, K., Szewczykowski, P., & Mazurkiewicz, A. (2023). Effect of Shock-Variable Environmental Temperature and Humidity Conditions on 3D-Printed Polymers for Tensile Properties. *Polymers*, *16*(1), 1. <https://doi.org/10.3390/polym16010001>
- Godec, D., Cano, S., Holzer, C., & Gonzalez-Gutierrez, J. (2020). Optimization of the 3D Printing Parameters for Tensile Properties of Specimens Produced by

- Fused Filament Fabrication of 17-4PH Stainless Steel. *Materials*, 13(3), 774.
<https://doi.org/10.3390/ma13030774>
- Gordelier, T. J., Thies, P. R., Turner, L., & Johannig, L. (2019). Optimising the FDM additive manufacturing process to achieve maximum tensile strength: A state-of-the-art review. *Rapid Prototyping Journal*, 25(6), 953–971.
<https://doi.org/10.1108/RPJ-07-2018-0183>
- Gu, Q., Jiang, M., Jiang, S., & Chen, L. (2021). Multi-objective particle swarm optimization with R2 indicator and adaptive method. *Complex & Intelligent Systems*, 7(5), 2697–2710. <https://doi.org/10.1007/s40747-021-00445-3>
- Guerreiro, A. P., Fonseca, C. M., & Paquete, L. (2020). *The Hypervolume Indicator: Problems and Algorithms*.
<https://doi.org/10.48550/ARXIV.2005.00515>
- Gupta, A., Stead, T. S., & Ganti, L. (2024). Determining a Meaningful R-squared Value in Clinical Medicine. *Academic Medicine & Surgery*.
<https://doi.org/10.62186/001c.125154>
- Gurralla, P. K., & Regalla, S. P. (2011). Optimization of Support Material and Build Time in Fused Deposition Modeling (FDM). *Applied Mechanics and Materials*, 110–116, 2245–2251.
<https://doi.org/10.4028/www.scientific.net/AMM.110-116.2245>
- Haldar, A. K., Managuli, V., Munshi, R., Agarwal, R. S., & Guan, Z. W. (2021). Compressive behaviour of 3D printed sandwich structures based on corrugated core design. *Materials Today Communications*, 26, 101725.
<https://doi.org/10.1016/j.mtcomm.2020.101725>
- Hanon, M. M. (2021). *Influence of the 3D Printing Process Settings on Tensile Strength of PLA and HT-PLA*.
- Hara, N., Taniguchi, S., Yamaki, T., Nguyen, T. T. H., & Kataoka, S. (2023). Bi-objective optimization of post-combustion CO₂ capture using methyldiethanolamine. *International Journal of Greenhouse Gas Control*, 122, 103815. <https://doi.org/10.1016/j.ijggc.2022.103815>

- Hergel, J., & Lefebvre, S. (2014). Clean color: Improving multi-filament 3D prints: Clean color: Improving multi-filament 3D prints. *Computer Graphics Forum*, 33(2), 469–478. <https://doi.org/10.1111/cgf.12318>
- Herianto, -, Setyawan, M. R., & Mastrisiswadi, H. (2022). 3D Print Continuation Process Parameter Setting to Optimize the Tensile Strength. *International Journal on Advanced Science, Engineering and Information Technology*, 12(1), 61. <https://doi.org/10.18517/ijaseit.12.1.13973>
- Hojjati, A., Monadi, M., Faridhosseini, A., & Mohammadi, M. (2018). Application and comparison of NSGA-II and MOPSO in multi-objective optimization of water resources systems. *Journal of Hydrology and Hydromechanics*, 66(3), 323–329. <https://doi.org/10.2478/johh-2018-0006>
- Hosseini Dehshiri, S. J., Yousefi Hanoomarvar, A., & Amiri, M. (2023). Comparative performance of the NSGA-II and MOPSO algorithms and simulations for evaluating time–cost–quality–risk trade-off in multi-modal PERT networks. *Soft Computing*, 27(24), 18651–18666. <https://doi.org/10.1007/s00500-023-09099-4>
- Hossen, M. M., Chan, T.-J., & Hasan, N. A. M. (2020). Mediating role of job satisfaction on internal corporate social responsibility practices and employee engagement in higher education sector. *Contemporary Management Research*, 16(3), 207–227. Scopus. <https://doi.org/10.7903/CMR.20334>
- Hsueh, M.-H., Lai, C.-J., Chung, C.-F., Wang, S.-H., Huang, W.-C., Pan, C.-Y., Zeng, Y.-S., & Hsieh, C.-H. (2021). Effect of Printing Parameters on the Tensile Properties of 3D-Printed Polylactic Acid (PLA) Based on Fused Deposition Modeling. *Polymers*, 13(14), 2387. <https://doi.org/10.3390/polym13142387>
- Ibrahim, H., Sebayang, A. H., Dharma, S., & Silitonga, A. S. (2017). PREDIKSI KINERJA MESIN DIESEL DENGAN BAHAN BAKAR BIODIESEL-SOLAR MENGGUNAKAN ARTIFICIAL NEURAL NETWORK. *Jurnal Muara Sains, Teknologi, Kedokteran dan Ilmu Kesehatan*, 1(1). <https://doi.org/10.24912/jmstkik.v1i1.391>

- Ishtiaq, M., Tiwari, S., Nagamani, M., Kang, S.-G., & Reddy, N. G. S. (2025). Data-Driven ANN-Based Predictive Modeling of Mechanical Properties of 5Cr-0.5Mo Steel: Impact of Composition and Service Temperature. *Crystals*, *15*(3), 213. <https://doi.org/10.3390/cryst15030213>
- Jackson, B., Fouladi, K., & Eslami, B. (2022). Multi-Parameter Optimization of 3D Printing Condition for Enhanced Quality and Strength. *Polymers*, *14*(8), 1586. <https://doi.org/10.3390/polym14081586>
- Jacobs, R., Schultz, L. E., Scourtas, A., Schmidt, K., Price-Skelly, O., Engler, W., Foster, I., Blaiszik, B., Voyles, P. M., & Morgan, D. (2024). Machine learning materials properties with accurate predictions, uncertainty estimates, domain guidance, and persistent online accessibility. *Machine Learning: Science and Technology*, *5*(4), 045051. <https://doi.org/10.1088/2632-2153/ad95db>
- Jiang, 2017.pdf. (n.d.). Processing rate and energy consumption analysis for additive manufacturing processes: Material extrusion and powder bed fusion (Doctoral dissertation, Massachusetts Institute of Technology)
- Jierula, A., Wang, S., Oh, T.-M., & Wang, P. (2021). Study on Accuracy Metrics for Evaluating the Predictions of Damage Locations in Deep Piles Using Artificial Neural Networks with Acoustic Emission Data. *Applied Sciences*, *11*(5), 2314. <https://doi.org/10.3390/app11052314>
- Kafshgar, A. R., Rostami, S., Aliha, M., & Berto, F. (2021). Optimization of Properties for 3D Printed PLA Material Using Taguchi, ANOVA and Multi-Objective Methodologies. *Procedia Structural Integrity*, *34*, 71–77. <https://doi.org/10.1016/j.prostr.2021.12.011>
- Kam, M., Ipekci, A., & Sengul, O. (2021). Taguchi Optimization of Fused Deposition Modeling Process Parameters on Mechanical Characteristics of PLA+ Filament Material. *Scientia Iranica*, *0*(0), 0–0. <https://doi.org/10.24200/sci.2021.57012.5020>
- Kananathan, J., Rajan, K., Samykano, M., Kadirgama, K., Moorthy, K., & Rahman, M. M. (2023). Preliminary Tensile Investigation of FDM Printed PLA/Coconut Wood Composite. In M. H. A. Hassan, M. H. Zohari, K. Kadirgama, N. A. N. Mohamed, & A. Aziz (Eds.), *Technological*

- Advancement in Instrumentation & Human Engineering* (Vol. 882, pp. 339–350). Springer Nature Singapore. https://doi.org/10.1007/978-981-19-1577-2_26
- Karadag, A., & Ulkir, O. (2025). Prediction of Dimensional Accuracy and Surface Quality in Additively Manufactured Biomedical Implants Using ANN. *International Journal of Precision Engineering and Manufacturing*, 26(5), 1187–1213. <https://doi.org/10.1007/s12541-025-01229-2>
- Karri, R. R., & Sahu, J. N. (2018). Modeling and optimization by particle swarm embedded neural network for adsorption of zinc (II) by palm kernel shell based activated carbon from aqueous environment. *Journal of Environmental Management*, 206, 178–191. <https://doi.org/10.1016/j.jenvman.2017.10.026>
- Kaveh, M., Badrossamay, M., Foroozmehr, E., & Hemasian Etefagh, A. (2015). Optimization of the printing parameters affecting dimensional accuracy and internal cavity for HIPS material used in fused deposition modeling processes. *Journal of Materials Processing Technology*, 226, 280–286. <https://doi.org/10.1016/j.jmatprotec.2015.07.012>
- Kennedy, J., & Eberhart, R. (1995). Particle swarm optimization. *Proceedings of ICNN'95 - International Conference on Neural Networks*, 4, 1942–1948. <https://doi.org/10.1109/ICNN.1995.488968>
- Khatavkar, N., & Singh, A. (2022). Robust Machine Learning Framework for Accurate Prediction of Mechanical Properties of Ni-Based Superalloys. *SSRN Electronic Journal*. <https://doi.org/10.2139/ssrn.4074830>
- K.N., R., Y., R. R., Kumar G, S., & Hk, R. (2025). Predictive modelling of mechanical properties of concrete using machine learning with secondary treated waste water and fly ash. *Cleaner Waste Systems*, 11, 100296. <https://doi.org/10.1016/j.clwas.2025.100296>
- Krishnaian, K., & Shahabudeen, P. (2012). *Applied design of experiments and taguchi methods*. PHI Learning Private Limited.
- Kumar, A. (2021). *Multi-stage, multi-swarm PSO for joint optimization of well placement and control* (Version 1). arXiv. <https://doi.org/10.48550/ARXIV.2106.01146>

- Kuppusamy, Y., Jayaseelan, R., Pandulu, G., Sathish Kumar, V., Murali, G., Dixit, S., & Vatin, N. I. (2022). Artificial Neural Network with a Cross-Validation Technique to Predict the Material Design of Eco-Friendly Engineered Geopolymer Composites. *Materials*, *15*(10), 3443. <https://doi.org/10.3390/ma15103443>
- Kuswanto, D., Iftira, N. J., & Hapinesa, O. M. (2018). 3D Printing for Fashion Development. *2018 4th International Conference on Science and Technology (ICST)*, 1–6. <https://doi.org/10.1109/ICSTC.2018.8528597>
- Laeng, et al., 2006.pdf.* (n.d.).
- Lakens, D. (2013). Calculating and reporting effect sizes to facilitate cumulative science: A practical primer for t-tests and ANOVAs. *Frontiers in Psychology*, *4*. <https://doi.org/10.3389/fpsyg.2013.00863>
- Laksono, 2016.pdf.* (n.d.). Optimizing flexible behaviour of bow prototype using Taguchi approach. *J. Appl. Sci.*, *6*, 622–630
- Lee, B. H., Abdullah, J., & Khan, Z. A. (2005). Optimization of rapid prototyping parameters for production of flexible ABS object. *Journal of Materials Processing Technology*, *169*(1), 54–61. <https://doi.org/10.1016/j.jmatprotec.2005.02.259>
- Lipowski, A., & Lipowska, D. (2012). Roulette-wheel selection via stochastic acceptance. *Physica A: Statistical Mechanics and Its Applications*, *391*(6), 2193–2196. <https://doi.org/10.1016/j.physa.2011.12.004>
- Liu, D., Virgolin, M., Alderliesten, T., & Bosman, P. A. N. (2022). *Evolvability Degeneration in Multi-Objective Genetic Programming for Symbolic Regression* (Version 2). arXiv. <https://doi.org/10.48550/ARXIV.2202.06983>
- Liu, H., Zhou, H., Lan, H., Liu, F., & Wang, X. (2018). Multinozzle Multichannel Temperature Deposition System for Construction of a Blood Vessel. *SLAS Technology*, *23*(1), 64–69. Scopus. <https://doi.org/10.1177/2472630317712221>
- Liu, H., Zhou, H., Lan, H., Liu, T., Liu, X., & Yu, H. (2017). 3D Printing of Artificial Blood Vessel: Study on Multi-Parameter Optimization Design for

- Vascular Molding Effect in Alginate and Gelatin. *Micromachines*, 8(8), 237.
<https://doi.org/10.3390/mi8080237>
- Liu, W., Wei, H., Zhang, M., Luo, Y., & Zhang, Y. (2022). Energy consumption modeling of additive-subtractive hybrid manufacturing based on cladding head moving state and deposition efficiency. *The International Journal of Advanced Manufacturing Technology*, 120(11–12), 7755–7770.
<https://doi.org/10.1007/s00170-022-09265-2>
- Liu, X., Zhang, M., Li, S., Si, L., Peng, J., & Hu, Y. (2017a). Mechanical property parametric appraisal of fused deposition modeling parts based on the gray Taguchi method. *The International Journal of Advanced Manufacturing Technology*, 89(5–8), 2387–2397. <https://doi.org/10.1007/s00170-016-9263-3>
- Liu, X., Zhang, M., Li, S., Si, L., Peng, J., & Hu, Y. (2017b). Mechanical property parametric appraisal of fused deposition modeling parts based on the gray Taguchi method. *The International Journal of Advanced Manufacturing Technology*, 89(5–8), 2387–2397. <https://doi.org/10.1007/s00170-016-9263-3>
- Liu, Z. Y., Li, C., Fang, X. Y., & Guo, Y. B. (2018). Energy Consumption in Additive Manufacturing of Metal Parts. *Procedia Manufacturing*, 26, 834–845. <https://doi.org/10.1016/j.promfg.2018.07.104>
- Lodetti, P. Z., Neto, E. A. C. A., Martins, M. A. I., Costa, G. H. D. S., & Ludwig, M. A. (2022). MAE and RMSE Analysis of K-means Predictive Algorithm for Photovoltaic Generation. *2022 International Conference on Electrical, Computer and Energy Technologies (ICECET)*, 1–6.
<https://doi.org/10.1109/ICECET55527.2022.9872976>
- Long, Y., Zhang, Z., Yan, C., Huang, Z., Fu, K., & Li, Y. (2022). Multi-objective optimization for improving printing efficiency and mechanical properties of 3D-printed continuous plant fibre composites. *Composites Communications*, 35, 101283. <https://doi.org/10.1016/j.coco.2022.101283>
- Lopez, D. M. B., & Ahmad, R. (2020). *Tensile Mechanical Behaviour of Multi-Polymer Sandwich Structures via Fused Deposition Modelling*.

- Luo, H., Tan, Y., Zhang, F., Zhang, J., Tu, Y., & Cui, K. (2019). Selectively Enhanced 3D Printing Process and Performance Analysis of Continuous Carbon Fiber Composite Material. *Materials*, *12*(21), 3529. <https://doi.org/10.3390/ma12213529>
- Maalihan, R. D. (2022). Modelling the Toughness of Nanostructured Polyhedral Oligomeric Silsesquioxane Composites Fabricated by Stereolithography 3D Printing: A Response Surface Methodology and Artificial Neural Network Approach. *Materials Science Forum*, *1053*, 41–46. <https://doi.org/10.4028/p-6s4jp4>
- Mahmood, M. A., Visan, A. I., Ristoscu, C., & Mihailescu, I. N. (2020). Artificial Neural Network Algorithms for 3D Printing. *Materials*, *14*(1), 163. <https://doi.org/10.3390/ma14010163>
- Malashin, I., Tynchenko, V., Gantimurov, A., Nelyub, V., & Borodulin, A. (2024). A Multi-Objective Optimization of Neural Networks for Predicting the Physical Properties of Textile Polymer Composite Materials. *Polymers*, *16*(12), 1752. <https://doi.org/10.3390/polym16121752>
- Mani, M., Karthikeyan, A. G., Kalaiselvan, K., Muthusamy, P., & Muruganandhan, P. (2022). Optimization of FDM 3-D printer process parameters for surface roughness and mechanical properties using PLA material. *Materials Today: Proceedings*, *66*, 1926–1931. <https://doi.org/10.1016/j.matpr.2022.05.422>
- Mohamed, O. A., Masood, S. H., & Bhowmik, J. L. (2015). Optimization of fused deposition modeling process parameters: A review of current research and future prospects. *Advances in Manufacturing*, *3*(1), 42–53. <https://doi.org/10.1007/s40436-014-0097-7>
- Mohamed, O. A., Masood, S. H., & Bhowmik, J. L. (2016a). Mathematical modeling and FDM process parameters optimization using response surface methodology based on Q-optimal design. *Applied Mathematical Modelling*, *40*(23–24), 10052–10073. <https://doi.org/10.1016/j.apm.2016.06.055>
- Mohamed, O. A., Masood, S. H., & Bhowmik, J. L. (2016b). Optimization of fused deposition modeling process parameters for dimensional accuracy using I-optimality criterion. *Measurement*, *81*, 174–196.

- Mohamed, O. A., Masood, S. H., Bhowmik, J. L., Nikzad, M., & Azadmanjiri, J. (2016a). Effect of Process Parameters on Dynamic Mechanical Performance of FDM PC/ABS Printed Parts Through Design of Experiment. *Journal of Materials Engineering and Performance*, 25(7), 2922–2935. <https://doi.org/10.1007/s11665-016-2157-6>
- Mohamed, O. A., Masood, S. H., Bhowmik, J. L., Nikzad, M., & Azadmanjiri, J. (2016b). Effect of Process Parameters on Dynamic Mechanical Performance of FDM PC/ABS Printed Parts Through Design of Experiment. *Journal of Materials Engineering and Performance*, 25(7), 2922–2935. <https://doi.org/10.1007/s11665-016-2157-6>
- Moradi, M., Beygi, R., Mohd. Yusof, N., Amiri, A., Da Silva, L. F. M., & Sharif, S. (2023). 3D Printing of Acrylonitrile Butadiene Styrene by Fused Deposition Modeling: Artificial Neural Network and Response Surface Method Analyses. *Journal of Materials Engineering and Performance*, 32(4), 2016–2028. <https://doi.org/10.1007/s11665-022-07250-0>
- Moslemi, H., & Zandieh, M. (2011). Comparisons of some improving strategies on MOPSO for multi-objective (r,Q) inventory system. *Expert Systems with Applications*, 38(10), 12051–12057. <https://doi.org/10.1016/j.eswa.2011.01.169>
- Mostaghim, S., & Teich, J. (2003). Strategies for finding good local guides in multi-objective particle swarm optimization (MOPSO). *Proceedings of the 2003 IEEE Swarm Intelligence Symposium. SIS'03 (Cat. No.03EX706)*, 26–33. <https://doi.org/10.1109/SIS.2003.1202243>
- Mueller, J., Kim, S. E., Shea, K., & Daraio, C. (2015). Tensile Properties of Inkjet 3D Printed Parts: Critical Process Parameters and Their Efficient Analysis. *Volume 1A: 35th Computers and Information in Engineering Conference*, V01AT02A040. <https://doi.org/10.1115/DETC2015-48024>
- Nader, J. W., Dagher, H. J., & Lopez-Anido, R. (2011). Size effects on the bending strength of fiber-reinforced polymer matrix composites. *Journal of Reinforced Plastics and Composites*, 30(4), 309–317. <https://doi.org/10.1177/0731684410396598>

- Nancharaiyah, T. (2011). *Optimization of Process Parameters in FDM Process Using Design of Experiments*.
- Napolitano, F., Cozzolino, E., Papa, I., Astarita, A., & Squillace, A. (2022). Experimental integrated approach for mechanical characteristic optimization of FDM-printed PLA in an energy-saving perspective. *The International Journal of Advanced Manufacturing Technology*, 121(5–6), 3551–3565. <https://doi.org/10.1007/s00170-022-09535-z>
- Nasution, A., Herianto, Rifai, A. P., & Atsani, S. I. (2025). Tensile performance of multi-material sandwich structures fabricated by multi-nozzle fused deposition modeling using PLA, ABS, and HIPS. *Results in Engineering*, 27, 106210. <https://doi.org/10.1016/j.rineng.2025.106210>
- Nyiranzeyimana, G., Mutua, J. M., Mose, B. R., & Mbuya, T. O. (2021). Optimization of process parameters in fused deposition modelling of thermoplastics: A review. *Materialwissenschaft Und Werkstofftechnik*, 52(6), 682–694. <https://doi.org/10.1002/mawe.202000193>
- Ochoa Pacheco, P., & Coello-Montecel, D. (2023). Does psychological empowerment mediate the relationship between digital competencies and job performance? *Computers in Human Behavior*, 140. Scopus. <https://doi.org/10.1016/j.chb.2022.107575>
- Oehlmann, P., Osswald, P., Blanco, J. C., Friedrich, M., Rietzel, D., & Witt, G. (2021). Modeling Fused Filament Fabrication using Artificial Neural Networks. *Production Engineering*, 15(3–4), 467–478. <https://doi.org/10.1007/s11740-021-01020-y>
- Okafor, C. E., Okafor, E. J., & Ikebudu, K. O. (2022). Evaluation of machine learning methods in predicting optimum tensile strength of microwave post-cured composite tailored for weight-sensitive applications. *Engineering Science and Technology, an International Journal*, 25, 100985. <https://doi.org/10.1016/j.jestch.2021.04.004>
- Omar, N. W. Y., Shuaib, N. A., Azmi, A. I., & Hadi, M. H. J. A. (2022). Effect of Build Parameters on Process Energy Consumption and Material Usage in

- Fused Deposition Modelling Method. *Journal of Physics: Conference Series*, 2312(1), 012015. <https://doi.org/10.1088/1742-6596/2312/1/012015>
- Pamasaria, H. A., & Saputra, T. H. (2019). *PENGARUH PARAMETER PROSES 3D PRINTING TIPE FDM (FUSED DEPOSITION MODELING) TERHADAP KUALITAS HASIL PRODUK*.
- Pamasaria, H. A., Saputra, T. H., Utama, A. S., & Budiyanoro, C. (2020). Optimasi Keakuratan Dimensi Produk Cetak 3D Printing berbahan Plastik PP Daur Ulang dengan Menggunakan Metode Taguchi. *JMPM (Jurnal Material dan Proses Manufaktur)*, 4(1). <https://doi.org/10.18196/jmpm.4148>
- Panda, B. N., Bahubalendruni, M. V. A. R., & Biswal, B. B. (2014). Comparative Evaluation of Optimization Algorithms at Training of Genetic Programming for Tensile Strength Prediction of FDM Processed Part. *Procedia Materials Science*, 5, 2250–2257. <https://doi.org/10.1016/j.mspro.2014.07.441>
- Panda, S. K., Padhee, S., Sood, A. K., & Mahapatra, S. S. (2009a). Optimization of Fused Deposition Modelling (FDM) Process Parameters Using Bacterial Foraging Technique. *Intelligent Information Management*, 01(02), 89–97. <https://doi.org/10.4236/iim.2009.12014>
- Panda, S. K., Padhee, S., Sood, A. K., & Mahapatra, S. S. (2009b). Optimization of Fused Deposition Modelling (FDM) Process Parameters Using Bacterial Foraging Technique. *Intelligent Information Management*, 01(02), 89–97. <https://doi.org/10.4236/iim.2009.12014>
- Parayoga, R., & Asih, A. M. S. (2021). *Empirical study of MOPSO and NSGA II comparison in multi-objective location routing problem incorporating the service level of delivery*.
- Pareek, C. M., Tewari, V. K., & Machavaram, R. (2023). Multi-objective optimization of seeding performance of a pneumatic precision seed metering device using integrated ANN-MOPSO approach. *Engineering Applications of Artificial Intelligence*, 117, 105559. <https://doi.org/10.1016/j.engappai.2022.105559>
- Parmita, et al., 2021.pdf. (n.d.). Sosialisasi Pengenalan 3d Printing Untuk Pemuda Dan Pemudi Di Balikpapan. *Jurnal Pengabdian Kepada Masyarakat*. Vol. 2,

No. 1 Juni 2021. asoemarsono,+{\$userGroup},+Final+Paper+317_PIKAT (2).pdf

- Patil, P. (2022). Modeling and analysis of surface roughness in fused deposition modeling based on infill patterns. *Indian Journal of Engineering and Materials Sciences*, 29(01). <https://doi.org/10.56042/ijems.v29i1.45585>
- Patil, P., Singh, D., Raykar, S. J., & Bhamu, J. (2021). Multi-objective optimization of process parameters of Fused Deposition Modeling (FDM) for printing Polylactic Acid (PLA) polymer components. *Materials Today: Proceedings*, 45, 4880–4885. <https://doi.org/10.1016/j.matpr.2021.01.353>
- Pătrăușanu, A., Florea, A., Neghină, M., Dicoiu, A., & Chiș, R. (2024). A Systematic Review of Multi-Objective Evolutionary Algorithms Optimization Frameworks. *Processes*, 12(5), 869. <https://doi.org/10.3390/pr12050869>
- Patti Antonella, Acierno Stefano, Cicala Gianluca, Tuccitto Nunzio, & Acierno Domenico. (2022). Refining the 3D Printer Set-up to Reduce the Environmental Impact of the Fused Deposition Modelling (fdm) Technology. *Chemical Engineering Transactions*, 91, 415–420. <https://doi.org/10.3303/CET2291070>
- Pawar, S., Quadri, S. A., Department of Mechanical Engineering, Jawaharlal Nehru Engineering College, MGM University, Aurangabad, India, Dolas, Dr. D., & Department of Mechanical Engineering, Jawaharlal Nehru Engineering College, MGM University, Aurangabad, India. (2021). OPTIMIZATION OF FUSED DEPOSITION MODELING PROCESS PARAMETERS FOR MATERIAL CONSUMPTION AND MANUFACTURING TIME. *Journal of Engineering Research*. <https://doi.org/10.36909/jer.ICIPPSD.15539>
- Peng, A., Xiao, X., & Yue, R. (2014). Process parameter optimization for fused deposition modeling using response surface methodology combined with fuzzy inference system. *The International Journal of Advanced Manufacturing Technology*, 73(1–4), 87–100. <https://doi.org/10.1007/s00170-014-5796-5>

- Peng, T., Lv, J., Majeed, A., & Liang, X. (2021). An experimental investigation on energy-effective additive manufacturing of aluminum parts via process parameter selection. *Journal of Cleaner Production*, 279, 123609. <https://doi.org/10.1016/j.jclepro.2020.123609>
- Petcharat, N., Wiangkham, A., Pichitkul, A., Tantrairatn, S., Aengchuan, P., Bureerat, S., Banpap, S., Khunthongplatprasert, P., & Ariyarit, A. (2023). The multi-objective optimization of material properties of 3D print onyx/carbon fiber composites via surrogate model. *Materials Today Communications*, 37, 107362. <https://doi.org/10.1016/j.mtcomm.2023.107362>
- Petruse, R. E., Simion, C., & Bondrea, I. (2024). Geometrical and Dimensional Deviations of Fused Deposition Modelling (FDM) Additive-Manufactured Parts. *Metrology*, 4(3), 411–429. <https://doi.org/10.3390/metrology4030025>
- Pollard, D., Herrmann, G., Ward, C., & Etches, J. (2018). A Comparison of FDM Structural Layouts and Implementation of an Open-Source Arm-Based System. *MATEC Web of Conferences*, 167, 03002. <https://doi.org/10.1051/mateconf/201816703002>
- Poonia, V., Kumar, R., Kulshrestha, R., & Sangwan, K. S. (2023a). Optimization of Specific Energy, Scrap, and Surface Roughness in 3D Printing Using Integrated ANN-GA Approach. *Procedia CIRP*, 116, 324–329. <https://doi.org/10.1016/j.procir.2023.02.055>
- Poonia, V., Kumar, R., Kulshrestha, R., & Sangwan, K. S. (2023b). Optimization of Specific Energy, Scrap, and Surface Roughness in 3D Printing Using Integrated ANN-GA Approach. *Procedia CIRP*, 116, 324–329. <https://doi.org/10.1016/j.procir.2023.02.055>
- Popescu, D., Zapciu, A., Amza, C., Baci, F., & Marinescu, R. (2018). FDM process parameters influence over the mechanical properties of polymer specimens: A review. *Polymer Testing*, 69, 157–166. <https://doi.org/10.1016/j.polymertesting.2018.05.020>
- Prabhu, P., Karthikeyan, B., Vannan, R. R. R. M., & Balaji, A. (2022). Mechanical, thermal and morphological analysis of hybrid natural and glass fiber-

- reinforced hybrid resin nanocomposites. *Biomass Conversion and Biorefinery*. <https://doi.org/10.1007/s13399-022-02632-9>
- Prajapati, A. (2021). A comparative study of many-objective optimizers on large-scale many-objective software clustering problems. *Complex & Intelligent Systems*, 7(2), 1061–1077. <https://doi.org/10.1007/s40747-021-00270-8>
- Pratama, W. H., -, H., & -, H. (2021). Optimasi Parameter Proses 3D Printing Terhadap Kuat Tarik Material Filamen PLA + Menggunakan Metode Taguchi. *SPROCKET JOURNAL OF MECHANICAL ENGINEERING*, 3(1), 39–45. <https://doi.org/10.36655/sprocket.v3i1.568>
- Qayyum Khan, A., Ahmad Awan, H., Rasul, M., Ahmad Siddiqi, Z., & Pimanmas, A. (2023). Optimized artificial neural network model for accurate prediction of compressive strength of normal and high strength concrete. *Cleaner Materials*, 10, 100211. <https://doi.org/10.1016/j.clema.2023.100211>
- Raheem. (2019). *Test Method for Compressive Properties of Rigid Plastics*. ASTM International. <https://doi.org/10.1520/D0695-15>
- Rahimi, I., Gandomi, A. H., Nikoo, M. R., & Chen, F. (2023). A comparative study on evolutionary multi-objective algorithms for next release problem. *Applied Soft Computing*, 144, 110472. <https://doi.org/10.1016/j.asoc.2023.110472>
- Rahimi, I., Qaderi, K., & Mohammad Abasiyan, A. (2013). Optimal Reservoir Operation Using MOPSO with Time Variant Inertia and Acceleration Coefficients. *Universal Journal of Agricultural Research*, 1(3), 74–80. <https://doi.org/10.13189/ujar.2013.010306>
- Rajkumar, S. (2022). *Effect of infill pattern and build orientation on mechanical properties of FDM printed parts: An experimental modal analysis approach* (Version 1). arXiv. <https://doi.org/10.48550/ARXIV.2202.05692>
- Raju, M., Gupta, M. K., Bhanot, N., & Sharma, V. S. (2019). A hybrid PSO–BFO evolutionary algorithm for optimization of fused deposition modelling process parameters. *Journal of Intelligent Manufacturing*, 30(7), 2743–2758. <https://doi.org/10.1007/s10845-018-1420-0>
- Ranganathan, S., Senthilvelan, T., & Sriram, G. (2010). Evaluation of Machining Parameters of Hot Turning of Stainless Steel (Type 316) by Applying ANN

- and RSM. *Materials and Manufacturing Processes*, 25(10), 1131–1141.
<https://doi.org/10.1080/10426914.2010.489790>
- Rastogi, P., Gharde, S., & Kandasubramanian, B. (2020). Thermal Effects in 3D Printed Parts. In S. Singh, C. Prakash, & R. Singh (Eds.), *3D Printing in Biomedical Engineering* (pp. 43–68). Springer Singapore.
https://doi.org/10.1007/978-981-15-5424-7_3
- Rayegani, F., & Onwubolu, G. C. (2014). Fused deposition modelling (FDM) process parameter prediction and optimization using group method for data handling (GMDH) and differential evolution (DE). *The International Journal of Advanced Manufacturing Technology*, 73(1–4), 509–519.
<https://doi.org/10.1007/s00170-014-5835-2>
- Rezasefat, M., & Hogan, J. D. (2023). Machine Learning-Assisted Characterization of Pore-Induced Variability in Mechanical Response of Additively Manufactured Components. *Modelling*, 5(1), 1–15.
<https://doi.org/10.3390/modelling5010001>
- Rinanto, A., Nugroho, A., Prasetyo, H., & Pujiyanto, E. (2018). *Simultaneous Optimization of Tensile Strength, Energy Consumption and Processing Time on FDM Process Using Taguchi and PCR-TOPSIS*.
- Rizky Ryandi, 2017.pdf. (n.d.). Penerapan Metode Artificial Neural Network (ANN) Untuk Peramalan Inflasi di Indonesia. Jurusan Sistem Informasi. Fakultas Teknologi Informasi. Institut Teknologi Sepuluh Nopember
- Rodriguez, et al., 2003.pdf. (n.d.). Design of fused-deposition ABS components for stiffness and strength. *J. Mech. Des.*, 125(3), 545-551.
<https://doi.org/10.1115/1.1582499>
- Rojek, I., Mikołajewski, D., Dostatni, E., & Macko, M. (2020a). AI-Optimized Technological Aspects of the Material Used in 3D Printing Processes for Selected Medical Applications. *Materials*, 13(23), 5437.
<https://doi.org/10.3390/ma13235437>
- Rojek, I., Mikołajewski, D., Dostatni, E., & Macko, M. (2020b). AI-Optimized Technological Aspects of the Material Used in 3D Printing Processes for

- Selected Medical Applications. *Materials*, 13(23), 5437.
<https://doi.org/10.3390/ma13235437>
- Saad, M. S., Nor, A. M., Baharudin, M. E., Zakaria, M. Z., & Aiman, A. F. (2019). Optimization of surface roughness in FDM 3D printer using response surface methodology, particle swarm optimization, and symbiotic organism search algorithms. *The International Journal of Advanced Manufacturing Technology*, 105(12), 5121–5137. <https://doi.org/10.1007/s00170-019-04568-3>
- Saadat, M., Khandelwal, M., & Monjezi, M. (2014). An ANN-based approach to predict blast-induced ground vibration of Gol-E-Gohar iron ore mine, Iran. *Journal of Rock Mechanics and Geotechnical Engineering*, 6(1), 67–76.
<https://doi.org/10.1016/j.jrmge.2013.11.001>
- Sağlıcan, E., & Afacan, E. (2024). MOEA/D vs. NSGA-II: A Comprehensive Comparison for Multi/Many Objective Analog/RF Circuit Optimization through a Generic Benchmark. *ACM Transactions on Design Automation of Electronic Systems*, 29(1), 1–23. <https://doi.org/10.1145/3626096>
- Sahib, M. M., & Kovács, G. (2025). Using Artificial Neural Networks to Predict the Bending Behavior of Composite Sandwich Structures. *Polymers*, 17(3), 337. <https://doi.org/10.3390/polym17030337>
- Samsuri, T. (2003). *KAJIAN TEORI, KERANGKA KONSEP DAN HIPOTESIS*.
- Santos, T., & Xavier, S. (2018). A Convergence Indicator for Multi-Objective Optimisation Algorithms. *TEMA (São Carlos)*, 19(3), 437.
<https://doi.org/10.5540/tema.2018.019.03.437>
- Satyanarayana, G., Swami Naidu, G., & Babu, N. H. (2018). Artificial neural network and regression modelling to study the effect of reinforcement and deformation on volumetric wear of red mud nano particle reinforced aluminium matrix composites synthesized by stir casting. *Boletín de La Sociedad Española de Cerámica y Vidrio*, 57(3), 91–100.
<https://doi.org/10.1016/j.bsecv.2017.09.006>

- Seçil, E., & Karakaya, C. (2025). Effects of Process Parameters on Tensile Properties of 3D-Printed PLA Parts Fabricated with the FDM Method. *Polymers*, *17*(14), 1934. <https://doi.org/10.3390/polym17141934>
- Shahkarami, M., & Zeinedini, A. (2022). Flexural Properties of 3D-printed hierarchical-sinusoidal corrugated core sandwich panels with natural fiber reinforced skins. *Polymers and Polymer Composites*, *30*, 09673911221101299. <https://doi.org/10.1177/09673911221101299>
- Shao, J., Lu, Y., Sun, Y., & Zhao, L. (2025). An improved multi-objective particle swarm optimization algorithm for the design of foundation pit of rail transit upper cover project. *Scientific Reports*, *15*(1), 10403. <https://doi.org/10.1038/s41598-025-87350-8>
- Sharma, R., Kodamana, H., & Ramteke, M. (2022). Multi-objective dynamic optimization of hybrid renewable energy systems. *Chemical Engineering and Processing - Process Intensification*, *170*, 108663. <https://doi.org/10.1016/j.cep.2021.108663>
- Sharma, V., Roozbahani, H., Alizadeh, M., & Handroos, H. (2021). 3D Printing of Plant-Derived Compounds and a Proposed Nozzle Design for the More Effective 3D FDM Printing. *IEEE Access*, *9*, 571107–571119. <https://doi.org/10.1109/ACCESS.2021.3071459>
- Shirmohammadi, M. (2021). Optimization of 3D printing process parameters to minimize surface roughness with hybrid artificial neural network model and particle swarm algorithm. *Progress in Additive Manufacturing*.
- Singh, G., Missiaen, J.-M., Bouvard, D., & Chaix, J.-M. (2021). Copper extrusion 3D printing using metal injection moulding feedstock: Analysis of process parameters for green density and surface roughness optimization. *Additive Manufacturing*, *38*, 101778. <https://doi.org/10.1016/j.addma.2020.101778>
- Singh, T. K., Birru, A. K., & Singh, K. N. (2024). Optimizing the printing parameters for dimensional accuracy of distal femur bone by using Taguchi's method. *Journal of Engineering and Applied Science*, *71*(1), 10. <https://doi.org/10.1186/s44147-023-00338-x>

- Siu Kit Yeung, Steele, J., Zloteanu, M., Jané, M. B., Elsherif, M., Moreau, D., Johnson, B. T., Riesthuis, P., Vieira, F. F., Röseler, L., Feldman, G., Qinyu Xiao, Ben-Shachar, M. S., Caldwell, A. R., Cousineau, D., & Dunleavy, D. J. (2023). *Guide to Effect Sizes and Confidence Intervals*. <https://doi.org/10.17605/OSF.IO/D8C4G>
- Solomon, I. J., Sevvel, P., & Gunasekaran, J. (2021). A review on the various processing parameters in FDM. *Materials Today: Proceedings*, 37, 509–514. <https://doi.org/10.1016/j.matpr.2020.05.484>
- Sondagar, H., Bhadauria, S. S., & Sharma, V. S. (2021). Artificial neural network (ANN) based prediction of process parameters in additive manufacturing. *IOP Conference Series: Materials Science and Engineering*, 1136(1), 012026. <https://doi.org/10.1088/1757-899X/1136/1/012026>
- Sood, A. K., Ohdar, R. K., & Mahapatra, S. S. (2009). Improving dimensional accuracy of Fused Deposition Modelling processed part using grey Taguchi method. *Materials & Design*, 30(10), 4243–4252. <https://doi.org/10.1016/j.matdes.2009.04.030>
- Sood, A. K., Ohdar, R. K., & Mahapatra, S. S. (2010a). Parametric appraisal of mechanical property of fused deposition modelling processed parts. *Materials & Design*, 31(1), 287–295. <https://doi.org/10.1016/j.matdes.2009.06.016>
- Sood, A. K., Ohdar, R. K., & Mahapatra, S. S. (2010b). Parametric appraisal of mechanical property of fused deposition modelling processed parts. *Materials & Design*, 31(1), 287–295. <https://doi.org/10.1016/j.matdes.2009.06.016>
- Sood, A. K., Ohdar, R. K., & Mahapatra, S. S. (2012). Experimental investigation and empirical modelling of FDM process for compressive strength improvement. *Journal of Advanced Research*, 3(1), 81–90. <https://doi.org/10.1016/j.jare.2011.05.001>
- Srivastava, M., Rathee, S., Maheshwari, S., & Kundra, T. K. (2018a). Multi-objective optimisation of fused deposition modelling process parameters using RSM and fuzzy logic for build time and support material. *International Journal of Rapid Manufacturing*, 7(1), 25. <https://doi.org/10.1504/IJRAPIDM.2018.089727>

- Srivastava, M., Rathee, S., Maheshwari, S., & Kundra, T. K. (2018b). Multi-objective optimisation of fused deposition modelling process parameters using RSM and fuzzy logic for build time and support material. *International Journal of Rapid Manufacturing*, 7(1), 25. <https://doi.org/10.1504/IJRAPIDM.2018.089727>
- Subramonian, S., Kadirgama, K., Al-Obaidi, A. Sh. M., Mohd Salleh, M. S., Vatesh, U. K., Pujari, S., Rao, D., & Ramasamy, D. (2023). Artificial Neural Network Performance Modeling and Evaluation of Additive Manufacturing 3D Printed Parts. *Engineering, Technology & Applied Science Research*, 13(5), 11677–11684. <https://doi.org/10.48084/etasr.6185>
- Suniya, N. K., Verma, A. K., & Department of Production and Industrial Engineering, MBM University. (2023). A review on optimization of process parameters of fused deposition modeling. *Research on Engineering Structures and Materials*. <https://doi.org/10.17515/resm2022.520ma0909>
- Surange, V. G., & Gharat, P. V. (2016). *3D Printing Process Using Fused Deposition Modelling (FDM)*. 03(03).
- Tanikella, N. G., Wittbrodt, B., & Pearce, J. M. (2017). Tensile strength of commercial polymer materials for fused filament fabrication 3D printing. *Additive Manufacturing*, 15, 40–47. <https://doi.org/10.1016/j.addma.2017.03.005>
- Tlegenov, Y., Hong, G. S., & Lu, W. F. (2018). Nozzle condition monitoring in 3D printing. *Robotics and Computer-Integrated Manufacturing*, 54, 45–55. <https://doi.org/10.1016/j.rcim.2018.05.010>
- Torres, J., Cole, M., Owji, A., DeMastry, Z., & Gordon, A. P. (2016a). An approach for mechanical property optimization of fused deposition modeling with polylactic acid via design of experiments. *Rapid Prototyping Journal*, 22(2), 387–404. <https://doi.org/10.1108/RPJ-07-2014-0083>
- Torres, J., Cole, M., Owji, A., DeMastry, Z., & Gordon, A. P. (2016b). An approach for mechanical property optimization of fused deposition modeling with polylactic acid via design of experiments. *Rapid Prototyping Journal*, 22(2), 387–404. <https://doi.org/10.1108/RPJ-07-2014-0083>

- Torres, J., Cotelo, J., Karl, J., & Gordon, A. P. (2015). Mechanical Property Optimization of FDM PLA in Shear with Multiple Objectives. *JOM*, *67*(5), 1183–1193. <https://doi.org/10.1007/s11837-015-1367-y>
- Tymrak, B. M., Kreiger, M., & Pearce, J. M. (2014). Mechanical properties of components fabricated with open-source 3-D printers under realistic environmental conditions. *Materials & Design*, *58*, 242–246. <https://doi.org/10.1016/j.matdes.2014.02.038>
- Verma, S., Pant, M., & Snasel, V. (2021). A Comprehensive Review on NSGA-II for Multi-Objective Combinatorial Optimization Problems. *IEEE Access*, *9*, 57757–57791. <https://doi.org/10.1109/ACCESS.2021.3070634>
- Verpoort, P. C., MacDonald, P., & Conduit, G. J. (2018). Materials data validation and imputation with an artificial neural network. *Computational Materials Science*, *147*, 176–185. <https://doi.org/10.1016/j.commatsci.2018.02.002>
- Vidakis, N., Kechagias, J. D., Petousis, M., Vakouftsi, F., & Mountakis, N. (2023). The effects of FFF 3D printing parameters on energy consumption. *Materials and Manufacturing Processes*, *38*(8), 915–932. <https://doi.org/10.1080/10426914.2022.2105882>
- Vidakis, N., Petousis, M., Mountakis, N., Maravelakis, E., Zaoutsos, S., & Kechagias, J. D. (2022). Mechanical response assessment of antibacterial PA12/TiO₂ 3D printed parts: Parameters optimization through artificial neural networks modeling. *The International Journal of Advanced Manufacturing Technology*, *121*(1–2), 785–803. <https://doi.org/10.1007/s00170-022-09376-w>
- Viharos, Z. J. (n.d.). *APPLICATION CAPABILITIES OF A GENERAL, ANN-BASED CUTTING MODEL IN DIFFERENT PHASES OF MANUFACTURING THROUGH AUTOMATIC DETERMINATION OF ITS INPUT-OUTPUT CONFIGURATION*.
- Walls, S., Binns, A. D., Levison, J., & MacRitchie, S. (2020). Prediction of actual evapotranspiration by artificial neural network models using data from a Bowen ratio energy balance station. *Neural Computing and Applications*, *32*(17), 14001–14018. <https://doi.org/10.1007/s00521-020-04800-2>

- Warke, S., & Puranik, V. S. (2022). Comparison of energy consumption of ABS and PLA while 3 D printing with fused deposition modeling process. *Materials Today: Proceedings*, 66, 2098–2103. <https://doi.org/10.1016/j.matpr.2022.05.509>
- Willmott, C., & Matsuura, K. (2005). Advantages of the mean absolute error (MAE) over the root mean square error (RMSE) in assessing average model performance. *Climate Research*, 30, 79–82. <https://doi.org/10.3354/cr030079>
- Wu, S., McAuley, K. B., & Harris, T. J. (2011). Selection of simplified models: I. Analysis of model-selection criteria using mean-squared error. *The Canadian Journal of Chemical Engineering*, 89(1), 148–158. <https://doi.org/10.1002/cjce.20406>
- Wu, W. Z., Geng, P., Zhao, J., Zhang, Y., Rosen, D. W., & Zhang, H. B. (2014). Manufacture and thermal deformation analysis of semicrystalline polymer polyether ether ketone by 3D printing. *Materials Research Innovations*, 18, S5-12. Scopus. <https://doi.org/10.1179/1432891714Z.000000000898>
- Xiaoyu, W., Song, Q., Qian, Y., Qiao, D., Wang, H., Zhang, Y., & Li, H. (2023). Effective Improved NSGA-II Algorithm for Multi-Objective Integrated Process Planning and Scheduling. *Mathematics*, 11(16), 3523. <https://doi.org/10.3390/math11163523>
- Xiong, Q., Dong, L., Chen, H., Zhu, X., Zhao, X., & Gao, X. (2024). Enhanced NSGA-II algorithm based on novel hybrid crossover operator to optimise water supply and ecology of Fenhe reservoir operation. *Scientific Reports*, 14(1), 31621. <https://doi.org/10.1038/s41598-024-80419-w>
- Xu, G., Luo, K., Jing, G., Yu, X., Ruan, X., & Song, J. (2020). On convergence analysis of multi-objective particle swarm optimization algorithm. *European Journal of Operational Research*, 286(1), 32–38. <https://doi.org/10.1016/j.ejor.2020.03.035>
- Yang, F., Zhang, M., Bhandari, B., & Liu, Y. (2018). Investigation on lemon juice gel as food material for 3D printing and optimization of printing parameters. *LWT*, 87, 67–76. <https://doi.org/10.1016/j.lwt.2017.08.054>

- Yang, Y., Wang, Y., Xue, B., Wang, C., & Yang, B. (2025). Optimization of Fused Deposition Modeling Parameters for Mechanical Properties of Polylactic Acid Parts Based on Kriging and Cuckoo Search. *Aerospace*, *12*(1), 38. <https://doi.org/10.3390/aerospace12010038>
- Yaqin, R. I., Siahaan, J. P., Tumpu, M., Prakoso, B., Hermawan, A., Luthfiani, F., Barokah, B., & Kurniawan, A. (2024). Material and process parameter optimization for dimensional accuracy in Fused Deposition Modeling 3D printing. *Jurnal Polimesin*, *22*(6), 581. <https://doi.org/10.30811/jpl.v22i6.5716>
- Yildirim, F., & Naktiyok, S. (2017). The mediating role of organizational support in the effect of transformational leadership on employee empowerment. *Polish Journal of Management Studies*, *16*(1), 292–303. Scopus. <https://doi.org/10.17512/pjms.2017.16.1.25>
- Yildiz, A. R. (2012). A comparative study of population-based optimization algorithms for turning operations. *Information Sciences*, *210*, 81–88. <https://doi.org/10.1016/j.ins.2012.03.005>
- Zaharia, S. M., Enescu, L. A., & Pop, M. A. (2020). Mechanical Performances of Lightweight Sandwich Structures Produced by Material Extrusion-Based Additive Manufacturing. *Polymers*, *12*(8), 1740. <https://doi.org/10.3390/polym12081740>
- Zarbakshshnia, N., Kannan, D., Kiani Mavi, R., & Soleimani, H. (2020). A novel sustainable multi-objective optimization model for forward and reverse logistics system under demand uncertainty. *Annals of Operations Research*, *295*(2), 843–880. <https://doi.org/10.1007/s10479-020-03744-z>
- Zgodavová, K., Lengyelová, K., Bober, P., Eguren, J. A., & Moreno, A. (2021). 3D Printing Optimization for Environmental Sustainability: Experimenting with Materials of Protective Face Shield Frames. *Materials*, *14*(21), 6595. <https://doi.org/10.3390/ma14216595>
- Zhang, G., Eddy Patuwo, B., & Y. Hu, M. (1998). Forecasting with artificial neural networks: *International Journal of Forecasting*, *14*(1), 35–62. [https://doi.org/10.1016/S0169-2070\(97\)00044-7](https://doi.org/10.1016/S0169-2070(97)00044-7)

- Zhang, J., Li, C., Yin, Y., Zhang, J., & Grzegorzec, M. (2023). Applications of artificial neural networks in microorganism image analysis: A comprehensive review from conventional multilayer perceptron to popular convolutional neural network and potential visual transformer. *Artificial Intelligence Review*, *56*(2), 1013–1070. <https://doi.org/10.1007/s10462-022-10192-7>
- Zhang, L. (2019). Characteristics of drop-on-demand droplet jetting with effect of altered geometry of printhead nozzle. *Sensors and Actuators, A: Physical*, *298*. Scopus. <https://doi.org/10.1016/j.sna.2019.111591>
- Zhang, Y., Luo, Y., Zhang, X., & Zhao, J. (2019). How green human resource management can promote green employee behavior in China: A technology acceptance model perspective. *Sustainability (Switzerland)*, *11*(19). Scopus. <https://doi.org/10.3390/su11195408>
- Zhang, Z., Wu, F., & Wu, A. (2024). Research on Multi-Objective Process Parameter Optimization Method in Hard Turning Based on an Improved NSGA-II Algorithm. *Processes*, *12*(5), 950. <https://doi.org/10.3390/pr12050950>
- Zheng, W., & Doerr, B. (2024). Runtime Analysis for the NSGA-II: Proving, Quantifying, and Explaining the Inefficiency for Many Objectives. *IEEE Transactions on Evolutionary Computation*, *28*(5), 1442–1454. <https://doi.org/10.1109/TEVC.2023.3320278>
- Ziemian, S., Okwara, M., & Ziemian, C. W. (2015). Tensile and fatigue behavior of layered acrylonitrile butadiene styrene. *Rapid Prototyping Journal*, *21*(3), 270–278. <https://doi.org/10.1108/RPJ-09-2013-0086>
- Zonoobi, M. A., Haghshenas Gorgani, H., & Javaherneshan, D. (2023). Experimental investigation and multi-objective optimization of FDM process parameters for mechanical strength, dimensional accuracy, and cost using a hybrid algorithm. *Scientia Iranica*, *0*(0), 0–0. <https://doi.org/10.24200/sci.2023.60960.7090>