



DAFTAR PUSTAKA

- Ahvenainen, P., Kontro, I., & Svedström, K. (2016). Comparison of sample crystallinity determination methods by X-ray diffraction for challenging cellulose I materials. *Cellulose*, 23(2), 1073–1086. <https://doi.org/10.1007/s10570-016-0881-6>
- Ali, M. F., Kamal, M., & Islam, S. (2020). Comparative Study on Physical Properties of Different Types of Leather in Bangladesh. *Mahbub Kamal Journal of Engineering Research and Application*, 10(02 (Series-III)), 55–63. <https://doi.org/10.9790/9622-1002035563>
- Antony, J. (2023). 4—A systematic methodology for design of experiments. In J. Antony (Ed.), *Design of Experiments for Engineers and Scientists (Third Edition)* (pp. 33–50). Elsevier. <https://doi.org/10.1016/B978-0-443-15173-6.00002-0>
- Aravindhan, R., Madhan, B., Thanikaivelan, P., Kanth, S. V., Rao, J. R., Gnanasekaran, C. S., & Nair, B. U. (2008). Upgradation of leathers: Masking defects using pigments in pre-finishing processes. *Journal of Scientific & Industrial Research*, 67(March), 233–238.
- Ariram, N., Pradeep, S., Sundaramoorthy, S., & Madhan, B. (2022). Single pot low float chromium tanning: Cleaner pathway approach to environment friendly leather manufacturing. *Process Safety and Environmental Protection*, 167, 434–442. <https://doi.org/10.1016/j.psep.2022.09.024>
- BASF. (2007). *Pocket Book for The Leather Technologist* (4th ed.). BASF Aktiengesellschaft 67056.
- Bickley, J. C., Lee, H., & Whitton, J. B. (1967). Comparison Between Conventional Chrome Tannage and Heated Low Float Tannage. *Journal Society Leather Technologists and Chemists*, 51, 385–397.
- Boujelben, R., Ellouze, M., Aziz, F., Ouazzani, N., & Sayadi, S. (2022). Box-Behnken approach for optimization of Cr(III) removal from a real tanning effluent using powdered marble. *International Journal of Environmental Science and Technology*, 19(5), 4305–4320. <https://doi.org/10.1007/s13762-021-03410-2>
- BSN. (1989). *Cara menyiapkan contoh uji kulit untuk pengujian fisis dan kimiawi. SNI 06-0643-1989*. Badan Standardisasi Nasional.
- BSN. (1998). *Cara uji tembus uap air pada kulit jadi. SNI 06-4587-1998*. Badan Standardisasi Nasional.
- BSN. (2005). *Cara Uji Suhu Pengkerutan Kulit Tersamak. SNI 06-7127-2005*. Badan Standardisasi Nasional.
- BSN. (2011a). *Kulit jaket domba/kambing. SNI 4593:2011*.



- BSN. (2011b). *Kulit—Domba/kambing krom basah (wet blue)—Spesifikasi. SNI 3538:2011*. Badan Standardisasi Nasional.
- BSN. (2012a). *Kulit—Metoda uji fisis dan mekanis—Penentuan kelembasan. Leather—Physical and mechanical test—Determination of softness. SNI 17235:2012*. Badan Standardisasi Nasional.
- BSN. (2012b). *Kulit—Metoda uji fisis dan mekanis—Persiapan dan pengkondisian contoh. SNI ISO 2419:2012*. Badan Standardisasi Nasional.
- BSN. (2013). *SNI ISO 5398-1: 2013: Kulit—Penentuan kimiawi kadar krom oksida—Bagian 1: Kuantifikasi dengan cara titrasi*. Badan Standardisasi Nasional.
- BSN. (2017). *Kulit—Uji Kimiawi, fisis, mekanis dan ketahanan—Lokasi pengambilan contoh uji. SNI ISO 2418:2017*. Badan Standardisasi Nasional.
- BSN. (2019). *SNI 6989-84:2019—Air dan Limbah—Bagian 84: Cara uji logam terlarut dan logam total secara Spektrometri Serapan Atom (SSA)—Nyala*. Badan Standardisasi Nasional.
- Carsote, C., & Badea, E. (2019). Micro differential scanning calorimetry and micro hot table method for quantifying deterioration of historical leather. *Heritage Science*, 7(48), 1–13. <https://doi.org/10.1186/s40494-019-0292-8>
- Christner, J., Doeppert, F., Fennen, J., & Pelckmans, J. T. (2012). Managing Chrome in Leather Manufacture. *Journal of American Leather Chemist Association*, 107, 409–415.
- Covington, A. D. (2009). *Tanning Chemistry: The Science of Leather* (1st ed.). The Royal Society of Chemistry.
- Daniels, R. P. (1994). *World Leather*. 7(2), 73.
- Das, S., & Mishra, S. (2017). Box-Behnken statistical design to optimize preparation of activated carbon from *Limonia acidissima* shell with desirability approach. *Journal of Environmental Chemical Engineering*, 5(1), 588–600. <https://doi.org/10.1016/j.jece.2016.12.034>
- Dettmer, A., Cavalli, E., Ayub, M. A. Z., & Gutterres, M. (2012). Optimization of the unhairing leather processing with enzymes and the evaluation of inter-fibrillary proteins removal: An environment-friendly alternative. *Bioprocess and Biosystems Engineering*, 35, 1317–1324. <https://doi.org/10.1007/s00449-012-0719-z>
- Dewani, R., Pervez, M. K., Mahboob, S. J., Ayaz, T., & Soomro, S. A. (2023). Objective review: Advanced testing and toxicity of restricted substances for sustainable leather industry. *Journal of American Leather Chemist Association*, 118(3), 117–128.



- Ding, Y. qiao, Guo, D. hui, Cheng, J. yong, Zhang, H. yong, & Sui, M. meng. (2016). A description of hydrogen bonds in the chromium(III)-crosslinked collagen: Insight from the molecular dynamics simulation. *Structural Chemistry*, 27(4), 1255–1263. <https://doi.org/10.1007/s11224-016-0752-7>
- Doherty, S. P., Henderson, S., Fiddymment, S., Finch, J., & Collins, M. J. (2021). Scratching the surface: The use of sheepskin parchment to deter textual erasure in early modern legal deeds. *Heritage Science*, 9(29), 29. <https://doi.org/10.1186/s40494-021-00503-6>
- Ekpenyong, M., Antai, S., Asitok, A., & Ekpo, B. (2017). Response surface modeling and optimization of major medium variables for glycolipopeptide production. *Biocatalysis and Agricultural Biotechnology*, 10, 113–121. <https://doi.org/10.1016/j.bcab.2017.02.015>
- Elkady, E. F., Fouad, M. A., & Mozayad, A. N. (2022). Application of Box-Behnken experimental design and response surface methodology for selecting the optimum RP-HPLC conditions for the simultaneous determination of methocarbamol, indomethacin and betamethasone in their pharmaceutical dosage form. *BMC Chemistry*, 16(1), 1–15. <https://doi.org/10.1186/s13065-022-00908-9>
- Fan, Q., Ma, J., & Xu, Q. (2019). Insights into functional polymer-based organic-inorganic nanocomposites as leather finishes. *Journal of Leather Science and Engineering*, 1(1), 2–10. <https://doi.org/10.1186/s42825-019-0005-9>
- Fourneau, M., Canon, C., Van Vlaender, D., Collins, M. J., Fiddymment, S., Poumay, Y., & Deparis, O. (2020). Histological study of sheep skin transformation during the recreation of historical parchment manufacture. *Heritage Science*, 8(1), 1–7. <https://doi.org/10.1186/s40494-020-00421-z>
- Gao, D., Cheng, Y., Wang, P., Li, F., Wu, Y., Lyu, B., Ma, J., & Qin, J. (2020). An eco-friendly approach for leather manufacture based on P(POSS-MAA)-aluminum tanning agent combination tannage. *Journal of Cleaner Production*, 257(120546), 1–13. <https://doi.org/10.1016/j.jclepro.2020.120546>
- Griyanitasari, G. (2017). Pengaruh Penambahan Jumlah Pigmen Pada Lapisan Dasar (Base Coat) Pada Proses Finishing Terhadap Sifat Fisik Kulit Sapi. *Buletin Peternakan*, 41(3), 307–318. <https://doi.org/10.21059/buletinpeternak.v41i3.16649>
- Gulbinienė, A., Jankauskaitė, V., & Arcišauskaitė, R. (2003). Effect of Leather Finishing on Water Vapour Transmission. Part I. Water Vapour Transfer through Pigment Finished Leather. *Material Science (Medžiagotyra)*, 9(3), 275–280.
- Gulbinienė, A., Jankauskaitė, V., & Urbelis, V. (2008). The Influence of Laminated Leather Structure on the Water Vapour Absorption and Desorption Behaviour. *Materials Science (Medžiagotyra)*, 14(1), 44–50.



- He, X., Wang, Y., Zhou, J., Wang, H., Ding, W., & Shi, B. (2019). Suitability of Pore Measurement Methods for Characterizing the Hierarchical Pore Structure of Leather. *Journal of The American Leather Chemists Association*, 114(2), 41–47. <https://doi.org/10.34314/jalca.v115i1.1465>
- Hou, X., Wang, X., Hou, S., Dang, J., Zhang, X., Tang, J., Shi, Y., Ma, S., & Xu, Z. (2024). Comparative skin ultrastructure and transcriptome analysis of indigenous, improved meat goats, and dairy goats breeds identified key genes and potential molecular mechanisms affecting goatskin quality. *BMC Genomics*, 25(1070), 1–13. <https://doi.org/10.21203/rs.3.rs-4544510/v1>
- Huang, W., Song, Y., Yu, Y., Wang, Y., & Shi, B. (2020). Interaction between retanning agents and wet white tanned by a novel bimetal complex tanning agent. *Journal of Leather Science and Engineering*, 2(1), 7–9. <https://doi.org/10.1186/s42825-020-00023-2>
- Indrajaya, I. N. R., Irfansyah, A. N., & Pirngadi, H. (2021). Titration otomatis untuk mengukur kadar kalsium karbonat (CaCO₃) pada batu kapur. *Jurnal Teknis ITS*, 10(2), 108–113.
- ISO. (2011). *Leather—Physical and mechanical test—Determination of tear load—Part 1: Single edge tear. ISO 3377-1:2011*. International Organization for Standardization.
- ISO. (2012). *Leather—Test for colour fastness—Colour fastness to crocking. ISO 20433:2012*. International Organization for Standardization.
- ISO. (2016). *Leather—Physical and mechanical test—Determination of thickness. ISO 2589: 2016*. International Organization for Standardization.
- ISO. (2020). *Leather—Physical and mechanical test—Determination of tensile strength and percentage elongation. ISO 3376: 2020*. International Organization for Standardization.
- ISO. (2021). *Personal protective equipment—Test method for footwear. ISO 20344: 2021*. International Organization for Standardization.
- ISO (International Standard Organization). (2007). *ISO 20879:2007 Footwear performance requirements for footwear-upper*. International Standard Organization.
- Jamwal, A., Agrawal, R., Sharma, M., Dangayach, G. S., & Gupta, S. (2020). Application of optimization techniques in metal cutting operations: A bibliometric analysis. *Materials Today: Proceedings*, 38, 365–370. <https://doi.org/10.1016/j.matpr.2020.07.425>
- Jawahar, M., Vani, K., & Chandra Babu, N. K. (2016). Leather Species Identification Based on Surface Morphological Characteristics using Image Analysis Technique. *Journal of American Leather Chemist and Association*, 111(8), 308–314.



- Jayakumar, G. C., Sathish, M., Aravindhan, R., & Rao, J. R. (2016). Studies on the use of Bi-functional Enzyme for Leather Making. *Journal of The American Leather Chemists Association*, 111(12), 455–460.
- Jayathilakan, K., Sultana, K., Radhakrishna, K., & Bawa, A. S. (2012). Utilization of byproducts and waste materials from meat, poultry and fish processing industries: A review. *Journal of Food Science and Technology*, 49(3), 278–293. <https://doi.org/10.1007/s13197-011-0290-7>
- Jean Serge, E., Alla, J. P., Belibi, P. D. B., Mbadcam, K. J., & Fathima, N. N. (2019). Clay/polymer nanocomposites as filler materials for leather. *Journal of Cleaner Production*, 237(117837), 9. <https://doi.org/10.1016/j.jclepro.2019.117837>
- Jinwei, Z., Nian, C., Nan, Z., & Wuyong, C. (2017). Hydrolysis and Olation of Chromium Sulphate Under Microwave Irradiation. *Journal of Society of Leather Technologist and Chemist*, 101(1), 1–5.
- John, G. (1996). *Possible Defects in Leather Production: Definitions, Causes, Consequences, Remedies, and Types of Leather*. Lampertheim Germany: Gerhard John.
- Kasmudjiastuti, E., & Murti, R. S. (2017). The effects of finish type on permeability and organoleptic properties of python (*Python reticulatus*) skin finished leather. *Majalah Kulit, Karet, Dan Plastik*, 33(1), 19–28. <https://doi.org/10.20543/mkkip.v33i1.1575>
- Kasmudjiastuti, E., Prayitno, P., Pidhatika, B., & Griyanitasari, G. (2016). Pengaruh perbedaan jumlah penambahan binder uretan dan berbagai motif embossing terhadap kualitas kulit reject. *Majalah Kulit, Karet, dan Plastik*, 32(1), 39–50. <https://doi.org/10.20543/mkkip.v32i1.958>
- Kechagias, J. D., & Vidakis, N. (2022). Parametric optimization of material extrusion 3D printing process: An assessment of Box-Behnken vs. Full-factorial experimental approach. *International Journal of Advanced Manufacturing Technology*, 121(5–6), 3163–3172. <https://doi.org/10.1007/s00170-022-09532-2>
- Kelly, S. J., Edmonds, R. L., Cooper, S., Sizeland, K. H., Wells, H. C., Ryan, T., Kirby, N., Hawley, A., Mudie, S., & Haverkamp, R. G. (2018). Mapping Tear Strength and Collagen Fibril Orientation in Bovine, Ovine and Cervine Hides and Skins. *Journal of American Leather Chemist and Association*, 113, 1–10.
- Keskin, S., Cheaburu-Yilmaz, C. N., Altinisik Tagac, A., Darie-Nita, R. N., & Yilmaz, O. (2025). Synthesis of Acrylic–Urethane Hybrid Polymer Dispersions and Investigations on Their Properties as Binders in Leather Finishing. *Polymers*, 17(308), 1–20. <https://doi.org/10.3390/polym17030308>
- Khan, Z., Shafique, M., Jabeen, N., Naz, S. A., Yasmeen, K., Ejaz, U., & Sohail, M. (2023). Protease from *Bacillus subtilis* ZMS-2: Evaluation of production



- dynamics through Response Surface Methodology and application in leather tannery. *Journal of King Saud University - Science*, 35(4), 1–7. <https://doi.org/10.1016/j.jksus.2023.102643>
- Kumar, A. G., Swarnalatha, S., Sairam, B., & Sekaran, G. (2008). Production of alkaline protease by *Pseudomonas aeruginosa* using proteinaceous solid waste generated from leather manufacturing industries. *Bioresource Technology*, 99(6), 1939–1944. <https://doi.org/10.1016/j.biortech.2007.03.025>
- Kumari, B., Tiwary, R. K., Yadav, M., & Singh, K. M. P. (2021). Nonlinear regression analysis and response surface modeling of Cr (VI) removal from synthetic wastewater by an agro-waste *Cocos Nucifera*: Box-Behnken Design (BBD). *International Journal of Phytoremediation*, 23(8), 791–808. <https://doi.org/10.1080/15226514.2020.1858399>
- Kumari, M., & Gupta, S. K. (2019). Response surface methodological (RSM) approach for optimizing the removal of trihalomethanes (THMs) and its precursor's by surfactant modified magnetic nanoadsorbents (sMNP)—An endeavor to diminish probable cancer risk. *Scientific Reports*, 9(18339), 1–11. <https://doi.org/10.1038/s41598-019-54902-8>
- Kumari, N. (2012). A Study of the Recruitment and Selection process: SMC Global. *Industrial Engineering Letters*, 2(1), 34–43.
- Lanxess. (2022). *Chromosal B*. <https://Lanxess.in/Industries-Products-India/Industries-India/Leather-India/Chromosal-India/>.
- Li, K., Yu, R., Zhu, R., Liang, R., Liu, G., & Peng, B. (2019). PH-Sensitive and Chromium-Loaded Mineralized Nanoparticles as a Tanning Agent for Cleaner Leather Production. *ACS Sustainable Chemistry and Engineering*, 7(9), 8660–8669. <https://doi.org/10.1021/acssuschemeng.9b00482>
- Li, Y., Jin, Y., Zhou, R., Zeng, W., & Mei, J. (2024). A rapid room-temperature self-healing, antibacterial, photoluminescent waterborne polyurethane coating with excellent mechanical properties based on double dynamic cross-linked network used for leather finishing. *Progress in Organic Coatings*, 190(108386), 1–12. <https://doi.org/10.1016/j.porgcoat.2024.108386>
- Li, Y., Zhang, C., Luo, F., & Peng, B. (2018). A new approach for quantitative characterization of hydrolytic action of proteases to elastin in leather manufacturing. *Applied Microbiology and Biotechnology*, 102(24), 10485–10494. <https://doi.org/10.1007/s00253-018-9419-1>
- Liu, H., Yin, Z., Zhang, Q., Li, X., Tang, K., Liu, J., Pei, Y., Zheng, X., & Ferah, C. E. (2019). Mathematical modeling of bovine hides swelling behavior by response surface methodology for minimization of sulfide pollution in leather manufacture. *Journal of Cleaner Production*, 237(2019), 109. <https://doi.org/10.1016/j.jclepro.2019.117800>



- Ludvík, J., & Buljan, J. (2000). *Chrome Management in The Yard: Regional Programme for Pollution Control in The Tanning Industry in South-East Asia* (US/RAS/92/120/11-51; pp. 1–40). United Nations Industrial Development Organization.
- Lyu, B., Chang, R., Gao, D., & Ma, J. (2018). Chromium Footprint Reduction: Nanocomposites as Efficient Pretanning Agents for Cowhide Shoe Upper Leather. *ACS Sustainable Chemistry & Engineering*, 6(4), 5413–5423. <https://doi.org/10.1021/acssuschemeng.8b00233>
- Ma, J., Lv, X., Gao, D., Li, Y., Lv, B., & Zhang, J. (2014). Nanocomposite-based green tanning process of suede leather to enhance chromium uptake. *Journal of Cleaner Production*, 72(2014), 120–126. <https://doi.org/10.1016/j.jclepro.2014.03.016>
- Memon, H., Chaklie, E. B., Yesuf, H. M., & Zhu, C. (2021). Study on Effect of Leather Rigidity and Thickness on Drapability of Sheep Garment Leather. *Materials*, 14(4553), 2–11. <https://doi.org/10.3390/ma14164553>
- Mengistie, E., Smets, I., & Van Gerven, T. (2016). Ultrasound assisted chrome tanning: Towards a clean leather production technology. *Ultrasonics Sonochemistry*, 32, 204–212. <https://doi.org/10.1016/j.ultsonch.2016.03.002>
- Miao, K., Li, X., Yang, D., Xu, Y., Mu, C., Li, D., & Ge, L. (2021). Hydrothermal shrinkage behavior of pigskin. *Thermochimica Acta*, 699, 1–8. <https://doi.org/10.1016/j.tca.2021.178896>
- Müller, B., & Poth, U. (2019). *Coatings Formulation: An International Textbook* (ke 2). Vincentz Network. <https://doi.org/10.1515/9783748600268>
- Mutlu, M., Ork, N., Yegin, O., & Bas, S. (2014). Mapping the variation of tensile strength over the area of sheepskin leather. *Annals of The University of Oradea Fascicle of Textile, Leatherwork*, 15, 157–162.
- Najmuddin, M., & Nasich, M. (2019). Produktivitas Induk Domba Ekor Tipis di Desa Sedan Kecamatan Sedan Kabupaten Rembang. *Ternak Tropika, Journal of Tropical Animal Production*, 20(1), 76–83. <https://doi.org/10.21776/ub.jtapro.2019.020.01.10>
- Nalbat, S., Onem, E., Basaran, B., Yorgancioglu, A., & Yilmaz, O. (2016). Effect of Finishing Density on the Physico-Mechanical Properties of Leather. *Journal of The Society of Leather Technologists and Chemists*, 100(2), 84–89.
- Nalyanya, K. M., Rop, R. K., Onyuka, A. S., Kilee, T., Migunde, P. O., & Ngumbu, R. G. (2016). Thermal and dynamic mechanical analysis of bovine hide: Effect of chrome-tanning process. *Journal of Thermal Analysis and Calorimetry*, 126(2), 725–732. <https://doi.org/10.1007/s10973-016-5535-2>



- Nasr, A. I. (2017). Influence of some mechanical finishing processes on manufactured leather properties. *Majalah Kulit, Karet, Dan Plastik*, 33(2), 99–107. <https://doi.org/10.20543/mkcp.v33i2.3139>
- Nikonova, A., Andreyeva, O., & Maistrenko, L. (2016). Application of Advanced Polymeric Compounds for Development of Leather Production. *IOP Conference Series: Materials Science and Engineering*, 111, 012024. <https://doi.org/10.1088/1757-899X/111/1/012024>
- Onem, E., Yorgancioglu, A., Bitlisli, B. O., Yilmaz, O., Cavdar, U., Yilmaz, Y., & Isbecer, A. (2025). An approach on sustainable leather production system and method: Chromium tanning in vacuum operated reaction vessel for sheepskins. *Journal of Industrial Textiles*, 55, 15280837241307856. <https://doi.org/10.1177/15280837241307856>
- Onem, E., Yorgancioglu, A., Karavana, H. A., & Yilmaz, O. (2017). Comparison of different tanning agents on the stabilization of collagen via differential scanning calorimetry. *Journal of Thermal Analysis and Calorimetry*, 129(1), 615–622. <https://doi.org/10.1007/s10973-017-6175-x>
- Ouyang, M., Hu, K., Jiang, Q., Yao, Q., Zhou, H., Deng, Y., Shen, Y., Li, F., Zhuang, L., & Wang, G. (2022). An approach on chromium discharge reduction: Effect and mechanism of ketone carboxylic acid as high exhaustion chrome tanning agent. *Journal of Cleaner Production*, 367(133125), 1–12. <https://doi.org/10.1016/j.jclepro.2022.133125>
- Pahlawan, I. F., & Kasmudjiastuti, E. (2012). Pengaruh jumlah minyak terhadap sifat fisis kulit ikan nila (*Oreochromis niloticus*) untuk bagian atas sepatu. *Majalah Kulit, Karet, dan Plastik*, 28(2), 105. <https://doi.org/10.20543/mkcp.v28i2.113>
- Pahlawan, I. F., Purbowati, E., Mulyani, S., Adiwintarti, R., Purnomoadi, A., Rianto, E., & Restitrisnani, V. (2023). The evaluation on the quality of lambskin leather originated from lambs fed by different feedstuffs. *AIP Conference Proceedings*, 2586, 040008-1–7. <https://doi.org/10.1063/5.0106682>
- Ponsubbiah, S., & Gupta, D. S. (2018). Role of Machineries for Film Forming in Leather Finishing. *International Journal of Latest Technology in Engineering, Management & Applied Science*, VII(IV), 330–337.
- Prokein, M., Hoffmanns, D., & Renner, M. (2023). Determination of dye uptake in leather coatings for waterless leather dyeing by ScCO₂ impregnation. *The Journal of Supercritical Fluids*, 198, 105933. <https://doi.org/10.1016/j.supflu.2023.105933>
- Pusat Data dan Sistem Informasi Pertanian. (2020). *Outlook Komoditas Kambing/Domba Tahun 2020*. Pusat Data dan Sistem Informasi Pertanian, Sekretariat Jenderal - Kementerian Pertanian.
- Salvatore, L., Gallo, N., Natali, M. L., Terzi, A., Sannino, A., & Madaghiele, M. (2021). Mimicking the Hierarchical Organization of Natural Collagen:



- Toward the Development of Ideal Scaffolding Material for Tissue Regeneration. *Frontiers in Bioengineering and Biotechnology*, 9. <https://doi.org/10.3389/fbioe.2021.644595>
- Santos, L. M., Gutterres, M., Aquim, P. M., & Priebe, G. (2005). Influence of fats during leathermaking. *2nd Mercosur Congress on Chemical Engineering. 4th Mercosur Congress on Process Systems Engineering*, 14–18.
- Sathish, M., azhar, Z. M. J., Fathima, N. N., & Rao, J. R. R. R. (2015). Effect of finishing auxiliaries on permeability of leathers. *Journal of the American Leather Chemists Association*, 110(11), 372–378.
- Schroepfer, M., & Meyer, M. (2017). DSC investigation of bovine hide collagen at varying degrees of crosslinking and humidities. *International Journal of Biological Macromolecules*, 103, 120–128. <https://doi.org/10.1016/j.ijbiomac.2017.04.124>
- Silvestre, F., Rocrelle, C., Rigal, L., & Gaset, A. (1994). Optimum conditions for the reactivity of chromium (III) salts on collagen in the solvent tanning process. *Journal of Chemical Technology & Biotechnology*, 60(1), 1–6. <https://doi.org/10.1002/jctb.280600102>
- Sizeland, K. H., Wells, H. C., Kelly, S. J. R., Edmonds, R. L., Kirby, N. M., Hawley, A., Mudie, S. T., Ryan, T. M., & Haverkamp, R. G. (2017). The influence of water, lanolin, urea, proline, paraffin and fatliquor on collagen D-spacing in leather. *RSC Adv.*, 7(64), 40658–40663. <https://doi.org/10.1039/C7RA05560A>
- Smiechowski, K., Zarlok, J., & Kowalska, M. (2014). The relationship between water vapour permeability and softness for leathers produced in Poland. *Journal of the Society of Leather Technologist & Chemist*, 98(6), 259–263.
- Song, Y., Zeng, Y., Xiao, K., Wu, H., & Shi, B. (2017). Effect of Molecular Weight of Acrylic Resin Retanning Agent on Properties of Leather. *Journal of the American Leather Chemist Association*, 112(04), 128–134.
- Sugihartono, Yuny Erwanto, & Rina Wahyuningsih. (2019). *Kolagen dan Gelatin untuk Industri Pangan dan Kesehatan* (A. R. P. Utami, Ed.). Lily Publisher.
- Sun, Y., Chen, W.-L., Lin, S.-J., Jee, S.-H., Chen, Y.-F., Lin, L.-C., So, P. T. C., & Dong, C.-Y. (2006). Investigating Mechanisms of Collagen Thermal Denaturation by High Resolution Second-Harmonic Generation Imaging. *Biophysical Journal*, 91(7), 2620–2625. <https://doi.org/10.1529/biophysj.106.085902>
- Tan, Y., & Chang, S. K. C. (2018). Isolation and characterization of collagen extracted from channel catfish (*Ictalurus punctatus*) skin. *Food Chemistry*, 242(September 2017), 147–155. <https://doi.org/10.1016/j.foodchem.2017.09.013>



- Tang, K., Wang, F., Liu, Jie, Jia, P., & Liu, Jinglong. (2013). Water vapor permeability of leathers by grey system theory. *Reviews on Advanced Materials Science*, 33(4), 373–382.
- Testex. (Tanpa tahun). *TS Water Vapour Absorption Tester: Instruction Manual*. Testex.
- Tu, Y. H., Ahn, M., Rakonjac, J., Holmes, G., & Norris, G. (2022). Milk provides the basis for an eco-friendly shorter process for skin preservation and leather manufacture. *Cleaner Engineering and Technology*, 8. <https://doi.org/10.1016/j.clet.2022.100464>
- Uddin, M. M., Hasan, M. J., Mahmud, Y., Zohra, F. T., & Ahmed, S. (2020). Evaluating suitability of glutaraldehyde tanning in conformity with physical properties of conventional chrome-tanned leather. *Textile and Leather Review*, 3(3), 135–145. <https://doi.org/10.31881/TLR.2020.09>
- Ugbaja, M. I., Ejila, A., Mamza, P. A. P., Uzochukwu, M. I., & Opara, H. (2007). *Evaluation and Application of Acrylic Based Binder for Leather Finishing*. 5(4), 4635–4644. <https://doi.org/10.56625/jipho.v7i4.385>
- Venkatramani, J., & Sahu, B. (2022). A Mini Review Role of Natural Binders in Leather Finishing- A Comparative Approach. *Journal of the American Leather Chemist Association*, 117(6), 223–231.
- Wang, J., Xu, H., Battocchi, D., & Bierwagen, G. (2014). The determination of critical pigment volume concentration (CPVC) in organic coatings with fluorescence microscopy. *Progress in Organic Coatings*, 77(12), 2147–2154. <https://doi.org/10.1016/j.porgcoat.2013.12.010>
- Wionczyk, B., Ławińska, K., Woźnicki, D., Wójcik, J., & Pietrzak, K. (2020). Study and new criteria for the assessment of upholstery leathers with a pigment finish in relation to the characteristics recommended in the PN-EN 13336 standard. *Fibres & Textiles in Eastern Europe*, 28(2(140)), 80–89. <https://doi.org/10.5604/01.3001.0013.7320>
- Xiao, Y., Wang, Y., Ren, K., Wang, C., Sang, J., Ma, M., Ma, L., & Lin, W. (2025). Engineering design of amphoteric acrylic polymer for rapid and reduced wet-finishing process of eco-leather production towards energy saving and carbon reduction. *Polymer*, 326, 128331. <https://doi.org/10.1016/j.polymer.2025.128331>
- Yao, Q., Chen, H., Huang, H., & Liu, B. (2018). Mechanism and effect of hydroxyl-terminated dendrimer as excellent chrome exhausted agent for tanning of pickled pelt. *Journal of Cleaner Production*, 202, 543–552. <https://doi.org/10.1016/j.jclepro.2018.08.164>
- Yao, Q., Wang, Y., Chen, H., Huang, H., & Liu, B. (2019). Mechanism of High Chrome Uptake of Tanning Pickled Pelt by Carboxyl-Terminated Hyper-Branched Polymer Combination Chrome Tanning. *ChemistrySelect*, 4(2), 670–680. <https://doi.org/10.1002/slct.201802952>



- Zengin, A. C. A., Oğlakcioğlu, N., & Bitlisli, B. O. (2017). Effect of Finishing Techniques on Some Physical Characteristics of Shoe Upper Leathers. *Textile and Apparel*, 27(2), 198–203.
- Zhang, J., & Chen, W. (2020). A rapid and cleaner chrome tanning technology based on ultrasound and microwave. *Journal of Cleaner Production*, 247(119452). <https://doi.org/10.1016/j.jclepro.2019.119452>
- Zhang, J., Wang, Y., Teng, B., & Chen, W. (2013). New chrome tanning method assisted by wringing and ultrasound. *Journal of the American Leather Chemist Association*, 108, 445–448.
- Zhang, Y., Mansel, B. W., Naffa, R., Cheong, S., Yao, Y., Holmes, G., Chen, H.-L., & Prabakar, S. (2018). Revealing Molecular Level Indicators of Collagen Stability: Minimizing Chrome Usage in Leather Processing. *ACS Sustainable Chemistry & Engineering*, 6(5), 7096–7104. <https://doi.org/10.1021/acssuschemeng.8b00954>
- Zhang, Y., Snow, T., Smith, A. J., Holmes, G., & Prabakar, S. (2019). A guide to high-efficiency chromium (III)-collagen cross-linking: Synchrotron SAXS and DSC study. *International Journal of Biological Macromolecules*, 126, 123–129. <https://doi.org/10.1016/j.ijbiomac.2018.12.187>
- Zhu, R., Yang, C., Li, K., Yu, R., Liu, G., & Peng, B. (2020). A smart high chrome exhaustion and chrome-less tanning system based on chromium (III)-loaded nanoparticles for cleaner leather processing. *Journal of Cleaner Production*, 277(123278), 1–13. <https://doi.org/10.1016/j.jclepro.2020.123278>