UNIVERSITAS
GADJAH MADA
**Pengaruh Variasi Konsentrasi Pigmen Termokromik melalui Metode Spray Coating terhadap Sifat Optik
dan Termal Kayu Transparan**
Timotius William Wuisang, Dr. Ir. Nur Abdillah Siddiq, S.T., IPP.; Ir. Sentagi Sesotya Utami, S.T., M.Sc., Ph.D., IPU.
Universitas Gadjah Mada, 2026 | Diunduh dari http://etd.repository.ugm.ac.id/

DAFTAR PUSTAKA

[1] K. Taing, P. Andre, and P. Leclercq, "Analysis of Thermal Performance of Naturally Ventilated Residential Building in Tropical Climate: Case Study of Phnom Penh, Cambodia," *IOP Conf. Ser. Earth Environ. Sci.*, vol. 1199, no. 1, p. 012038, Jul. 2023, doi: 10.1088/1755-1315/1199/1/012038.

[2] *ANSI/ASHRAE Standard 55-2017, thermal environmental conditions for human occupancy*.

[3] A. Aderinsola, O. Dare-Abel, O. Arayela, and O. Ajayi, "Evaluating Thermal Comfort Standards of Residential Housing in Tropical Climates: A Systematic Review," *J. Built Environ. Geol. Res.*, Aug. 2025, doi: 10.70382/ajbegr.v8i4.045.

[4] T. Karyono, "Predicting Comfort Temperature in Indonesia, an Initial Step to Reduce Cooling Energy Consumption," *Buildings*, vol. 5, no. 3, pp. 802–813, Jul. 2015, doi: 10.3390/buildings5030802.

[5] W. H. Ko *et al.*, "The impact of a view from a window on thermal comfort, emotion, and cognitive performance," *Build. Environ.*, vol. 175, p. 106779, May 2020, doi: 10.1016/j.buildenv.2020.106779.

[6] J. L. Aguilar-Santana, M. Velasco-Carrasco, and S. Riffat, "Thermal Transmittance (U-value) Evaluation of Innovative Window Technologies," *Future Cities Environ.*, vol. 6, no. 1, p. 12, Dec. 2020, doi: 10.5334/fce.99.

[7] R. Mi *et al.*, "A Clear, Strong, and Thermally Insulated Transparent Wood for Energy Efficient Windows," *Adv. Funct. Mater.*, vol. 30, no. 1, p. 1907511, Jan. 2020, doi: 10.1002/adfm.201907511.

[8] T. B. Jele, J. Andrew, M. John, and B. Sithole, "Engineered transparent wood composites: a review," *Cellulose*, vol. 30, no. 9, pp. 5447–5471, Jun. 2023, doi: 10.1007/s10570-023-05239-z.

[9] Y. Li, Q. Fu, S. Yu, M. Yan, and L. Berglund, "Optically Transparent Wood from a Nanoporous Cellulosic Template: Combining Functional and Structural Performance," *Biomacromolecules*, vol. 17, no. 4, pp. 1358–1364, Apr. 2016, doi: 10.1021/acs.biomac.6b00145.

[10] Y. Li, E. Vasileva, I. Sychugov, S. Popov, and L. Berglund, "Optically Transparent Wood: Recent Progress, Opportunities, and Challenges," *Adv. Opt. Mater.*, vol. 6, no. 14, p. 1800059, Jul. 2018, doi: 10.1002/adom.201800059.

[11] N. Li *et al.*, "Evaluation of optical properties and chemical structure changes in enzymatic hydrolysis lignin during heat treatment," *RSC Adv.*, vol. 7, no. 34, pp. 20760–20765, 2017, doi: 10.1039/C7RA02005H.

[12] M. Li *et al.*, "Construction and mechanism analysis of flame-retardant, energy-storage and transparent bio-based composites based on natural cellulose template," *Int. J. Biol. Macromol.*, vol. 263, p. 130317, Apr. 2024, doi: 10.1016/j.ijbiomac.2024.130317.

[13] D. A. Maharani, N. A. Siddiq, and S. S. Utami, "The Potential of Transparent Wood Biocomposites for Sustainable Acoustics Panel Membrane," *J. Stud. Sci. Eng.*, vol. 5, no. 2, pp. 144–158, Dec. 2025, doi: 10.53898/josse2025537.

UNIVERSITAS GADJAH MADA
Pengaruh Variasi Konsentrasi Pigmen Termokromik melalui Metode Spray Coating terhadap Sifat Optik dan Termal Kayu Transparan
Timotius William Wuisang, Dr. Ir. Nur Abdillah Siddiq, S.T., IPP.; Ir. Sentagi Sesotya Utami, S.T., M.Sc., Ph.D., IPU.
Universitas Gadjah Mada, 2026 | Diunduh dari http://etd.repository.ugm.ac.id/

[14] H. Zhang, F. Xu, L. Xu, and C. Zheng, "The effect of delignification ratio on the PMMA occupation in poplar wood cell wall by the macro and micro comparative study," *J. Wood Sci.*, vol. 69, no. 1, p. 10, Feb. 2023, doi: 10.1186/s10086-023-02082-5.

[15] R. Mi *et al.*, "Scalable aesthetic transparent wood for energy efficient buildings," *Nat. Commun.*, vol. 11, no. 1, p. 3836, Jul. 2020, doi: 10.1038/s41467-020-17513-w.

[16] T. Le Duc, Nguyen Thanh-Long, Nguyen Thi Mai Huong, Ngo Thanh Hai, Cong Ngoc Thang, and Tong Thi Thanh Huong, "Fabrication of Transparent Wood by Impregnation of Epoxy Resin into Modified Balsa Wood for Application in Energy Saving Materials," *Vietnam J. Catal. Adsorpt.*, vol. 14, no. 1, pp. 45–50, Mar. 2025, doi: 10.62239/jca.2025.009.

[17] A. Samanta, H. Chen, P. Samanta, S. Popov, I. Sychugov, and L. A. Berglund, "Reversible Dual-Stimuli-Responsive Chromic Transparent Wood Biocomposites for Smart Window Applications," *ACS Appl. Mater. Interfaces*, vol. 13, no. 2, pp. 3270–3277, Jan. 2021, doi: 10.1021/acsami.0c21369.

[18] L. Zhang, A. Wang, T. Zhu, Z. Chen, Y. Wu, and Y. Gao, "Transparent Wood Composites Fabricated by Impregnation of Epoxy Resin and W-Doped VO_2 Nanoparticles for Application in Energy-Saving Windows," *ACS Appl. Mater. Interfaces*, vol. 12, no. 31, pp. 34777–34783, Aug. 2020, doi: 10.1021/acsami.0c06494.

[19] X. Guo, S. Daka, M. Fan, X. Lin, and W. Sun, "Reversibly thermochromic wood," *J. Mater. Sci.*, vol. 58, no. 5, pp. 2188–2197, Feb. 2023, doi: 10.1007/s10853-022-08042-6.

[20] Z. Tatíčková, J. Kudláček, M. Zoubek, and J. Kuchař, "Behaviour of Thermochromic Coatings under Thermal Exposure," *Coatings*, vol. 13, no. 3, p. 642, Mar. 2023, doi: 10.3390/coatings13030642.

[21] X. Yan, Y. Chang, and X. Qian, "Effect of the Concentration of Pigment Slurry on the Film Performances of Waterborne Wood Coatings," *Coatings*, vol. 9, no. 10, p. 635, Oct. 2019, doi: 10.3390/coatings9100635.

[22] M. H. Ramage *et al.*, "The wood from the trees: The use of timber in construction," *Renew. Sustain. Energy Rev.*, vol. 68, pp. 333–359, Feb. 2017, doi: 10.1016/j.rser.2016.09.107.

[23] S.- Slamet, B.- Santoso, and Q.- Qomaruddin, "KARAKTERISASI SIFAT FISIS, MEKANIS DAN REDAMAN AKUSTIK KAYU LOKAL SEBAGAI BAHAN ALAT MUSIK," *J. Mech. Des. Test.*, vol. 5, no. 2, Dec. 2023, doi: 10.22146/jmdt.74965.

[24] R. Ghozali, T. Susdiyanti, K. B. Meiganati, and K. Krisdianto, "STRUKTUR ANATOMI KAYU YANG DIPERDAGANGKAN DI KABUPATEN ACEH BESAR," *J. Nusa Sylva*, vol. 22, no. 1, pp. 27–33, Jun. 2023, doi: 10.31938/jns.v22i1.496.

[25] K. Ziemińska, M. Westoby, and I. J. Wright, "Broad Anatomical Variation within a Narrow Wood Density Range—A Study of Twig Wood across 69 Australian Angiosperms," *PLOS ONE*, vol. 10, no. 4, p. e0124892, Apr. 2015, doi: 10.1371/journal.pone.0124892.

UNIVERSITAS
GADJAH MADA
**Pengaruh Variasi Konsentrasi Pigmen Termokromik melalui Metode Spray Coating terhadap Sifat Optik
dan Termal Kayu Transparan**
Timotius William Wuisang, Dr. Ir. Nur Abdillah Siddiq, S.T., IPP.; Ir. Sentagi Sesotya Utami, S.T., M.Sc., Ph.D., IPU.
Universitas Gadjah Mada, 2026 | Diunduh dari http://etd.repository.ugm.ac.id/

[26] E. Prihatini, A. Maddu, I. S. Rahayu, and M. Kurniati, "Sifat Dasar Kayu Ganitri (Elaeocarpus sphaericus (Gaertn.) K. Schum.) dari Sukabumi dan Potensi Penggunaannya," *J. Ilmu Kehutan.*, vol. 14, no. 1, p. 109, Jul. 2020, doi: 10.22146/jik.57480.

[27] S. Gea, *Kimia Kayu dan Modifikasinya*. Medan: USU Press, 2021.

[28] J. Zakzeski, P. C. A. Bruijnincx, A. L. Jongerius, and B. M. Weckhuysen, "The Catalytic Valorization of Lignin for the Production of Renewable Chemicals," *Chem. Rev.*, vol. 110, no. 6, pp. 3552–3599, Jun. 2010, doi: 10.1021/cr900354u.

[29] B. Liu *et al.*, "Effect of Substituents on Molecular Reactivity during Lignin Oxidation by Chlorine Dioxide: A Density Functional Theory Study," *Int. J. Mol. Sci.*, vol. 24, no. 14, p. 11809, Jul. 2023, doi: 10.3390/ijms241411809.

[30] X. Zhang, L. Li, and F. Xu, "Chemical Characteristics of Wood Cell Wall with an Emphasis on Ultrastructure: A Mini-Review," *Forests*, vol. 13, no. 3, p. 439, Mar. 2022, doi: 10.3390/f13030439.

[31] Y. Wu, J. Zhou, Q. Huang, F. Yang, Y. Wang, and J. Wang, "Study on the Properties of Partially Transparent Wood under Different Delignification Processes," *Polymers*, vol. 12, no. 3, p. 661, Mar. 2020, doi: 10.3390/polym12030661.

[32] Y. Li, Q. Fu, R. Rojas, M. Yan, M. Lawoko, and L. Berglund, "Lignin-Retaining Transparent Wood," *ChemSusChem*, vol. 10, no. 17, pp. 3445–3451, Sep. 2017, doi: 10.1002/cssc.201701089.

[33] W. Gan, S. Xiao, L. Gao, R. Gao, J. Li, and X. Zhan, "Luminescent and Transparent Wood Composites Fabricated by Poly(methyl methacrylate) and γ-Fe_2O_3 @YVO_4:Eu^{3+} Nanoparticle Impregnation," *ACS Sustain. Chem. Eng.*, vol. 5, no. 5, pp. 3855–3862, May 2017, doi: 10.1021/acssuschemeng.6b02985.

[34] Y. Li, E. Vasileva, I. Sychugov, S. Popov, and L. Berglund, "Optically Transparent Wood: Recent Progress, Opportunities, and Challenges," *Adv. Opt. Mater.*, vol. 6, no. 14, p. 1800059, Jul. 2018, doi: 10.1002/adom.201800059.

[35] P. Terzopoulou, E. C. Vouvoudi, and D. S. Achilias, "Delignification as a Key Strategy for Advanced Wood-Based Materials: Chemistry, Delignification Parameters, and Emerging Applications," *Forests*, vol. 16, no. 6, p. 993, Jun. 2025, doi: 10.3390/f16060993.

[36] L. V. Hai, N. Srikanth, T. D. T. Le, S. H. Park, and T. H. Kim, "Transparent Wood Fabrication and Applications: A Review," *Molecules*, vol. 30, no. 7, p. 1506, Mar. 2025, doi: 10.3390/molecules30071506.

[37] A. Rudin and P. Choi, *The elements of polymer science and engineering*, Third edition. San Diego: Elsevier/AP, 2013.

[38] A. Shundo, S. Yamamoto, and K. Tanaka, "Network Formation and Physical Properties of Epoxy Resins for Future Practical Applications," *JACS Au*, vol. 2, no. 7, pp. 1522–1542, Jul. 2022, doi: 10.1021/jacsau.2c00120.

[39] A. Gomez-Lopez *et al.*, "Poly(hydroxyurethane) Adhesives and Coatings: State-of-the-Art and Future Directions," *ACS Sustain. Chem. Eng.*, vol. 9, no. 29, pp. 9541–9562, Jul. 2021, doi: 10.1021/acssuschemeng.1c02558.

UNIVERSITAS
GADJAH MADA
**Pengaruh Variasi Konsentrasi Pigmen Termokromik melalui Metode Spray Coating terhadap Sifat Optik
dan Termal Kayu Transparan**
Timotius William Wuisang, Dr. Ir. Nur Abdillah Siddiq, S.T., IPP.; Ir. Sentagi Sesotya Utami, S.T., M.Sc., Ph.D., IPU.
Universitas Gadjah Mada, 2026 | Diunduh dari http://etd.repository.ugm.ac.id/

[40] Polimix, "Polyurethane: Everything you need to know about this versatile material." Apr. 2024. [Online]. Available: https://www.polimix.eu/en/post/what-is-polyurethane

[41] T. Türel, B. Eling, A. M. Cristadoro, T. Mathieu, M. Linnenbrink, and Ž. Tomović, "Novel Furfural-Derived Polyaldimines as Latent Hardeners for Polyurethane Adhesives," *ACS Appl. Mater. Interfaces*, vol. 16, no. 5, pp. 6414–6423, Feb. 2024, doi: 10.1021/acsami.3c17416.

[42] A. Hakami, S. S. Srinivasan, P. K. Biswas, A. Krishnegowda, S. L. Wallen, and E. K. Stefanakos, "Review on thermochromic materials: development, characterization, and applications," *J. Coat. Technol. Res.*, vol. 19, no. 2, pp. 377–402, Mar. 2022, doi: 10.1007/s11998-021-00558-x.

[43] S. Hossain, A. Sadoh, and N. M. Ravindra, "Principles, properties and preparation of thermochromic materials," *Mater. Sci. Eng. Int. J.*, vol. 7, no. 3, pp. 146–156, Aug. 2023, doi: 10.15406/mseij.2023.07.00218.

[44] D. Dinda, N. M. Pérez, J. Faraudo, D. Ruiz-Molina, and C. Roscini, "High-Contrast Colorless-to-Colored Thermochromic Materials," *Small*, vol. 21, no. 51, p. e11454, Dec. 2025, doi: 10.1002/smll.202511454.

[45] O. Panák, M. Držková, and M. Kaplanová, "Insight into the evaluation of colour changes of leuco dye based thermochromic systems as a function of temperature," *Dyes Pigments*, vol. 120, pp. 279–287, Sep. 2015, doi: 10.1016/j.dyepig.2015.04.022.

[46] A. B. M. Supian *et al.*, "Thermochromic Polymer Nanocomposites for the Heat Detection System: Recent Progress on Properties, Applications, and Challenges," *Polymers*, vol. 16, no. 11, p. 1545, May 2024, doi: 10.3390/polym16111545.

[47] X. Zhu, Y. Liu, N. Dong, and Z. Li, "Fabrication and characterization of reversible thermochromic wood veneers," *Sci. Rep.*, vol. 7, no. 1, p. 16933, Dec. 2017, doi: 10.1038/s41598-017-17238-9.

[48] A. Maho, S. Nayak, F. Gillissen, R. Cloots, and A. Rougier, "Film Deposition of Electrochromic Metal Oxides through Spray Coating: A Descriptive Review," *Coatings*, vol. 13, no. 11, p. 1879, Nov. 2023, doi: 10.3390/coatings13111879.

[49] W. Zhang, Y. Zou, X. Yan, and J. Li, "Influence of Two Types of Microcapsule Composites on the Performance of Thermochromic UV Coatings on Bleached Poplar Wood Surfaces," *Coatings*, vol. 15, no. 9, p. 1001, Aug. 2025, doi: 10.3390/coatings15091001.

[50] J. P. Holman, *Heat transfer*, 10. ed. in McGraw-Hill series in mechanical engineering. Boston, Mass.: McGraw-Hill Higher Education, 2010.

[51] Q. Zheng, S. Kaur, C. Dames, and R. S. Prasher, "Analysis and improvement of the hot disk transient plane source method for low thermal conductivity materials," *Int. J. Heat Mass Transf.*, vol. 151, p. 119331, Apr. 2020, doi: 10.1016/j.ijheatmasstransfer.2020.119331.

[52] S. Kumar B. N., C. S., A. K., Y. Urs S., and M. V B., "Methods to Measure the Thermal Conductivity," *Int. J. Innov. Sci. Res. Technol. IJISRT*, pp. 2383–2392, Sep. 2024, doi: 10.38124/ijisrt/IJISRT24AUG705.

UNIVERSITAS
GADJAH MADA
**Pengaruh Variasi Konsentrasi Pigmen Termokromik melalui Metode Spray Coating terhadap Sifat Optik
dan Termal Kayu Transparan**
Timotius William Wuisang, Dr. Ir. Nur Abdillah Siddiq, S.T., IPP.; Ir. Sentagi Sesotya Utami, S.T., M.Sc., Ph.D., IPU.
Universitas Gadjah Mada, 2026 | Diunduh dari http://etd.repository.ugm.ac.id/

[53] *ISO 22007-2:2022 Plastics, Determination of thermal conductivity and thermal diffusivity Part 2: Transient plane heat source (hot disc) method*.

[54] E. Hecht, *Optics*, 5 ed/fifth edition, Global edition. Boston Columbus Indianapolis New York San Francisco Amsterdam Cape Town Dubai London Madrid Milan Munich: Pearson, 2017.

[55] M. Chutturi *et al.*, "A comprehensive review of the synthesis strategies, properties, and applications of transparent wood as a renewable and sustainable resource," *Sci. Total Environ.*, vol. 864, p. 161067, Mar. 2023, doi: 10.1016/j.scitotenv.2022.161067.

[56] *ISO 8980-3:2013 Ophthalmic optics - Uncut finished spectacle lenses Part 3: Transmittance specifications and test methods*.

[57] B. Hill, Th. Roger, and F. W. Vorhagen, "Comparative analysis of the quantization of color spaces on the basis of the CIELAB color-difference formula," *ACM Trans. Graph.*, vol. 16, no. 2, pp. 109–154, Apr. 1997, doi: 10.1145/248210.248212.

[58] J. Beetsma, "The CIELAB System – the Method to Specify Colors of Coatings." [Online]. Available: https://www.ulprospector.com/knowledge/16423/pc-the-cielab-system-the-method-to-specify-colors-of-coatings/

[59] H. Yan *et al.*, "Heterogeneous Thermochromic Hydrogel Film Based on Photonic Nanochains," *Nanomaterials*, vol. 12, no. 11, p. 1867, May 2022, doi: 10.3390/nano12111867.

[60] G. E. P. Hardiwiyanto, N. A. Siddiq, and S. S. Utami, "STUDI FABRIKASI DAN KARAKTERISASI KAYU TRANSPARAN TERMOKROMIK BERDASARKAN SIFAT OPTIK DAN TERMAL," Universitas Gadjah Mada, 2025.

[61] Y. Du *et al.*, "Perovskite-Coated Thermochromic Transparent Wood: A Novel Material for Smart Windows in Energy-Efficient and Sustainable Buildings," *ACS Appl. Mater. Interfaces*, vol. 15, no. 42, pp. 49665–49677, Oct. 2023, doi: 10.1021/acsami.3c11706.

[62] S. Liu *et al.*, "Self-Densified Optically Transparent VO_2 Thermochromic Wood Film for Smart Windows," *ACS Appl. Mater. Interfaces*, vol. 13, no. 19, pp. 22495–22504, May 2021, doi: 10.1021/acsami.1c03803.

[63] A. F. Al Kahlout, F. Baharum, and A. A. M. Alqanoo, "Transparent wood for next-generation windows: A review of thermal transmittance, solar heat gain coefficient, and energy performance," *Build. Environ.*, vol. 276, p. 112880, May 2025, doi: 10.1016/j.buildenv.2025.112880.

[64] S. Liu *et al.*, "Bioinspired thermochromic transparent hydrogel wood with advanced optical regulation abilities and mechanical properties for windows," *Appl. Energy*, vol. 297, p. 117207, Sep. 2021, doi: 10.1016/j.apenergy.2021.117207.