

DAFTAR PUSTAKA

- Abraham, E., Deepa, B., Pothan, L.A., Jacob, M., Thomas, S., Cvelbar, U., Anandjiwala, R., 2011. Extraction of *nanocellulose* fibrils from lignocellulosic fibres: A novel approach. *Carbohydr. Polym.* 86, 1468–1475.
- Abraham, E., Deepa, B., Pothan, L.A., Cintil, J., Thomas, S., John, M.J., Anandjiwala, R., Narine, S.S., 2013. Environmental friendly method for the extraction of coir fibre and isolation of nanofibre. *Carbohydr. Polym.* 92, 1477–1483.
- Abdullah, N.M. dan Ahmad, I., 2013, "Potential of Using Polyester Reinforced Coconut Fiber Composites Derived from Recycling Polyethylene Terephthalate (PET) Waste", *Fibers and Polymers* 2013, Vol.14, No.4, 584-590.
- Alvira P, Tomas-Pejo E, Ballesteros M, Negro MJ. Pretreatment technologies for an efficient bioethanol production process based on enzymatic hydrolysis: a review. *Bioresour Technol* 2010;101:4851-61.
- Anarsis, W., 2006, "Agribisnis Komoditas Salak", Cetakan Ke-2, PT Bumi Aksara, Jakarta.
- Ansori, M., 2004, "Karakteristik Degradasi Buah Salak Pasca Pengawetan Dengan Perlakuan Radiasi Gamma", Jurusan TJP, Fakultas Teknik, Universitas Negeri Semarang, Indonesia.
- Arantes V, Saddler JN. Cellulose accessibility limits the effectiveness of minimum cellulase loading on the efficient hydrolysis of pretreated lignocellulosic substrates. *Biotechnol Biofuels* 2011;4:3.
- Arrakhiz, F.Z., El Achaby, M., Kakou, A.C., Vaudreuil, S., Benmoussa, K., Bouhfid, R., Fassi-Fehri, O. and Qaiss, A., 2012. Mechanical properties of high density polyethylene reinforced with chemically modified coir fibers: impact of chemical treatments. *Materials & Design*, 37, pp.379-383.

- Astabi, A., Raharjo, W.W., Sukanto, H., 2015. “Pengaruh Konsentrasi Silane Coupling Agent Terhadap Sifat Tarik Komposit Serat Kenaf-Poypropylene” Jurusan Teknik Mesin, Fakultas Teknik, Universitas Sebelas Maret, Indonesia.
- ASTM D3379, 1975, Standard Test Method for Tensile Strength and Young’s Modulus for High Modulus Single Filament Fibers, American Society of Testing and Materials (ASTM), Philadelphia, USA.
- Badan Pusat Statistik, 2015, Kalimantan Barat Dalam Angka, BPS Provinsi Kalimantan Barat, Pontianak.
- Bahrudin, Z., 2008, “Akselerasi Ekspor Salak melalui Pola Kemitraan”, Dirjen Pengolahan dan Pemasaran Hasil Pertanian, mengutip Harian Sinar Harapan, Olahan Pangan, Tabloid SINAR TANI. SMS ke: 0815 8441 4991.
- Bahrudin, Z., 2008, “Akselerasi Ekspor Salak melalui Pola Kemitraan”, Dirjen Pengolahan dan Pemasaran Hasil Pertanian, mengutip Harian Sinar Harapan, Olahan Pangan, Tabloid SINAR TANI.
- Chandra RP, Bura R, Mabee WE, Berlin A, Pan X, Saddler JN. Substrate pretreatment: the key to effective enzymatic hydrolysis of lignocellulosics *Adv Biochem Eng Biotechnol* 2007;108:67-93.
- Cherian, B.M., Leão, A.L., de Souza, S.F., Thomas, S., Pothan, L. a., Kottaisamy, M., 2010, “Isolation of nanocellulose from pineapple leaf fibres by steam explosion. *Carbohydr. Polym.* 81, 720–725.
- Darmanto, S., Rochardjo, H.S., Jamasri and Widyorini, R., 2017, January. Effects of alkali and steaming on mechanical properties of snake fruit (*Salacca*) fiber. In *AIP Conference Proceedings* (Vol. 1788, No. 1, p. 030060). AIP Publishing.
- Deepa, B., Abraham, E., Cherian, B. M., Bismarck, A., Blaker, J. J., Pothan, L. A., Leao, A. L., Souza, S. F. S., Kottaisamy, M., 2010. Structure, morphology and thermal characteristics of banana nano fibers obtained by steam explosion. *Bioresource Technology* 102, 1988–97

- Deepa, B., Abraham, E., Cherian, B.M., Bismarck, A., Blaker, J.J., Pothan, L.A., Leao, A.L., de Souza, S.F., Kottaisamy, M., 2011. Structure, morphology and thermal characteristics of banana nano fibers obtained by steam explosion. *Bioresour. Technol.* 102, 1988–97
- Diharjo, K., 2006. Pengaruh perlakuan alkali terhadap sifat tarik bahan komposit serat rami-polyester. *Jurnal Teknik Mesin*, 8(1), pp.pp-8.
- Fang H, Deng J, Zhang X (2011) Continuous steam explosion of wheat straw by high pressure mechanicalrefining system to produce sugars for bioconversion. *Bioresources* 6(4):4468-4480.
- FitzPatrick M, Champagne P, Cunningham MF, Whitney RA. A biorefinery processing perspective: treatmentof lignocellulosic materials for the production of value-added products. *Bioresour Technol* 2010;101:8915-22.
- Garrote G, Dominguez H, Parajo JC (1999) Hydrothermal processing of lignocellulosic materials.*Holzforschung.* 57:191-202.
- George, J., Weyenberg, I.V.D. Ivens, J dan Verpoest, I, 1999, ” Mechanical Properties o Flax Fibre Reinforced Epoxy Composites”, Department MTM, Katholieke Universiteit Leuven Belgium.
- Gibso, L. J., 2012, ”The hierarchical structure andmechanics of plant materials”, Department of Materials Science and Engineering, Massachusetts Institute of Technology,Cambridge, MA 02139, USA.
- Gomes, A, Goda, K. dan Ohgi J, 2004, ” Effect of Alkali Treatment to Reinforcement on Tensile Properties ofCuraua Fiber Green Composites ”, *JSME International Journal, Series A, Vol 47, No. 4. Hal 541 -546.*
- Gräve, L., Putniņa, A., Kukle, S., Stramkale, V., 2013. Steam Explosion Impact to Technical Hemp Fiber Diameter 1, 112–115
- Hahn-Hagerdal B, Galbe M, Gorwa-Grauslund MF, Liden G, Zacchi G. Bio-ethanol e the fuel of tomorrowfrom the residues of today. *Trends Biotechnol* 2006;24:549-56

- Han, G., Deng, J., Zhang, S., Bicho, P., Wu, Q., 2009. Effect of steam explosion treatment on characteristics of wheat straw. College of Material Science and Engineering, Northeast Forestry University, Harbin 150040, China.
- Hemsri, S., Grieco, K., Asandei, A.D. and Parnas, R.S., 2012. Wheat gluten composites reinforced with coconut fiber. *Composites Part A: Applied Science and Manufacturing*, 43(7), pp.1160-1168.
- Hestiawan, H., Jamasri and Kusmono, 2017. Effect of chemical treatments on tensile properties and interfacial shear strength of unsaturated polyester/fan palm fibers. *Journal of Natural Fibers*, pp.1-14.
- Ibrahima, C., Diop, K., Lavoie, J., Huneault, M.A., 2015. Structural changes of *Salix miyabeana* cellulose fibres during dilute-acid steam explosion: Impact of reaction temperature and retention time. *Carbohydr. Polym.* 119, 8–17.
- Intani, U.N., 2007, "Pemanfaatan Batang Salak Tua Dari Kecamatan Cineam, Kabupaten Tasikmalaya Jawa Barat Sebagai Salah Satu Bahan Baku Tekstil", Abstrak Tugas Akhir.
- Jacquet, N., Quiévy, N., Vanderghem, C., Janas, S., Blecker, C., Wathelet, B., Devaux, J., Paquot, M., 2011. Influence of steam explosion on the thermal stability of cellulose fibres 96, 1582–1588
- Jayabal, S., Velumani, S., Navaneethkrishnan, P. dan Palanikumar, K., 2013, "Mechanical and Machinability Behaviors of Woven Coir Fiber-Reinforced Polyester Composite", *Fibers and Polymers*, Vol.14, No.9, 1505-1514,
- Jayabal, S., Sathiyamurthy, S., Loganathan, K.T. dan Kalyanasundaram, S., 2012, "Effect of soaking time and concentration of NaOH solution on mechanical properties of coir–polyester composites", *Bull. Mater. Sci.*, Vol. 35, No. 4, pp. 567–574.
- Jeoh, T., 1998. *Steam explosion pretreatment of cotton gin waste for fuel ethanol production* (Doctoral dissertation, Virginia Tech).

- Jonsson LJ, Alrikasson B, Nilvebrant N-O. Bioconversion of lignocelluloses: inhibitors and detoxification. *Biotechnol Biofuels* 2013;6:16.
- Joseph, K., Filho, R.D.T., James, B., Thomas, S., dan Carvalho, L.H., 1999, " A Review on Sisal Fiber Reinforced Polymer Composites ", *R. Bras. Eng. Agric. Ambiental, Campina Grande*, v.3, n.3, p. 367-379
- John, M.J., dan Rajesh D. Anandjiwala, 2008, "Recent Developments in Chemical Modification and Characterization of Natural Fiber-Reinforced Composites", *CSIR Materials Science and Manufacturing, Fibers and Textiles Competence Area, Port Elizabeth 6000, 2Department of Textile Science, Faculty of Science, Published online in Wiley InterScience.*
- Khan, M.A., Mina F. dan Drzal, L.T., "Influence of Silane Coupling Agent of Different Functionalities on the Performance of Jute-Polycarbonate Composite", *Radiation and Polymer Chemistry Laboratory, Institu of Nuclear Science and Technology, Bangladesh.*
- Kumar R, Hu F, Sannigrahi P, Jung S, Ragauskas AJ, Wyman CE. Carbohydrate derived-pseudo-lignin can retard cellulose biological conversion. *Biotechnol Bioeng* 2012;110:737e53.
- Lee, H. V., Hamid, S. B. A., dan Zain, S. K., 2014, "Conversion of Lignocellulosic Biomass to Nanocellulose: Structure and Chemical Process", *Hindawi*, Vol. 2014, 631013.
- Li JB, Henriksson G, Gellerstedt G. Lignin depolymerization/repolymerization and its critical role for delignification of aspen wood by steam explosion. *Bioresour Technol* 2007;98:3061-8.
- Lynd LR, Laser MS, Bransby D, Dale BE, Davison B, Hamilton R, et al. How biotech can transform biofuels. *Nat Biotechnol* 2008;26:169e72.
- Manik, P., Eko Sasmita Hadi dan Dedi Cristianto, 2004, "Kajian Teknik Penggunaan Serat Bambu Sebagai Bahan Komposit Pembuatan Kulit Kapal", *Laporan Penelitian Dosen Muda, Dikti.*

Mason WH. Process and apparatus for disintegration of wood and the like. US Patent: 1578609; 1926

Mezey, Z., Danyadi, L., Tibor C. Dan Pukanszky, 2002, "Investigation of the Mechanical properties of Sisal Fiber Reinforced Polypropylene Composites", Budafest University of Technology and Economics, Hungary.

Michalowicz G, Toussaint B, Vignon MR. Ultrastructural changes in poplar cell wall during steam explosion treatment. *Holzforchung* 1991;45:175-9.

Munawar, S.S., Kenji Umemura · Fumio Tanaka dan Shuichi Kawai, 2007, "Effects of alkali, mild steam, and chitosan treatments on the properties of pineapple, ramie, and sansevieria fiber bundles", *J Wood Sci*, Research Institute for Sustainable Humanosphere, Kyoto University, Gokasho, Uji, Kyoto 611-0011, Japan.

Öztürk, H.B. dan Bechtold, T., 2007, , The Christian-Doppler-Laboratory for Textile and Fibre Chemistry in Cellulosics, Research Institute for Textile Chemistry and Textile Physics, University of Innsbruck, Vol. 15, No. 5 - 6 (64 - 65).

Palonen H, Viikari L. Role of oxidative enzymatic treatments on enzymatic hydrolysis of softwood. *BiotechnolBioeng* 2004;86:550-7.

Pan XJ, Zhang X, Gregg DJ, Saddler JN. Enhanced enzymatic hydrolysis of steam-exploded douglas fir wood by alkali-oxygen post-treatment. *Appl Biochem Biotechnol* 2004;113-116:1103-14.

Pan XJ, Zhang X, Xie D, Gregg DJ, Saddler JN. Strategies to enhance the enzymatic hydrolysis of pretreated softwood with high residual lignin content. *Appl Biochem Biotechnol* 2004;121-124:1069-80.

Panagiotopoulos IA, Chandra RP, Saddler JN. A two-stage pretreatment approach to maximise sugar yield and enhance reactive lignin recovery from poplar wood chips. *Bioresour Technol* 2013;130:570-7.

Perez J, Munoz-Dorado J, De-la-Rubia T, Martinez J. Biodegradation and biological treatment of cellulose, hemicelluloses and lignin: an overview. *Int Microbiol* 2002;5:53-63.

- Punsuvon, V., Vaithanomsat, P. and Iiyama, K., 2008. Simultaneous production of alpha-cellulose and furfural from bagasse by steam explosion pretreatment. *Maejo International Journal of Science and Technology*, 2 (1), pp.182-191.
- Qing Q, Yang B, Wyman CE. Xylooligomers are strong inhibitors of cellulose hydrolysis by enzymes. *Bioresour Technol* 2010;101:131-46.
- Qing Q, Wyman CE. Supplementation with xylanase and b-xylosidase to reduce xylo-oligomer and xylaninhibition of enzymatic hydrolysis of cellulose and pretreated corn stover. *Biotechnol Biofuels* 2011;4:18.
- Rochardjo, H.B.S, Jamasri, Widyorini, R., Darmanto, S, Bostelin, B. dan Kurniawan, 2014, "Peningkatan Kekuatan Teknik Serat Kelapa dan Sejenisnya Sebagai Serat Biokomposit Melalui Perlakuan Fisik Dan Kimia", Pra-eksperimen Distertasi S3 Teknik Mesin fak teknik UGM Yogyakarta.
- Rocha GJM, Martin C, da Silva VFN, Gomez EO, Goncalves AR. Mass balance of pilot-scale pretreatment of sugarcane bagasse by steam explosion followed by alkaline delignification. *Bioresour Technol* 2012;111:447-52.
- Rubin EM. Genomics of cellulosic biofuels. *Nature* 2008;454:841-5.
- Sanyoto, S., 2009, "Salak Magelang Diekspor ke China", Antara News Senin, 18 Mei 2009, Mengutip Bupati Magelang.
- Saraswati, I., 2008, "Suryo Agung Memaksimalkan Potensi Salak Pondoh", Inovasi Usaha, Kutipan dari Suryo Agung. Ketua kelompok Tani Salak.
- Schell DJ, Farmer J, Newman M, McMillan JD. Dilute sulfuric acid pretreatment of corn stover in pilot-scale reactor. *Appl Biochem Biotechnol* 2003;105-108:69-85.
- Shevchenko SM, Chang K, Robinson J, Saddler JN. Optimization of monosaccharide recovery by posthydrolysis of the water-soluble hemicellulose component after steam explosion of softwood chips. *Bioresour Technol* 2000;72:207-11.

- Silvija Kukle, Jānis Grāvītis, Anna Putniņa, A.S., 2011. The Effect Of Steam Explosion Treatment On Technical Hemp Fibres. *Environ. Technol. Resour. Proc. 8th Int. Sci. Pract. Conf. Vol. 1 1*, 230–237.
- Stefanus, Syahfudin dan Ridwan, 2004, Pengaruh Susunan Serat Kaca terhadap Kekuatan Komposit Plastik (Fiber Glass Reinforcement Plastic), Abstrak skripsi, Universitas Gunadarma.
- Sun SL, Wen JL, Ma MG, Sun RC, Jones GL. Structural features and antioxidant activities of degraded lignins from steam exploded bamboo stem. *Ind Crop Prod* 2014;56:128-36.
- Sun SN, Cao XF, Xu F, Sun RC, Jones GL. Structural features and antioxidant activities of lignins from steam exploded bamboo (*Phyllostachys pubescens*). *J Agric Food Chem* 2014;62:5939-47
- Sun XF, Xu F, Sun RC, Wang YX, Fowler P, Baird MS. Characteristics of degraded lignins obtained from steam exploded wheat straw. *Polym Degrad Stab* 2004;86:245-56.
- Sutka, A., Kukle, S., Gravitis, J., Berzins, A., 2013. Chemical and physical modification of hemp fibres by steam explosion technology. *Mater. Sci. Eng.* 012053, 49
- Supardi, 2009, "2010 Banjarnegara Ekspor Salak ke Luar Negeri", Laporan daerah Kab. Banjarnegara.
- Tanahashi M (1990) Characterization and degradation mechanisms of wood components by steam explosion and utilization of exploded wood. *Wood Research* 77:49-117.
- Taurista, A.Y., Agita O. R. dan Khrisna H. P., 2005, "Komposit Laminat Bambu Serat Woven Sebagai Bahan Alternatif Pengganti Fiber Glass pada Kulit Kapal", Laporan (PKMI) Program Kreatif Mahasiswa, Dikti.
- Theuretzbacher, F., Lizasoain, J., Lefever, C., Saylor, M.K., Enguidanos, R., Weran, N., Gronauer, A., Bauer, A., 2015. Steam explosion pretreatment of wheat

straw to improve methane yields: Investigation of the degradation kinetics of structural compounds during anaerobic digestion. *Bioresour. Technol.* 179, 299–30

Thongsang, S., dan Sombatsompop, N., 2005, "Effect of Filler Surface Treatment on Properties of Fly Ash/NR Blend", *Polymer Processing and Flow Group, School of Eng & Material King Mongkut's University of Technology Thonburi (KMUTT) Bangkok Thailand.*

Tjahjadi, N., 2007, "Bertanam Salak", Cetakan ke-15, Kanisius, Yogyakarta.

Wang, B., 2004, "Pre-Treatment of Flax Fibers for Use in Rotationally Molded Biocomposites", Thesis for degree of Master of Science, Department of agricultural and Bioresource Engineering, University of Saskatchewan.

Wang, B., Panigrahi, S., Crerar, and Tabil, L., 2003, "Application of Pre-Treated Flax Fibers in Composites", Department of Agricultural and Bioresource Engineering, University of Saskatchewan 57 Campus Drive, Saskatoon, SK S7N 5A9 Canada.

Wang, B., Panigrahi, S., Tabil, L., Crerar, W dan Sokansanj, S., 2003, "Modification Flax Fiber by Chemical Treatment", Presentasi di CSAE/SCGR 2003 Meeting Montreal Quebec entitled "Different Functionalities on the Performance of Jute-Polycarbonate Composite", Radiation and Polymer Chemistry Laboratory, Institute of Nuclear Science and Technology, Bangladesh

Wang, K., Chen, J., Sun, S., Sun, R., 2015. Chapter 6 – Steam Explosion. *Pretreatment of Biomass.* 75-104.

Wang K, Jiang JX, Xu F, Sun RC. Effects of incubation time on the fractionation and characterization of lignin during steam explosion pretreatment. *Ind Eng Chem Res* 2012;51:2704-13.

- Wang K, Sun RC. Biorefinery straw for bioethanol. In: Sun RC, editor. Cereal straw as a resource for sustainable biomaterials and biofuels. Oxford: Elsevier; 2011. pp. 267-87.
- Wang K, Jiang JX, Xu F, Sun RC. Influence of steaming explosion time on the physic-chemical properties of cellulose from Lespedeza stalks (*Lespedeza crytobotrya*). *Bioresour Technol* 2009;100:5288-94.
- Wang K, Jiang JX, Xu F, Sun RC. Influence of steaming pressure on steam explosion pretreatment of *Lespedeza* stalks (*Lespedeza crytobotrya*): Part 1. Characteristics of degraded cellulose. *Polym Degrad Stab* 2009;94:1379-88.
- Willy, D., Adhitama, G.P., 2008, "Pemanfaatan Dahan Salak (*Salacca Edullis*) untuk Komponen Interior & Kria: Sebuah Upaya Pelestarian Perkebunan Salak Cineam, Tasikmalaya", hasil penelitian dan pemberdayaan masyarakat bekerjasama dengan IKM Manikmaya, Yayasan Apikayu, KK Manusia dan Ruang Interior ITB, PP Seni Rupa dan Desain ITB, LPPM ITB
- Wijaya, H, 2009, "Singapura dan Cina, Potensi Tujuan Ekspor Salak Nglumut", *Harian Suara Merdeka*, 11 Desember 2009.
- Yamashiki T, Matsui T, Saitoh M, Okajima K, Kamide K. Characterisation of cellulose treated by the steam explosion method. Part 1: influence of cellulose resources on changes in morphology, degree of polymerisation, solubility and solid structure. *Br Polym J* 1990;22:73-83.
- Yang B, Boussaid A, Mansfield SD, Gregg DJ, Saddler JN. Fast and efficient alkaline peroxide treatment to enhance the enzymatic digestibility of steam-exploded softwood substrates. *Biotechnol Bioeng* 2002;77:678-84.
- Yang B, Wyman CE. BSA treatment to enhance enzymatic hydrolysis of cellulose in lignin containing substrates. *Biotechnol Bioeng* 2006;94:611e7.