

TABLE OF CONTENTS

APPROVAL PAGE.....	ii
STATEMENT OF ORIGINAL AUTHORSHIP.....	iii
DEDICATION.....	iv
ACKNOWLEDGEMENTS.....	v
TABLE OF CONTENTS.....	vii
LIST OF FIGURES.....	x
LIST OF TABLES.....	xiii
ABBREVIATIONS.....	xiv
ABSTRACT.....	xv
INTISARI.....	xvi
Chapter I. INTRODUCTION.....	1
1.1 Background.....	1
1.2 Formulation of the Problem.....	5
1.3 Limitations of the Research.....	6
1.4 Research Aims.....	6
1.5 Research Advantages.....	6
Chapter II. LITERATURE REVIEW.....	7
Chapter III THEORETICAL BACKGROUND.....	11
3.1 Plasma.....	11
3.1.1 Plasma definition.....	11
3.1.2 Basics Plasma Parameters.....	12
3.1.3 Plasma Sheath.....	15
3.1.4 Plasma Oscillations.....	17
3.2 Elementary Ion Sources.....	18
3.2.1 Terminology.....	18
3.2.2 Quintessential Ion Source.....	19
3.2.3 Ion Beam Formation.....	19
3.3 Radio Frequency-driven Ion Source.....	19
3.3.1 Source Operation with an External RF Antenna.....	20
3.3.2 Multiscup Source Operation with an Internal RF Antenna.....	21
3.4 Ion Extraction.....	23
3.4.1 Ion Extraction from Plasma Ion Source.....	23
3.4.2 Beam Quality.....	28
3.5 Compact Neutron Generator.....	33
3.5.1 Axial Neutron Generator.....	33
3.5.2 Co-axial Neutron Generator.....	35
3.5.3 Fusion-based White Neutron Source.....	36
3.6 Collimator.....	38
3.6.1 Moderator.....	39

3.6.2 An Example of Shielding and Collimator.....	39
3.7 Target System.....	39
3.8 MCNPX (Monte Carlo N-Particle eXtended).....	40
3.8.1 SurfaceCard.....	41
3.8.2 Data Card.....	43
3.8.3 Cell Card.....	44
3.8.4 Running Simulation onMCNPX.....	45
3.8.5 Tally (Parameter Calculation).....	46
3.9 SIMION Software.....	46
3.10 Stopping and Range of Ions in Matter (SRIM).....	50
3.11 Subcritical Assembly for Molybdenum-99 Production (SAMOP).....	51

Chapter IV RESEARCH METHODOLOGY.....55

4.1 Literature Study.....	56
4.2 Place of Research.....	56
4.3 Research Procedure.....	56
4.3.1 Literature Study about SIMION Software.....	56
4.3.2 Literature Study about SRIM Software.....	60
4.3.3 Literature Study about MCNPX Program.....	60
4.4 Table of Data Analysis.....	62
4.4.1 Plasma Chamber Simulation.....	62
4.4.2 System Extraction Simulation.....	64
4.4.3 Target System Simulation.....	64
4.4.4 Collimator Simulation.....	65

Chapter V RESULTS AND DISCUSSIONS.....67

5.1 The plasmaChamber.....	67
5.1.1 Theoretical Analytical Analysis of Magnetic Field and Electric Field using Maple Program.....	67
5.1.2 Simulation of Magnetic and Electric Field using SIMION Software.....	70
5.1.3 Kinetic Energy Distribution.....	78
5.2 Extraction System.....	89
5.2.1 Deuterium Ion D ⁺ Beam Extraction.....	89
5.2.2 Parallel Ion Beam.....	92
5.3 Target System.....	94
5.3.1 Simulation of the Target using the Stopping and Range of Ions in Matter (SRIM) Program.....	94
5.3.2 Energy Variation from the Target Ti-T (Titanium-Tritium) using the SRIM Program.....	96
5.3.4 Data Analysis from the Simulation of the Target using SRIM Program.....	97
5.4 Collimator	100
5.4.1 Collimator Simulations using MCNPX Software.....	100



Chapter VI CONCLUSION AND SUGGESTION.....	107
6.1 Conclusion.....	107
6.2 Suggestion.....	108
REFERENCES.....	109
APPENDIX A.....	112
APPENDIX B.....	125
APPENDIX C.....	150
APPENDIX D.....	152
APPENDIX E.....	154
APPENDIX F.....	157

LIST OF FIGURES

Figure 3.1	Plasma potential and the regions between the plasma and the wall (Cinar, 2011).....	16
Figure 3.2	The elemental ion source: a plasma source for ion production and an electrode system for forming the ions into a beam (Brown,2004).....	19
Figure 3.3	A Thonemann type RF ion source.....	21
Figure 3.4	Schematic diagram of the RF multicusp ion source.....	22
Figure 3.5	Schematic of Field and Power in RF Coil.....	23
Figure 3.6	Diode extraction system and beam formation. PE – plasma electrode; GND – ground electrode; d – gap distance; d^* – real gap distance; r -aperture radius.....	24
Figure 3.7	The plasma meniscus for (a) convex, (b) flat plasma and (c) concave plasma (Abdelrahman and Abdelsalam, 2011).....	25
Figure 3.8	AXCEL-INP simulation for a diode system with three different plasma densities and the same voltage drop. From left to right: $N1 < N2 < N3$ (Brown, 2004).....	27
Figure 3.9	Triode system with potential lines from -6 kV to 55 kV. Electrodes from left to right: Plasma electrode (PE), screening electrode (SE), ground electrode (GND). Left: Potential lines without ion beam. Right: Potential lines with ion beam (Brown, 2004).....	27
Figure 3.10	Simplified schematic of some different kinds of extractor systems (Brown, 2004).....	28
Figure 3.11	The beam of many particles (Bernal, 2008).....	29
Figure 3.12	Accelerator and Beam Diagnostics (Bernal, 2008).....	29
Figure 3.13	Variation of the ellipse along the transport line (Bernal, 2008).....	30
Figure 3.14	The emittance ellipse (Bernal, 2008).....	31
Figure 3.15	AXCEL-INP simulation for extraction of a nearly parallel ion beam (left), and extraction with increased field strength (right), favorable for accelerator injection application.....	33
Figure 3.16	Triode extraction system designed for a high intensity proton beam (Brown, 2004).....	33
Figure 3.17	Axial extraction neutron generator (Leung et al, 2015).....	34
Figure 3.18	Co-axial neutron generator (Lou, 2003).....	36
Figure 3.19	Ion beam dynamics simulation using IGUN.....	36
Figure 3.20	Neutron spectra due to D-D, D-T, and T-T reactions (Lou, 2003).....	37
Figure 3.21	Neutron production cross-section for D-D, D-T, and D-T reactions (Lou, 2003).....	37
Figure 3.22	Design Collimator for a reaction D-T (Anggraeni et al, 2016).....	38

Figure 3.23	The historical development of the MCNPX from the original theoretical idea of several physicist: Fermi, Richtmyer, Von Neumann, Ulam, Metropolis, etc. (Pelowitz et al, 2008).....	40
Figure 3.24	Example of geometry in the xz plane.....	44
Figure 3.25	Example of geometry in the xy plane.....	44
Figure 3.26	Geometry in 3D.....	44
Figure 3.27	The initial view of the running process (Pelowitz, 2008)....	45
Figure 3.28	SAMOP using CNG.....	52
Figure 3.29	SAMOP device (Syarip et al, 2016)	53
Figure 3.30	Schematic Diagram of the SAMOP System (Huisman, 2013).....	54
Figure 4.1	Flow Chart of Ion plasma simulation using SIMION Software.....	57
Figure 4.2	Flow Chart of Extraction System using SIMION Software... ..	58
Figure 4.3	Flow Chart of the Target System using SRIM program.....	60
Figure 4.4	Flow Chart of Collimator using MCNPX program	61
Figure 5.1	Schematic of a loop on the coil positioned outside the plasma chamber.....	68
Figure 5.2	Magnetic field as a function of position (m)	69
Figure 5.3	Electric Field of the Cylindrical Loop	70
Figure 5.4	Magnetic field of various currents.....	73
Figure 5.5	Electric Field of Various Current.....	73
Figure 5.6	Magnetic field with various N-turns.....	74
Figure 5.7	Electric Field of Various N-turns.....	74
Figure 5.8	Magnetic Field of various dimensions.....	75
Figure 5.9	Electric Field of Various Dimensions.....	76
Figure 5.10	Magnetic Field of Various Radius.....	76
Figure 5.11	Electric Field of Various Radius.....	77
Figure 5.12	Electrons kinetic energy as a function of coils current.....	79
Figure 5.13	Electrons kinetic energy as a function of number of coils turns.....	80
Figure 5.14	Electron kinetic energy as a function of coils radius.....	80
Figure 5.15	Kinetic Energy distribution with ToF 0.05 and coil radius 50 mm, as a function of radial distance from the center axis of the plasma chamber.....	81
Figure 5.16	Electrons kinetic energy as a function of electrons time of flight.....	82
Figure 5.17	Kinetic Energy Distribution for various electrons time of flight.....	83
Figure 5.18	Electrons kinetic energy as a function of electrons omega 1.....	84
Figure 5.19	Electrons kinetic energy as a function of electrons omega 2.....	85
Figure 5.20	The electron impact ionization cross section as function of electron energy for Deuterium (Ian, 2004).....	85

Figure 5.21	Percentage of Kinetic Energy with Time of Flight (ToF) Variation.....	86
Figure 5.22	Percentage of Kinetic Energy with Current Variations.....	87
Figure 5.23	Percentage of Kinetic Energy with Radius Variation.....	87
Figure 5.24	Percentage of Kinetic Energy with N-turns Variation.....	88
Figure 5.25	Percentage of Kinetic Energy with Omega Variation.....	88
Figure 5.26	Construction of electrodes for extraction system.....	90
Figure 5.27	Distribution total of the simulation of ion extraction for (100e- +100D+) until (1500e- +1500D+).....	91
Figure 5.28	Kinetic Energy variation of the simulation of ion extraction for (100e- +100D+) until (1500e- +1500D+)....	91
Figure 5.29	Emittance plot of the extracted beam using SIMION program.....	92
Figure 5.30	Construction of electrodes for extraction system.....	93
Figure 5.31	Extraction ion Simulation for parallel ion beam on 1XY-axis, on 2ZY-axis, on 3XZ-axis and on 3D view using SIMION program.....	94
Figure 5.32	Active cooled Ti-T target with the supporting material Al used to capture the accelerated ion D+ beam.....	95
Figure 5.33	Energy variations for the simulation of the target Ti-T with 1000 ions and with Ti-T atomic ratio of 1:1 using SRIM software.....	96
Figure 5.34	Energy variations for the simulation of the target Ti-T with 1000 ions and with Ti-T atomic ratio of 1:2 using SRIM software.....	97
Figure 5.35	Energy variations for the simulation of the target Ti-T with 1000 ions and with Ti-T atomic ratio of 2:1 using SRIM software.....	97
Figure 5.36	A simple schematic of energy with depth x varying energy 100keV until 200 keV to see the reaction will happen on energy 100keV.....	98
Figure 5.37	Schematic of collimator design with the radius of moderator 4 cm.....	101
Figure 5.38	Neutron flux with material of moderator variation.....	102
Figure 5.39	Neutron flux with thickness of moderator variation.....	103
Figure 5.40	Neutron flux with thickness of reflector Variation	
Figure 5.41	104
	Neutron flux with length of moderator Variation.....	105
Figure 5.42	Neutron flux with source of neutron flux variation	106

LIST OF TABLES

Table 3.1	The mnemonic for various surface geometry, and their mathematical equation	41
Table 3.2	Types of Tally	46
Table 3.3	Specification Data Terrace SAMOP and Components Supporting Surrounding	53
Table 4.1	Analysis of plasma chamber for coils currents variation.....	62
Table 4.2	Analysis of plasma chamber for coils number variation.....	62
Table 4.3	Analysis of plasma chamber for distance between coils variation.....	62
Table 4.5	Analysis of plasma chamber for omega 1 variation.....	63
Table 4.6	Analysis of plasma chamber for omega 2 variation.....	63
Table 4.7	Data for the Extraction Ion Simulation from (100e- + 100D+ until (1500e- + 1500D+)......	64
Table 4.8	Analysis table for the target system using SRIM program...	64
Table 4.9	Simulation of material moderator with thickness 5cm	65
Table 4.10	Simulation of Moderator Thickness Variation.....	66
Table 4.11	Simulation of radius moderator	66
Table 4.12	Simulation of Source of neutron flux Variation	66