



DAFTAR PUSTAKA

- Anugraha, R., Tamura, K., Hidaka, Y., Oikawa, N., & Kai, S. (2008). Order-disorder phase transition in a chaotic system. *Physical Review Letters*, *100*, 1–4.
- Anonim-a. (2013). Thermoplastic Polysulfone (PSF). http://www.substech.com/dokuwiki/doku.php?id=thermoplastic_polysulfone_psf. diakses 21 Mei 2018.
- Baccaro, S., Pajewski, L. A., Scoccia, G., Volpe, R., & Rosiak, J. M. (1995). Mechanical properties of polyvinylpyrrolidone (PVP) hydrogels undergoing radiation. *Nuclear Inst. and Methods in Physics Research B*, *105*, 100–102.
- Berreman, D.W. (1972). Solid surface shape and the alignment of an adjacent nematic liquid crystal. *Physical Review Letters*, *28*, 1683–1686.
- Blinov, L.M. (2011). *Structure and Properties of Liquid Crystals*. Netherlands, NL: Springer.
- Blinov, L.M., & Chigrinov, V.G. (1994). *Electrooptic Effects in Liquid Crystal Materials*. New York, USA: Springer-Verlag New York, Inc.
- Bognitzki, M., Czado, W., Frese, T., Schaper, A., Hellwig, M., Steinhart, M., ... Wendorff, J.H. (2001). Nanostructured fibers via electrospinning. *Adv. Mater*, *13*, 70–72.
- Cai, X., Zhu, P., Lu, X., Liu, Y., & Sun, D. (2017). Electrospinning of very long and highly aligned fibers. *Journal of Materials Science*, *52*, 14004–14010.
- Chandrasekar, S. (1992). *Liquid Crystal* (2nd ed.). Newyork, USA: Cambridge University Press.
- De Gennes, P.G., & Prost, J. (1993). *The Physics of Liquid Crystals* (2nd ed.). Oxford, England: Oxford University Press.
- Demus, D., Goodby, J., Gray, G.W., Spiess, H.-W., & Vill, V. (1998). *Physical Properties of Liquid Crystal: Fundamentals* (Vol. 1). Weinheim, Germany: Willey-VCH.
- Dersch, R., Graeser, M., Greiner, A., & Wendorff, J.H. (2007). Electrospinning of nanofibres: towards new techniques, functions, and applications. *J. Chem*, *60*, 719–728.
- de Souza, R.F., -Ke Yang, D., Lenzi, E.K, Evangelista, L.R., & Zola, R.S. (2014). Effect of surface viscosity, anchoring energy, and cell gap on the response time of nematic liquid crystals. *Annals of Physics*, *346*, 14–21.
- Gopal, R., Kaur, S., Feng, C.Y., Chan, C., Ramakrishna, S., Tabe, S., & Matsuura, T. (2007). Electrospun nanofibrous polysulfone membranes as pre-filters: Particulate removal. *Membrane Science*, *289*, 210–219.
- Gou, Y., Liu, C., Lei, T., & Yang, F. (2014). Nanofiber alignment during electrospinning: effects of collectorstructure and governing parameters. *International Conference on Manipulation, Manufacturing and Measurement on the Nanoscale (3M-NANO)*, 62–65.



- Hoogboom, J., Rasing, T., Rowan, A.E., & Nolte, R.J.M. (2005). LCD alignment layers. Controlling nematic domain properties. *Journal of Materials Chemistry*, 16, 1305–1314.
- Huang, L., Bui, N., Manickam, S.S., & McCutcheon, J.R. (2011). Controlling electrospun nanofiber morphology and mechanical properties using humidity. *Journal of Polymer Science, Part B*, 49, 1734–1744.
- Huh, J., Yusuf, Y., Hidaka, Y., & Kai, S. (2002). Prewavy instability of nematic liquid crystals in a high-frequency electric field. *Physical Review E*, 66, 031705.
- Kakade, M.V., Givens, S., Gardner, K., Lee, K.H., Chase, D.B., & Rabolt, J.F. (2007). Electric field induced orientation of polymer chains in macroscopically aligned electrospun polymer nanofibers. *Journal of the American Chemical Society*, 129, 2777–2782.
- Koczur, K.M., Mourdikoudis, S., Polavarapu, L., & Skrabalak, S.E. (2015). Polyvinylpyrrolidone (PVP) in nanoparticle synthesis. *Dalton Transactions, Royal Society of Chemistry*, 44 (41), 17883–17905.
- Kozuka, H., Kajimura, M., Hirano, T., & Katayama, K. (2000). Crack-free, thick ceramic coating films via non-repetitive dip-coating using polyvinylpyrrolidone as stress-relaxing agent. *Journal of Sol-Gel Science and Technology*, 19, 205–209.
- Kumar, N.B.R., Crasta, V., & Praveen, B.M. (2016). Dielectric and electric conductivity studies of PVA (Mowiol 10-98) doped with MWCNTs and WO₃nanocomposites films. *Materials Research Express*, 3, 1–12.
- Lee, J.S., Choi, K.H., Ghim, H.D., Kim, S.S., Chun, D.H., Kim, H.Y., & Lyoo, W.S. (2004). Role of molecular weight of atactic poly(vinyl alcohol) (PVA) in the structure and properties of PVA nanofabric prepared by electrospinning. *Journal of Applied Polymer Science*, 93, 1638–1646.
- Li, D., Wang, Y., & Xia, Y. (2003). Electrospinning of polymeric and ceramic nanofibers as uniaxially aligned arrays. *Nano Letters*, 3, 1167–1171.
- Li, G., Li, P., Yu, Y., Jia, X., Zhang, S., Yang, X., & Ryu, S. (2008). Novel carbon fiber/epoxy composite toughened by electrospun polysulfone nanofibers. *Materials Letters*, 62, 511–514.
- Liu, C., Hsu, P.C., Lee, H.W., Ye, M., Zheng, G., Liu, N., Li, W., & Cui, Y. (2015). Transparent air filter for high-efficiency PM_{2.5} capture. *Nature Communications*, 6, 1–9.
- Liu, L., Jiang, K.L., & Fan, S.S. (2005). Liquid crystal display and manufacturing method there for comprising alignment films of oriented carbon nanotubes. [Patent Document]. United States Patent. doi: 10.1145/634067.634234.
- Peng, S., Zhou, M., Liu, F., & Zhang, C. (2017). Flame-retardant polyvinyl alcohol membrane with high transparency based on a reactive phosphorus-containing compound. *R. Soc. open sci.*, 4, 170512.
- Ravi, M., Bhavani, S., Kumar, K.K., Rao, V. V.R.N. (2013). Investigations on electrical properties of PVP:KIO₄polymer electrolyte films. *Solid State Sciences*, 19, 85–93.



- Sani, N.A.A., Lau, W.J., & Ismail, A.F. (2015). Morphologies and separation characteristics of polyphenylsulfone-based solvent resistant nanofiltration membranes: Effect of polymer concentration in casting solution and membrane pretreatment condition. *Korean Journal of Chemical Engineering*, 32 (4), 743-752.
- Sawicka, K., Gouma, P., & Simon, S. (2005). Electrospun biocomposite nanofibers for urea biosensing. *Sensors and Actuators B*, 108, 585–588.
- Schroeder, R., Majewski, L.A., & Grell, M. (2005). High-performance organic transistors using solution-processed nanoparticle -filled high-*k* polymer gate insulator. *Advance Materials*, 17, 1535–1539.
- Singh, S. (2002). *Liquid Crystals Fundamentals*. Farrer Road, Singapore: World Scientific Publishing Co. Pte. Ltd.
- Slistan-Grijalva, A., Herrera-Urbina, R., Rivas-Silva, J.F., Ávalos-Borja, M. Castellón-Barraza, F.F., & Posada-Amarillas, A. (2008). Synthesis of silver nanoparticles in a polyvinylpyrrolidone (PVP) paste, and their optical properties in a film and in ethylene glycol. *Materials Research Bulletin*, 43, 90–96.
- Son, P.K., & Choi, S.W. (2010). Preferred pretilt direction of liquid crystal molecules on rubbed polyimide surfaces. *Journal of the Korean Physical Society*, 57, 207–209.
- Subbiah, T., Bhat, G. S., Tock, R. W., Parameswaran, S., & Ramkumar, S. S. (2005). Electrospinning of nanofibers. *Journal of Applied Polymer Science*, 96, 557–569.
- Sundaray, B., Subramanian, V., Natarajan, T.S., Xiang, R.Z., Chang, C.C., & Fann, W.S. (2004). Electrospinning of continuous aligned polymer fiber. *Applied Physics Letters*, 7, 1222–1224.
- Theron, A., Zussman, E., & Yarin, A.L. (2001). Electrostatic field-assisted alignment of electrospun nanofibers. *Nanotechnology*, 12, 384–390.
- Weng, L., Varanytsia, A., Hee, S., Lin, J.H., Chang, S.C., Li, Y.H., Urbanski, M., ... Moritake, H. (2017). Improved response time of thick liquid crystal device by using electrospun nanofiber. *Japanese Journal of Applied Physics*, 56, 061701.
- Wu, S.T., & Yang, D.K. (2006). *Fundamental of Liquid Crystal Devices*. West Sussex, England: John Wiley & Sons Ltd.
- Yao, J., Bastiaansen, C.W.M., & Peijs, T. (2014). High Strength and High Modulus Electrospun Nanofibers. *Fibers*, 2, 158–187.
- Yuan, X., Zhang, Y., Dong, C., & Sheng, J. (2004). Morphology of ultrafine polysulfone fibers prepared by electrospinning. *Polymer International*, 53, 1704–1710.
- Yusuf, Y., Kusumasari, E., Ula, N.M., Jahidah, K., Triyana, K., ... Harsojo (2016). Optical properties of planar nematic liquid crystals samples which are parallel oriented by nanofibers. *AIP Conference Proceeding*, 1725, 020103.
- Zhang, C., & Yu, S. (2014). Nanoparticles meet electrospinning: Recent advances and future prospects. *Chemical Society Reviews*, 43, 4423.