

DAFTAR PUSTAKA

- [1] Z. Karoutas *et al.*, “The maturing of nuclear fuel: Past to Accident Tolerant Fuel,” *Prog. Nucl. Energy*, vol. 102, pp. 68–78, 2018.
- [2] S. M. Bragg-Sitton, “Update on Accident Tolerant Fuel and IAEA Technical Meeting on ATF Accident Tolerant Fuel (ATF),” in *Idaho National Laboratory*, 2015.
- [3] S. Bragg-Sitton *et al.*, “Advanced Fuels Campaign: Enhanced LWR Accident Tolerant Fuel Performance Metrics,” Idaho National Laboratory, 2014.
- [4] P. B. Abramson, *Guidebook to Light Water Reactor Safety Analysis*. Hemisphere Publishing Corporation, 1985.
- [5] S. J. Zinkle, K. A. Terrani, J. C. Gehin, L. J. Ott, and L. L. Snead, “Accident tolerant fuels for LWRs: A perspective,” *J. Nucl. Mater.*, vol. 448, no. 1–3, pp. 374–379, 2014.
- [6] Y. Idaho, R. Sonat, and S. Idaho, “Impact of Accident-Tolerant Fuels and Claddings on the Overall Fuel Cycle: A Preliminary Systems Analysis,” *Nucl. Technol.*, no. May, 2014.
- [7] L. J. Ott, K. R. Robb, and D. Wang, “Preliminary assessment of accident-tolerant fuels on LWR performance during normal operation and under DB and BDB accident conditions,” *J. Nucl. Mater.*, vol. 448, no. 1–3, pp. 520–533, 2014.
- [8] L.-Y. Cheng, A. Cuadra, and N. Brown, “PWR Plant Model to Assess Performance of Accident Tolerant Fuel in Anticipated Transients and Accidents,” in *Accident Tolerant Fuel Concepts for Light Water Reactors Conference*, 2015.
- [9] N. M. El-sahlamy, “SBLOCA Analysis for a 3-Loop Westinghouse PWR Reactor Using TRACE,” vol. 51, no. 1, pp. 73–84, 2018.
- [10] J. D. Stempien, D. M. Carpenter, G. Kohse, and M. S. Kazimi, “Characteristics of Composite Silicon Carbide Fuel Cladding after Irradiation under Simulated PWR Conditions,” *Nucl. Technol.*, vol. 183, no. 1, pp. 13–29, 2013.
- [11] M. Ishikawa, *A Study of the Fukushima Daiichi Nuclear Accident Process*. 2015.
- [12] Siemens Power Corporation, “PWR Small Break LOCA Evaluation Model , S-RELAP5 Based,” 2000.
- [13] O. P. Kauppinen, V. Kouhia, V. Riikonen, J. Hyvärinen, and H. Sjövall, “Computer analyses on loop seal clearing experiment at PWR PACTEL,” *Ann. Nucl. Energy*, vol. 85, pp. 47–57, 2015.

- [14] RELAP5/Mod3.3 Code Development Team, “Relap5/Mod3 .3 Code Manual,” Idaho Falls, Idaho, 2001.
- [15] International Atomic Energy Agency, “Nuclear power reactors in the world,” 2017.
- [16] S. B. Ross and M. S. El-Genk, “Thermal Conductivity Correlation for UN fuel between 10 and 1923 K,” *J. Nucl. Mater.*, vol. 151, no. February 1988, pp. 313–317, 1988.
- [17] S. L. Hayes, J. K. Thomas, and K. L. Peddicord, “Material Property Correlations for Uranium Mononitride IV. Thermodynamic Properties,” *J. Nucl. Mater.*, vol. 171, pp. 300–318, 1990.
- [18] J. T. White, A. T. Nelson, J. T. Dunwoody, D. D. Byler, D. J. Safarik, and K. J. McClellan, “Thermophysical properties of U₃Si₂ to 1773 K,” *J. Nucl. Mater.*, vol. 464, pp. 275–280, 2015.
- [19] J. H. Chun, S. W. Lim, B. D. Chung, and W. J. Lee, “Safety evaluation of accident-tolerant FCM fueled core with SiC-coated zircalloy cladding for design-basis-accidents and beyond DBAs,” *Nucl. Eng. Des.*, vol. 289, pp. 287–295, 2015.
- [20] L. L. Snead, T. Nozawa, Y. Katoh, T.-S. Byun, S. Kondo, and D. A. Petti, “Handbook of SiC properties for fuel performance modeling,” *J. Nucl. Mater.*, vol. 371, no. 1, pp. 329–377, 2017.
- [21] C. W. Lee, F. J. Pineau, and J. C. Corelli, “Thermal properties of neutron-irradiated SiC; effects of boron doping,” *J. Nucl. Mater.*, vol. 108–109, no. C, pp. 678–684, 1982.
- [22] K. G. Field, M. Snead, Y. Yamamoto, B. A. Pint, and K. A. Terrani, “Materials properties of FeCrAl alloys for nuclear power production applications,” 2017.
- [23] A. Agung, J. Bánáti, M. Stálek, and C. Demazière, “Validation of PARCS/RELAP5 coupled codes against a load rejection transient at the Ringhals-3 NPP,” *Nucl. Eng. Des.*, vol. 257, pp. 31–44, 2013.
- [24] F. D’Auria, *Thermal Hydraulics in Water-Cooled Nuclear Reactors*. Woodhead Publishing, 2017.
- [25] K. A. Terrani, D. Wang, L. J. Ott, and R. O. Montgomery, “The effect of fuel thermal conductivity on the behavior of LWR cores during loss-of-coolant accidents,” *J. Nucl. Mater.*, vol. 448, no. 1–3, pp. 512–519, 2014.