



## REFERENCES

- [1] S. Kajita, H. Hirohisa, K. Harada, and J. Yokoi, *Introduction to Humanoid Robotics*, 2013.
- [2] J. Rudy, “ZMP walking controller for humanoid walking using darwin-op,” *Degree Thesis*, p. 73, 2014.
- [3] S. J. Yi, B. T. Zhang, D. Hong, and D. D. Lee, “Online learning of a full body push recovery controller for omnidirectional walking,” *IEEE-RAS International Conference on Humanoid Robots*, pp. 1–6, 2011.
- [4] M. Vukobratovic, B. Borovac, D. Surla, and D. Stokic, *Biped Locomotion: Dynamics, Stability, Control and Application*, ser. Communications and Control Engineering. Springer Berlin Heidelberg, 2012.
- [5] M. H. Raibert, *Legged Robots that Balance*, ser. Artificial Intelligence. MIT Press, 1986.
- [6] S. Kajita, F. Kanehiro, K. Kaneko, K. Yokoi, and H. Hirukawa, “The 3D linear inverted pendulum mode: a simple modeling for a biped walking pattern generation,” in *Proceedings 2001 IEEE/RSJ International Conference on Intelligent Robots and Systems. Expanding the Societal Role of Robotics in the the Next Millennium (Cat. No.01CH37180)*, vol. 1. IEEE, pp. 239–246.
- [7] S. Kajita, F. Kanehiro, K. Kaneko, K. Fujiwara, K. Yokoi, and H. Hirukawa, “A realtime pattern generator for biped walking,” in *Proceedings 2002 IEEE International Conference on Robotics and Automation (Cat. No.02CH37292)*, vol. 1. IEEE, pp. 31–37.
- [8] S. Kajita and K. Tani, “Study of dynamic biped locomotion on rugged terrain-theory and basic experiment,” in *Fifth International Conference on Advanced Robotics 'Robots in Unstructured Environments*. IEEE, 1991, pp. 741–746 vol.1.
- [9] M. Shibuya, T. Suzuki, and K. Ohnishi, “Trajectory Planning of Biped Robot Using Linear Pendulum Mode for Double Support Phase,” in *IECON 2006 - 32nd Annual Conference on IEEE Industrial Electronics*. IEEE, nov 2006, pp. 4094–4099.
- [10] Kyung-Kon Noh, Jin-Geol Kim, and Uk-Youl Huh, “Stability experiment of a biped walking robot with inverted pendulum,” in *30th Annual Conference of IEEE Industrial Electronics Society, 2004. IECON 2004*, vol. 3. IEEE, pp. 2475–2479.



- [11] T. Sugihara, Y. Nakamura, and H. Inoue, “Real-time humanoid motion generation through ZMP manipulation based on inverted pendulum control,” in *Proceedings 2002 IEEE International Conference on Robotics and Automation (Cat. No.02CH37292)*, vol. 2. IEEE, pp. 1404–1409.
- [12] S. Kajita, F. Kanehiro, K. Kaneko, K. Fujiwara, K. Harada, K. Yokoi, and H. Hirukawa, “Biped walking pattern generation by using preview control of zero-moment point,” in *2003 IEEE International Conference on Robotics and Automation (Cat. No.03CH37422)*. IEEE, pp. 1620–1626.
- [13] Chi Zhu, Y. Tomizawa, Xiang Luo, and A. Kawamura, “Biped Walking with Variable ZMP, Frictional Constraint, and Inverted Pendulum Model,” in *2004 IEEE International Conference on Robotics and Biomimetics*. IEEE, pp. 425–430.
- [14] Seung-Joon Yi, D. Hong, and D. D. Lee, “A hybrid walk controller for resource-constrained humanoid robots,” *International Conference on Humanoid Robots*, pp. 88–93, 2013.
- [15] “ROS.org | Powering the world’s robots.”
- [16] S.-J. Yi, B.-T. Zhang, D. Hong, and D. D. Lee, “Whole-Body Balancing Walk Controller for Position Controlled Humanoid Robots,” *International Journal of Humanoid Robotics*, vol. 13, no. 01, p. 1650011, 2016.
- [17] B. Siciliano and O. Khatib, *Springer Handbook of Robotics*, ser. Springer Handbooks. Springer International Publishing, 2016.
- [18] “Qt | Cross-platform software development for embedded & desktop.”