

TABLE OF CONTENTS

FINAL PROJECT	i
RATIFICATION.....	i
DECLARATION	ii
ACKNOWLEDGEMENT	iii
DEDICATION	iv
PREFACE	v
TABLE OF CONTENTS.....	vi
LIST OF TABLES	ix
LIST OF FIGURES	x
ABSTRACT	xii
CHAPTER 1 INTRODUCTION.....	1
1.1 Background.....	1
1.2 Research Statement.....	2
1.3 Objectives	3
1.4 Limitations	3
1.5 Benefits	3
1.6 Authenticity.....	4
CHAPTER 2 LITERATURES REVIEW.....	6
2.1 Copper Slag.....	6
2.2 Copper Slag as Supplementary Cementitious Material	7
2.3 Copper Slag as Fine Aggregate Replacement in Concrete	8
CHAPTER 3 THEORETICAL FRAMEWORK	16
3.1 Mix Design Procedure	16

vi

3.2	Target Performance.....	16
3.2.1	Defining target performance	16
3.2.2	Durability	17
3.3	Determination of Mix Requirements	18
3.3.1	Maximum size of coarse aggregate.....	18
3.3.2	Water content	18
3.3.3	Cement content.....	19
3.3.4	Sand-aggregate ratio.....	19
3.4	Compressive Strength Test	22
3.5	Chloride Penetration on the Concrete Surface.....	22
3.6	Specification of Coefficient of Chloride Ion Diffusion in Concrete.....	23
3.7	Chloride Migration into Concrete	24
3.8	Effective Diffusion Coefficient for Steady State Migration Test	25
3.9	Diffusion Coefficient for Non-Steady State Migration Test.....	26
CHAPTER 4 RESEARCH METHODS		29
4.1	Research Introduction	29
4.2	Materials	30
4.3	Mix Design.....	31
4.4	Test Methods.....	32
4.4.1	Compressive strength test	33
4.4.2	Chloride migration test in non-steady state and steady state condition	33
CHAPTER 5 RESULTS AND DISCUSSIONS		39
5.1	Compressive Strength	39
5.2	Non-Steady State Migration	42

5.2.1	Chloride penetration depth.....	42
5.2.2	Solution temperature and electrical current applied.....	43
5.2.3	Chloride diffusion coefficient	44
5.3	Steady State Migration.....	45
5.3.1	Chloride penetration rate.....	45
5.3.2	Effective chloride ion diffusion coefficient	47
5.4	Relationship of Strength Properties and Durability Performance toward Chloride Resistance	49
CHAPTER 6 CONCLUSIONS AND RECOMMENDATIONS.....		51
6.1	Conclusions.....	51
6.2	Recommendations.....	51
BIBLIOGRAPHY		53
APPENDIX		55