



TABLE OF CONTENTS

COVER PAGE	i
APPROVAL PAGE	ii
STATEMENT	iii
FOREWORD	vi
TABLE OF CONTENTS	ix
LIST OF TABLES	xi
LIST OF FIGURES	xii
ABBREVIATIONS AND ACRONYMS	xiii
ABSTRACT	xiv
INTISARI	xv
CHAPTER I INTRODUCTION	1
1.1 Background	1
1.2 Research Problem	3
1.3 Research Scope.....	3
1.4 Research Objective	3
1.5 Research Advantages.....	3
1.6 Research Methodology	4
1.7 Thesis Organization	5
CHAPTER II LITERATURE REVIEW	7
CHAPTER III THEORETICAL BASIS	13
3.1 Bandwidth Management	13
3.2 Hierarchical Token Bucket (HTB)	14
3.3 Quality of Service (QoS).....	16
3.3.1 Throughput.....	17
3.3.2 Jitter	18
3.3.3 Delay (Latency)	19
3.3.4 Packet loss.....	19
3.4 Software-Defined Network (SDN).....	21
3.5 OpenFlow.....	24
3.5.1 OpenFlow Switch	24
3.6 Ryu	24
3.7 IP Traffic.....	26
CHAPTER IV ANALYSIS AND SYSTEM DESIGN	27
4.1 General Analysis	27
4.2 System Design.....	29
4.2.1 HTB Scheme.....	31
4.2.2 Network Topology Scheme.....	32
4.2.3 Ryu Scheme	34
4.3 System Initialization	34



4.4 Data Analysis.....	35
CHAPTER V IMPLEMENTATION.....	42
5.1 Hardware and Software Specifications.....	42
5.2 Initialization of SDN Environment	42
5.2.1 Emulator Initialization	42
5.3 Implementation of Ryu Controller.....	44
5.4 Initialization of OVS	44
5.5 Implementation of Topology Design	46
5.6 Implementation of HTB Algorithm.....	48
5.7 Testing of QoS Parameter.....	51
CHAPTER VI RESULT AND DISCUSSION	53
6.1 Result and Analysis.....	53
6.1.2 Jitter Performance	54
6.1.3 Throughput Performance	57
6.1.4 Delay (Latency) Performance	60
6.1.5 Packet Loss Performance	62
CHAPTER VII CONCLUSION AND FUTURE WORKS	65
7.1 Conclusion	65
7.2 Future Works	66
REFERENCE.....	68
ATTACHMENTS	71