

TABLE OF CONTENTS

TABLE OF CONTENTS.....	i
LIST OF FIGURES.....	iii
LIST OF TABLES.....	vi
CHAPTER 1 – INTRODUCTION	1
1.1 Background.....	1
1.2 Location of the study area	2
1.3 Problem Statement	4
1.4 Research Objectives	5
1.5 Originality of the Research	6
1.6 Research Outcome	6
CHAPTER 2 – LITERATURE REVIEWS AND THEORETICAL BACKGROUND.....	7
2.1 Tectonic Setting of Java.....	7
2.2 Historical Earthquake of Yogyakarta and surrounding area.....	8
2.3 Previous Study.....	10
2.4 General Geology of Yogyakarta.....	13
2.4.1 Stratigraphy of Yogyakarta	15
2.4.2 Opak Fault System	17
2.5 Estimating local site effects based on ambient noise recording.....	20
2.6 Multichannel Analysis of Surface Wave Method	20
2.7 Soil and dynamics properties of soil.....	26
2.8 Shear wave velocity	27
2.9 Seismic Hazard Analysis	27
2.10 Green’s function Method.....	29
2.11 Response spectrum.....	31
2.12 Hypothesis	32
CHAPTER 3 – RESEARCH METHODOLOGY	34
3.1 Material and Equipment	34

3.2 Research Variable.....	38
3.3 Sampling Method.....	38
3.4 Data Analysis.....	42
CHAPTER 4 – RESULTS AND DISCUSSION.....	54
4.1 Lineament analysis showing Opak Fault System.....	54
4.2 H/V ratio results.....	64
4.3 Shear wave velocity results of MASW	65
4.4 Shear wave velocity results of borehole.....	67
4.5 Simulation of strong ground motion results for 2006 Yogyakarta earthquake	70
4.6 Validation of synthetic peak ground acceleration (PGA).....	80
4.7 Response spectrum analysis results with SAP 2000.....	82
4.8 Opak Fault System model and estimating maximum magnitude for future earthquake.....	91
CHAPTER 5 – CONCLUSIONS AND RECOMMENDATIONS FOR FUTURE STUDIES.....	93
5.1 Conclusion.....	93
5.2 Recommendations for future studies.....	94
REFERENCES	96
APPENDICES.....	106

LIST OF FIGURES

Figures	Page
1.1 Location map of the study area	3
2.1 Tectonic model and subduction seismic source parameters “Megathrust” In Java Island, Indonesia Region (Irsyam et al.2010)	8
2.2 Historical earthquake of Yogyakarta and surrounding area, M >4.0 from year of 1840 to2016 (Husein et al., 2008)	10
2.3 Geological Map of the Yogyakarta and surrounding area (Compile from Surorno et al. 1992 and Rahardjo et al.1995, the original map scale: 1:100,000)	14
2.4 Opak fault Map, Opak fault is Black line, Red line is inferred trace of earthquake rupture fault from ground surface deformation and Orange line across Yogyakarta represents the western edge of the subsidence	18
2.5 The aftershock locations (red dots) and the cross-section A-B shows the hypocenters of the aftershocks and the distance to the earthquake	19
2.6 Schematic of the active remote MASW field survey, (Park et.al., 1999)	22
2.7 Schematic view of the active MASW data analysis	24
2.8 Schematic of the passive remote MASW field survey,(Park et.al., 1999)	25
2.9 Steps for seismic hazard analysis (SNI - 1726:2012)	28
2.10 Schematic illustration of stochastic Green’s function method, http://iisee.kenken.go.jp/eqcat/strong_motion	30
2.11 Comparison between observed and simulated ground motions using a characterized source model (Miyake et.al, 2003)	31
3.1 DJI Phantom 4 PRO+ drone	35
3.2 Three component Seismometer	36
3.3 MASW Equipment	37
3.4 H/V survey sites around Opak fault (Geophysics Department (UGM)	39
3.5 MASW survey location map	40

3.6	Example of geophone configuration	41
3.7	The general layout of the Geopsy Software	44
3.8	Data acquisition and processing (a) MASW raw wiggle plot (b) dispersion curve signal interface (c) Vs profile	46
3.9	Location of Boreholes in Yogyakarta Area	48
3.10	Flow chart of Research Method	52
4.1	Lineament of Opak Fault System	55
4.2	Morphologic section across lineament 5V = 1H	56
4.3	Outcrop at Tebing Breksi with reverse fault (left side, picture was taken from south) and outcrop at Piyungan (right side, picture was taken from north)	57
4.4	Panoramic view of southern mountain, Photo taking from Tebing Breksi, Camera facing to southeast	58
4.5	Steep vertical fault scarp near Piyungan (east side of Opak river), Camera facing toward northeast	59
4.6	Steep vertical fault scarp around Oya river, (Photo taking from Bukit Panguk Kediwung, Camera facing toward south)	59
4.7	An example of active erosional valley developing along Oya River (Photo taking from north of Bukit Panguk Kediwung, Camera facing to southeast)	60
4.8	An example of active erosional Oya river valley (Photo taking from Gardu Pandang Mangunan, Camera facing to southwest)	60
4.9	Point cloud mesh obtained from the photogrammetric model	62
4.10	Triangle surface represented by high quality texture mode	62
4.11	Digital Elevation model, red line = lineament, black arrow = outcrop of Nglanggran Formation (NF) reverse faulted on Semilir Formation (SF)	63
4.12	Digital Elevation Model with 1m interval contours lines, red line = lineament	63

4.13	Orthomosaic image	64
4.14	H/V spectral plot of ambient-noise seismic data	65
4.15	The shear-wave velocity profile of each MASW site	67
4.16	Average shear-wave velocity distribution map to the depth of 30m	69
4.17	Synthetic PGA of BPKP-1[PGAM of SNI-1726:2012(0.568g)]	73
4.18	Synthetic PGA of MASW Site -1 [PGAM of SNI-1726:2012(0.668g)]	74
4.19	Synthetic PGA of MASW Site-2[PGAM of SNI-1726:2012(0.686g)]	75
4.20	Peak Ground Acceleration (NS) map from synthetic waveforms	76
4.21	Peak Ground Acceleration (EW) map from synthetic waveforms	77
4.22	Peak Ground Acceleration (UD) map from synthetic waveforms	78
4.23	An example of synthetic peak ground velocity for SPT sites and MASW sites	80
4.24	(a) Observed peak ground acceleration for 2006 Yogyakarta earthquake at Yogi station (MAE Center Report No.07-02) (b) Synthetic peak ground acceleration for 2006 Yogyakarta earthquake	81
4.25	Two story building model	83
4.26	Synthetic time history of 2006 Yogyakarta earthquake	84
4.27	Load case data	84
4.28	Plot function	85
4.29	Response spectrum curve	85
4.30	The comparison of predicted response spectra acceleration using SAP computer program (blue line), based on PGA (yellow line), based on SDs and SD1 (red line) and SNI 1726:2012 (green line)	90
4.31	Fault model of Opak Fault System model	92

LIST OF TABLES

Table	Page
2.1 Acquisition Parameters for typical Multichannel Analysis of Surface Waves (MASW) Analyses	23
2.2 The grain size criteria of soil (NZGS-2005)	26
3.1 Main technical characteristics of DJI Phantom 4 PRO+	35
3.2 Data acquisition parameters by active MASW method	41
3.3 The relationship of frequency and soil type (Nogoshi and Igarashi 1971)	44
3.4 Site classification according to the NEHRP code (Building Seismic safety council, 2003) and Indonesia code 1726-2012	47
3.5 Research Schedule	53
4.1 Geotechnical properties of each borehole	68
4.2 Input parameters for the stochastic model of the 2006 Yogyakarta earthquake	70
4.3 Empirical relationships between moment magnitude (M_w) and surface rupture length, L (Km) and rupture area, A (km ²), (After Wells and Coppersmith, 1994)	71
4.4 The calculated spectral acceleration (S_a) results for each location	86