

## DAFTAR PUSTAKA

- Ariningtyas, N., 2015, “Studi Numerik Pengaruh Konfigurasi Pengumpanan Dua Jenis Batubara dengan Metode *In-Furnace Blending* terhadap Proses Pembakaran pada *Boiler* Tangensial”, Teknik Mesin FTI-ITS, Surabaya.
- Asotani, T., Yamashita, T., Tominaga, H., Uesugi, Y., Itaya, Y., dan Mori, S., 2008, “Prediction of Ignition Behavior in a Tangentially Fired Pulverized Coal Boiler Using CFD”, *Fuel*, Vol. 87, Hal 482–490.
- ASTM, 2009, “*Gaseous fuels; Coal and Coke Vol 05.06*”, Annual book of ASTM Standards, ASTM, US.
- Babcock and Wilcox company. 2005. “*Steam its Generation and Use 41<sup>st</sup> Edition*”. *McDermott Company. Ohio, USA*.
- Candra, F.E., 2015, “Studi Numerik Karakteristik Aliran dan Pembakaran *Tangentially Fired Pulverized-Coal Boiler* 660MWe dengan Penambahan Variasi Injeksi *Oxy-Fuel* pada Udara Pembakaran”, Teknik Mesin FTI-ITS, Surabaya.
- Cengel, Yunus A. dan Boles M. A., 2006, *Thermodynamics An Engineering Approach*, 5 ed., McGraw-Hill.
- Center of Coal Utilization Japan, 2003, *Technology Transfer Project on Clean Coal Technology*.
- Choi, R.C., dan Kim, C.N., 2009, “Numerical Investigation on the Flow, Combustion, and NO<sub>x</sub> emission Characteristics in a 500MWe Tangentially Fired Pulverized Coal Boiler”. *Fuel*, Vol. 88, Hal. 1720-1731.
- Deng, Kangjie dan Yang, Chen, 2017, Start-Up dynamic Processes Simulation of Supercritical Once-through Boiler, ScienceDirect, *Applied Thermal Engineering* 115, no.937-946.
- Fan J., Qian L., Ma Y., Sun P., dan Cen K., 2001, “Computational Modeling of Pulverized Coal Combustion Processes in Tangentially Fired Furnaces”, *Chemical Engineering Journal*, Vol. 81, Hal. 261-269.

- Febyanasari, R., 2014, “Studi Numerik Karakteristik Aliran dan Pembakaran pada *Tangentially Fired Pulverized Coal Boiler* dengan Menggunakan *Oxy Fuel* pada Kasus *Coal Blending* antara *Medium Rank Coal* (MRC) dan *Low Rank Coal* (LRC)”, Teknik Mesin FTI-ITS, Surabaya.
- Hidayat, R., 2015, “Studi Numerik Karakteristik Aliran Gas-Solid dan Pembakaran *Tangentially Fired Pulverized Coal Boiler* 315 MWe dengan Variasi Sudut *Tilting* dan Nilai Kalor Batubara (Studi Kasus PLTU Pacitan Unit 1)”, Teknik Mesin FTI-ITS, Surabaya.
- Kumar, R.P., Raju, R.V., dan Kumar, R. N., 2013, “Effect of Parameter in OnceTrough Boiler for Controlling Reheat Steam Temperature in Supercritical Power Plants”, *Research Journal of Engineering Sciences*, Vol 2, Hal 27-34.
- Razali, N.M., Boosroh, M.H., Hasini, H., Shuaib, N.H., 2009, “Impact of tangential *burner* firing angle on combustion characteristics of large scale coal-fired boiler”, *International Conference on Energy and Environment*, Malaysia.
- Sa’adiyah, D.S., 2013, “Studi Numerik Karakteristik Aliran, Pembakaran dan Emisi Gas Buang pada *Tangentially Fired Boiler* 625 MWe dengan Komposisi Batubara 70% LRC dan 30% MRC pada Kondisi Pengoperasian yang Berbeda (Studi Kasus PLTU Suralaya Unit 8)”, Teknik Mesin FTI-ITS, Surabaya.
- Santoso, 2018, “Perancangan *Supercritical Once-Through Boiler* untuk Pembangkit Listrik Kapasitas 40 MW, Teknik Mesin UGM, Jogjakarta.
- Spliethoff, H., 2010, *Power Generation from Solid Fuels*, Springer, NY, US.
- Warnatz, J., Maas, U., Dibble, R.W., (2006), *Combustion* 4<sup>th</sup> edition, Springer, Berlin.