
DAFTAR PUSTAKA

- Animapauh, S. O. (2012). RTICLES Tannin extraction from the barks of three tropical hardwoods for the production of adhesives, 8(6), 2959–2965.
- Aries, R. S. and Newton, R. D., 1955, Chemical Engineering Cost Estimation, pp. 1-16; 52; 77-78; 97-119; 163-164; 177; 185-197; 203-209, McGraw-Hill Book Company, Inc., New York.
- Bi, A. B., Anris, S. P. E., Safou-tchiam, R., & Santiago-medina, F. J. (2018). Industrial Crops & Products Chemical composition of African mahogany (*K. ivorensis* A. Chev) extractive and tannin structures of the bark by MALDI-TOF. *Industrial Crops & Products*, 113(July 2017), 167–178. <https://doi.org/10.1016/j.indcrop.2018.01.013>
- Brown, G.G., Katz, D., Foust, A.S., and Schneidewind, C., 1978, “Unit Operation”, John Wiley and Sons, Inc., New York
- Brownell, L.E. and Young, E.H., 1979, “Process Equipment Design”, John Wiley and Sons, Inc., New York.
- Coulson, J. M., dan Richardson, J.F., 2005, “Chemical Engineering Design”, vol 6, 4th ed., Elsevier Butterworth-Heinemann, Oxford, pp. 208, 477.
- Crowl, D.A, Louvar, J.F. 2002. *Chemical Process Safety*. Prentice Hall. New Jersey.
- European Comission. 2006. “Emission from Storage”. Best Available Techniques Document.
- Gmaps. (2018). Kabupaten Wonosobo. Retrieved from <https://www.google.com/maps/place/Kabupaten+Wonosobo,+Jawa+Tengah/@-7.3997747,109.7655932,11z/data=!3m1!4b1!4m5!3m4!1s0x2e7aa182f62f7513:0x3027a76e352bab0!8m2!3d-7.3632094!4d109.9001796>
- Gemse, Thomas, 2016, “Extraction: Liquid-Liquid Extraction, Solid-Liquid Extraction, High Pressure Extraction”, Graz University of Technology
- Grand View Research. (n.d.). Retrieved from <https://www.grandviewresearch.com/industry-analysis/tannin-market>
- Gulrajani, M. L. (2001). Present status of natural dyes. *Indian Journal of Fibre and Textile Research*, 26(1–2), 191–201.

-
- <http://bi.go.id/> diakses pada tanggal 1 September 2019 pukul 20.00 WIB
- <http://matche.com/equipcost/Default.html>, diakses pada tanggal 29 Agustus 2019 pukul 14.00 WIB.
- <http://www.mhhe.com/engcs/chemical/peters/data/ce.html>, diakses pada tanggal 29 Agustus 2019 pukul 14.00 WIB.
- Indradjaja, D.D., 2010, Status Lingkungan Hidup Indonesia 2010, Kementerian Lingkungan Hidup Republik Indonesia, Jakarta.
- Ismail, 2010, “Prarancangan Pabrik Tanin dari Biji Pinang Kapasitas Produksi 27.775 Ton/Tahun”, Skripsi pada Program Studi Teknik Kimia Universitas Sumatera Utara, Medan.
- Ismarani. (2012). POTENSI SENYAWA TANNIN DALAM MENUNJANG PRODUKSI RAMAH LINGKUNGAN Ismarani Abstract menjadi hydrolyzable tannin dan condensed tannins (proanthocyanidins). *Agribisnis Dan Pengembangan Wilayah*, 3(2), 46–55.
- Karrasik, I.J., dkk, 2001, Pump Handbook, 3rd ed., McGraw-Hill, New York.
- Kern, D. Q., 1965, Process Heat Transfer, McGraw-Hill Book Company, Japan.
- Malik et al. 2016. Merbau Extractive Impregnant. *BioResources* 11(3), 7737-7753.
- Marr, C.W., 1995, “Choosing a Chipper/Shredder”, Solid Waste Management Fact Sheet No. 15, Manhattan.
- Masters, K., 1979, Spray Drying Handbook, 3rd ed., John Wiley and Sons, Inc., New York
- Material Safety Data Sheet.
- Occupational Safety and Health Act. 2000. Process Safety Management. U.S. Department of Labor
- Peraturan Menteri Lingkungan Hidup Nomor 21 Tahun 2008 tentang Baku Mutu Emisi Gas.
- Peraturan Pemerintah Republik Indonesia Nomor 121 Tahun 2015 tentang Pengusahaan Sumber Daya Air.

-
- Perry, R.H. and Green, D.W., 1984, Perry's Chemical Engineer's Handbook, 6ed.,
Mc Graw Hill Book Co: Singapore.
- Peters, M. S., and Timmerhaus, K. D., 1991, Plant Design and Economics for Chemical
Engineers, 4th ed., McGraw-Hill, Singapore.
- Prayitno, endro kisworo, N. (2003). Proses Ekstraksi Bahan Pewarna Alam Dari
kayu mahoni. *Ilmiah*, 209.
- Rase, H.F., 1977, "Chemical Reactor Design for Process Plant", 1st ed., McGraw
Hill Book Company, Inc., New York.
- Richardson, J.F., Harker, J.H dan Backhurst, J.R., 2002, Coulson & Richardson's
Chemical Engineering: Particle Technoogy and Separation Processes, Vol. 2,
5th ed., Butterworth-Heinemann: Oxford.
- Santoso, A. (2016). KARAKTERISTIK EK S TRAK KULIT KAYU MAHONI
SEBAGAI BAHAN PEREKAT KAYU (Characteristics of Mahogany Bark
Extract as Wood Adhesive), 34(4), 269–284.
- Saxena, S., & Raja, A. S. M. (2015). *Roadmap to Sustainable Textiles and Clothing*.
<https://doi.org/10.1007/978-981-287-164-0>
- Science, E. (2018). Microwave-assisted extraction (MAE) of bioactive saponin
from mahogany seed (Swietenia mahogany Jacq) Microwave-assisted
extraction (MAE) of bioactive saponin from mahogany seed (Swietenia
mahogany Jacq).
- Sinnott, R.K., 1999, Coulson & Richardson's Chemical Engineering: Chemical
Engineering Design, Vol. 6, 3rd ed., Butterworth-Heinemann: Oxford.
- Smith, J.M., Van Ness, H.C., dan Abbot, M.M., 2001, Introduction to Chemical
Engineering Thermodynamics, 6th ed, MgGraw-Hill: New York.
- Treybal, R.E., 1981, "Mass Transfer Operation", 3rd ed., pp. 655-686, McGraw-
Hill Book Company, Inc., New York.
- Walas, Stanley M. 1990. Chemical Process Equipment. Butterworth-Heinemann :
Washington
- Windsor, B., 2017, "Ion Exchange Design – Hand Calculation", *Purolite
International Ltd.*
- Yaws, C.L., 1999, Chemical Properties Handbook, New York, McGraw-Hill.
-

www.lenntech.com diakses pada 25 Juli 2019 pukul 18.00 WIB.

www.woodenergy.ie diakses pada 26 Juli 2019 pukul 21.00 WIB.