

## DAFTAR PUSTAKA

- Ahmed, W. H., Aman, A. M., Badr, H. M., & Al-Qutub, A. M. (2016). Air injection methods: The key to a better performance of airlift pumps. *Experimental Thermal and Fluid Science*, 70, 354–365. <https://doi.org/10.1016/j.expthermflusci.2015.09.022>
- Apazidis, N. (1985). Influence of bubble expansion and relative velocity on the performance and stability of an airlift pump. *International Journal of Multiphase Flow*, 11(4), 459–479. [https://doi.org/10.1016/0301-9322\(85\)90070-9](https://doi.org/10.1016/0301-9322(85)90070-9)
- Chladek, J., Enstad, G. G., & Melaaen, M. C. (2011). Effect of operating conditions and particle properties on performance of vertical air-lift. *Powder Technology*, 207(1–3), 87–95. <https://doi.org/10.1016/j.powtec.2010.10.013>
- Clark, N. N. and Dabolt, R. J., A general design equation for air lift pumps operating in slug flow, *AIChE J.*, vol. 32, no. 1, pp. 56–64, 1986.
- Chaziteodorou, G., 1977, *Fundamentals of Oceanic Mining*, Dr. Riederer-Verlag, Stuttgart.
- Deendarlianto, Supraba, I., Majid, A. I., Pradecta, M. R., Indarto, & Widyaparaga, A. (2019). Experimental investigation on the flow behavior during the solid particles lifting in a micro-bubble generator type airlift pump system. *Case Studies in Thermal Engineering*, 13(March 2018), 100386. <https://doi.org/10.1016/j.csite.2018.100386>
- Fujimoto, H., Murakami, S., Omura, A., & Takuda, H. (2004). Effect of local pipe bends on pump performance of a small air-lift system in transporting solid particles. *International Journal of Heat and Fluid Flow*, 25(6), 996–1005. <https://doi.org/10.1016/j.ijheatfluidflow.2004.02.025>
- Fujimoto, H., Ogawa, S., Takuda, H., & Hatta, N. (2003). Operation performance of a small air-lift pump for conveying solid particles. *Journal of Energy Resources Technology, Transactions of the ASME*, 125(1), 17–25. <https://doi.org/10.1115/1.1514498>

- Fujimoto, H., Nagatani, T., & Takuda, H. (2005). Performance characteristics of a gas-liquid-solid airlift pump. *International Journal of Multiphase Flow*, 31(10–11), 111–61133. <https://doi.org/10.1016/j.ijmultiphaseflow.2005.06.008>
- Hanafizadeh, P., Ghanbarzadeh, S., & Saidi, M. H. (2011). Visual technique for detection of gas-liquid two-phase flow regime in the airlift pump. *Journal of Petroleum Science and Engineering*, 75(3–4), 327–335. <https://doi.org/10.1016/j.petrol.2010.11.028>
- Hanafizadeh, P., & Ghorbani, B. (2012). Review study on airlift pumping systems. *Multiphase Science and Technology*, 24(4), 323–362. <https://doi.org/10.1615/MultScienTechn.v24.i4.30>
- Hatta, N., Fujimoto, H., Isobe, M., & Kang, J. S. (1998). Theoretical analysis of flow characteristics of multiphase mixtures in a vertical pipe. *International Journal of Multiphase Flow*, 24(4), 539–561. [https://doi.org/10.1016/S0301-9322\(97\)00074-8](https://doi.org/10.1016/S0301-9322(97)00074-8)
- Hayata, Y. (2002). NII-Electronic Library Service. *Chemical Pharmaceutical Bulletin*, (43), 2091. Retrieved from <http://www.mendeley.com/research/geology-volcanic-history-eruptive-style-yakedake-volcano-group-central-japan/>
- Hu, D., Tang, C. L., Cai, S. P., & Zhang, F. H. (2012). The effect of air injection method on the airlift pump performance. *Journal of Fluids Engineering, Transactions of the ASME*, 134(11), 1–7. <https://doi.org/10.1115/1.4007592>
- Hu, D., Kang, Y., Tang, C. lin, & Wang, X. chuan. (2015). Modeling and analysis of airlift system operating in three-phase flow. *China Ocean Engineering*, 29(1), 121–132. <https://doi.org/10.1007/s13344-015-0009-z>
- Lawniczak, F., Francois, P., Scrivener, O., Kastrinakis, E. G., & Nychas, S. G. (1999). The efficiency of short airlift pumps operating at low submergence ratios. *Canadian Journal of Chemical Engineering*, 77(1), 3–10. <https://doi.org/10.1002/cjce.5450770103>
- Kassab, S. Z., Kandil, H. A., Warda, H. A., & Ahmed, W. H. (2007). Experimental and analytical investigations of airlift pumps operating in three-phase flow.

*Chemical Engineering Journal*, 131(1–3), 273–281.

<https://doi.org/10.1016/j.cej.2006.12.009>

Kawashima, T., Noda, K., Masuyama, T. & Oda, S. 1975 Hydraulic transport of solids by air lift pump. *J. Mining Metall. Inst. Japan* 91, 765-772. In Japanese

Khalil, M. F., Elshorbagy, K. A., Kassab, S. Z., & Fahmy, R. I. (1999). Effect of air injection method on the performance of an air lift pump. *International Journal of Heat and Fluid Flow*,

20(6), 598–604.

[https://doi.org/10.1016/S0142-727X\(99\)00051-X](https://doi.org/10.1016/S0142-727X(99)00051-X)

Kim, S. H., Sohn, C. H., & Hwang, J. Y. (2014). Effects of tube diameter and submergence ratio on bubble pattern and performance of air-lift pump.

*International Journal of Multiphase Flow*, 58, 195–204.

<https://doi.org/10.1016/j.ijmultiphaseflow.2013.09.007>

Kumar, E. A., Kumar, K. R. V., & Ramayya, A. V. (2003). Augmentation of airlift pump performance with tapered upriser pipe - An experimental study. *Journal of the Institution of Engineers (India): Mechanical Engineering Division*,

84(3), 114–119.

Matrawy, K. K., & El-kom, S. (2014). Effect of Air Injection Strategy on Airlift Pump Performance. *International Journal of Control, Automation and Systems*,

3(4).

Margaris, D. P., & Papanikas, D. G. (1997). A generalized gas-liquid-solid three-phase flow analysis for airlift pump design. *Journal of Fluids Engineering*,

*Transactions of the ASME*, 119(4), 995–1002.

<https://doi.org/10.1115/1.2819528>

Morrison, G. L., Zeineddine, T. I., Henriksen, M., and Tatterson, G. B., Experimental analysis of the mechanics reverse circulation air lift pump, *Chem. Eng. Res.*, vol. 26, pp. 387–391, 1987.

Munson, B. R., Young, D. F., & Okiishi, T. H. (2009). *Fundamentals of Fluid Mechanics*. (W. Anderson, Ed.) (4th ed.). New York: John Wiley & Sons, Inc.

Pougatch, K., & Salcudean, M. (2008). Numerical modelling of deep sea air-lift. *Ocean Engineering*,

35(11–12), 1173–1182.

<https://doi.org/10.1016/j.oceaneng.2008.04.006>

- Sadatomi, M., Kawahara, A., & Nishiyama, T. (2012). Experiment and Performance Prediction of Bubble-Jet Type Air-Lift Pump for Dredging Sediments on Sea and Lake Beds. *Advances in Fluid Mechanics and Heat Transfer*, 311–316.
- Sorour, M. M., Experiments in two phase flow bubble slug transition in a vertical annulus, *Int. J. Multiphase Flow*, vol. 1, pp. 167–183, 1984.
- Sorour, M. M. and Elbeshbeeshy, M. S., Void fraction and pressure fluctuations of bubbly flow in a vertical annular channel, *Exp. Fluids*, vol. 4, pp. 163–170, 1986.
- Tighzert, H., Brahimi, M., Kechroud, N., & Benabbas, F. (2013). Effect of submergence ratio on the liquid phase velocity, efficiency and void fraction in an air-lift pump. *Journal of Petroleum Science and Engineering*, 110, 155–161. <https://doi.org/10.1016/j.petrol.2013.08.047>
- Usami, T. & Saito, T. 1986 Studies on the hydraulic lifting of solids by air-lift pump. Report of the National Research Institute for Pollution and Resources 38, pp. 1-101. In Japanese.
- Wahba, E. M., Gadalla, M. A., Abueidda, D., Dalaq, A., Hafiz, H., Elawadi, K., & Issa, R. (2014). On the Performance of Air-Lift Pumps: From Analytical Models to Large Eddy Simulation. *Journal of Fluids Engineering, Transactions of the ASME*, 136(11). <https://doi.org/10.1115/1.4027473>
- Weber, M., and Dedegil, Y., 1976, "Transport of Solids According to the Airlift Principle," Fourth International Conference on the Hydraulic Transport of Solids in Pipes, May 18-21, Alberta, Canada, paper HI.
- Weber, M., 1982, "Vertical Hydraulic Conveying of Solids by Airlift," *Journal of Pipelines*, pp. 137-152.
- Yoshinaga, T., & Sato, Y. (1996). PERFORMANCE OF AN AIR-LIFT PUMP FOR CONVEYING COARSE PARTICLES. *International Journal Multiphase Flow*, vol 22, 223–238.