

DAFTAR PUSTAKA

- Abriyant, R. Y., (2019). Studi Eksperimental Pengaruh *Submergence Ratio* dan Debit Udara Masuk Terhadap Kinerja *Airlift pump microbubble generator type* Dua Fasa *Liquid-Gas*. (Skripsi sarjana, Departemen Teknik Mesin dan Industri, Universitas Gadjah Mada, Yogyakarta).
- Jana, A. K., Das, G., & Das, P. K. (2006). Flow regime identification of two-phase liquid-liquid upflow through vertical pipe. *Chemical engineering science*, 61(5), 1500-1515. <https://doi.org/10.1016/j.ces.2005.09.001>.
- Barnea, D., Shoham, O., & Taitel, Y., (1980). Flow Pattern Characterization in Two Phase Flow by Electrical Conductance Probe. *Int. J. Multiphase Flow*, Vol. 6, pp. 387-397. [https://doi.org/10.1016/0301-9322\(80\)90001-4](https://doi.org/10.1016/0301-9322(80)90001-4).
- Bin Sun, Yongjun Zheng, (2008). Hilbert-Huang Transform Analysis of Dynamic Differential Pressure Signal of Gas-liquid Two-phase Flow, *Congress on Image and Signal Processing, IEEE*. <https://doi.org/10.1109/CISP.2008.604>.
- Callister Jr, W. D. (2009). Rethwisch, David G.,". *Materials science and engineering: an introduction*," New York: John Wiley & Sons.
- Cengel, Y. A. (2006). *Thermodynamics An Engineering Approach 5th Edition* by Yunus A. Cengel: *Thermodynamics An Engineering Approach*. Boston: McGraw-Hill.
- CNN Indonesia. (2019). *kemarau-panjang-krisis-air-bersih-meluas-di-sejumlah-wilayah*. <https://www.cnnindonesia.com/nasional/20190815064634-32-421471/kemarau-panjang-krisis-air-bersih-meluas-di-sejumlah-wilayah>. Diakses online pada 12 Oktober 2019.

- Damarjati, B. A. (2019). *Teknologi Aerasi untuk Pengolahan Limbah*.
<https://wastewater.wg.ugm.ac.id/2019/09/04/teknologi-aerasi-untuk-pengolahan-limbah/>. Diakses online pada 13 Oktober 2019.
- Deendarlianto, Wiratni, Alva, E. T., Indarto, Anggita, G. W. I., (2015), The Implementation of a Developed Micro bubble Generator on The Aerobic Wastewater Treatment. *International Journal of Technology*, Vol. 6, pp. 924-930. <https://doi.org/10.14716%2Fijtech.v6i6.1696>.
- Deendarlianto, Supraba, I., Majid, A. I., Pradecta, M. R., Widyaparaga, A. (2019). Experimental investigation on the flow behavior during the solid particles lifting in a micro-bubble generator type airlift pump system. *Case Studies in Thermal Engineering*, Vol. 13, 100386. <https://doi.org/10.1016/j.csite.2018.100386>.
- Erian, F. R., Pease, L.F., (2007). Three- Phase Upward Flow in a Vertical Pipe. *International Journal of Multiphase Flow*, Vol. 33, No. 5, pp. 498-509. <https://doi.org/10.1016/j.ijmultiphaseflow.2006.12.007>.
- Franca F., Acikgoz M., Lahey R. T., Clause A., (1991). The Use of Fractal Techniques for Flow Regime Identification. *Int. J. Multiphase Flow*, 17, 545-552.
- Hanafizadeh, P., Ghanbarzadeh, S., Saidi, M. H. (2011). Visual Technique for Detection of Gas-Liquid Two-Phase Flow Regime in The Airlift pump. *Journal of Petroleum Science and Engineering*, Vol. 75, No. 3–4, pp. 327–335. <https://doi.org/10.1016/j.petrol.2010.11.028>.
- Hanafizadeh, Ghorbani., B. (2012). Review Study on Airlift Pumping System. *Multiphase Science and Technology*, Vol. 24, No. 4, pp. 323-362. <https://doi.org/10.1615/MultScienTechn.v24.i4.30>.

- Hubbard, N. G., Dukler A. E., (1966). The Characterization of Flow Regimes for Horizontal TwoPhase Flow. *Proc. Heat Transfer and Fluid Mechanics Institute*, 1966, pp. 100-121.
- Ighagai, S., Yamane, M., Roko, K. (1965). Measurement of the component flows in a vertical, two-phase flow by making use of the pressure fluctuations. *Bulletin. J.S.M.E.* 8(31), 375-390. <https://doi.org/10.1299/jsme1958.8.375>.
- Jaiboon, O. A., Chalermssinsuwan, B., Mekasut, L., & Piumsomboon, P. (2013). Effect of flow pattern on power spectral density of pressure fluctuation in various fluidization regimes. *Powder technology*, 233, 215-226. <https://doi.org/10.1016/j.powtec.2012.09.014>.
- Jones, O. C., Zuber, N. (1975). The Interrelation Between Void Fraction Fluctuations and Flow Patterns in Two Phase Flow. *Int. J. Multiphase Flow*. Vol. 2, pp. 273-306. [https://doi.org/10.1016/0301-9322\(75\)90015-4](https://doi.org/10.1016/0301-9322(75)90015-4).
- Juwana, W.E., Widayatama, A., Dinaryanto, O., Budhijanto, W. (2019). Hydrodynamic characteristics of the microbubble dissolution in liquid using orifice type microbubble generator. *Chemical Engineering Research and Design*, Vol. 141, pp. 436-448. <https://doi.org/10.1016/j.cherd.2018.11.017>.
- Kato, H., Miyazawa, T., Timaya, S., & Iwasaki, T. (1975). A study of an air-lift pump for solid particles. *Bulletin of JSME*, 18(117), 286-294. <https://doi.org/10.1299/jsme1958.18.286>.

- Kassab, S. Z., Kandil, H. A., Warda, H. A., Ahmed, W. H. (2007). Experimental and analytical investigations of airlift pumps operating in three-phase flow. *Chemical Engineering Journal*, 131(1-3), 273-281. <https://doi.org/10.1016/j.cej.2006.12.009>.
- Kassab, S. Z., Kandil, H. A., Warda, H. A., & Ahmed, W. H. (2009). Air-lift pumps characteristics under two-phase flow conditions. *International Journal of Heat and Fluid Flow*, 30(1), 88-98. <https://doi.org/10.1016/j.ijheatfluidflow.2008.09.002>.
- Kurniawan, D., (2019). Studi Eksperimental Pengaruh Submergence Ratio dan Debit Udara Masuk Terhadap Karakteristik *Airlift pump microbubble generator type* Dua Fasa *Liquid-Gas*. (Skripsi sarjana, Departemen Teknik Mesin dan Industri, Universitas Gadjah Mada, Yogyakarta).
- Li, P. (2006). Development of Advanced Water Treatment Technology Using *Microbubbles*. *PhD Dissertation Keio University, Japan*, (October).
- Li, P., & Tsuge, H. (2006). Water treatment by induced air flotation using microbubbles. *Journal of Chemical Engineering of Japan*, 39(8), 896-903. <https://doi.org/10.1252/jcej.39.896>.
- Lin, P. Y., Hanratty, T. J. (1987). Detection of Slug Flow from Pressure Measurements. *International Journal of Multiphase Flow*, 13(1), 13-21. [https://doi.org/10.1016/0301-9322\(87\)90003-6](https://doi.org/10.1016/0301-9322(87)90003-6).
- Matsui, G., (1984). Identification of Flow Regimes in Vertical Gas-Liquid Two-Phase Flow Using Differential Pressure Fluctuations. *International Journal of Multiphase Flow*, Vol. 10, pp. 711-720. [https://doi.org/10.1016/0301-9322\(84\)90007-7](https://doi.org/10.1016/0301-9322(84)90007-7).

- Matsui, G., (1986). Automatic Identification of Flow Regimes in Vertical Two-Phase Flow Using Differential Pressure Fluctuations. *Nuclear Engineering and Design*, Vol. 95, pp. 221-231. [https://doi.org/10.1016/0029-5493\(86\)90049-X](https://doi.org/10.1016/0029-5493(86)90049-X).
- Munson, B. R., Young, D. F., & Okiishi, T. H. (2009). *Fundamentals of Fluid Mechanics*. (W. Anderson, Ed.) (4th ed.). New York: John Wiley & Sons, Inc.
- Nurlina, N. (2013). Penentuan Mean, Variansi, Skewness dan Kurtosis dari Distribusi Gamma dan Weibull dengan Menggunakan Momen Pertama Hingga Momen ke Empat. (*Doctoral dissertation, Universitas Islam Negeri Alauddin Makassar*). <http://repositori.uin-alauddin.ac.id/11496/>.
- Ohnari, H. (2002). Water purification of ocean environment and revival of fisheries cultivation using micro bubble technology. In *The 21st Symposium on Multiphase Flow, Nagoya, Japan, 2002*.
- Polizelli, M.A., Menegalli, F.C., Telis, V.R.N., Telis- Romero, J., (2003). *Friction losses in valves and fittings for power-law fluid*. Braz. J. Chem. Eng. 20, 455-463.
- Sadatomi, M., Kawahara, A., Kano, A., Ohtomo, A., (2005), Performance of New Microbubble Generator with a Spherical Body in a Flowing Water Tube, *Experimental Thermal and Fluid Science*, Vol. 29, No.5, pp. 615 – 623. <https://doi.org/10.1016/j.expthermflusci.2004.08.006>.

- Sadatomi, M., Kawahara, A., Nishiyama, T. (2012). Experiment and Performance Prediction of Bubble-Jet Type Air-Lift Pump for Dredging Sediments on Sea and Lake Beds. *Advances in Fluid Mechanics and Heat Transfer*, pp. 311–316. <http://dx.doi.org/10.1016/j.expthermflusci.2012.03.002>.
- Sadatomi, M., Kawahara, A., Matsuura, H., Shikatani, S., (2012), Microbubble Generation and Bubble Dissolution in Water by a Multi - fluid Mixer with Orifice and Porous Tube. *Experimental Thermal and Fluid Science*, Vol. 41, pp. 23–30.
- SAMCO. (2017). *How Much Does an Industrial Water Treatment System Cost?* <https://www.samcotech.com/how-much-does-an-industrial-water-treatment-system-cost/>. Diakses online pada 12 Oktober 2019.
- Sciencedaily. (2019). *Water Scarcity*. https://www.sciencedaily.com/terms/water_scarcity.htm. Diakses online pada 12 Oktober 2019.
- Shaban, H., Tavoularis, S. (2014). Identification of flow regime in vertical upward air–water pipe flow using differential pressure signals and elastic maps. *International Journal of Multiphase Flow*, 61, 62-72. <https://doi.org/10.1016/j.ijmultiphaseflow.2014.01.009>.
- Spedding, P. L., Spence, D. R. (1993). Flow regimes in two-phase gas-liquid flow. *International journal of multiphase flow*, 19(2), 245-280. [https://doi.org/10.1016/0301-9322\(93\)90002-C](https://doi.org/10.1016/0301-9322(93)90002-C).
- Stenning, A.H, Martin, C. B. (2011). An Analytical and Experimental Study of Air-Lift Pump Performance. *Journal of Engineering for Gas Turbines and Power*. Vol. 90, No. 2, pp. 106-110. <https://doi.org/10.1115/1.3609143>.

- Taleb, Fawzy Sh. Abou., Al-Jarrah, Jawdat A., (2017), Experimental Study of an Air-Lift Pump. *Engineering, Technology & Applied Science Research*, Vol.7, No.3, pp. 1676-1680.
- Tempo.co. (2011). 30 Penyakit Ini Akibat Krisis Air Bersih. <https://gaya.tempo.co/read/354927/30-penyakit-iniakibat-krisis-air-bersih/full&view=ok>. Diakses online pada 12 Oktober 2019.
- Tighzert, H., Brahimi, M., Kechroud, N., & Benabbas, F. (2013). Effect of submergence ratio on the liquid phase velocity, efficiency and void fraction in an air-lift pump. *Journal of Petroleum Science and Engineering*, 110, 155-161. <https://doi.org/10.1016/j.petrol.2013.08.047>.
- Tutu, (1982), Pressure Fluctuations and Flow Pattern Recognition in Vertical Two Phase Gas-Liquid Flows. *International Journal of Multiphase Flow*, Vol. 8, pp. 443–447. [https://doi.org/10.1016/0301-9322\(82\)90053-2](https://doi.org/10.1016/0301-9322(82)90053-2).
- Wang, Z., Deng, Y., Pan, Y., Jin, Y., & Huang, F. (2020). Experimentally investigating the flow characteristics of airlift pumps operating in gas-liquid-solid flow. *Experimental Thermal and Fluid Science*, 112, 109988. <https://doi.org/10.1016/j.expthermflusci.2019.109988>.
- Weisman J., Duncan D., Gibson J. et al, (1979). Effects of Fluid Properties and Pipe Diameter on Two-Phase Flow Patterns in Horizontal Lines. *Int. J. Multiphase Flow*, Vol. 5, No.6, pp. 437-462. [https://doi.org/10.1016/0301-9322\(79\)90031-4](https://doi.org/10.1016/0301-9322(79)90031-4).

Wilkins, R. J., D. K. Thomas, (2008). A Simple Technique for Determining *Slug* Frequency Using Differential Pressure. *Journal of Energy Resources Technology*, Vol. 130(1). <https://doi.org/10.1115/1.2824297>.

Wu Haojiang, Zhou Fangde, Wu Yuyuan, (2001). Intelligent Identification System of Flow Regime of Oil-Gas-Water Multiphase Flow. *Int. J. Multiphase Flow*, Vol. 27, pp. 459-475. [https://doi.org/10.1016/S0301-9322\(00\)00022-7](https://doi.org/10.1016/S0301-9322(00)00022-7).

Xie Tao, (2004). Hydrodynamic Characteristics of Gas/Liquid/Fiber Three-Phase Flows Based on Objective and Minimally-Intrusive Pressure Fluctuation Measurements. *Dissertation, Georgia Institute of Technology*. <http://hdl.handle.net/1853/4814>.

Yoshinaga, T., Sato, Y. (1996). Performance of an Air-Lift *Pump* for Conveying Coarse Particles. *International Journal of Multiphase Flow*, 22, 223–238. [https://doi.org/10.1016/0301-9322\(95\)00067-4](https://doi.org/10.1016/0301-9322(95)00067-4).