

## DAFTAR PUSTAKA

- Abhinash, K., & Kishore, P. S. (2018). Performance of a tangentially fired boiler in a thermal power plant. *International Journal of Research - Granthaalayah*, 391-406.
- Achmad, R. (2004). *Kimia Lingkungan*. Yogyakarta: Andi.
- Asotani, T., Yamashita, T., Tominaga, H., Uesugi, Y., Itaya, Y., & Mori, S. (2008). Prediction of Ignition Behavior in a Tangentially Fired Pulverized Coal Boiler Using CFD. *Fuel* 87, 482-490.
- Cengel, Y. A., & Boles, M. A. (2006). *Thermodynamics An Engineering Approach*. McGraw-Hill.
- Febyansari, R. (2013). Studi Numerik Karakteristik Aliran dan Pembakaran pada Tangentially Fired Pulverized Coal Boiler dengan Menggunakan Oxy Fuel pada Kasus Coal Blending antara Medium Rank Coal (MRC) dan Low Rank Coal (LRC). *Teknik Mesin FTI-ITS*.
- Hu, L., Zhang, Y., Chen, D., Fang, J., Zhang, M., Wu, Y., . . . Lyu, J. (2019). Experimental study on the combustion and NO<sub>x</sub> emission characteristic of a bituminous coal blended with semi-coke. *Applied Thermal Engineering* 160.
- Ikeda, M., & Makino, H. (2003). Development of reduction technology of both emissions of NO<sub>x</sub> and unburned carbon by infurnace blended method. *Report No. M07007*.
- Kent, & A., J. (1992). *Riegel's Handbook of Industrial Chemistry*. USA: Springer.
- Kumar, A. (2009). *Energy performance assessment of boiler*. India: Bureau of Energy Efficiency.
- Li, Z., & Miao, Z. (2019). Primary air ratio affects coal utilization mode and NO<sub>x</sub> emission in lignite pulverized boiler. *Energy* 187.

- Li, Z., Miao, Z., Zhou, Y., Wen, S., & Li, J. (2018). Influence of increased primary air ratio on boiler performance in a 660 MW brown coal boiler. *Energy* 152, 804-817.
- Vu, J. (2017). Modelling of Convective Heat Transfer in Porous Media. *Electronic Thesis and Dissertation Repository*.