

DAFTAR PUSTAKA

- Avouris, P., and Dimitrakopoulos, C., 2012, Graphene: synthesis and applications, *Materials Today*, 15(3), 86-97.
- Bianco, A., Cheng, H. M., Enoki, T., Gogotsi, Y., Hurt, R. H., Koratkar, N., Kyotani, T., Monthieux, M., Park, C. R., Tascon, J. M. D., and Zhang, J., 2013, All in the Graphene Family – A Recommended Nomenclature for Two-Dimensional Carbon Materials, *Carbon*, 65, 1-6.
- Chang, Y., Lye, M. L., and Zeng, H.C., 2005, Large-Scale Synthesis of High-Quality Ultralong Copper Nanowires, *Langmuir*, 21, 3746-3748.
- Choi, J. H., Lee, J., Byeon, M., Hong, T. E., Park, H., and Lee, C. Y., 2020, Graphene-Based Gas Sensors with High Sensitivity and Minimal Sensor-to-Sensor Variation, *ACS Appli. Nano Matter.*, 3, 2257-2265.
- Cui, F., Yu, Y., Dou, L. T., Sun, J. W., Yang, Q., Schildknecht, C., Schierle, A. K., and Yang, P. D., 2015, Synthesis of Ultrathin Copper Nanowires Using Tris(Trimethylsilyl)Silane for High-Performance and Low-Haze Transparent Conductors, *Nano Lett.*, 15, 7610-7615.
- Fan, X., Nie, W., Tsai, H., Wang, N., Huang, H., Cheng, Y., Wen, R., Ma, L., Yan, F., and Xia, Y., 2019, PEDOT:PSS for Flexible and Stretchable Electronics: Modifications, Strategies, and Applications, *Adv. Sci.*, 6(1900813), 1-41.
- Figueiredo, V., Elangovan, E., Gonçalves, G., Barquinha, P., Pereira, L., Franco, N., Alves, E., Martins, R., and Fortunato, E., 2008, Effect of Post-Annealing on the Properties of Copper Oxide Thin Films Obtained from the Oxidation of Evaporated Metallic Copper, *Applied Surface Science*, 254(13), 3949-3954.
- Fraden, J., 2010, *HandBook of Modern Sensor: Physics, Designs, and Applications*, 4th Edition, Springer, New York.
- Guo, H. Z., Lin, N., Chen, Y. Z., Wang, Z. W., Xie, Q. S., Zheng, T. C., Gao, N., Li, S. P., Kang, J. Y., and Cai, D. J., 2013, Copper Nanowires as Fully Transparent Conductive Electrodes, *Sci. Rep.*, 3.
- Hakimi, M., Salehi, A., and Boroumand, F. A., 2016, Fabrication and Characterization of an Ammonia Gas Sensor Based on PEDOT:PSS with N-doped Graphene Quantum Dots Dopant, *IEEE Sensors Journal*, 1-7.
- Haynes, W.M., 2014, *Handbook of Chemistry and Physics*, Boca Raton : CRC press.
- Jin, M. S., He, G. N., Zhang, H., Zeng, J., Xie, Z. X., and Xia, Y. N., 2011, Shape-Controlled Synthesis of Copper Nanocrystals in an Aqueous Solution with

- Glucose as a Reducing Agent and Hexadecylamine as a Capping Agent, *Angew.Chem. Int. Ed.*, 50, 10560-10564.
- Kim, Y. J., Kim, Y., Novoselov, K., Hong, B. H., Engineering Electrical Properties of Graphene: Chemical Approaches, 2015, *2D Mater.*, 2, 042001.
- Mardiansyah, D., Badloe, T., Triyana, K., Mehmood, M, Q., Hosseini, N, R., Lee, Y., Sabarman, H., Kim, K., and Rho, J., 2018, Effect of Temperature on the Oxidation of Cu Nanowires and Development of an Easy to Produce, Oxidation-Resistant Transparent Conducting Electrode Using a PEDOT:PSS Coating, *Scientific Reports*, 8:10639, 1-9.
- Nag, A., Mitra, A., and Mukhopadhyay, C. S., 2017, Graphene and Its Sensor-Based Applications: A Review, *Sensors and Actuators A:Physical*, 270, 177-194.
- Nam, V. B., and Lee, D., 2016, Copper Nanowires and Their Applications for Flexible, Transparent Conducting Films: A Review, *Nanomaterials*, 6(47), 1-17.
- Paknahad, M., Mcintosh, C., and Hoorfar, M., 2019, Selective Detection of Volatile Organic Compounds in Microfluidic Gas Detectors Based on “like dissolves like”, *Scientific Reports*, 9(161), 1-11.
- Park, C., Yoo, D., Im, S., Kim, S., Cho, W., Ryu, J., and Kim, H. J., 2017, Large-Scale Scalable RTCVD Graphene/PEDOT:PSS Hybrid Conductive Film for Application in Transparent and Flexible Thermoelectric Nanogenerators, *RSC Adv.*, 7, 25237-25243.
- Pinto, R. J. B., Lucas, J. M. F., Silva, F. M., Girão, A. V., Oliveira, F. J., Marques, P. A. A. P., and Freire, C. S. R., 2019, Bio-Based Synthesis of Oxidation Resistant Copper Nanowires Using an Aqueous Plant Extract, *Journal of Cleaner Production*, 221, 122-131.
- Rathmell, A. R., Bergin, S. M., Hua, Y. L., Li, Z. Y., and Willey, B. J., 2010, The Growth Mechanism of Copper Nanowires and Their Properties in Flexible, Transparent Conducting Films, *Adv. Matter*, 22, 3558-3563.
- Revathi, S., and Vijayakumar, S., 2018, Review on Graphene Synthesis and Sensor Applications, *IJECS*, 7(4), 9-16.
- Shi, Y., Li, H., Chen, L. Q., and Huang, X. J., 2005, Obtaining Ultra-Long Copper Nanowires via a Hydrothermal Process, *Sci. Technol. Adv. Mater*, 6, 761-765.
- Sun, K., Zhang, S., Li, P., Xia, Y., Zhang, X., Du, D., Isikgor, H. F., and Ouyang, J., 2015, Review on Application of PEDOTs and PEDOT:PSS in Energy Conversion and Storage Devices, *J Mater Sci: Mater Electron*, 1-26.



- Tang, Y., Ruan, H., Huang, Z., Shi, D., Liu, H., Chen, S., and Zhang, J., 2018, Fabrication of High-Quality Copper Nanowires Flexible Transparent Conductive Electrodes with Enhanced Mechanical and Chemical Stability, *Nanotechnology*, 29, 455706.
- Tarmidzi, F. M., and Sasongko, S. B., 2018, Synthesis A Flexible Conductive Film of Poly 3,4-Ethylenedioxythiophene Polystyrene Sulfonate (PEDOT:PSS) Using Spray Pyrolysis Method, *Int. Journal of Renewable Energy Development*, 7(2), 159-162.
- Umar, A., and Hahn, B. Y., 2010, Metal Oxide Nanostructures and Their Applications, American Scientific Publishers, 26650 The Old Road, Suite 208 Valencia, California 91381-0751, USA
- Xu, P., Chen, W., Wang, Q., Zhu, T., Wu, M., Qiao, J., Chen, Z., and Zhang, J., 2015, Effect of Transition Metal Precursors (Co, Fe, Cu, Mn, or Ni) on Pyrolyzed Carbon Supported Metal-Aminopyrine Electrocatalysts for Oxygen Reduction Reaction, *RSC Adv.*, 5, 6195-6206.
- Yang, P., Ye, X., Lau, C., Li, Z., Liu, X., and Lu, J., 2007, Design of Efficient Zeolite Sensor Materials for *n*-Hexane, *Analytical Chemistry*, 79(4), 1425-1432.
- You, Y., Zeng, W., Yin, Y.X., Zhang, J., Yang, C. P., Zhu, Y., 2015, Hierarchically Micro/Mesoporous Activated Graphene with A Large Surface Area for High Sulfur Loading in Li-S Batteries, *J. Mater. Chem. A*, 3, 4799-4802.
- Zhang, D. Q., Wang, R. R., Wen, M. C., Weng, D., Cui, X., Sun, J., Li, H. X., and Lu, Y. F., 2012, Synthesis of Ultralong Copper Nanowires for High-Performance Transparent Electrodes, *J. Am. Chem. Soc.*, 134, 14283-14286.