



## DAFTAR PUSTAKA

- Waston dkk, 1996, Characterization of na active clamp flyback topology for Power factor Corrections applications, *IEEE Trans. Power Electron.*, vol.11,no1,Pp.191-198.
- Pinheiro ddk, 2002, A Comparison of UPS for Powering Hybrid Fiber/Coaxial Networks, *IEEE Trans. Power Electronics*, vol. 17,no. 3, pp. 389-397.
- H.F.Liu dkk, 2002, “Flexible and low cost design for a flyback AC/DC converter with harmonic current correction,” *IEEE Trans. PowerElectron.*, vol. 20, no. 1, pp. 17–24
- H. F. Liu dkk, 2005, “Flexible and low cost design for a flybackAC/DC converter with harmonic current correction,” *IEEE Trans. Power Electron.*, vol. 20, no. 1, pp. 17–24.
- L.Shi dkk, 2012, “Design of rectifier diode temperature compensation circuit in flyback converter,” *IET Circuits Devices Syst.*, vol. 6, no. 4, pp. 246–251.
- B. Wang dkk, 2010, “A method of reducing the peakto average ratio of LED current for electrolytic capacitor-less AC/DCdrivers,” *IEEE Trans. Power Electron.*, vol. 25, no. 3, pp. 592–601.
- T. T. Vu dkk, 2012, “Primary-side sensing for a flyback converter in both continuous and discontinuous conduction mode,” in *Proc. Int. Conf. IET Irish Signals Syst.*
- H. H. Chou dkk, 2013, “An adaptive output current estimation circuit for a primary-side controlled LED driver,” *IEEE Trans.Power Electron.*, vol. 28, no. 10, pp. 4811–4819.



- P. Hsieh dkk, 2013, “A primary-side-control quasi-resonant flyback converter with tight output voltage regulation and self-calibrated valley switching,” in *Proc. Int. Expo. IEEE Energy Convers. Congr.* pp. 3406–3412.
- X. Chen dkk, 2013, “Evaluation of primary side control schemes for flyback converter with constant current output,” in *Proc. Int. Conf. IEEE App. Power Electron* pp.1859–1863.
- J. Park dkk, 2014, “A CCM/DCM dual-mode synchronous rectification controller for a high-efficiency flyback converter,” *IEEE Trans. Power Electron.*, vol. 29, no. 2, pp. 768–774.
- L. Shi dkk, 2015, “Current estimation circuit for discontinuous conduction mode flybackpulse-width modulation controller,” *IET Power Electron.*, vol. 8, no. 7, pp. 1217–1223.
- C. N. Wu dkk, 2015, “Primary-side peak current measurement strategy for high-precision constant output current control,” *IEEE Trans Power Electron.*, vol. 30, no. 2, pp. 967–975.
- Swati ddk,2017, Flyback Converter Design and Simulation,International jurnal of advanced Research in electrical,Electronics and instrumentation engineering,vol.6,issn 2278 – 8875
- Yogi dkk,2017, Design of a Low Cost High Efficiency Multiple Output Self Oscillating Flyback Converter,IJITEE,vol 1,no2
- Chong dkk,2019,A Single-Switchd High-Switching-Frequencsy Quasi-Resoant Flyback Converter, IEEE Transactions On Power Electronics, Vol. 34, No. 9