

## TABLE OF CONTENTS

|  |              |
|--|--------------|
| <b>THESIS PROPOSAL</b>   | <b>i</b>     |
| <b>VALIDATION</b>  | <b>ii</b>    |
| <b>FINAL ASSIGNMENT QUESTION SCRIPT</b>  | <b>iii</b>   |
| <b>PLAGIATION FREE STATEMENT</b>   | <b>iv</b>    |
| <b>DEDICATION PAGE</b>   | <b>v</b>     |
| <b>PREFACE</b>   | <b>vi</b>    |
| <b>TABLE OF CONTENTS</b>   | <b>viii</b>  |
| <b>LIST OF FIGURES</b>   | <b>xi</b>    |
| <b>LIST OF TABLES</b>  | <b>xiv</b>   |
| <b>LIST OF NOTATIONS AND ABBREVIATIONS</b>   | <b>xvi</b>   |
| <b>ABSTRACT</b>  | <b>xvii</b>  |
| <b>INTISARI</b>  | <b>xviii</b> |
| <b>CHAPTER I</b>   | <b>1</b>     |
| 1.1. Background  | 1            |
| 1.2. Problem Statement   | 2            |
| 1.3. Scope of Problem  | 3            |
| 1.4. Object of Research  | 3            |
| 1.5. Benefit of Research   | 3            |
| <b>CHAPTER II</b>  | <b>4</b>     |
| 2.1. Use of parallelism Filament Composites for Orthosis Applications<br>by 3D printing                              | 5            |
| 2.2. Use of Parallelism Materials for Tissue Engineering<br>Scaffolds Fabricated by Microcellular Injection Moulding | 7            |
| 2.3. Use of Parallelism Material for Bioplastics and Elastomers  | 8            |
|  | <b>viii</b>  |

|  |           |
|--|-----------|
| <b>CHAPTER III</b>   | <b>11</b> |
| 3.1. Polylactic Acid (PLA)   | 11        |
| 3.2. Thermoplastic Polyurethane (TPU)  | 11        |
| 3.3. Fused Deposition Modelling (FDM)  | 13        |
| 3.4. Mechanical properties on material   | 14        |
| 3.4.1. Stress  | 14        |
| 3.4.2. Strain  | 15        |
| 3.4.3. Stress-Strain Curve   | 15        |
| 3.5. Tensile test  | 16        |
| <b>CHAPTER IV</b>  | <b>18</b> |
| 4.1. Research Materials  | 18        |
| 4.2. Research Tools  | 19        |
| 4.3. Research Procedure  | 20        |
| 4.3.1. Design  | 20        |
| 4.3.2. 3D Printing   | 21        |
| 4.3.3. Testing   | 23        |
| 4.4. Research Flow Chart   | 25        |
| <b>CHAPTER V</b>   | <b>26</b> |
| 5.1. Effect of Extrusion Temperature on the Tensile Strength of PLA/TPU multi-materials using the FDM Method | 26        |
| 5.2. Effect of Raster Orientation on the Tensile Strength of TPU and PLA using the FDM Method                | 29        |
| 5.2.1. PLA Specimen  | 30        |
| 5.2.2. TPU Specimen  | 32        |
| 5.2.3. PLA-TPU multi-material Specimen   | 34        |
| 5.2.4. Overall Characteristic for PLA/TPU multi-material   | 37        |

|  |  |           |
|--|--|-----------|
| 5.3.   | Observation of material macro structure  | 39        |
| 5.4.   | Discussion   | 42        |
| 5.4.1.   | Appropriate extrusion temperature for PLA/TPU multi-material                     | 42        |
| 5.4.2.   | Appropriate raster orientation for PLA/TPU multi-material                        | 43        |
| 5.4.3.   | Possibility of controlling mechanical properties using a multi-material approach | 44        |
| <b>CHAPTER VI</b>  |  | <b>45</b> |
| 6.1.   | Conclusions  | 45        |
| 6.2.   | Recommendations  | 45        |
| <b>REFERENCE</b>   |  | <b>47</b> |
| <b>ATTACHMENT</b>  |  | <b>49</b> |
| Attachment 1. Tensile test results with extrusion temperature variations for PLA/TPU multi-material          |  | 49        |
| Attachment 2. Tensile test results with raster orientation variations to for PLA specimen                    |  | 51        |
| Attachment 3. Tensile test results with raster orientation variations to for TPU specimen                    |  | 52        |
| Attachment 4. Tensile test results with raster orientation variations to for PLA/TPU multi-material specimen |  | 53        |