

TABLE OF CONTENTS

STATEMENT OF ANTI PLAGIARISM	2
APPROVAL FORM	3
PROJECT FORM.....	4
TABLE OF CONTENTS	5
LIST OF FIGURES.....	6
LIST OF TABLES	7
ABSTRACT	8
1. Introduction	9
1.1 Introduction to OAKRIDGE	9
1.2 Introduction to Fukushima Corium Extraction Project	10
1.2.1 Fukushima Accident.....	10
1.2.2 IRID.....	10
1.2.3 Oakridge Proposition.....	11
1.2.4 Extraction System	12
1.3 Objectives and Goals.....	13
1.4 Scope and Limit	13
2. General Introduction	14
2.1 Progress of Debris Extraction Project	14
2.2 Introduction to PANTHERE	14
2.2.1 Mathematical models used in PANTHERE	16
2.2.2 Comparison Validation of PANTHERE and MCNP	17
2.2.3 PANTHERE Technical validation	17
2.2.4 Geometry Importation	18
2.2.5 Distance study for DED	20
2.3 Corium Study	21
3. Methodology	23
3.1 Corium Modelisation.....	23
3.2 Capsule Modelling	24
3.2.1 Characterization and Zoning	24
3.3 BWR Reactor Modelling.....	26
3.4 Creation of Extraction System	28
3.4.1 Objectives.....	28
3.4.2 The Modeling of Capsule travel from the reactor to SFP	28
4. Results and Discussions	30
4.1 Calculation of dose rate based on the trajectory of the capsule	30
5. Conclusion and Recommendation.....	32
5.1 Conclusion.....	32
5.2 Recommendation.....	32
REFERENCE.....	34
APPENDIX	35
Appendix 1 Abstract, Conclusion and Recommendation in French	35
Appendix 2 SALOME integration Module	38
Appendix 3 PANTHERE Validation Case.....	40
Appendix 4 Corium characterization	42

LIST OF FIGURES

Figure 1 OAKRIDGE field of Nuclear and its clients	9
Figure 2 IRID objectives after the establishment	10
Figure 3 OAKRIDGE debris retrieval proposal	12
Figure 4 Capsule design	13
Figure 5 PATHERE integration system	15
Figure 6 The attenuation principle for shielding materials in gamma decay	16
Figure 7 STEP Random geometry	19
Figure 8 STL random geometry with a radioactive source (orange) and point 3, point 2 and point 1 (from right to left)	19
Figure 9 IGES/IGS random geometry	20
Figure 10 Capsule Co-60 in the container with several points to test the distance	20
Figure 11 DED calculation based on different distance	21
Figure 12 Corium composition in ORIGEN	23
Figure 13 Simplified corium composition in PANTHERE	24
Figure 14 Capsule and tube modeled by PANTHERE	24
Figure 15 Capsule and tube zoning to get rendering data around the capsule	25
Figure 16 Graphic presenting the three configurations	26
Figure 17 Initial blueprint of BWR	26
Figure 18 BWR modeled in PANTHERE	27
Figure 19 Legends on point of observation in Fukushima Reactor	27
Figure 20 Image of Capsule, tube, and concrete modeled in MCNP	29
Figure 21 The simulation of the capsule positions and his path from the RPV to the SFP	29
Figure 22 The 6 points of observation generated at the top of the reactor	29
Figure 23 Dose rate based on the travel of the capsule	30
Figure 24 Dose rate proportion of each capsule	31



LIST OF TABLES

Table 1 Comparison between PANTHERE and MCNP (if we use MCNP as Detector)	17
Table 2 PANTHERE Installation Validation from two sources	18
Table 3 STEP file Calculation result.....	19
Table 4 STL file Calculation result	19
Table 5 IGES/IGS file Calculation result.....	20
Table 6 DED of two sources based on different points on Full-scale BWR(in mSv/h)	28