

DAFTAR PUSTAKA

- Ang, K. C., Leong, K. F., Chua, C. K., & Chandrasekaran, M. (2006). Investigation of the mechanical properties and porosity relationships in fused deposition modelling-fabricated porous structures. *Rapid Prototyping Journal*, 12(2), 100-105. doi:10.1108/13552540610652447
- Benwood, C., Anstey, A., Andrzejewski, J., Misra, M., & Mohanty, A. K. (2018). Improving the Impact Strength and Heat Resistance of 3D Printed Models: Structure, Property, and Processing Correlations during Fused Deposition Modeling (FDM) of Poly (Lactic Acid). *ACS Omega*, 3(4), 4400-4411. doi:10.1021/acsomega.8b00129
- BS EN ISO 179-1, 2010, *Plastics - Determination of Charpy impact properties*.
- Chacón, J., Caminero, M., García-Plaza, E., & Núñez, P. (2017). Additive manufacturing of PLA structures using fused deposition modelling: Effect of process parameters on mechanical properties and their maksimal selection. *Materials & Design*, 124, 143-157. doi:10.1016/j.matdes.2017.03.065
- Coogan, T. J., & Kazmer, D. O. (2017). Healing simulation for bond strength prediction of FDM. *Rapid Prototyping Journal*, 23(3), 551–561. <https://doi.org/10.1108/RPJ-03-2016-0051>
- Farah, S., Anderson, D. G., & Langer, R. (2016). Physical and mechanical properties of PLA, and their functions in widespread applications — A comprehensive review. *Advanced Drug Delivery Reviews*, 107, 367-392. doi:10.1016/j.addr.2016.06.012
- Firmansyah. (2020, June 16). Impact Test. Retrieved August 17, 2020, from <https://www.detch.co.id/impact-test/>
- Harris, M., Potgieter, J., Archer, R., & Arif, K. M. (2019). Effect of Material and Process Specific Factors on the Strength of Printed Parts in Fused Filament Fabrication: A Review of Recent Developments. *Materials*, 12(10), 1664. doi:10.3390/ma12101664

- Jonathan, T., Torres, J., Cole, M., Owji, A., DeMastry, Z., & Gordon, A. P. (2016). An approach for mechanical property optimization of fused deposition modeling with polylactic acid via design of experiments. *Rapid Prototyping Journal*, 22(2), 387–404. <https://doi.org/10.1108/RPJ-07-2014-0083>
- Ngo, T. D., Kashani, A., Imbalzano, G., Nguyen, K. T., & Hui, D. (2018). Additive manufacturing (3D printing): A review of materials, methods, applications and challenges. *Composites Part B: Engineering*, 143, 172-196. doi:10.1016/j.compositesb.2018.02.012
- Ostafinska, A., Fortelny, I., Nevoralova, M., Hodan, J., Kredatusova, J., & Slouf, M. (2015). Synergistic effects in mechanical properties of PLA/PCL blends with optimized composition, processing, and morphology. *RSC Advances*, 5(120), 98971-98982. doi:10.1039/c5ra21178f
- Popescu, D., Zapciu, A., Amza, C., Baci, F., & Marinescu, R. (2018). FDM process parameters influence over the mechanical properties of polymer specimens: A review. *Polymer Testing*, 69(April), 157–166. <https://doi.org/10.1016/j.polymertesting.2018.05.020>
- Putra, W. T., Ismono, I., Fadelan, F., & Winardi, Y. (2017). Analisa Hasil Uji Impak Sampah Plastik Jenis PP, PET, dan Campuran (PP + PET). *R.E.M. (Rekayasa Energi Manufaktur) Jurnal*, 2(1), 51. doi:10.21070/r.e.m.v2i1.751
- Svensson, E. (2017). *Material Characterization of 3D-Printed Energy-Absorbent Polymers Inspired by Nature* (Unpublished master's thesis). Chalmers University of Technology.
- Too, M., Leong, K., Chua, C., Du, Z., Yang, S., Cheah, C., & Ho, S. (2002). Investigation of 3D Non-Random Porous Structures by Fused Deposition Modelling. *The International Journal of Advanced Manufacturing Technology*, 19(3), 217-223. doi:10.1007/s001700200016
- Ultimaker. (2017). Technical Datasheet PLA.
- Valerio, O., Misra, M., & Mohanty, A. K. (2017). Sustainable biobased blends of poly(lactic acid) (PLA) and poly(glycerol succinate-co-maleate) (PGSMA) with balanced performance prepared by dynamic vulcanization. *RSC Advances*, 7(61), 38594-38603. doi:10.1039/c7ra06612k
- Yang, T. (2018). Effect of Extrusion Temperature on the Physico-Mechanical Properties of Unidirectional Wood Fiber-Reinforced Polylactic Acid Composite

(WFRPC) Components Using Fused Deposition Modeling. *Polymers*, 10(9), 976. doi:10.3390/polym10090976