

DAFTAR PUSTAKA

- [1] S. SERBI, “Sejarah Singkat Internet of Things (Iot),” *Netnesia*, 2015.
<https://idcloudhost.com/yuk-ketahui-sejarah-singkat-mengenai-internet-things-iot/> (accessed Aug. 24, 2020).
- [2] Firdaus, *Wireless Sensor Network Teori dan Aplikasi*. Yogyakarta: Graha Ilmu, 2014.
- [3] C. A. L. Garzón and O. J. R. Riveros, “Temperature, humidity and luminescence monitoring system using Wireless Sensor Networks (WSN) in flowers growing,” *2010 IEEE ANDESCON Conf. Proceedings, ANDESCON 2010*, pp. 1–4, 2010, doi: 10.1109/ANDESCON.2010.5633140.
- [4] Djunaiddin, B. Armynah, and B. Abdullah, “Desain dan Implementasi Sistem Alat Ukur Kelembapan Tanah,” *Fis. Fak. Mat. dan Ilmu Pengetah. Alam Univ. Hasanuddin*, pp. 1–5, 2015.
- [5] N. F. Puspitasari, “Analisis Rssi (Receive Signal Strength Indicator) Terhadap Ketinggian Perangkat Wi-Fi Di Lingkungan Indoor Nila Feby Puspitasari Pendahuluan Latar Belakang Masalah Batasan Masalah Tujuan dan Manfaat Penelitian Dasar Teori Wi-Fi (Wireless Fidelity) Ars,” *J. Ilm. Dasi*, vol. 15, no. 04, pp. 32–38, 2018.
- [6] J. T. Zou, C. Y. Wang, and Y. M. Wang, “The development of indoor positioning aerial robot based on motion capture system,” *Proc. IEEE Int. Conf. Adv. Mater. Sci. Eng. Innov. Sci. Eng. IEEE-ICAMSE 2016*, pp. 380–383, 2017, doi: 10.1109/ICAMSE.2016.7840347.
- [7] P. Wang and Y. Luo, “Research on WiFi indoor location algorithm based on RSSI Ranging,” *Proc. - 2017 4th Int. Conf. Inf. Sci. Control Eng. ICISCE 2017*, no. 2, pp. 1694–1698, 2017, doi: 10.1109/ICISCE.2017.354.
- [8] T. Chuenurajit, S. Phimmasean, and P. Cherntanomwong, “Robustness of 3D indoor localization based on fingerprint technique in wireless sensor

- networks,” *2013 10th Int. Conf. Electr. Eng. Comput. Telecommun. Inf. Technol. ECTI-CON 2013*, 2013, doi: 10.1109/ECTICon.2013.6559523.
- [9] S. Gansemer, S. Hakobyan, S. Püschel, and U. Großmann, “3D WLAN indoor positioning in multi-storey buildings,” *Proc. 5th IEEE Int. Work. Intell. Data Acquis. Adv. Comput. Syst. Technol. Appl. IDAACS’2009*, no. September, pp. 669–672, 2009, doi: 10.1109/IDAACS.2009.5342893.
- [10] L. Han, L. Jiang, Q. Kong, J. Wang, A. Zhang, and S. Song, “Indoor localization within multi-story buildings using MAC and RSSI fingerprint vectors,” *Sensors (Switzerland)*, vol. 19, no. 11, 2019, doi: 10.3390/s19112433.
- [11] T. Chuenurajit, D. Suroso, and P. Cherntanomwong, “Implementation of RSSI-Based 3D Indoor Localization using Wireless Sensor Networks Based on ZigBee Standard,” *J. Inf. Sci. Technol.*, vol. 3, no. 2, pp. 1–6, 2012, [Online]. Available: http://ist-journal.mut.ac.th/Journal/vol3-2/Vol32_PP_1_6.pdf.
- [12] H. Li, “Low-cost 3D bluetooth indoor positioning with least square,” *Wirel. Pers. Commun.*, vol. 78, no. 2, pp. 1331–1344, 2014, doi: 10.1007/s11277-014-1820-1.
- [13] C. Y. Shih and P. J. Marrón, “COLA: Complexity-reduced trilateration approach for 3D localization in wireless sensor networks,” *Proc. - 4th Int. Conf. Sens. Technol. Appl. SENSORCOMM 2010*, no. 2, pp. 24–32, 2010, doi: 10.1109/SENSORCOMM.2010.11.
- [14] N. A. Alrajeh, M. Bashir, and B. Shams, “Localization techniques in wireless sensor networks,” *Int. J. Distrib. Sens. Networks*, vol. 2013, no. June, 2013, doi: 10.1155/2013/304628.
- [15] Z. Farid, R. Nordin, and M. Ismail, “Recent advances in wireless indoor localization techniques and system,” *J. Comput. Networks Commun.*, vol. 2013, 2013, doi: 10.1155/2013/185138.
- [16] G. Zanca, F. Zorzi, A. Zanella, and M. Zorzi, “Experimental comparison of

- RSSI-based localization algorithms for indoor wireless sensor networks,” *REALWSN 2008 - Proc. 2008 Work. Real-World Wirel. Sens. Networks*, pp. 1–5, 2008, doi: 10.1145/1435473.1435475.
- [17] B. Rattanalert, W. Jindamaneepon, K. Sengchuai, A. Booranawong, and N. Jindapetch, “Problem investigation of min-max method for RSSI based indoor localization,” *ECTI-CON 2015 - 2015 12th Int. Conf. Electr. Eng. Comput. Telecommun. Inf. Technol.*, pp. 1–5, 2015, doi: 10.1109/ECTICon.2015.7207057.
- [18] F. M. Wibowo, “Metode Trilaterasi untuk Penentuan Posisi dalam Ruang Menggunakan Bluetooth Low Energy,” Universitas Gadjah Mada, 2016.
- [19] P. Christensson, “Wi-Fi Definition,” *TechTerms*, 2014.
<https://techterms.com/definition/wi-fi> (accessed Aug. 26, 2020).
- [20] Constantine A. Balanis, *Antenna Theory: Analysis Design*, 4th ed. New York: Wiley, 2015.
- [21] Nurhadi Budi Santoso, *Perekayasaan Sistem Antena*, Edisi Pert. Jakarta: Kementerian Pendidikan & Kebudayaan Direktorat Jenderal Peningkatan Mutu Pendidik & Tenaga Kependidikan, 2013.
- [22] dan A. M. S. Nurul Y. Arrifa, R. V. Hari Ginardi, “Implementasi Indoor Localization Menggunakan Sinyal Wi-Fi dan Decision Tree untuk Pelacakan Keberadaan Seseorang di Kampus Teknik Informatika ITS,” vol. 2, no. 1, pp. 1–4, 2013.
- [23] A. El-rabbany, *Introduction to GPS: The Global Position System*. Artech House, 2002.
- [24] S. Chan and G. Sohn, “indoor localization using wi-fi based fingerprinting and indoor localization using wi-fi based fingerprinting and,” *ISPRS - Int. Arch. Photogramm. Remote Sens. Spat. Inf. Sci.*, no. November 2015, pp. 3–8, 2012, doi: 10.5194/isprsarchives-XXXVIII-4-C26-1-2012.
- [25] L. Hu and D. Evans, “Localization for Mobile Sensor Networks,” 2004.
- [26] S. Singh, R. Shakya, and Y. Singh, “Localization Techniques in Wireless

- Sensor Networks,” vol. 6, no. 1, pp. 844–850, 2015.
- [27] and S.-H. Y. Alhmiedat, Tareq Ali, “A survey : localization and tracking mobile targets through wireless sensors network,” pp. 4–11, 2019.
- [28] S. Pal and S. C. Sharma, “Range Free Localization Techniques in Wireless Sensor Networks : A Review,” *Procedia - Procedia Comput. Sci.*, vol. 57, no. i, pp. 7–16, 2015, doi: 10.1016/j.procs.2015.07.357.
- [29] F. L. Villafuerte, “Localization of Wireless Sensor Nodes Based on Local Network Density,” Institute of Computer Science, Freie Universität Berlin, 2010.
- [30] H. Karl and A. Willig, *protocols and architectures for wireless sensor and architectures for wireless sensor*. 2005.
- [31] P. K. Sahu, E. H. Wu, and J. Sahoo, “DuRT : Dual RSSI Trend Based Localization for Wireless Sensor Networks,” *IEEE*, no. c, 2013.
- [32] S. Nnebe, “Pathloss Prediction Model of a Wireless Sensor Network in an Indoor Environment,” *IJAREEIE*, no. September 2014, 2016, doi: 10.15662/ijareeie.2014.0309003.
- [33] M. R. K. Aziz, “Mengenal TOA, TOF, dan TDOA dalam Wireless Geolocation - ITERA.” Institute Teknologi Sumatera, [Online]. Available: <https://www.itera.ac.id/mengenal-toa-tof-dan-tdoa-dalam-wireless-geolocation/>.
- [34] A. A. Khudhair, S. Q. Jabbar, M. Q. Sulttan, and D. Wang, “Wireless indoor localization systems and techniques: Survey and comparative study,” *Indones. J. Electr. Eng. Comput. Sci.*, vol. 3, no. 2, pp. 392–409, 2016, doi: 10.11591/ijeecs.v3.i2.pp392-409.
- [35] S. Nindito, N. A. Siswandari, and O. Puspitorini, “Analisa Pathloss Exponent Pada Daerah Urban dan Suburban,” pp. 1–5.
- [36] L. Kleinrock and J. Silvester, “*optimum transmission radii for packet radio networks or why six is a magic number*,” *Network*.

- [37] A. Goldsmith, *WIRELESS COMMUNICATIONS*. Stanford University, 2004.
- [38] D. Wang, L. Song, X. Kong, and Z. Zhang, “Near-ground path loss measurements and modeling for wireless sensor networks at 2.4 GHz,” *Int. J. Distrib. Sens. Networks*, vol. 2012, 2012, doi: 10.1155/2012/969712.
- [39] S. Kaddouri, M. El Hajj, G. Zaharia, and G. El Zein, “Indoor Path Loss Measurements and Modeling in an Open-Space Office at 2.4 GHz and 5.8 GHz in the Presence of People,” *IEEE Int. Symp. Pers. Indoor Mob. Radio Commun. PIMRC*, vol. 2018-September, 2018, doi: 10.1109/PIMRC.2018.8580695.
- [40] K. Langendoen and N. Reijers, “Distributed localization in wireless sensor networks : a quantitative comparison,” vol. 43, pp. 499–518, 2003, doi: 10.1016/S1389-1286(03)00356-6.
- [41] P. Kristalina, “Fundamental Teknik Lokalisasi pada Jaringan Sensor Nirkabel,” 2013.