

DAFTAR PUSTAKA

- A. Salomi, A. G., F. Feline, O. M., & Maffezzoli, A. (2007). A preliminary study on Bladder-assisted rotomolding of thermoplastic polymer composites. *Advances in Polymer Technology*, 26(1), 21–32. <https://doi.org/10.1002/adv>
- Afzaluddin, A., Jawaid, M., Salit, M. S., & Ishak, M. R. (2019). Physical and mechanical properties of sugar palm/glass fiber reinforced thermoplastic polyurethane hybrid composites. *Journal of Materials Research and Technology*, 8(1), 950–959. <https://doi.org/10.1016/j.jmrt.2018.04.024>
- Aitomäki, Y., Moreno-rodriguez, S., Lundström, T. S., & Oksman, K. (2016). Vacuum infusion of cellulose nano fibre network composites : Influence of porosity on permeability and impregnation. *Materials and Design*, 95, 204–211.
- Anderson, J. P., & Altan, M. C. (2012). Properties of Composite Cylinders Fabricated by Bladder Assisted Composite Manufacturing Properties of Composite Cylinders Fabricated by Bladder Assisted Composite Manufacturing. *Journal of Engineering Materials and Technology*, 134 / 0445(January). <https://doi.org/10.1115/1.4007017>
- Anderson, J. P., & Altan, M. C. (2014). Bladder Assisted Composite Manufacturing (BACM): Challenges and Opportunities, (October), 1–4. <https://doi.org/10.13140/2.1.2139.6169>
- Anderson, J. P., & Altan, M. C. (2016). Reduction of Microvoids in Composite Laminates Fabricated by Bladder Assisted Composite Manufacturing (BACM). *Polymer Composites*, 116(1), 561–572. <https://doi.org/10.1002/pc>
- Anderson, J., Proto, C., Kelly, A., Siddique, Z., & Altan, M. C. (2010). Fabrication of Hollow Composite Parts Using Inflatable Bladders : Processing and Properties. *Polymer*.
- Antameng, B. P. (2020). *DESAIN CETAKAN YANG EFEKTIF DALAM KONSUMSI ENERGI UNTUK MANUFAKTUR PRODUK HOLLOW COMPOSITE DENGAN METODE BLADDER COMPRESSION MOLDING EFFECTIVE*. Universitas Gadjah Mada.
- Askeland, D. R., Fulay, P. P., & Wright, W. J. (2010). *The Science and Engineering of Materials, Sixth Edition*. Stamford, CT 06902: Cengage Learning.

- Avci, A., Arian, H., & Akdemir, A. (2004). Fracture behavior of glass fiberreinforced polymer composite. *Cement and Concrete Research*, 34(3), 429–434. <https://doi.org/10.1016/j.cemconres.2003.08.027>
- Baran, I. (2015). Pultrusion processes for composite manufacture. *Advances in Composites Manufacturing and Process Design*.
- Basyarahil, Z. I. (2017, Juli). Tugas Akhir. *Karakterisasi dan Proses Manufaktur Komposit Polypropylene berpenguat Serat Dendrocalamus Asper untuk Aplikasi Ruang Mesin Otomotif*. Surabaya, Jawa Timur, Indonesia: Institut Teknologi Sepuluh Nopember Surabaya.
- Bere, P., Berce, P., & Dudescu, C. (2014). Manufacturing method of carbon/epoxy composite bent tubes with variable section. *Academic Journal of Manufacturing Engineering*, 12(3), 84–89.
- Callister, W. D., & Rethwisch, D. G. (2013). *Materials sciences and Engineering*. wiley (9th ed., Vol. 32). United State: Wiley. https://doi.org/10.1007/3-540-29970-X_12
- Chawla, K. K. (2012). *Composite Materials* (3th ed.). Birmingham: Springer US. <https://doi.org/10.1007/978-0-387-74365-3>
- Dickson, Andrew N., James N. Barry, Kevin A. McDonnell, and Denis P. Dowling. 2017. “Fabrication of Continuous Carbon, Glass and Kevlar Fibre Reinforced Polymer Composites Using Additive Manufacturing.” *Additive Manufacturing* 16 (June): 146–52. <https://doi.org/10.1016/j.addma.2017.06.004>.
- Eggers, F., Almeida, J. H. S., Azevedo, C. B., & Amico, S. C. (2019). Mechanical response of filament wound composite rings under tension and compression. *Polymer Testing*, 78(January). <https://doi.org/10.1016/j.polymertesting.2019.105951>
- Elkazaz, E., Crosby, W. A., Ollick, A. M., & Elhadary, M. (2020). Effect of fiber volume fraction on the mechanical properties of randomly oriented glass fiber reinforced polyurethane elastomer with crosshead speeds. *Alexandria Engineering Journal*, 59(1), 209–216. <https://doi.org/10.1016/j.aej.2019.12.024>
- Gibson, R. F. (2016). *Principles of composite material mechanics*. (L. . Faulkner, Ed.). CRC Press and Taylor & Francis Group.
- Hamill, L., Centea, T., & Nutt, S. (2015). Surface porosity during vacuum bag-only prepreg processing: Causes and mitigation strategies. *Composites Part A*:

Applied Science and Manufacturing, 75, 1–10.
<https://doi.org/10.1016/j.compositesa.2015.04.009>

Ismadi, I. H. (2019). *PENGARUH TEKANAN TERHADAP SIFAT MEKANIK PADA MANUFAKTUR KOMPOSIT SERAT KARBON/EPOXY DENGAN METODA BLADDER COMPRESSION MOULDING*. Universitas Gadjah Mada.

Justus Kimia raya. 2020. *Material Safety Data Sheet (MSDS) epoxy bisphenol AEpichlorohydrin*. Semarang.

Kalantari, M., Dong, C., & Davies, I. J. (2017). Effect of matrix voids, fibre misalignment and thickness variation on multi-objective robust optimization of carbon/glass fibre-reinforced hybrid composites under flexural loading. *Composites Part B: Engineering*, 123, 136–147.
<https://doi.org/10.1016/j.compositesb.2017.05.022>

Kechout, K., Amirat, A., & Zeghib, N. (2019). Residual stress analyses in multilayer PP/GFP/PP composite tube. *International Journal of Advanced Manufacturing Technology*, 103(9–12), 4221–4231.
<https://doi.org/10.1007/s00170-019-03843-7>

Lee, D. G., Chin, W. S., Kwon, J. W., & Yoo, A. K. (2002). Repair of underground buried pipes with resin transfer molding. *Composite Structures*, 57(1–4), 67–77. [https://doi.org/10.1016/S0263-8223\(02\)00066-1](https://doi.org/10.1016/S0263-8223(02)00066-1)

Nayak, Suhas Yeshwant, Shenoy B. Satish, Mohamed Thariq Hameed Sultan, Chandrakant R. Kini, K. Rajath Shenoy, Rashmi Samant, Praneeth P. Sarvade, Adi Azriff Basri, and Faizal Mustapha. 2020. “Influence of Fabric Orientation and Compression Factor on the Mechanical Properties of 3D E-Glass Reinforced Epoxy Composites.” *Journal of Materials Research and Technology* 9 (4): 8517–27.
<https://doi.org/10.1016/j.jmrt.2020.05.111>.

Nuryono, (2020). Kemendikbud. Diambil kembali dari Kemendikbud Website : <http://kebudayaan.kemdikbud.go.id/bkborobudur/wp-content/uploads/sites/12/2020/02/2-Resin-Alam-Prof-NURYONO.pdf>.

Partridge, I. (2016). *NetComposites*. Diambil kembali dari NetComposites Web site: <https://netcomposites.com/guide-tools/guide/manufacturing/cure-monitoring>.

Putra, M. I. (2020). *PENGARUH CURING TIME TERHADAP SIFAT MEKANIS PADA PEMBENTUKAN KOMPOSIT EPOXY/CARBON FIBER DAN EPOXY/GLASS FIBER DENGAN METODE BLADDER COMPRESSION MOLDING*. Universitas Gadjah Mada.

- Sahami, M., & Heidary, H. (2019). Parametric study on drilling of GFRP composite pipe produced by filament winding process in different backup condition. *Composite Structures*, (May), 111661. <https://doi.org/10.1016/j.compstruct.2019.111661>.
- Schillfahrt, C., Fauster, E., & Schledjewski, R. (2017). Influence of process pressures on filling behavior of tubular fabrics in bladder-assisted resin transfer molding. *Advanced Manufacturing: Polymer and Composites Science*, 3(4), 148–158. <https://doi.org/10.1080/20550340.2017.1389048>.
- Setyoko, A. D. (2019). *PENGARUH TEMPERATUR CURING TERHADAP SIFAT MEKANIK PADA MANUFAKTUR KOMPOSIT SERAT KARBON/EPOKSI DENGAN METODA PEMBENTUKAN BLADDER COMPRESSION MOULDING*. Universitas Gadjah Mada.
- Srinivas, M., Srikanth, I., Rao, G. R., & Naidu, G. S. (2019). Effect of volume fraction of reinforcement layers on the mechanical properties of S-glass-carbon-epoxy hybrid composites. *Materials Today: Proceedings*, 18, 4580–4588. <https://doi.org/10.1016/j.matpr.2019.07.432>.
- Taktak, R., Guermazi, N., & Kossentini Kallel, T. (2017). Effect of E-Glass fibre and ply orientation on the mechanical behaviour of FRP composites used for pressure pipe. *International Journal of Advanced Manufacturing Technology*, 92(5–8), 1741–1749. <https://doi.org/10.1007/s00170-017-0276-3>.
- Toh, W., Tan, L. Bin, Tse, K. M., Giam, A., Raju, K., Lee, H. P., & Tan, V. C. (2018). Material characterization of filament-wound composite pipes. *Composite Structures Journal*, 206(July), 474–483.
- Vadivelvivek, V. (2017). Mechanical Behavior of Epoxy Reinforced Natural Fiber Composites (Palm Sprout Fibre Composite), 14.
- Vasudevan, A., B. Navin Kumar, Melvin Victor Depoures, T. Maridurai, and V. Mohanavel. 2020. “Tensile and Flexural Behaviour of Glass Fibre Reinforced Plastic – Aluminium Hybrid Laminate Manufactured by Vacuum Resin Transfer Moulding Technique (VARTM).” *Materials Today: Proceedings*, no. xxxx. <https://doi.org/10.1016/j.matpr.2020.07.573>.
- Wang, C., Bai, G., Yue, G., Wang, Z., Li, J., & Zhang, B. (2016). Optimization of Resin Infusion Processing for Composite Pipe Key-Part and K/T Type Joints Using Vacuum-Assisted Resin Transfer Molding. *Applied Composite Materials*, 23(5), 1065–1078. <https://doi.org/10.1007/s10443-016-9498-z>.

- Wang, J., Simacek, P., & Advani, S. G. (2017). Use of medial axis to find optimal channel designs to reduce mold filling time in resin transfer molding. *Composites Part A: Applied Science and Manufacturing*, 95, 161–172. <https://doi.org/10.1016/j.compositesa.2017.01.003>.
- Wilberforce, S., & Hashemi, S. (2009). Effect of fibre concentration, strain rate and weldline on mechanical properties of injection-moulded short glass fibre reinforced thermoplastic polyurethane. *Journal of Materials Science*, 44(5), 1333–1343. <https://doi.org/10.1007/s10853-008-3233-6>.
- Xu, J., Ma, Y., Zhang, Q., Sugahara, T., Yang, Y., & Hamada, H. (2016). Crashworthiness of carbon fiber hybrid composite tubes molded by filament winding. *Composite Structures*, 139, 130–140. <https://doi.org/10.1016/j.compstruct.2015.11.053>.
- Yekani Fard, M., Raji, B., Woodward, J., & Padilla, M. (2019). Experimental characterization of damage mechanisms of seamless net-shaped circular pre-form and overlapped stitched composite pipes. *Polymer Testing*, 78(March). <https://doi.org/10.1016/j.polymertesting.2019.105934>.
- Zhang, H., Li, W., Yang, X., Lu, L., Wang, X., Sun, X., & Zhang, Y. (2007). Development of polyurethane elastomer composite materials by addition of milled fiberglass with coupling agent. *Materials Letters*, 61(6), 1358–1362. <https://doi.org/10.1016/j.matlet.2006.07.031>.
- Zuhudi, N. Z. M., Lin, R. J. T., & Jayaraman, K. (2014). Flammability , thermal and dynamic mechanical properties of bamboo – glass hybrid composites. *Journal of Thermoplastic Composite Materials*, 1–19. <https://doi.org/10.1177/0892705714563118>.