

## REFERENCES

- Al-Dahir, Z.A. and Morgenstern, N.R. (1969). Intake Factors for Cylindrical Piezometer Tips, *Soil Science*, pp.107.
- ASTM 422-63, 1963, Standard Test Method For Particle Size Analysis of soils.
- ASTM d 2434-68, 1968. Standard test Method for Permeability of Granular Soils ( Constant Head).
- Brand, E. W. and Premchitt, J. (1980a). Shape factors of some non-cylindrical piezometers, *Geotechnique*, vol. 30, pp. 536–537.
- Brand, E. W. and Premchitt, J.(1980b).Shape factors of cylindrical piezometers, *Geotechnique*, vol. 30, pp. 369–384.
- Bear, J. and Verroijt, A. (1987). *Modeling Groundwater Flow and Pollution*, pp.414.
- Bouwer H, Rice RC. (1976). A slug test for determining hydraulic conductivity of unconfined aquifers with completely or partially penetrating wells. *Water resources research*. 1976 Jun; 12(3):423-8.
- Chapuis R.P. (1989). Shape Factors for Permeability Test in Boreholes and Piezometers, *GROUND WATER*, vol.27, no.5, September- October 1989.
- Dordrecht. Brand E.W., Premchitt J, (1980). Shape Factors of Cylindrical Piezometers, *Geotechnique*.V.30, no.4, pp.368-384.
- J.A and J.Harb, 2013. Use of the Falling-Head Method to Assess Permeability of Freshly Mixed Conventitious-Based Materials. *Journal of Materials in Engineering*.
- Hvorslev, M.J. (1951), Time lag and Soil Permeability in Groundwater Observations , Waterways Experiment Station, US Corps of Engineers, *Bulletin* No.36.
- Kruseman, N.A and de. Ridder, (1994). *Analysis and Evaluation of Pumping Test Data*. 2<sup>nd</sup> Edition. The Netherlands.



Lowther, G. (1978) A note on Hvorslev's intake factors, *Geotechnique*, Vol.28, pp. 465-466.

Luthfiana A.B. (2015). *Determination of in situ soils permeability based on shape factor development, constant discharge procedure* Bachelor Program Thesis JTSL-FT-UGM.

Permana AA. (2015). *Determination of soils permeability in unsaturated condition based on constant discharge by shape factor development*, Bachelor Thesis Program JTSL-FT-UGM.

Ratnam, S., Soga, K. and Whittle, R.W. (2001). Revisiting Hvorslev's Intake Factors Using the Finite Element Method, *Geotechnique*, 51(7), pp 641-645.

Rana, F. (2002). Intake shape factors for transversely isotropic porous media. May.

Smiles, D. E. and Youngs, E. G.(1965). Hydraulic conductivity determination by several field methods in a sand tank, *Soil Science.*, vol. 99, pp. 83-87.

Sunjoto S. (1989). *Pengembangan Model Hidraulik Aliran Bawah Permukaan, Laporan Penelitian* PAU-IT-UGM-1988/1989. (Development of groundwater hydraulic model, Report of research PAU-IT-UGM-1988/1989.

Sunjoto S. (2002). Recharge Wells as Drainage System to Increase Groundwater Storage, Proc. on the 13<sup>rd</sup> IAHR-APD Congress, Advance in Hydraulics Water Engineering, Singapore, 6-8 August 2002 Vol.I, pp. 511-514.

Sunjoto S. (2014). Drawdown Minimizing to Restraining Sea Water Intrusion in Urban Coastal Area, Proc. 8<sup>th</sup> South East Consortium Technical University Cooperation (SEATUC) Symposium, Ibnu Sina Institut for Fundamental Science Studies, UTM, Johor Bahru, 3-5 March 2014.

Sunjoto, S. (2016). Influence of Shape Factor to the Hydraulic Pumping Power, E-proceeding 20<sup>th</sup> Congress of the IAHR APD 2016, Colombo Sri Lanka 28 August-31 September 2016.

Sunjoto, S. (2017). The inventions technology on water resources to support environmental engineering based infrastructure (p. 020055).

Selvadurai, A.P.S. and Bronelle, J. (2001), On Intake Shape Factors for Entry Point Located at Hydraulically Inhomogeneous Interfaces, Proc.1<sup>st</sup> Asia-Pacific Conference on Computational



*Mechanics* ( APCOM 01), (S.Valliappan and N.Khalili Eds.), Sydney. Australia, Elsevier,1, pp.591-597.

Selvadurai, A. (2003). Intake shape factors for entry points in porous media with transversely isotropic hydraulic conductivity. *International Journal of Geomechanics*, 3(December), pp.152–159.

Todd D.K. (1980). *Groundwater Hydrology*, 2<sup>nd</sup> Edition, John Wiley and Son, New York, pp. 304.

Youngs, E.G. (1968) Shape factors for Kirkham's piezometer method for determining the hydraulic conductivity of soil in situ for soil overlying an impermeable floor or infinitely permeable stratum, *Soil Science*, Vol.106, pp.235-237.

Youngs, E.G. (1980). Discussion of A note on Hvorslev's intake factors, *Geotechnique*, Vol.30, pp.328-331.