



REFERENCES

- Altschul, S. F. *et al.* (1997) ‘Gapped BLAST and PSI-BLAST: a new generation of protein database search programs’, *Nucleic acids research*, 25(17), pp. 3389–3402.
- Anfinsen, C. B. (1973) ‘Principles that govern protein folding’, *Science*, 181(4096), pp. 223–230.
- Asgari, E. *et al.* (2019) ‘DeepPrime2Sec: Deep learning for protein secondary structure prediction from the primary sequences’, *bioRxiv*. doi: 10.1101/705426.
- Asgari, E. and Mofrad, M. R. K. (2015) ‘Protvec: A continuous distributed representation of biological sequences’, *Computer Science*, 10(11), p. e0141287.
- Busia, A., Collins, J. and Jaitly, N. (2016) ‘Protein Secondary Structure Prediction Using Deep Multi-scale Convolutional Neural Networks and Next-Step Conditioning’, pp. 1–10. Available at: <http://arxiv.org/abs/1611.01503>.
- Drozdetskiy, A. *et al.* (2015) ‘JPred4: a protein secondary structure prediction server’, *Nucleic acids research*, 43(W1), pp. W389–W394.
- Eiben, A. E., Smith, J. E. and others (2003) *Introduction to evolutionary computing*. Springer.
- Fischer, A. W. *et al.* (2016) ‘CASP11 - An evaluation of a modular BCL: Fold-based protein structure prediction pipeline’, *PLoS ONE*, 11(4), pp. 1–19. doi: 10.1371/journal.pone.0152517.
- Goodfellow, I., Bengio, Y. and Courville, A. (2016) *Deep Learning*. MIT Press.
- Huang, C. L. and Wang, C. J. (2006) ‘A GA-based feature selection and parameters optimization for support vector machines’, *Expert Systems with Applications*, 31(2), pp. 231–240. doi: 10.1016/j.eswa.2005.09.024.
- Huang, Y. F. and Chen, S. Y. (2013) ‘Extracting physicochemical features to predict protein secondary structure’, *The Scientific World Journal*, 2013. doi: 10.1155/2013/347106.



- Jacobson, M. and Sali, A. (2004) ‘Comparative protein structure modeling and its applications to drug discovery’, *Annu. Rep. Med. Chem.*, 39(85), pp. 259–274.
- Kendrew, J. C. *et al.* (1960) ‘Structure of myoglobin: A three-dimensional Fourier synthesis at 2 Å resolution.’, *Nature*, 185(4711), pp. 422–427. doi: 10.1038/185422a0.
- LeCun, Y. *et al.* (1998) ‘Gradient-based learning applied to document recognition’, *Proceedings of the IEEE*, 86(11), pp. 2278–2323. doi: 10.1109/5.726791.
- Li, Z. and Yu, Y. (2016) ‘Protein secondary structure prediction using cascaded convolutional and recurrent neural networks’, *IJCAI International Joint Conference on Artificial Intelligence*, 2016-Janua, pp. 2560–2567.
- Lin, Z., Lanchantin, J. and Qi, Y. (2016) ‘MUST-CNN: A multilayer shift-And-stitch deep convolutional architecture for sequence-based protein structure prediction’, *30th AAAI Conference on Artificial Intelligence, AAAI 2016*, (Jones 1999), pp. 27–34.
- Meiler, J. *et al.* (2001) ‘Generation and evaluation of dimension-reduced amino acid parameter representations by artificial neural networks’, *Journal of Molecular Modeling*, 7(9), pp. 360–369. doi: 10.1007/s008940100038.
- Miller, B. L., Goldberg, D. E. and others (1995) ‘Genetic algorithms, tournament selection, and the effects of noise’, *Complex systems*, 9(3), pp. 193–212.
- Mnih, V. *et al.* (2013) ‘Playing Atari with Deep Reinforcement Learning’, pp. 1–9. Available at: <http://arxiv.org/abs/1312.5602>.
- Olah, C. (2015) *Understanding LSTM Networks*. Available at: <https://colah.github.io/posts/2015-08-Understanding-LSTMs/> (Accessed: 20 May 2020).
- Peters, M. E. *et al.* (2018) ‘Deep contextualized word representations’, *arXiv preprint arXiv:1802.05365*.
- Pevsner, J. (2004) *Bioinformatics and Functional Genomics, Briefings in Functional Genomics and Proteomics*. doi: 10.1093/bfgp/3.2.187.
- Qi, Y. *et al.* (2012) ‘A unified multitask architecture for predicting local protein properties’, *PloS one*, 7(3), p. e32235.



- Sak, H., Senior, A. and Beaufays, F. (2014) ‘Long Short-Term Memory Based Recurrent Neural Network Architectures for Large Vocabulary Speech Recognition’, (Cd). Available at: <http://arxiv.org/abs/1402.1128>.
- Santana, L. M. Q. De *et al.* (2018) ‘Deep Neural Networks for Acoustic Modeling in the Presence of Noise’, *IEEE Latin America Transactions*, 16(3), pp. 918–925. doi: 10.1109/LA.2018.8358674.
- Schleif, R. (1993) *Genetics and molecular biology, Current Opinion in Lipidology*. doi: 10.1097/MOL.0b013e32835133e3.
- Schuster, M. and Paliwal, K. K. (1997) ‘Bidirectional recurrent neural networks’, *IEEE Transactions on Signal Processing*, 45(11), pp. 2673–2681. doi: 10.1109/78.650093.
- Sønderby, S. K. and Winther, O. (2014) ‘Protein Secondary Structure Prediction with Long Short Term Memory Networks’. Available at: <http://arxiv.org/abs/1412.7828>.
- Wang, S. *et al.* (2016) ‘Protein Secondary Structure Prediction Using Deep Convolutional Neural Fields’, *Scientific Reports*, 6, pp. 109–114. doi: 10.1038/srep18962.
- Yang, C. H. *et al.* (2019) ‘Effective hybrid approach for protein structure prediction in a two-dimensional Hydrophobic–Polar model’, *Computers in Biology and Medicine*, 113(August), p. 103397. doi: 10.1016/j.combiomed.2019.103397.
- Zhang, B., Li, J. and Lü, Q. (2018) ‘Prediction of 8-state protein secondary structures by a novel deep learning architecture’, *BMC Bioinformatics*, 19(1), pp. 1–13. doi: 10.1186/s12859-018-2280-5.
- Zhou, J. *et al.* (2018) ‘CNNH_PSS: Protein 8-class secondary structure prediction by convolutional neural network with highway’, *BMC Bioinformatics*, 19(Suppl 4). doi: 10.1186/s12859-018-2067-8.
- Zhou, J. and Troyanskaya, O. G. (2014) ‘Deep supervised and convolutional generative stochastic network for protein secondary structure prediction’, *31st International Conference on Machine Learning, ICML 2014*, 2, pp. 1121–1129.