

TABLE OF CONTENTS

| | Page |
|--|-------------|
| ACKNOWLEDGEMENT | ii |
| ABSTRACT | iii |
| SARI | vi |
| TABLE OF CONTENTS | viii |
| LIST OF TABLES | xi |
| LIST OF FIGURES | xii |
| SYMBOLS AND ABBREVIATIONS | xvii |
| | |
| CHAPTER 1. INTRODUCTION | 1 |
| 1.1 Background | 1 |
| 1.2 Location of the study area | 5 |
| 1.3 Statements of Problem | 7 |
| 1.4 Purpose of the Study | 12 |
| 1.5 Authenticity of the Research | 12 |
| 1.6 Research Limitations | 13 |
| 1.7 Research Outcomes..... | 14 |
| | |
| CHAPTER 2 LITERATURE REVIEWS AND THEORETICAL BACKGROUND | 15 |
| 2.1 General Geology | 15 |
| 2.1.1 Geology of the Ende Quadrangle, East Nusa Tenggara..... | 15 |
| 2.1.2 Previous Studies | 20 |
| 2.2 Historical Seismicity around Ende Area..... | 22 |
| 2.3 Theoretical Background..... | 27 |
| 2.3.1 Microtremors | 27 |
| 2.3.1.1 Methods of Microtremor Measurement | 29 |
| 2.3.1.2 H/V Ratio (QTS) Technique | 30 |
| 2.3.2 Strong Ground Motion | 34 |
| (1) Amplitude | 35 |
| (2) Frequency | 36 |
| 2.3.3 Estimation of Predominant Periods | 38 |
| 2.3.4 Thickness of Sediments Calculated by the H/V Ratio of Seismic Noise | 41 |
| 2.3.5 Vulnerability Indices of Ground and Structures and Effective Shear Strain (K_g -values) | 43 |
| 2.3.6 Relationship between Predominant Period and Peak Ground Acceleration (PGA) | 46 |
| 2.3.7 Identification of Ground Profile | 47 |
| 2.3.7.1 Discrete Wavenumber Method(for incident SH wave) | 48 |
| 2.3.7.2 Discrete Wavenumber Method(for incident P and SVwave) | 55 |
| 2.3.8 Subsurface Geology of the Ende area inferred from microtremor data..... | 59 |
| 2.3.9 Microzonation map Based on Simple Additive Weighting (SAW) Methods..... | 61 |
| 2.3.10 Hypothesis | 63 |
| | viii |

| | |
|---|-----|
| CHAPTER 3 METHODOLOGY | 65 |
| 3.1 Desk Study | 65 |
| 3.2 Field investigation..... | 65 |
| 3.3 Data Processing..... | 69 |
| 3.4 Single Microtremor accelerometer | 70 |
| 3.5 Method of Study | 72 |
| | |
| CHAPTER 4 RESULTS AND DISCUSSIONS | 74 |
| 4.1 Geology of Ende Area..... | 74 |
| 4.2 Seismic Response Analysis..... | 81 |
| 4.2.1 Predominant frequency of research results in Ende area | 81 |
| 4.2.2 Amplification of research results in Ende area | 86 |
| 4.2.3 Peak Ground Acceleration of research results in Ende area (PGA) . | 88 |
| 4.2.4 Seismic vulnerability index value of research results in Ende area... | 94 |
| 4.2.5 Shear Strain of research results in Ende area (γ) | 96 |
| 4.2.6 Identification of Ground Profile..... | 100 |
| (a) SH wave analysis | 100 |
| (b) P-Sv wave analysis | 103 |
| (c) Estimation ground profile using Microtremor and Discrete Wavenumber Method..... | 104 |
| 4.2.7 Distribution of sediment thickness | 119 |
| 4.2.8 Modeling three-dimensional subsurface structure | 121 |
| 4.2.9 Bedrock Morphology | 122 |
| 4.2.10 Estimation Fault Orientation and Subsurface Geology of the Ende area | 124 |
| 4.2.11 Identification Soil type comparing geological lithology of rock with predominant period from HVSr..... | 127 |
| 4.3 Seismicity Microzonation map Based on Simple Additive Weighting SAW) Method | 135 |
| | |
| CHAPTER 5 CONCLUSION AND SUGGESTIONS | 141 |
| 5.1 Conclusion | 141 |
| 5.2 Suggestions | 144 |
| | |
| REFERENCES | 146 |
| APPENDICES | 150 |
| APPENDIX (A) STRATIGRAPHIC COLUMN OF THE OUTCROPS AT THE STUDY AREA | 151 |
| APPENDIX (B) SPECIFICATIONS AND CHARACTERIZATION OF GPL-6A3P OF MICROTREMOR DEVICE | 160 |
| APPENDIX (C) STEPS OF PROCESSING AND ANALYSIS OF THE SINGLE MICROTREMORS DATA | 165 |
| APPENDIX (D) THE RESULTS OF THE H/V SPECTRAL RATIO [HVSr] AND THE CALCULATED RESULTS DERIVED FROM HVSr OF SINGLE MICROTREMOR OBSERVATIONS IN ENDE AREA, EAST NUSA TENGGARA | 176 |

| | |
|--|-----|
| APPENDIX (E) STEPS OF PROCESSING AND ANALYSIS OF DISCRETE WAVENUMBER METHOD | 199 |
| APPENDIX (F) SEDIMENT THICKNESS [m] | 210 |

LIST OF TABLES

| | Page |
|--|-------------|
| Table 1.1 Destructive earthquakes and earthquake-tsunami in the last 37 years in the Indonesian region (http://earthquake.usgs.gov/earthquakes/eqarchive/s/year/byyear.php) | ----- 5 |
| Table 2.1 The relationship of soil types and predominant periods (Okada, 1971) | ----- 40 |
| Table 2.2 Strain Dependence of Dynamic Properties of Soil (Nakamura,1997) | ----- 44 |
| Table 4.2.1 Shear wave velocity of soil layer from SH and SV by DWM method for each profile | ----- 117 |
| Table 4.2.2 Comparison between Geological lithology and predominant periods | ----- 134 |
| Table 4.3.1 Weights, alternative and rank before normalization for total result | ----- 137 |

LIST OF FIGURES

| | | Page |
|-------------|---|-------------|
| Figure 1.1 | Tectonic map of Eastern Indonesia, which shows the tectonic setting of the Flores Island | ----- 3 |
| Figure 1.2 | Major tectonic features in the eastern Sunda arc | ----- 4 |
| Figure 1.3 | Location map of the Ende area, East Nusa Tenggara, Indonesia | ----- 6 |
| Figure 1.4 | Topography of the study area | ----- 8 |
| Figure 1.5 | Seismic Intensity Map of East Nusa Tenggara in 1992 earthquake (Irsyam, 2007) | ----- 9 |
| Figure 1.6 | Location of the Iya volcano at the southern part of the study area | ----- 11 |
| Figure 1.7 | Illustration of population in the study area | ----- 11 |
| Figure 2.1 | Geology map of the study area | ----- 19 |
| Figure 2.2 | Amplification map of rock/soil in Ende city (Saputra, et al., 2010) | ----- 21 |
| Figure 2.3 | Predominant period map of rock/soil in Ende city (Saputra, et al., 2010) | ----- 21 |
| Figure 2.4 | Historical Seismicity in Nusa Tenggara Timur, $M_w > 4.0$ (1840-2014) | ----- 23 |
| Figure 2.5 | Tectonic and earthquake epicenter map of the eastern Sunda arc | ----- 23 |
| Figure 2.6 | Damage map due to On December 12th, 1992 Flores earthquake in Ende area | ----- 26 |
| Figure 2.7 | Effect of artificial noise on short period microtremors (Nakamura, 1989) | ----- 28 |
| Figure 2.8 | Effect of oceanic swell on long period microtremors (Yamanaka, et al., 1993) | ----- 29 |
| Figure 2.9 | Determination of spectral amplification factor and the predominant soil period from H/V ratios. (Galerce, 1991) | ----- 31 |
| Figure 2.10 | A sample geological setting to illustrate the soil amplification and elimination of source effects in H/V spectra (Galerce, 1991) | ----- 33 |
| Figure 2.11 | The typical shape of the H/V spectral ratio (Nakamura, 2008) | ----- 34 |
| Figure 2.12 | Two hypothetical Fourier amplitude spectra with same predominant period, but very different frequency content (Kramer, 1996) | ----- 36 |
| Figure 2.13 | Raw and smooth Fourier amplitude spectra (a) rock (b) soil (Kramer, 1996). | ----- 37 |
| Figure 2.14 | Process of Fourier series representing the | |

| | | | |
|----------------|--|-------|----|
| | complicated loading can allow relatively simple solutions for harmonic loading to be used to produce total response (Kramer, 1996). | ----- | 38 |
| Figure 2.15 | Spectra of long-period microtremors observed at Hachinohe and estimated spectral peak period ((Naruse et al., 1976) | ----- | 39 |
| Figure 2.16 | Relation of predominant period to underground structures in Hachinohe (after Ohta, 1978) | ----- | 40 |
| Figure 2.17 | Microtremor characteristics with respect to site conditions (Ishiyama, 1982) | ----- | 41 |
| Figure 2.18 | Basic principle of site response, transfer function (Ibs-von Seht and Wohlenberg, 1999) | ----- | 42 |
| Figure 2.19 | Shear deformation of surface ground (Nakamura, 1997) | ----- | 45 |
| Figure 2.20 | K_g -values derived from QTS of Microtremor in S.F. (Nakamura, 1997) | ----- | 46 |
| Figure 2.21 | Schematic cross section displaying the layered-medium configuration and coordinate axes(Aki, K. L. Larner ,1970) | ----- | 50 |
| Figure 2.22 | Schematic illustration of the region near the interface displaying causes of the Rayleigh ansatz error. (Aki, K. L. Larner ,1970) | ----- | 52 |
| Figure 2.23 | sketch model of the subsurface geology of two layers and spectral response (Marjiyono, et al., 2014) | ----- | 61 |
| Figure 2.24 | Flow diagram SAW method | ----- | 64 |
| Figure 3.1 | location of the outcrops in the study area | ----- | 66 |
| Figure 3.2 | location of the geological outcrop-1 in the study area | ----- | 67 |
| Figure 3.3 | Location map of microtremor single station sites in Ende area. | ----- | 68 |
| Figure 3.4 | Single microtremor measurement at observation site (39) | ----- | 69 |
| Figure 3.5 | Flow chart of modeling the shallow subsurface structure | ----- | 71 |
| Figure 3.6 (a) | Instrument of GPL 6A-3P of serial No. 0418707 (Mitsutoyo), external view | | |
| | (b) Instrument of GPL 6A-3P of serial No. 0418707 (Mitsutoyo), internal view | ----- | 72 |
| Figure 3.7 | Flow chart of research in general | ----- | 73 |
| Figure 4.1.1 | Breccia interbedded with volcanic breccia in the Ndao village (outcrop – 1) and sandy tuff overlay on the conglomerate tuff at Potu village (outcrop – | ----- | 75 |

2).

| | | | |
|---------------|---|-------|-----|
| Figure 4.1.2 | Sandy gravel at Kuzazo village (outcrop-3) and iron sand at Kuzazo village (outcrop – 4) | ----- | 76 |
| Figure 4.1.3 | Sand at Mautapaga village (outcrop-5) and river deposit at Nanga Nasa (outcrop – 6) | ----- | 76 |
| Figure 4.1.4 | Gravelly sand at Paupanda Atas village (outcrop-7) and volcanic clastic at Waniwona village (outcrop – 8) | ----- | 77 |
| Figure 4.1.5 | Shaded relief model from SRTM elevation (http://earthexplorer.usgs.gov/) | ----- | 79 |
| Figure 4.1.6 | Geological map of the study area | ----- | 80 |
| Figure 4.2.1 | (a) a single clear peak, (b) almost flat spectral ratio and (c) without clear peaks. | ----- | 83 |
| Figure 4.2.2 | Predominant Frequency Map of Ende | ----- | 84 |
| Figure 4.2.3 | The frequent occurrence of predominant frequency (Hz) values at the study area. | ----- | 85 |
| Figure 4.2.4 | Amplitude of H/V map of Ende area. | ----- | 87 |
| Figure 4.2.5 | The frequent occurrence of amplitude of H/V values at the study area. | ----- | 88 |
| Figure 4.2.6 | Peak Ground Acceleration in Soil Layer Map of Ende area | ----- | 90 |
| Figure 4.2.7 | Seismic zonation in Indonesia (SNI-1726-2010) | ----- | 92 |
| Figure 4.2.8 | Seismic zonation in Indonesia (SNI- 1726-2012) | ----- | 93 |
| Figure 4.2.9 | Seismic Vulnerability Index map of Ende area | ----- | 95 |
| Figure 4.2.10 | Peak Ground Acceleration in bedrock Map of Ende area | ----- | 98 |
| Figure 4.2.11 | Shear Strain map of Ende area | ----- | 99 |
| Figure 4.2.12 | Magnification factors of some frequency for different incident wave angles ($\theta=0^\circ, 30^\circ, 45^\circ$ & 60°)obtained by the discrete wave number method | ----- | 101 |
| Figure 4.2.13 | Magnification factors of some frequency at depth 50m and 200m for SH wave input obtained by the discrete wave number method | ----- | 102 |
| Figure 4.2.14 | Frequency response for P-Sv wave input | ----- | 104 |
| Figure 4.2.15 | Four profile map in Ende area | ----- | 106 |
| Figure 4.2.16 | An example simple ground model for two layer media with Observation Points | ----- | 107 |
| Figure 4.2.17 | Response Function of SH input for profile (1) obtained by DWM | ----- | 108 |

| | | | |
|---------------|---|-------|-----|
| Figure 4.2.18 | Response Function of SV input for profile (1) obtained by DWM | ----- | 109 |
| Figure 4.2.19 | H/V ratio of microtremor data for profile (1) | ----- | 110 |
| Figure 4.2.20 | An example of comparison the value of Frequency from SH and SV by DWM method and HVSR for observation site (18) | ----- | 110 |
| Figure 4.2.21 | Identified ground profile (1) from SH and SV obtained by DWM method | ----- | 111 |
| Figure 4.2.22 | Response Function of SH input for profile (2) obtained by DWM | ----- | 111 |
| Figure 4.2.23 | Response Function of SV input for profile (2) obtained by DWM | ----- | 112 |
| Figure 4.2.24 | H/V ratio of microtremor data for profile (2) | ----- | 112 |
| Figure 4.2.25 | Identified ground profile (2) from SH and SV obtained by DWM method | ----- | 113 |
| Figure 4.2.26 | Response Function of SH input for profile (3) obtained by DWM | ----- | 113 |
| Figure 4.2.27 | Response Function of SV input for profile (3) obtained by DWM | ----- | 114 |
| Figure 4.2.28 | H/V ratio of microtremor data for profile (3) | ----- | 114 |
| Figure 4.2.29 | Identified ground profile (3) from SH and SV obtained by DWM method | ----- | 115 |
| Figure 4.2.30 | Response Function of SH input for profile (4) obtained by DWM | ----- | 115 |
| Figure 4.2.31 | Response Function of SV input for profile (4) obtained by DWM | ----- | 116 |
| Figure 4.2.32 | H/V ratio of microtremor data for profile (4) | ----- | 116 |
| Figure 4.2.33 | Identified ground profile (4) from SH and SV obtained by DWM method | ----- | 117 |
| Figure 4.2.34 | Sediment thickness map of Ende area. | ----- | 120 |
| Figure 4.2.35 | Distribution of Sediment thickness(m) at the study area | ----- | 121 |
| Figure 4.2.36 | Three-dimensional shape of the soil layer of the estimated subsurface structure in the study area | ----- | 122 |
| Figure 4.2.37 | Bedrock height map | ----- | 123 |
| Figure 4.2.38 | Three-dimensional shape of the bedrock in the study area | ----- | 123 |
| Figure 4.2.39 | Location of the HVSR spectrum cross-section in Ende area | ----- | 124 |
| Figure 4.2.40 | HVSR spectrum cross-section 1 and 2 | ----- | 125 |

| | | | |
|---------------|---|-------|-----|
| Figure 4.2.41 | (a) Location of conglomerate tuff outcrop at Potu village in the northern part of the study area | | |
| | (a) Predominant soil period amplitude from H/V ratios in observation site (80) | ----- | 127 |
| Figure 4.2.42 | (a) Location of sandy gravel outcrop at Kuzazo village in the study area | | |
| | (b) Predominant soil period amplitude from H/V ratios in observation site (77) | ----- | 128 |
| Figure 4.2.43 | (a) Location of iron sand outcrop at Kuzazo village (western seashore) in the study area | | |
| | (b) Predominant soil period amplitude from H/V ratios in observation site (76) | ----- | 129 |
| Figure 4.2.44 | (a) Location of sand outcrop at Mautapaga village in the eastern part in the study area | | |
| | (b) Predominant soil period amplitude from H/V ratios in observation site (57) | ----- | 130 |
| Figure 4.2.45 | (a) Location of river deposits outcrop at Nanga Nasa in the study area | | |
| | (b) Predominant soil period amplitude from H/V ratios in observation site (154) | ----- | 131 |
| Figure 4.2.46 | a) Location of gravelly sand outcrop at Paupanda Atas village in the middle part in the study area | | |
| | (b) Predominant soil period amplitude from H/V ratios in observation site (19) | ----- | 132 |
| Figure 4.2.47 | (a) Location of volcanic clastic outcrop at Waniwona village at the base of Maja Mountain that is located beside of Iya volcano in the study area | | |
| | (b) Predominant soil period amplitude from H/V ratios in observation site (37) | ----- | 133 |
| Figure 4.3.1 | Seismicity microzonation map | ----- | 138 |
| Figure 4.3.2 | Seismicity microzonation map comparing with damage area in 1992 earthquake | ----- | 139 |